8. NMAP using TryHackMe

Aim:
To Discover Live Host using Nmap Scan (ARP, ICMP, TCP/UDP) on the tryhackme platform Room link:
https://tryhackme.com/room/nmap01

Subnetworks:

A network Segment is a group of Computers linked to a shared medium like an Ethernet switch or wifi access point. In Ip networks, a subnetwork typically consist is a logical connection

In the provided network diagram. there are four network Segments or Subnetwork, your System would manually connected Security policies.

The figure displays two types of Subnets.

/16 Subnets. These have a Subnet mask of 255.255 and can accomdate approximately.

/24 Student Subnets: These feature a Subnet mask of 255.255.255.0 and can Support arround 250 host

Key to Run Compiler

If from Computer 1

iii) packType = "ARP Request"

iv) Data computer (because was one asking for computer 6 MAC address using ARP Request

How
Discovering live host.

Tcp Ip Layers

1) ARP from Link layer
2) ICMP from Network Layer.
3) TCP from Transport Layer
4) UDP from Transport Layer.

Send a packet with the following

i) from Computer 1
ii) To computer 3.

NMAP HOST Discovery using ARP:

How we can determine which host are operational?

It's crucial to prevent unnecessary port scanning on hosts that are offline or not in use.

This allows you to discover live system on the same subset as you traget machine without conduct any port scans.

Result:

Therefore the Discover Live HOST using Nmap Scan platform link was executed successfully.