MOTILAL NEHRU NATIONAL INSTITUTE OF TECHNOLOGY, ALLAHABAD

DATA STRUCTURE LAB

ASSIGNMENT- 2

1. Suppose you are a software developer working on an application for a library. The application maintains a list of books, each with a unique identification number. The library wants to implement a feature that displays books in increasing order of their ID numbers. To achieve this, the library has requested you to implement an **Insertion Sort** algorithm to sort the array of book IDs. Also analyze the run time complexity of the algorithms.
2. You are working as a software developer in a company that processes transaction amounts for various departments. Your task is to sort an array of transaction amounts in ascending order to help the finance team generate monthly reports more efficiently. The company prefers using **Selection Sort** because of its simplicity, but they need you to implement it and explain its run-time complexity.
3. You need to implement a **recursive Selection Sort** to sort customer transaction IDs in ascending order. The algorithm recursively finds the minimum element in the unsorted part, swaps it with the first unsorted element, and calls itself for the next unsorted portion. The **run-time complexity** of recursive Selection Sort is $\mathbf{O(n^2)}$ in all cases because it performs n-1, n-2, ..., 1 comparisons, resulting in a quadratic time complexity. Also discuss the problem in case of large dataset is sorted using this approach.
4. Write a C program to implement **Heap sort** in a given array of larger size. You also have to find the number of comparisons and time and space required to sort the array.