

```
import cvxpy as cp
import numpy as np
from itertools import product
```

▼ Data of the Problem

```
shipping_cost = np.array([[1,3,2],[3,2,2]]).reshape(2,3)
production_cost = np.array([11,10]).reshape(2,1)
given_demand = np.array([[100,150,120],[120,180,150],[150,200,180]]).reshape(3,3)
selling_price = np.array([16,16]).reshape(2,1)
produce = np.array([100,200]).reshape(2,1)
produce_limit = np.array([300,300]).reshape(2,1)
senario = 27
senario_prob = (1/senario)*(np.ones((senario,1)))
```

▼ Senario generation of the demand

```
senario = given_demand.T
senario_comb = []
index = np.arange(0,3)
index_permute = product(index,repeat=3)
for i in index_permute:
    temp_array = []
    for j in range(0,3):
        temp_array.append(float(senario[j,:][i[j]]))
    senario_comb.append(temp_array)
all_demand = np.array(senario_comb).reshape(27,3)
```

Question 1.3 Solve large scale problem combining all senarios into one problem

▼ Large scale problem solution

```
produce = cp.Variable(shape=(2,1))
sell = cp.Variable(shape=(54,3))
salvage = cp.Variable(shape=(54,1))
produce_limit = np.array([300,300]).reshape(2,1)

ls_constraints_senario = []
for index,demand in enumerate(all_demand):
    i = index*2
    ls_constraints_senario.append(cp.sum(sell[i:i+2,:],axis=1,keepdims=True) + salvage[i:i+2,:] <= produce)
    ls_constraints_senario.append(cp.sum(sell[i:i+2,:],axis=0,keepdims=True) <= demand.reshape(1,-1))

ls_constraints = [produce>=0,produce<=produce_limit,sell>= np.zeros_like(sell),salvage>= np.zeros_like(salvage)]
ls_constraints.extend(ls_constraints_senario)

ls_objective = cp.Minimize((production_cost.T@produce)-(16/27)*cp.sum(sell,keepdims=True) + (1/27)*cp.trace((((np.repeat([shipping_cost],27
ls_problem = cp.Problem(ls_objective, ls_constraints)
ls_problem.solve()

-1609.9999997418313
-----Large scale problem results -----

print("----Large Scale formulation results----")
print("Optimal Production plan ", produce.value)
print("Optimal Value of the Problem",ls_problem.value)

----Large Scale formulation results----
Optimal Production plan [[120.00000002]
[299.99999999]]
Optimal Value of the Problem -1609.9999997418313
```

✓ Expected value of demand

```

expected_demand = np.mean(all_demand,axis=0)

produce = cp.Variable(shape=(2,1))
sell = cp.Variable(shape=(2,3))
salvage = cp.Variable(shape=(2,1))
produce_limit = np.array([300,300]).reshape(2,1)

ed_constraints_senario = []
ed_constraints_senario.append(cp.sum(sell,axis=1,keepdims=True) +salvage <= produce)
ed_constraints_senario.append(cp.sum(sell,axis=0,keepdims=True) <= expected_demand.reshape(1,-1))

ed_constraints = [produce>=0,produce<=produce_limit,sell>= np.zeros_like(sell),salvage>= np.zeros_like(salvage)]
ed_constraints.extend(ed_constraints_senario)

ed_objective = cp.Minimize((production_cost.T@produce)-(16)*cp.sum(sell,keepdims=True) + (1)*cp.trace((((np.repeat([shipping_cost],1,axis=0
ed_problem = cp.Problem(ed_objective, ed_constraints)
ed_problem.solve()

```

----- Deterministic Expected Demand -----

↻ -1773.3333279947847

```

print("----- Results using deterministic expected demand-----")
print("\nOptimal Production plan using",produce.value)
print("\nOptimal Value of the Problem",ed_problem.value)

```

↻ ----- Results using deterministic expected demand----

```

Optimal Production plan using [[150.0000002 ]
[299.99999937]]

```

Optimal Value of the Problem -1773.3333279947847

✓ Q-1.4

Solving problem treating each demand individually

```

produce_over_scenario = []
objective_over_scenario = []
for demand in all_demand:
    produce = cp.Variable(shape=(2,1))
    sell = cp.Variable(shape=(2,3))
    salvage = cp.Variable(shape=(2,1))
    produce_limit = np.array([300,300]).reshape(2,1)

    constraints_senario = []
    constraints_senario.append(cp.sum(sell,axis=1,keepdims=True) +salvage <= produce)
    constraints_senario.append(cp.sum(sell,axis=0,keepdims=True) <= demand.reshape(1,-1))

    constraints = [produce>=0,produce<=produce_limit,sell>= np.zeros_like(sell),salvage>= np.zeros_like(salvage)]
    constraints.extend(constraints_senario)

    objective = cp.Minimize((production_cost.T@produce)-(16)*cp.sum(sell,keepdims=True) + (1)*cp.trace((((np.repeat([shipping_cost],1,axis=0
    problem = cp.Problem(objective, constraints)
    problem.solve()

    produce_over_scenario.append(produce.value)
    objective_over_scenario.append(problem.value)

print("Production plan considering each demand as determinstic:\n")
for index,demand in enumerate(all_demand):
    print(f"\n-----Senario {index}-----")
    print("\n Demand : ",demand)
    print("Optimal production",produce_over_scenario[index])

```

```
print("Optimal objective value",objective_over_scenario[index])
```

----- Production plan for each individual demand -----

↗ Production plan considering each demand as deterministic:

-----Senario 0-----

```
Demand : [100. 150. 120.]
Optimal production [100.00000039 269.99999935]
Optimal objective value [-1479.99999364]
```

-----Senario 1-----

```
Demand : [100. 150. 150.]
Optimal production [100.00000002 299.99999981]
Optimal objective value [-1599.99999832]
```

-----Senario 2-----

```
Demand : [100. 150. 180.]
Optimal production [130.00000026 299.99999889]
Optimal objective value [-1689.99999141]
```

-----Senario 3-----

```
Demand : [100. 180. 120.]
Optimal production [100.00000005 299.99999988]
Optimal objective value [-1599.99999891]
```

-----Senario 4-----

```
Demand : [100. 180. 150.]
Optimal production [130.00000023 299.99999923]
Optimal objective value [-1689.99999382]
```

-----Senario 5-----

```
Demand : [100. 180. 180.]
Optimal production [159.99999998 299.99999967]
Optimal objective value [-1779.9999969]
```

-----Senario 6-----

```
Demand : [100. 200. 120.]
Optimal production [120.00000025 299.99999945]
Optimal objective value [-1659.99999698]
```

-----Senario 7-----

```
Demand : [100. 200. 150.]
Optimal production [149.99999993 299.99999961]
Optimal objective value [-1749.99999596]
```

-----Senario 8-----

```
Demand : [100. 200. 180.]
Optimal production [180.00000003 299.99999979]
Optimal objective value [-1839.99999805]
```

-----Senario 9-----

✓ Calculating value of perfect information

----- value of perfect information -----

```
produce_over_scenario = np.array(produce_over_scenario).reshape(27,2)
objective_over_scenario = np.array(objective_over_scenario).reshape(27,1)
value_of_perfect_info = ls_problem.value - np.mean(objective_over_scenario)
```

```
print("Value of value of perfect information ",value_of_perfect_info)
```

↗ Value of value of perfect information 159.9999967386409

✓ Q 1.5

Solve the scenario formulation with nonanticipativity constraints.

```

produce = cp.Variable(shape=(2,27))
sell = cp.Variable(shape=(54,3))
salvage = cp.Variable(shape=(54,1))
produce_limit = (np.array([300,300]).reshape(2,1))
produce_limit_ext = np.repeat([produce_limit],27,axis=0).reshape(2,27)

na_constraints = []


# Nonanticipativity constraints
for index,demand in enumerate(all_demand):
    na_constraints.append(cp.reshape(produce[:,index],shape=(2,1))==(1/27)*cp.sum(produce,axis=1,keepdims=True))

for index,demand in enumerate(all_demand):
    i = index*2
    na_constraints.append(cp.sum(sell[i:i+2,:],axis=1,keepdims=True) +salvage[i:i+2,:] <= cp.reshape(produce[:,index],shape=(2,1)))
    na_constraints.append(cp.sum(sell[i:i+2,:],axis=0,keepdims=True) <= demand.reshape(1,-1))

constraints = [produce>=0,produce<=produce_limit,sell>= np.zeros_like(sell),salvage>= np.zeros_like(salvage)]
na_constraints.extend(constraints)

na_objective = cp.Minimize((1/27)*cp.sum(production_cost.T@produce)-(16/27)*cp.sum(sell,keepdims=True) + (1/27)*cp.trace((((np.repeat([ship
na_problem = cp.Problem(na_objective, na_constraints)
na_problem.solve()

```


 -1609.999999266336

-----Results using non anticaptivity constraints-----

```

print("----- Results using nonanticipativity -----")
print("\nOptimal Production plan using",produce.value)
print("\nOptimal Value of the Problem",na_problem.value)

```

 ----- Results using nonanticipativity -----

```

Optimal Production plan using [[120.00000001 120.00000001 120.00000001 120.00000001 120.00000001
120.00000001 120.00000001 120.00000001 120.00000001 120.00000001 120.00000001
120.00000001 120.00000001 120.00000001 120.00000001 120.00000001 120.00000001
120.00000001 120.00000001 120.00000001 120.00000001 120.00000001 120.00000001
120.00000001 120.00000001]
[299.99999999 299.99999999 299.99999999 299.99999999 299.99999999 299.99999999
299.99999999 299.99999999 299.99999999 299.99999999 299.99999999 299.99999999
299.99999999 299.99999999 299.99999999 299.99999999 299.99999999 299.99999999
299.99999999 299.99999999 299.99999999 299.99999999 299.99999999 299.99999999
299.99999999 299.99999999]]

```

Optimal Value of the Problem -1609.999999266336

-----Dual Values-----

```

for i in range(0,27):
    print(f"\nSecinario-{i}-----")
    print("Dual values for non anticipativiaty constraints")
    print(na_problem.constraints[i].dual_value)

```



```

Secinario-20-----
Dual values for non anticipativiaty constraints
[[0.14818783]
 [0.13000983]]

Secinario-21-----
Dual values for non anticipativiaty constraints
[[0.14818783]
 [0.10750179]]

Secinario-22-----
Dual values for non anticipativiaty constraints
[[0.14818783]
 [0.13000983]]

Secinario-23-----
Dual values for non anticipativiaty constraints
[[0.14818783]
 [0.13000983]]

Secinario-24-----
Dual values for non anticipativiaty constraints
[[0.14818783]
 [0.13000984]]

Secinario-25-----
Dual values for non anticipativiaty constraints
[[0.14818783]
 [0.13000984]]

Secinario-26-----
Dual values for non anticipativiaty constraints
[[0.14818783]
 [0.13000984]]

```

✓ Q-1.6

Solve the problem by the cutting plane method in the basic version (Benders decomposition)

```

def solve_second_stage_problem(produce,demand,shipping_cost):

    sell = cp.Variable(shape=(2,3))
    salvage = cp.Variable(shape=(2,1))

    objective = cp.Minimize(-16*cp.sum(sell,keepdims=True) + cp.trace((((shipping_cost@(sell.T))))))
    constraints = [cp.sum(sell,axis=1,keepdims=True) +salvage <= produce,cp.sum(sell,axis=0,keepdims=True) <= demand.reshape(1,-1), sell>= r

    problem = cp.Problem(objective, constraints)
    problem.solve()

    return problem

def solve_master_problem(produce,produce_limit,g_ks,alpha_ks):

    production_cost = np.array([11,10]).reshape(2,1)
    produce = cp.Variable(shape=(2,1),name="produce")
    v = cp.Variable(shape=(1,1),name="value")

    constraints = []
    for i in range(0,len(g_ks)):
        constraints.append(np.array(g_ks[i]).T@produce+np.array(alpha_ks[i])<=v)

    constraints.extend([produce>=0,v>=-100000,produce<=produce_limit])

    objective = cp.Minimize(production_cost.T@produce + v)

    problem = cp.Problem(objective, constraints)
    problem.solve()

    return problem

```

```

produce = np.array([100,200]).reshape(2,1) # Initial Guess
g_ks = []
alpha_ks = []

objective_values = [np.nan]
epsilon = 10*(-4)
iter = 0

while True:

    # Solve Second stage problem for each demand and store its duals and objective values
    duals = []
    objs = []
    for demand in all_demand:

        second_stage_sol = solve_second_stage_problem(produce,demand,shipping_cost)

        temp_dual = second_stage_sol.constraints[0].dual_value # Take the duals of 1st constraint
        temp_obj = second_stage_sol.value # Take the objective value of second stage problem

        # Store duals and objective values for each scenario
        duals.append(temp_dual)
        objs.append(temp_obj)

    # Reshaping the values
    duals = np.array(duals).reshape(-1,2)
    objs = np.array(objs).reshape(-1,1)

    g_ks_temp = (-scenario_prob.T@duals).T
    alpha_ks_temp = scenario_prob.T@objs - g_ks_temp.T@produce

    g_ks.append(g_ks_temp)
    alpha_ks.append(alpha_ks_temp)

    first_stage_sol = solve_master_problem(produce,produce_limit,g_ks,alpha_ks)
    obj_value = first_stage_sol.value
    new_produce = first_stage_sol.var_dict["produce"].value
    new_limit = first_stage_sol.var_dict["value"].value

    if np.abs(obj_value - objective_values[-1])<= epsilon:
        print("Terminating condition satisfied !")
        break
    else:
        pass

    objective_values.append(obj_value)
    produce,limit = new_produce,new_limit # swap the values
    iter = iter+1

    print(f"\n-----Iteration no. {iter}-----")
    print(f"\nproduction is {produce}")
    print(f"\nobjective value is {first_stage_sol.value}\n")

```

----- Results using Bender algorithm -----



```

-----Iteration no. 1-----

production is [[300.00000004]
 [299.99999992]]

objective value is -2351.895943550797

-----Iteration no. 2-----

production is [[149.00805118]
 [299.9999992 ]]

objective value is -1784.2447749212179

-----Iteration no. 3-----

production is [[112.70470909]
 [300.00000003]]

objective value is -1647.7631011106232

```

```

-----Iteration no.  4-----

production is [[125.23365091]
 [299.99999495]]

objective value is -1618.5289057328064

-----Iteration no.  5-----

production is [[119.99999869]
 [299.99999991]]

objective value is -1609.9999959895367

Terminating condition satisfied !

print("----- Results using Bender Decompostion -----")
print(f"\nproduction is {produce}")
print(f"\nobjective value is {first_stage_sol.value}\n")

```

↗ ----- Results using Bender Decompostion -----

```

production is [[119.99999869]
 [299.99999991]]

objective value is -1609.9999957406962

```

✓ Q-1.7 (Solve the problem by the multicut method)

```

def solve_master_problem_m1(produce,g_ks,alpha_ks,senario_prob,production_cost,produce_limit):

    produce = cp.Variable(shape=(2,1),name="produce")
    v = cp.Variable(shape=(len(senario_prob),1),name="value")

    constraints = []
    for i in range(0,len(g_ks)):
        for j in range(0,len(g_ks[i])):
            constraints.append(np.array([g_ks[i][j]])@produce+np.array([alpha_ks[i][j]])<=v[j])

    constraints.extend([produce>=0,v>=-100000,produce<=produce_limit])

    objective = cp.Minimize(production_cost.T@produce + senario_prob.T@v)

    problem = cp.Problem(objective, constraints)
    problem.solve()

    return problem

g_ks = []
alpha_ks = []
senario = 27
objective_values = [np.nan]
epsilon = 10**(-4)
iter = 0
while True:

    # Solve Second stage problem for each demand and store its duals and objective values
    duals = []
    objs= []
    for demand in all_demand:

        second_stage_sol = solve_second_stage_problem(produce,demand,shipping_cost)

        temp_dual = second_stage_sol.constraints[0].dual_value # Take the duals of 1st contraint
        temp_obj = second_stage_sol.value # Take the objective value of second stage problem

        # Store duals and objective values for each senario
        duals.append(temp_dual)

```

```

objs.append(temp_obj)

# Reshaping the values
duals = np.array(duals).reshape(-1,2)
objs = np.array(objs).reshape(-1,1)

gks_batch = []
alpha_ks_batch = []

for i in range(0,senario):
    gks_batch.append(-duals[i])
    alpha_ks_batch.append(objs[i]+duals[i].T@produce)

g_ks.append(gks_batch)
alpha_ks.append(alpha_ks_batch)

first_stage_sol = solve_master_problem_m1(produce,g_ks,alpha_ks,senario_prob,production_cost,produce_limit)
obj_value = first_stage_sol.value
new_produce = first_stage_sol.var_dict["produce"].value
new_limit = first_stage_sol.var_dict["value"].value

if np.abs(obj_value - objective_values[-1])<= epsilon:
    print("Terminating condition satisfied !")
    break

else:
    pass

objective_values.append(obj_value)
produce,limit = new_produce,new_limit # swap the values
iter = iter+1

print(f"\n-----Iteration no. {iter}-----")
print(f"\nproduction is {produce}")
print(f"\nobjective value is {first_stage_sol.value}\n")

```

----- Results using multicut method -----



```
-----Iteration no. 1-----
```

```
production is [[299.99999989]
 [299.99999992]]

objective value is -1727.7034315843757
```

```
-----Iteration no. 2-----
```

```
production is [[120.00000283]
 [299.99999952]]

objective value is -1609.9999916085671
```

```
Terminating condition satisfied !
```

```
print("----- Results using Multicut Method----")
print(f"\nproduction is {produce}")
print(f"\nobjective value is {first_stage_sol.value}\n")

```



```
----- Results using Multicut Method----
```

```
production is [[120.00000283]
 [299.99999952]]

objective value is -1609.999988313576
```