

# Wildfire Risk Score Review — Recommendation:

## Remediate Before Appealing

**Subject property:** 2269 SANTA ROSA AVE, ALTADENA, CA 91001 **Date:** 2026-08-10 **Prepared for the policyholder and producer — not for filing.** Complete the actions below first; when filed, the producer's §2644.9(j) 5-day forwarding duty applies.

### DECISION

**REMEDiate-FIRST** — Documented gaps (2) outweigh met standards (1). Filing now invites a reconsideration that re-affirms the score. Close the ranked gaps below, then appeal.

Scorecard: 1 met · 2 not met · 9 unknown (of 12 enumerated standards).

### SUBJECT PARCEL EXPOSURE — INDEPENDENTLY CITED FACTS

CAL FIRE's official Fire Hazard Severity Zone map (CAL FIRE OSFM LRA FHSZ (recommended), map dated 2025-03-24, all 4 rollout phases) classifies the subject parcel as **Non-Wildland** (responsibility area: LRA). The written reconsideration required by §2644.9(i) should reconcile the insurer's wildfire risk score with the State's own hazard classification of this parcel.

| Fact                            | Value                | Source                      | Confidence | Vintage                                                                                 |
|---------------------------------|----------------------|-----------------------------|------------|-----------------------------------------------------------------------------------------|
| fire_hazard_severity_zone_class | Non-Wildland         | CALFIRE_FHSZ                | high       | CAL FIRE OSFM LRA FHSZ (recommended), map dated 2025-03-24, all 4 rollout phases        |
| fire_hazard_responsibility_area | LRA                  | CALFIRE_FHSZ                | high       | CAL FIRE OSFM LRA FHSZ (recommended), map dated 2025-03-24, all 4 rollout phases        |
| lcms_class                      | Barren or Impervious | USFS_LCMS                   | medium     | USFS LCMS Land_Cover CONUS v2025-11 (2025 annual), ~120 m block-mode CONUS COG          |
| tree_canopy_pct                 | 24 percent           | USFS_NLCD_TCC               | high       | USFS/MRLC NLCD Tree Canopy Cover 2025 (v2025-6), CONUS COG (~120 m block-mean canopy %) |
| ndvi_current                    | 0.142                | COPERNICUS_S2_SR_HARMONIZED | high       | S2 SR 60d window @ 2026-08-10                                                           |
| ndvi_change_5y                  | -0.047               | COPERNICUS_S2_SR_HARMONIZED | medium     | —                                                                                       |
| slope_degrees                   | 5.235 degrees        | USGS_3DEP_COG               | medium     | —                                                                                       |

| Fact      | Value          | Source        | Confidence | Vintage                          |
|-----------|----------------|---------------|------------|----------------------------------|
| elevation | 361.013 meters | USGS_3DEP_COG | medium     | 3DEP 1/3 arc-second seamless DEM |

Location resolution: rooftop-accuracy geocode (parcel-grade) of "2269 Santa Rosa Ave, Altadena, CA 91001" via geocodio.

**Evidence in flight:** this agent has requested additional fields from the data provider — nearest\_fire\_perimeter\_distance\_m (CAL FIRE FRAP); most\_recent\_burn\_year; incident\_name (request fr\_43cf7d4595af48c38390a83589b22c80 , filed 2026-08-10, provider ETA 2026-08-11). This packet will be supplemented when the fields are delivered.

## ASSESSMENT AGAINST THE ENUMERATED MITIGATION STANDARDS (10 CCR §2644.9(D)(1))

The argument of this packet is the enumerated Safer-from-Wildfires standards the regulation requires rating plans to reflect. Survivor comparables (below) corroborate; they are not the argument.

| Std                              | Enumerated standard (verbatim)                                                                                                                       | Status     | Evidence                                                                                                                               |
|----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|------------|----------------------------------------------------------------------------------------------------------------------------------------|
| A1 (10 CCR §2644.9(d)(1) (A))    | Fire Risk Reduction Community listed by the Board of Forestry pursuant to Public Resources Code section 4290.1                                       | unknown    | No evidence available yet.                                                                                                             |
| A2 (10 CCR §2644.9(d)(1) (A))    | Firewise USA Site in Good Standing                                                                                                                   | unknown    | No evidence available yet.                                                                                                             |
| B1a (10 CCR §2644.9(d)(1) (B)1.) | Clearing of vegetation and debris from under decks                                                                                                   | unknown    | No evidence available yet.                                                                                                             |
| B1b (10 CCR §2644.9(d)(1) (B)1.) | Clearing of vegetation, debris, mulch, stored combustible materials, and any and all movable combustible objects, from the area within five (5) feet | unknown    | No evidence available yet.                                                                                                             |
| B1c (10 CCR §2644.9(d)(1) (B)1.) | Incorporation of only noncombustible materials into that portion of any improvements situated within five (5) feet                                   | unknown    | No evidence available yet.                                                                                                             |
| B1d (10 CCR §2644.9(d)(1) (B)1.) | Removal or absence of combustible structures from the area within thirty (30) feet                                                                   | unknown    | No evidence available yet.                                                                                                             |
| B1e (10 CCR §2644.9(d)(1) (B)1.) | Whether the property complies with Section 4291 of the Public Resources Code, and any applicable local ordinances                                    | unknown    | No evidence available yet.                                                                                                             |
| B2a (10 CCR §2644.9(d)(1) (B)2.) | Class-A Fire Rated Roof                                                                                                                              | unknown    | CAL FIRE inspector recorded roof material: Asphalt. Material does not establish Class-A rating — status unknown pending documentation. |
| B2b (10 CCR §2644.9(d)(1) (B)2.) | Enclosed Eaves                                                                                                                                       | NOT MET    | CAL FIRE inspector recorded eaves: Unenclosed.                                                                                         |
| B2c (10 CCR §2644.9(d)(1) (B)2.) | Fire-Resistant Vents                                                                                                                                 | NOT MET    | CAL FIRE inspector recorded vent screening: Mesh Screen > 1/8".                                                                        |
| B2d (10 CCR §2644.9(d)(1) (B)2.) | Multipane windows, including dual pane windows, or functional shutters                                                                               | <b>MET</b> | CAL FIRE inspector recorded window panes: Multi Pane.                                                                                  |

| Std                              | Enumerated standard (verbatim)                                             | Status  | Evidence                   |
|----------------------------------|----------------------------------------------------------------------------|---------|----------------------------|
| B2e (10 CCR §2644.9(d)(1) (B)2.) | At least six (6) inches of noncombustible vertical clearance at the bottom | unknown | No evidence available yet. |

## RANKED REMEDIATION LIST (CLOSE THESE, THEN APPEAL)

1. **B2c** — Fire-Resistant Vents
  - Eaton Fire DINS: remediating raises comparable survival by ~22 pp ('Unknown' excluded).
2. **B2b** — Enclosed Eaves
  - Eaton Fire DINS: remediating raises comparable survival by ~17 pp ('Unknown' excluded).

## DEMAND UNDER §2644.9(K)(B)

The eventual appeal will demand, for each mitigation measure below, the disclosure the regulation requires, verbatim:

*The amount of premium reduction the policyholder or applicant would realize as a result of performing each such measure under the insurer's rating plan that is in effect at the time.*

| # | Mitigation measure (enumerated standard) | Eaton survival delta (SFR, Unknown excluded) | Disclosure demanded                                                                                      |
|---|------------------------------------------|----------------------------------------------|----------------------------------------------------------------------------------------------------------|
| 1 | Fire-Resistant Vents (B2c)               | +22 pp                                       | Dollar premium reduction for completing this measure, itemized in the §2644.9(i) written reconsideration |
| 2 | Enclosed Eaves (B2b)                     | +17 pp                                       | Dollar premium reduction for completing this measure, itemized in the §2644.9(i) written reconsideration |

## CORROBORATION: CAL FIRE DINS SURVIVOR COMPARABLES (EATON FIRE)

Subject property's own CAL FIRE damage-inspection record: damage="No Damage", roof=Asphalt, vents=Mesh Screen > 1/8", eaves=Unenclosed, windows=Multi Pane, siding=Stucco Brick Cement, built 1952, APN 5839006005.

**Survival by ROOFCONSTRUCTION** (No Damage vs Destroyed (>50%)):

| Category           | No Damage | Destroyed | Survival |
|--------------------|-----------|-----------|----------|
| Combustible        | 1         | 0         | 100%     |
| Other              | 16        | 4         | 80%      |
| Concrete           | 125       | 48        | 72%      |
| Tile               | 1069      | 620       | 63%      |
| Asphalt            | 3803      | 4410      | 46%      |
| Metal              | 34        | 53        | 39%      |
| Wood               | 9         | 31        | 23%      |
| Non Combustible    | 0         | 1         | 0%       |
| Unknown (excluded) | 25        | 838       | —        |

**Survival by VENTSCREEN** (No Damage vs Destroyed (>50%)):

| Category            | No Damage | Destroyed | Survival |
|---------------------|-----------|-----------|----------|
| Unscreened          | 206       | 26        | 89%      |
| No Vents            | 912       | 153       | 86%      |
| Mesh Screen <= 1/8" | 795       | 291       | 73%      |
| Mesh Screen > 1/8"  | 3016      | 2859      | 51%      |
| Unknown (excluded)  | 153       | 2676      | —        |

**Survival by EAVES** (No Damage vs Destroyed (>50%)):

| Category           | No Damage | Destroyed | Survival |
|--------------------|-----------|-----------|----------|
| Combustible        | 2         | 0         | 100%     |
| Enclosed           | 1206      | 163       | 88%      |
| No Eaves           | 391       | 109       | 78%      |
| Unenclosed         | 3468      | 1383      | 71%      |
| Unknown (excluded) | 15        | 4350      | —        |

**Survival by WINDOWPANE** (No Damage vs Destroyed (>50%)):

| Category           | No Damage | Destroyed | Survival |
|--------------------|-----------|-----------|----------|
| Multi Pane         | 2683      | 950       | 74%      |
| Single Pane        | 2361      | 1661      | 59%      |
| No Windows         | 18        | 30        | 38%      |
| Asphalt            | 0         | 1         | 0%       |
| Unknown (excluded) | 20        | 3363      | —        |

**Survival by EXTERIORSIDING** (No Damage vs Destroyed (>50%)):

| Category            | No Damage | Destroyed | Survival |
|---------------------|-----------|-----------|----------|
| Vinyl               | 53        | 12        | 82%      |
| Other               | 25        | 7         | 78%      |
| Wood                | 1111      | 350       | 76%      |
| Metal               | 8         | 6         | 57%      |
| Stucco Brick Cement | 3878      | 5386      | 42%      |
| Unknown (excluded)  | 7         | 244       | —        |

**Methodology disclosure.** Comparisons are restricted to single-family residences (roughly 30% of Eaton DINS records are utility/miscellaneous structures — sheds, garages — which distort pooled survival rates) and exclude structures whose feature value is "Unknown". Unknowns concentrate among destroyed structures because inspectors cannot assess features that burned; including them would overstate every survival effect (survivorship artifact). Counts of excluded records are disclosed per table above.

**PROVENANCE APPENDIX**

---

- Mireye parcel facts: mode= live (8 fields via POST /v1/fetch, preset wildfire\_underwrite, fetched 2026-08-10T23:17:12.881329+00:00)

- [parcel] fire\_hazard\_severity\_zone\_class = "Non-Wildland" — CALFIRE\_FHSZ  
[https://services1.arcgis.com/jUJYI09tSA7EHvfZ/arcgis/rest/services/FHSALRA25\\_v1\\_All/FeatureServer/0](https://services1.arcgis.com/jUJYI09tSA7EHvfZ/arcgis/rest/services/FHSALRA25_v1_All/FeatureServer/0)  
(confidence: high) fetched 2026-08-10T22:20:37.817842+00:00 vintage CAL FIRE OSFM LRA FHSZ (recommended), map dated 2025-03-24, all 4 rollout phases — note: CAL FIRE LRA Fire Hazard Severity Zone at the point (FHSZ code -3); read with fire\_hazard\_responsibility\_area, which decides what the class legally means.
- [parcel] fire\_hazard\_responsibility\_area = "LRA" — CALFIRE\_FHSZ  
[https://services1.arcgis.com/jUJYI09tSA7EHvfZ/arcgis/rest/services/FHSALRA25\\_v1\\_All/FeatureServer/0](https://services1.arcgis.com/jUJYI09tSA7EHvfZ/arcgis/rest/services/FHSALRA25_v1_All/FeatureServer/0)  
(confidence: high) fetched 2026-08-10T22:20:37.817774+00:00 vintage CAL FIRE OSFM LRA FHSZ (recommended), map dated 2025-03-24, all 4 rollout phases — note: responsibility area from the SRA attribute of the same CAL FIRE LRA polygon that carries the FHSZ class.
- [parcel] lcms\_class = "Barren or Impervious" — USFS\_LCMS  
<https://data.fs.usda.gov/geodata/rastergateway/LCMS/> (confidence: medium) fetched 2026-08-10T22:20:36.906003+00:00 vintage USFS LCMS Land\_Cover CONUS v2025-11 (2025 annual), ~120 m block-mode CONUS COG — note: LCMS Land\_Cover class sampled from the bootstrapped ~120 m block-mode CONUS COG
- [parcel] tree\_canopy\_pct = 24 percent — USFS\_NLCD\_TCC  
<https://data.fs.usda.gov/geodata/rastergateway/treecanopycover/> (confidence: high) fetched 2026-08-10T22:20:36.908259+00:00 vintage USFS/MRLC NLCD Tree Canopy Cover 2025 (v2025-6), CONUS COG (~120 m block-mean canopy %) — note: tree canopy cover (%) sampled from the bootstrapped USFS/NLCD CONUS COG
- [parcel] ndvi\_current = 0.14210902154445648 — COPERNICUS\_S2\_SR\_HARMONIZED  
[https://developers.google.com/earth-engine/datasets/catalog/COPERNICUS\\_S2\\_SR\\_HARMONIZED](https://developers.google.com/earth-engine/datasets/catalog/COPERNICUS_S2_SR_HARMONIZED) (confidence: high) fetched 2026-08-10T22:20:44.029365+00:00 vintage S2 SR 60d window @ 2026-08-10
- [parcel] ndvi\_change\_5y = -0.046905517578125 — COPERNICUS\_S2\_SR\_HARMONIZED  
[https://developers.google.com/earth-engine/datasets/catalog/COPERNICUS\\_S2\\_SR\\_HARMONIZED](https://developers.google.com/earth-engine/datasets/catalog/COPERNICUS_S2_SR_HARMONIZED) (confidence: medium) fetched 2026-08-10T22:20:44.029502+00:00
- [parcel] slope\_degrees = 5.234614372253418 degrees — USGS\_3DEP\_COG  
<https://www.usgs.gov/3d-elevation-program> (confidence: medium) fetched 2026-08-10T22:20:37.928134+00:00
- [parcel] elevation = 361.0125732421875 meters — USGS\_3DEP\_COG  
<https://www.usgs.gov/3d-elevation-program> (confidence: medium) fetched 2026-08-10T22:20:37.927523+00:00 vintage 3DEP 1/3 arc-second seamless DEM
- [B2a] ROOFCONSTRUCTION = "Asphalt" — CAL FIRE DINS damage-inspection record for the subject property (POSTFIRE\_MASTER\_DATA\_SHARE, Eaton Fire)  
[https://services1.arcgis.com/jUJYI09tSA7EHvfZ/arcgis/rest/services/POSTFIRE\\_MASTER\\_DATA\\_SHARE/F](https://services1.arcgis.com/jUJYI09tSA7EHvfZ/arcgis/rest/services/POSTFIRE_MASTER_DATA_SHARE/F)
- [B2a] Corroboration: Eaton Fire survival by ROOFCONSTRUCTION (No Damage vs Destroyed, 'Unknown' excluded): Other 80%, Concrete 72%, Tile 63%, Asphalt 46%, Metal 39%, Wood 23%.
- [B2b] EAVES = "Unenclosed" — CAL FIRE DINS damage-inspection record for the subject property (POSTFIRE\_MASTER\_DATA\_SHARE, Eaton Fire)  
[https://services1.arcgis.com/jUJYI09tSA7EHvfZ/arcgis/rest/services/POSTFIRE\\_MASTER\\_DATA\\_SHARE/F](https://services1.arcgis.com/jUJYI09tSA7EHvfZ/arcgis/rest/services/POSTFIRE_MASTER_DATA_SHARE/F)
- [B2b] Corroboration: Eaton Fire survival by EAVES (No Damage vs Destroyed, 'Unknown' excluded): Enclosed 88%, No Eaves 78%, Unenclosed 71% — standard-conforming category: Enclosed.
- [B2c] VENTSCREEN = "Mesh Screen > 1/8"" — CAL FIRE DINS damage-inspection record for the subject property (POSTFIRE\_MASTER\_DATA\_SHARE, Eaton Fire)

[https://services1.arcgis.com/jUJYI09tSA7EHvfZ/arcgis/rest/services/POSTFIRE\\_MASTER\\_DATA\\_SHARE/F](https://services1.arcgis.com/jUJYI09tSA7EHvfZ/arcgis/rest/services/POSTFIRE_MASTER_DATA_SHARE/F)

- [B2c] Corroboration: Eaton Fire survival by VENTSCREEN (No Damage vs Destroyed, 'Unknown' excluded): Unscreened 89%, No Vents 86%, Mesh Screen  $\leq 1/8$ " 73%, Mesh Screen  $> 1/8$ " 51% — standard-conforming category: Mesh Screen  $\leq 1/8$ ".
- [B2d] WINDOWPANE = "Multi Pane" — CAL FIRE DINS damage-inspection record for the subject property (POSTFIRE\_MASTER\_DATA\_SHARE, Eaton Fire)  
[https://services1.arcgis.com/jUJYI09tSA7EHvfZ/arcgis/rest/services/POSTFIRE\\_MASTER\\_DATA\\_SHARE/F](https://services1.arcgis.com/jUJYI09tSA7EHvfZ/arcgis/rest/services/POSTFIRE_MASTER_DATA_SHARE/F)
- [B2d] Corroboration: Eaton Fire survival by WINDOWPANE (No Damage vs Destroyed, 'Unknown' excluded): Multi Pane 74%, Single Pane 59%, No Windows 38% — standard-conforming category: Multi Pane.
- Regulation text: 10 CCR §2644.9 via Cornell LII  
<https://www.law.cornell.edu/regulations/california/10-CCR-2644.9>, fetched 2026-08-10.
- DINS: CAL FIRE POSTFIRE\_MASTER\_DATA\_SHARE FeatureServer, queried live 2026-08-10.

---

*Verification statement: every regulation quotation in this packet was fetched from the primary source on the date shown, not reproduced from memory; every data fact carries its source, source URL, retrieval timestamp, and dataset vintage; every survivor comparison discloses its conditioning. Anything this packet could not verify is marked unknown rather than asserted.*