

Wildfire Risk Score Review — Recommendation:

Remediate Before Appealing

Subject property: 2269 SANTA ROSA AVE, ALTADENA, CA 91001 **Date:** 2026-08-10 **Prepared for filing via producer** (agent/broker forwarding duty, 10 CCR §2644.9(j): "the policyholder or applicant may appeal orally or in writing to the agent or broker ... who shall then forward that appeal to the insurer no later than five (5) calendar days after receiving the appeal.")

DECISION

REMEDiate-FIRST — Documented gaps (2) outweigh met standards (1). Filing now invites a reconsideration that re-affirms the score. Close the ranked gaps below, then appeal.

Scorecard: 1 met · 2 not met · 9 unknown (of 12 enumerated standards).

SUBJECT PARCEL EXPOSURE — INDEPENDENTLY CITED FACTS

CAL FIRE's official Fire Hazard Severity Zone map (CAL FIRE OSFM LRA FHSZ (recommended), map dated 2025-03-24, all 4 rollout phases) classifies the subject parcel as **Non-Wildland** (responsibility area: LRA). The written reconsideration required by §2644.9(i) should reconcile the insurer's wildfire risk score with the State's own hazard classification of this parcel.

Fact	Value	Source	Confidence	Vintage
fire_hazard_severity_zone_class	Non-Wildland	CALFIRE_FHSZ	high	CAL FIRE OSFM LRA FHSZ (recommended), map dated 2025-03-24, all 4 rollout phases
fire_hazard_responsibility_area	LRA	CALFIRE_FHSZ	high	CAL FIRE OSFM LRA FHSZ (recommended), map dated 2025-03-24, all 4 rollout phases
lcms_class	Barren or Impervious	USFS_LCMS	medium	USFS LCMS Land_Cover CONUS v2025-11 (2025 annual), ~120 m block-mode CONUS COG
tree_canopy_pct	24 percent	USFS_NLCD_TCC	high	USFS/MRLC NLCD Tree Canopy Cover 2025 (v2025-6), CONUS COG (~120 m block-mean canopy %)
ndvi_current	0.142	COPERNICUS_S2_SR_HARMONIZED	high	S2 SR 60d window @ 2026-08-10
ndvi_change_5y	-0.047	COPERNICUS_S2_SR_HARMONIZED	medium	—

Fact	Value	Source	Confidence	Vintage
slope_degrees	5.235 degrees	USGS_3DEP_COG	medium	—
elevation	361.013 meters	USGS_3DEP_COG	medium	3DEP 1/3 arc-second seamless DEM

Location resolution: rooftop-accuracy geocode (parcel-grade) of "2269 Santa Rosa Ave, Altadena, CA 91001" via geocodio.

ASSESSMENT AGAINST THE ENUMERATED MITIGATION STANDARDS (10 CCR §2644.9(D)(1))

The argument of this packet is the enumerated Safer-from-Wildfires standards the regulation requires rating plans to reflect. Survivor comparables (below) corroborate; they are not the argument.

Std	Enumerated standard (verbatim)	Status	Evidence
A1 (10 CCR §2644.9(d)(1) (A))	Fire Risk Reduction Community listed by the Board of Forestry pursuant to Public Resources Code section 4290.1	unknown	No evidence available yet.
A2 (10 CCR §2644.9(d)(1) (A))	Firewise USA Site in Good Standing	unknown	No evidence available yet.
B1a (10 CCR §2644.9(d)(1) (B)1.)	Clearing of vegetation and debris from under decks	unknown	No evidence available yet.
B1b (10 CCR §2644.9(d)(1) (B)1.)	Clearing of vegetation, debris, mulch, stored combustible materials, and any and all movable combustible objects, from the area within five (5) feet	unknown	No evidence available yet.
B1c (10 CCR §2644.9(d)(1) (B)1.)	Incorporation of only noncombustible materials into that portion of any improvements situated within five (5) feet	unknown	No evidence available yet.
B1d (10 CCR §2644.9(d)(1) (B)1.)	Removal or absence of combustible structures from the area within thirty (30) feet	unknown	No evidence available yet.
B1e (10 CCR §2644.9(d)(1) (B)1.)	Whether the property complies with Section 4291 of the Public Resources Code, and any applicable local ordinances	unknown	No evidence available yet.
B2a (10 CCR §2644.9(d)(1) (B)2.)	Class-A Fire Rated Roof	unknown	CAL FIRE inspector recorded roof material: Asphalt. Material does not establish Class-A rating — status unknown pending documentation.
B2b (10 CCR §2644.9(d)(1) (B)2.)	Enclosed Eaves	NOT MET	CAL FIRE inspector recorded eaves: Unenclosed.
B2c (10 CCR §2644.9(d)(1) (B)2.)	Fire-Resistant Vents	NOT MET	CAL FIRE inspector recorded vent screening: Mesh Screen > 1/8".
B2d (10 CCR §2644.9(d)(1) (B)2.)	Multipane windows, including dual pane windows, or functional shutters	MET	CAL FIRE inspector recorded window panes: Multi Pane.
B2e (10 CCR §2644.9(d)(1) (B)2.)	At least six (6) inches of noncombustible vertical clearance at the bottom	unknown	No evidence available yet.

RANKED REMEDIATION LIST (CLOSE THESE, THEN APPEAL)

1. **B2c** — Fire-Resistant Vents

- Eaton Fire DINS: remediating raises comparable survival by ~22 pp ('Unknown' excluded).

2. **B2b** — Enclosed Eaves

- Eaton Fire DINS: remediating raises comparable survival by ~17 pp ('Unknown' excluded).

DEMAND UNDER §2644.9(K)(B)

The eventual appeal will demand, for each mitigation measure below, the disclosure the regulation requires, verbatim:

The amount of premium reduction the policyholder or applicant would realize as a result of performing each such measure under the insurer's rating plan that is in effect at the time.

#	Mitigation measure (enumerated standard)	Eaton survival delta (SFR, Unknown excluded)	Disclosure demanded
1	Fire-Resistant Vents (B2c)	+22 pp	Dollar premium reduction for completing this measure, itemized in the §2644.9(i) written reconsideration
2	Enclosed Eaves (B2b)	+17 pp	Dollar premium reduction for completing this measure, itemized in the §2644.9(i) written reconsideration

CORROBORATION: CAL FIRE DINS SURVIVOR COMPARABLES (EATON FIRE)

Subject property's own CAL FIRE damage-inspection record: damage="No Damage", roof=Asphalt, vents=Mesh Screen > 1/8", eaves=Unenclosed, windows=Multi Pane, siding=Stucco Brick Cement, built 1952, APN 5839006005.

Survival by ROOFCONSTRUCTION (No Damage vs Destroyed (>50%)):

Category	No Damage	Destroyed	Survival
Combustible	1	0	100%
Other	16	4	80%
Concrete	125	48	72%
Tile	1069	620	63%
Asphalt	3803	4410	46%
Metal	34	53	39%
Wood	9	31	23%
Non Combustible	0	1	0%
Unknown (excluded)	25	838	—

Survival by VENTSCREEN (No Damage vs Destroyed (>50%)):

Category	No Damage	Destroyed	Survival
Unscreened	206	26	89%
No Vents	912	153	86%

Category	No Damage	Destroyed	Survival
Mesh Screen <= 1/8"	795	291	73%
Mesh Screen > 1/8"	3016	2859	51%
Unknown (excluded)	153	2676	—

Survival by EAVES (No Damage vs Destroyed (>50%)):

Category	No Damage	Destroyed	Survival
Combustible	2	0	100%
Enclosed	1206	163	88%
No Eaves	391	109	78%
Unenclosed	3468	1383	71%
Unknown (excluded)	15	4350	—

Survival by WINDOWPANE (No Damage vs Destroyed (>50%)):

Category	No Damage	Destroyed	Survival
Multi Pane	2683	950	74%
Single Pane	2361	1661	59%
No Windows	18	30	38%
Asphalt	0	1	0%
Unknown (excluded)	20	3363	—

Survival by EXTERIORSIDING (No Damage vs Destroyed (>50%)):

Category	No Damage	Destroyed	Survival
Vinyl	53	12	82%
Other	25	7	78%
Wood	1111	350	76%
Metal	8	6	57%
Stucco Brick Cement	3878	5386	42%
Unknown (excluded)	7	244	—

Methodology disclosure. Comparisons are restricted to single-family residences (roughly 30% of Eaton DINS records are utility/miscellaneous structures — sheds, garages — which distort pooled survival rates) and exclude structures whose feature value is "Unknown". Unknowns concentrate among destroyed structures because inspectors cannot assess features that burned; including them would overstate every survival effect (survivorship artifact). Counts of excluded records are disclosed per table above.

PROVENANCE APPENDIX

- Mireye parcel facts: mode= fixture (8 fields via POST /v1/fetch, preset wildfire_underwrite, fetched 2026-08-10T22:20:44.046028+00:00)
- [parcel] fire_hazard_severity_zone_class = "Non-Wildland" — CALFIRE_FHSZ
https://services1.arcgis.com/jUJYI0gtSA7EHvfZ/arcgis/rest/services/FHSALRA25_v1_All/FeatureServer/0
(confidence: high) fetched 2026-08-10T22:20:37.817842+00:00 vintage CAL FIRE OSFM LRA FHSZ (recommended), map dated 2025-03-24, all 4 rollout phases — note: CAL FIRE LRA Fire

Hazard Severity Zone at the point (FHSZ code -3); read with fire_hazard_responsibility_area, which decides what the class legally means.

- [parcel] fire_hazard_responsibility_area = "LRA" — CALFIRE_FHSZ
https://services1.arcgis.com/jUJYI09tSA7EHvfZ/arcgis/rest/services/FHSALRA25_v1_All/FeatureServer/0
(confidence: high) fetched 2026-08-10T22:20:37.817774+00:00 vintage CAL FIRE OSFM LRA FHSZ (recommended), map dated 2025-03-24, all 4 rollout phases — note: responsibility area from the SRA attribute of the same CAL FIRE LRA polygon that carries the FHSZ class.
- [parcel] lcms_class = "Barren or Impervious" — USFS_LCMS
<https://data.fs.usda.gov/geodata/rastergateway/LCMS/> (confidence: medium) fetched 2026-08-10T22:20:36.906003+00:00 vintage USFS LCMS Land_Cover CONUS v2025-11 (2025 annual), ~120 m block-mode CONUS COG — note: LCMS Land_Cover class sampled from the bootstrapped ~120 m block-mode CONUS COG
- [parcel] tree_canopy_pct = 24 percent — USFS_NLCD_TCC
<https://data.fs.usda.gov/geodata/rastergateway/treecanopycover/> (confidence: high) fetched 2026-08-10T22:20:36.908259+00:00 vintage USFS/MRLC NLCD Tree Canopy Cover 2025 (v2025-6), CONUS COG (~120 m block-mean canopy %) — note: tree canopy cover (%) sampled from the bootstrapped USFS/NLCD CONUS COG
- [parcel] ndvi_current = 0.14210902154445648 — COPENICUS_S2_SR_HARMONIZED
https://developers.google.com/earth-engine/datasets/catalog/COPENICUS_S2_SR_HARMONIZED (confidence: high) fetched 2026-08-10T22:20:44.029365+00:00 vintage S2 SR 60d window @ 2026-08-10
- [parcel] ndvi_change_5y = -0.046905517578125 — COPENICUS_S2_SR_HARMONIZED
https://developers.google.com/earth-engine/datasets/catalog/COPENICUS_S2_SR_HARMONIZED (confidence: medium) fetched 2026-08-10T22:20:44.029502+00:00
- [parcel] slope_degrees = 5.234614372253418 degrees — USGS_3DEP_COG
<https://www.usgs.gov/3d-elevation-program> (confidence: medium) fetched 2026-08-10T22:20:37.928134+00:00
- [parcel] elevation = 361.0125732421875 meters — USGS_3DEP_COG
<https://www.usgs.gov/3d-elevation-program> (confidence: medium) fetched 2026-08-10T22:20:37.927523+00:00 vintage 3DEP 1/3 arc-second seamless DEM
- [B2a] ROOFCONSTRUCTION = "Asphalt" — CAL FIRE DINS damage-inspection record for the subject property (POSTFIRE_MASTER_DATA_SHARE, Eaton Fire)
https://services1.arcgis.com/jUJYI09tSA7EHvfZ/arcgis/rest/services/POSTFIRE_MASTER_DATA_SHARE/F
- [B2a] Corroboration: Eaton Fire survival by ROOFCONSTRUCTION (No Damage vs Destroyed, 'Unknown' excluded): Other 80%, Concrete 72%, Tile 63%, Asphalt 46%, Metal 39%, Wood 23%.
- [B2b] EAVES = "Unenclosed" — CAL FIRE DINS damage-inspection record for the subject property (POSTFIRE_MASTER_DATA_SHARE, Eaton Fire)
https://services1.arcgis.com/jUJYI09tSA7EHvfZ/arcgis/rest/services/POSTFIRE_MASTER_DATA_SHARE/F
- [B2b] Corroboration: Eaton Fire survival by EAVES (No Damage vs Destroyed, 'Unknown' excluded): Enclosed 88%, No Eaves 78%, Unenclosed 71% — standard-conforming category: Enclosed.
- [B2c] VENTSCREEN = "Mesh Screen > 1/8"" — CAL FIRE DINS damage-inspection record for the subject property (POSTFIRE_MASTER_DATA_SHARE, Eaton Fire)
https://services1.arcgis.com/jUJYI09tSA7EHvfZ/arcgis/rest/services/POSTFIRE_MASTER_DATA_SHARE/F
- [B2c] Corroboration: Eaton Fire survival by VENTSCREEN (No Damage vs Destroyed, 'Unknown' excluded): Unscreened 89%, No Vents 86%, Mesh Screen <= 1/8" 73%, Mesh Screen

> 1/8" 51% — standard-conforming category: Mesh Screen <= 1/8".

- [B2d] WINDOWPANE = "Multi Pane" — CAL FIRE DINS damage-inspection record for the subject property (POSTFIRE_MASTER_DATA_SHARE, Eaton Fire)
https://services1.arcgis.com/jUJYIo9tSA7EHvfZ/arcgis/rest/services/POSTFIRE_MASTER_DATA_SHARE/F
- [B2d] Corroboration: Eaton Fire survival by WINDOWPANE (No Damage vs Destroyed, 'Unknown' excluded): Multi Pane 74%, Single Pane 59%, No Windows 38% — standard-conforming category: Multi Pane.
- Regulation text: 10 CCR §2644.9 via Cornell LII
<https://www.law.cornell.edu/regulations/california/10-CCR-2644.9>, fetched 2026-08-10.
- DINS: CAL FIRE POSTFIRE_MASTER_DATA_SHARE FeatureServer, queried live 2026-08-10.