


CS-E4740 Federated Learning

"Network Models"


Dipl.-Ing. Dr. techn. Alexander Helmut Jung

What are main components of ML and how are they combined?

Plain Old Machine Learning.




Train and Validate.




Basic Idea of Model Selection

- choose model with smallest validation error!

training
error validation
error




model 1
degree 1 polyn.




model 2:
degree 3 polyn.

Data and Model Size




crucial parameter is the
ratio d/m



training error


validation error



Networked Data

Networked Weather Data





ImageNet.

“...ImageNet is an image database organized according to the WordNet hierarchy (currently only the nouns), in **which each node** of the hierarchy is depicted by **hundreds and thousands of images...**”

<https://image-net.org/>




Devopedia. 2021. "ImageNet." Version 16, April 7. Accessed 2023-02-11. <https://devopedia.org/imagenet>


Noble Networks.



Finance Networks.




Algebraic Networks




Example 4.3. Let $G = D_n$, the dihedral group of order $2n$, and take $S = \{r, r^{n-1}, s\}$.

Petteri Kaski, Eigenvectors and spectra of Cayley graphs, 2002

Point Cloud Networks.




Road Network



Business Process





https://www.wikidata.org/wiki/Wikidata:Main_Page

Empirical Graph - Nodes

i=1



2



3



4



each node carries:

- local dataset

```
# the node attribute "X" stores  
G.nodes[iter_node]["X"] = X
```

```
# the node attribute "y" stores  
G.nodes[iter_node]["y"] = y
```

```
G_FMI = nx.Graph()  
G_FMI.add_nodes_from(range(0, num_stations))
```

Attach Local Datasets to Nodes

```
for i, station in enumerate(data.station.unique())

    # first filter out rows in dataframe data with
    # current value of station

    df = data[data.station==station]

    # store the name of the current station in the
    G_FMI.nodes[i]['name'] = station
    # store the lat and lon of the current station
    G_FMI.nodes[i]['coord'] = np.array([df.latitude, df.longitude])
    # store the min. daytime temp. in the node at
    G_FMI.nodes[i]['X'] = df.min_temp.to_numpy().
    # store the max. daytime temp. in the node at
    G_FMI.nodes[i]['y'] = df.max_temp.to_numpy().
```


name of FMI station

latitude, longitude of FMI station

use min. daytime tmp. as feature of
datapoint (=some day)

use max. daytime tmp. as labels of
datapoint (= some day)

Empirical Graph - Edges



How To Measure Statistical Sim.?

```
>>> from scipy.stats import ks_2samp
>>> import numpy as np
>>>
>>> np.random.seed(12345678)
>>> x = np.random.normal(0, 1, 1000)
>>> y = np.random.normal(0, 1, 1000)
>>> z = np.random.normal(1.1, 0.9, 1000)
>>>
>>> ks_2samp(x, y)
Ks_2sampResult(statistic=0.022999999999999999, pvalue=0.95189016804849647)
>>> ks_2samp(x, z)
Ks_2sampResult(statistic=0.41800000000000004, pvalue=3.7081494119242173e-77)
```


<https://stackoverflow.com/questions/10884668/two-sample-kolmogorov-smirnov-test-in-python-scipy>

https://en.wikipedia.org/wiki/Kolmogorov%E2%80%93Smirnov_test

23

Spatio-Temporal Similarity


connect FMI stations with its k nearest neighbours (use geodesic distance)



How to choose Empirical Graph?

- empirical graph is design choice
- more edges means more comp./comm.
- sufficiently many edges between similar datasets

Graph Laplacian Matrix




$$\mathbf{L} = \begin{pmatrix} A_{1,2} & -A_{1,2} & 0 \\ -A_{1,2} & A_{1,2} + A_{2,3} & -A_{2,3} \\ 0 & -A_{2,3} & A_{2,3} \end{pmatrix}$$

\mathbf{L} is psd with eig.vals $\lambda_1 = 0 \leq \lambda_2 \dots \leq \lambda_{nr \text{ nodes}}$


Spectral Graph Clustering

eig.vecs of L corresponding to smallest pos. eig.vals $\lambda_1 = 0 \leq \lambda_2$ are piece-wise constant over clusters



What is Component 2 of ML ?

Local Model for Local Data



each node carries:


- local dataset

```
# the node attribute "X" stores  
G.nodes[iter_node]["X"] = X  
  
# the node attribute "y" stores  
G.nodes[iter_node]["y"] = y
```


- local model

```
# the node attribute "model" stores a ML model of  
G.nodes[iter_node]["model"] = LinearRegression()  
G.nodes[iter_node]["model"].fit(G.nodes[iter_node]
```

Networked Models




Option 1: Train Separately




```
for iter_node in G.nodes:  
    # the node attribute "model" stores a ML model of your choice  
    # if iter_node < 3 :  
        G.nodes[iter_node]["model"] = LinearRegression() # initial  
    # else:  
        # G.nodes[iter_node]["model"] = DecisionTreeRegressor(max  
        G.nodes[iter_node]["model"].fit(G.nodes[iter_node]["X"], G.r
```



Pro: Personalization




Con: Overfitting




Option 2: Global Model




Pro: No Overfitting



Con: Low Accuracy



Option 3: Networked FL




Networked FL


- maintain local models for each node (local dataset)
- local models are trained on local datasets
- couple the training of local models
- coupling via clustering (global model per cluster)
- different clustering methods

Coupling of Local Models

- coupling based on edges
- local models at connected nodes should deliver similar predictions




Coupling via Regularization



```
# the following for loop computes the local gradient at each node
for node_i in G.nodes(data=False):
    tmp_y = G.nodes[node_i]["y"].reshape(-1,1)
    tmp_X = G.nodes[node_i]["X"]
    sample_weight = np.ones((samplesize,1))
    # loop over all neighbours of current node "node_i"
    for node_j in G[node_i]:
        tmp_X = np.vstack((tmp_X,G.nodes[node_j]["X"]))
        tmp_y = np.vstack((tmp_y,G.nodes[node_j]["model"].predict(G.nodes[node_i]["X"]).reshape(-1,1)))
        sample_weight = np.vstack((sample_weight,100*np.ones((samplesize,1))))
    # print(tmp_X.shape)


    G.nodes[node_i]["model"].fit(tmp_X,tmp_y,sample_weight.reshape(-1))
```


Clustering Assumption



local datasets often too small
let's pool or cluster them but how ?


Clustering Assumption



the local datasets form clusters.

local datasets in same cluster c contain data points that can be approximated as realizations of i.i.d. RVs with prob. dist $p(x,y;c)$

Cluster-Wise Training



pool local datasets of nodes in same cluster to train ML model

trained model is used for all nodes in same cluster

pooling via regularization

Wrap-Up.

- emp. graph with nodes carrying local datasets and models
- undirected weighted edges represent similarities
- different sources for similarity
- emp. graph is a design choice

Any Questions ?