

LOW-LEVEL DESIGN DOCUMENT

Loan Application & Compliance Review Assistant

Component-level design: class structure, algorithms, data schemas, interface contracts and control enforcement points.

Document ID	LLD-LACR-001
Version	1.0
Date	17 September 2026
Author	Aayush Mathur
Programme	CapGemini AI Launchpad — Capstone Use Case 4
Status	Final — for evaluation
Classification	Internal / Academic
Related documents	HLD-LACR-001 (High-Level Design)

Scope of this document

This LLD specifies how the architecture described in HLD-LACR-001 is realised in code: project structure, class responsibilities, the eligibility algorithm, persistence schema, port contracts, the MCP wire protocol, and the exact points at which each business rule is enforced.

Table of Contents

1. Introduction

- 1.1 Purpose
- 1.2 Conventions

2. Solution Structure

- 2.1 Projects
- 2.2 Namespace map
- 2.3 Dependency rules

3. Domain Layer

- 3.1 Entities and value objects
- 3.2 Enumerations
- 3.3 ApplicantFacts and effective values

4. Eligibility Algorithm

- 4.1 Signature
- 4.2 Steps
- 4.3 Status precedence
- 4.4 Worked examples
- 4.5 Edge cases

5. Application Layer

- 5.1 Ports
- 5.2 Handlers
- 5.3 Agents
- 5.4 Orchestration

6. Infrastructure Layer

- 6.1 Adapters
- 6.2 Retrieval
- 6.3 Resilience

7. Data Design

- 7.1 Entity schema
- 7.2 Mapping strategy
- 7.3 Migrations

8. Interface Specifications

- 8.1 Web routes
- 8.2 MCP protocol
- 8.3 Tool schemas
- 8.4 Health endpoints

9. Security Implementation

- 9.1 Enforcement matrix
- 9.2 PII masking
- 9.3 Injection guard
- 9.4 Scope validation

10. Observability Implementation

11. Error Handling

12. Test Design

- 12.1 Suites
- 12.2 Representative cases

13. Configuration Reference

14. Known Gaps and Planned Work

1. Introduction

1.1 Purpose

This Low-Level Design specifies the implementation of the Loan Application and Compliance Review Assistant at component and class level. It is intended to be read alongside HLD-LACR-001, which establishes the architecture, boundaries and rationale that this document realises.

1.2 Conventions

Convention	Meaning
Monospace	A type, member, file, route or configuration key as it appears in code
BR-nn	A release-critical business rule defined in the specification
FR-nn	A functional requirement defined in the specification
Effective value	A fact resolved through verified-over-stated precedence (BR-02)

2. Solution Structure

2.1 Projects

Project	Type	Key contents
Loan.Domain	Class library	Applications, Eligibility, Products, Recommendations, Documents, Common
Loan.Application	Class library	Abstractions, Agents, Documents, ProductAdvice, Recommendations, Verification, Common, DTOs
Loan.Infrastructure	Class library	AzureOpenAI, Search, Documents, MCP, Persistence, SemanticKernel, Telemetry, Resilience, Verification, Migrations
Loan.Web	ASP.NET Core MVC	Controllers, Views, Middleware, Models, wwwroot, SampleDocuments, App_Data
Loan.Workers	Worker service	Indexing, Processing
Tests (6 projects)	NUnit	Domain, Application, Contract, Integration, Prompt, EndToEnd

2.2 Namespace Map

Loan.Domain	
.Applications	LoanApplication, ApplicantFacts, ExtractedField
.Eligibility	EligibilityCalculator, EligibilityIndicators
.Products	ProductRules
.Recommendations	Recommendation, RecommendationCitation, RecommendationAuditEntry
.Documents	ExtractedDocumentRecord, ExtractedFieldRecord, FieldOverrideAuditEntry
.Common	Money, DomainExceptions
Loan.Application	
.Abstractions	IChatModel, IPolicyRetriever, IDocumentExtractor, IVerificationServices, IRepositories, ITelemetryCollector, IDocumentStorageService
.Agents	DocumentAnalysisAgent, EligibilityAnalysisAgent, ComplianceReviewAgent, RecommendationOrchestratorAgent, AgentPrompts, AgentModels
.Common	PiiMasker, PromptInjectionGuard
Loan.Infrastructure	
.AzureOpenAI	AzureOpenAIChatModel, SyntheticChatModel
.Search	AzureAiSearchPolicyRetriever, PolicyIndexer
.MCP	McpToolServer, McpModels
.Persistence	LoanDbContext, SqlRepositories, InMemoryRepositories
.SemanticKernel	SemanticKernelAgentService, Plugins

2.3 Dependency Rules

Enforced by project references and verified by the compiler:

- Loan.Domain declares no package or project references.
- Loan.Application references Domain only.
- Loan.Infrastructure references Application and Domain, and implements Application port interfaces.
- Loan.Web calls Application; Infrastructure types appear only in the composition root (dependency-injection registration).

3. Domain Layer

3.1 Entities and Value Objects

Type	Kind	Key members	Notes
LoanApplication	Aggregate root	ApplicationId, ApplicantId, ProductId, Status, Facts, ProductRules, Indicators, CurrentRecommendation, CreatedAtUtc, UpdatedAtUtc	Mutating members are private-set; state transitions occur through methods such as EvaluateEligibility and SetRecommendation
ApplicantFacts	Entity	SyntheticId, MonthlyGrossIncome, MonthlyDebts, RequestedLoanAmount, EstimatedPropertyValue, CreditScore, verified counterparts and verification flags	Exposes EffectiveMonthlyIncome and EffectiveCreditScore (BR-02)
ProductRules	Value object	MaxDtiRatio, MaxLtvRatio, MinCreditScore, MinMonthlyIncome, MaxLoanAmount, RequiresPropertyValuation, RequiresIdentityVerification, RequiresIncomeVerification, PolicyVersion	Factory methods construct standard mortgage and personal-loan rule sets
EligibilityIndicators	Value object	DebtToIncomeRatio, LoanToValueRatio, per-check booleans, Status, UnmetConditions, EvaluatedAtUtc	Nullable ratios distinguish not-applicable and not-computable from zero
Recommendation	Entity	RecommendationId, DecisionRecommendation, Status, RiskScore, SummaryReasoning, Citations, PolicyViolations, MissingEvidenceItems, ApprovedByOfficerId, ApprovedAtUtc, OfficerDecisionNotes	Audit entries are appended, never replaced (BR-07)
Money	Value object	Amount	Prevents raw decimal arithmetic errors and clarifies intent at call sites

3.2 Enumerations

Enumeration	Values
EligibilityStatus	Eligible, PendingInformation, ReferToHuman, Ineligible
ApplicationStatus	Application lifecycle states from draft through officer decision
RecommendationStatus	Draft and officer-decision states
RecommendationType	The type of recommendation prepared for officer review

3.3 ApplicantFacts — Effective Values (BR-02)

Verified-over-stated precedence is implemented as computed properties rather than as a rule applied at call sites. Because the calculator reads only these properties, using a stated value where a verified one exists is structurally impossible rather than merely discouraged.

```
public Money EffectiveMonthlyIncome =>
    IsIncomeVerified && VerifiedMonthlyIncome.HasValue
        ? VerifiedMonthlyIncome.Value
        : MonthlyGrossIncome;

public int EffectiveCreditScore =>
    IsCreditVerified && VerifiedCreditScore.HasValue
        ? VerifiedCreditScore.Value
        : CreditScore;
```

4. Eligibility Algorithm

`Loan.Domain.Eligibility.EligibilityCalculator` is the authoritative decision-support computation (BR-03). It is a pure static function: no I/O, no clock access, no model involvement. The evaluation timestamp is passed in so results are reproducible.

4.1 Signature

```
public static EligibilityIndicators Evaluate(
    ApplicantFacts facts,
    ProductRules rules,
    DateTime evaluationTimestampUtc)
```

4.2 Steps

#	Step	Logic
1	DTI with zero-income guard	If effective income ≤ 0 : ratio is null, DTI ineligible, and an unmet condition is recorded stating DTI cannot be performed. Otherwise ratio = debts / income, eligible when ratio $\leq$ MaxDtiRatio.
2	LTV with product-applicability guard	If the product does not require property valuation: ratio null, treated as eligible (not applicable). If required but property value ≤ 0 : ratio null, ineligible, unmet condition recorded. Otherwise ratio = loanAmount / propertyValue, eligible when $\leq$ MaxLtvRatio.
3	Threshold checks	Credit score $\geq$ MinCreditScore; effective income $\geq$ MinMonthlyIncome; requested amount $\leq$ MaxLoanAmount. Each failure appends a descriptive unmet condition.
4	Verification checks	If the product requires identity or income verification and the corresponding flag is false, an unmet condition is recorded.
5	Status resolution	Precedence applied as specified in 4.3.

4.3 Status Precedence

Order is significant and deliberate. Pending verification outranks every other outcome, because an application cannot be judged on evidence that has not arrived.

Order	Status	Triggered when	Rationale
1	PendingInformation	A required identity or income verification is outstanding	BR-06 — incomplete evidence must not produce a judgement
2	Ineligible	Zero income; missing property value on a secured product; credit score, income threshold or loan amount outside policy	Hard policy failures, not matters of discretion
3	ReferToHuman	DTI above threshold, or LTV above threshold on a secured product	Ratio breaches may be offset by compensating factors; that judgement belongs to an officer
4	Eligible	All checks passed	Ready for officer review

4.4 Worked Examples

Scenario	Inputs	DTI	LTV	Status
Standard mortgage, all verified	income 8,000; debts 2,400; loan 400,000; property 550,000; score 720	0.30	0.727	Eligible

Scenario	Inputs	DTI	LTV	Status
Personal loan, unsecured	income 5,000; debts 1,500; loan 20,000; no property; score 680	0.30	n/a	Eligible
DTI breach	income 4,000; debts 2,000; loan 150,000; property 300,000; score 700	0.50	0.50	ReferToHuman
Zero income	income 0; debts 1,200	null	—	Ineligible
Income not yet verified	verification required, flag false	computed	computed	PendingInformation

4.5 Edge Cases and Their Handling

Edge case	Handling	Why
Zero or negative income	Ratio set to null, not zero	A zero ratio would read as a perfect DTI — the dangerous failure mode
Unsecured product	LTV null and treated as eligible	An inapplicable check must not block an otherwise eligible applicant
Secured product with no valuation	LTV null and ineligible	An applicable check that cannot be performed is a failure, not a pass
Exact threshold value	Inclusive comparison ($\leq$ for maxima, $\geq$ for minima)	Boundary behaviour is specified and covered by tests
Null arguments	ArgumentNullException thrown at entry	Fail fast rather than compute on partial state

5. Application Layer

5.1 Port Interfaces

Port	Members	Implemented by
IChatModel	GenerateCompletionAsync, GenerateStructuredAsync<T>, StreamCompletionAsync	AzureOpenAIChatModel, SyntheticChatModel
IPolicyRetriever	SearchPolicyAsync(query, productId, effectiveVersion, topK)	AzureAiSearchPolicyRetriever
IDocumentExtractor	Candidate field extraction with provenance	AzureOpenAiDocumentExtractor, SyntheticDocumentExtractor
IIdentityReader	VerifyIdentityAsync(syntheticId)	SyntheticIdentityService
IIncomeReader	VerifyIncomeAsync(syntheticId)	SyntheticIncomeService
ICreditReader	GetCreditScoreAsync(syntheticId)	SyntheticCreditService
ILoanApplicationRepository	GetByIdAsync, persistence of application state	SqlLoanApplicationRepository, in-memory equivalent
IRecommendationRepository	Persist draft and approval state	SqlRecommendationRepository, in-memory equivalent
IDocumentStorageService	Stream-based document storage	AzureBlobDocumentStorageService with local fallback
ITelemetryCollector	RecordToolCall, RecordAgentStageLatency, RecordError, token and latency capture	InMemoryTelemetryCollector

5.2 Command and Query Handlers

The Application layer follows a CQRS-style separation. Commands mutate state through repositories; queries read. Handlers are thin: they orchestrate ports and delegate all business logic to the Domain.

Handler	Responsibility
AskProductQuestionQuery	Guard input, retrieve version-filtered policy evidence, compose a grounded answer with citations and disclaimer
SaveRecommendationDraftCommandHandler	Validate routing state, construct the recommendation, append an audit entry, persist
Document handlers	Validate upload, store, trigger extraction, record provenance, manage confirmation of low-confidence fields
Verification handlers	Invoke typed readers and record timestamped results

5.3 Agents

Agent	Permitted	Prohibited
DocumentAnalysisAgent	Evaluate extraction confidence (< 0.85 is low), identify missing mandatory documents and unconfirmed fields, summarise document health	Numerical DTI/LTV arithmetic; compliance or underwriting decisions

Agent	Permitted	Prohibited
EligibilityAnalysisAgent	Invoke verification tools, request the Domain calculation, explain the resulting factors	Overriding deterministic results; inventing values
ComplianceReviewAgent	Check policy version, consent and citations; raise exceptions	Altering facts; approving an application

5.4 Orchestration

RecommendationOrchestratorAgent.ProcessApplicationAsync executes four instrumented stages and then applies the deterministic override.

```
stage 1 DocumentAnalysis -> telemetry.RecordAgentStageLatency(...)
stage 2 EligibilityAnalysis -> telemetry.RecordAgentStageLatency(...)
stage 3 ComplianceReview -> telemetry.RecordAgentStageLatency(...)
stage 4 OrchestratorSynthesis -> chat completion, temperature 0.1

// The model's synthesis contributes narrative only.
var deterministicStatus = application.Indicators.Status;

string routingState = deterministicStatus switch
{
    EligibilityStatus.PendingInformation => "PendingInformation",
    EligibilityStatus.Ineligible => "ManualReview",
    EligibilityStatus.ReferToHuman => "ManualReview",
    EligibilityStatus.Eligible => "ReadyForOfficerReview",
};
```

BR-01 enforcement point 1 of 3

Routing state is derived from the Domain status. No model output path can set it.




Figure 1 — Orchestration sequence

6. Infrastructure Layer

6.1 Adapters

Adapter	Implements	Notes
AzureOpenAIChatModel	IChatModel	Azure.AI.OpenAI 2.1.0; deployment name from configuration, defaulting to gpt-4o
SyntheticChatModel	IChatModel	Deterministic offline substitute used by the evaluation harness and tests
AzureAiSearchPolicyRetriever	IPolicyRetriever	Hybrid vector + keyword search; returns empty on misconfiguration
AzureOpenAiDocumentExtractor	IDocumentExtractor	LLM-assisted extraction with a synthetic extractor fallback
SqlLoanApplicationRepository	ILoanApplicationRepository	EF Core 8 against SQL Server
SqlRecommendationRepository	IRecommendationRepository	EF Core 8 against SQL Server
AzureBlobDocumentStorageService	IDocumentStorageService	Blob storage with local App_Data fallback
McpToolServer	—	JSON-RPC 2.0 tool server; see section 8.2
SemanticKernelAgentService	—	Kernel with four plugins; not on the live orchestration path (see HLD AD-04)
InMemoryTelemetryCollector	ITelemetryCollector	Bounded in-memory ring of telemetry records

6.2 Retrieval Implementation

The retriever reads endpoint, key and index name from configuration. If any is absent or still contains a placeholder, it logs a warning, records a `SearchUnavailable` telemetry error and returns an empty sequence. It deliberately does not substitute synthetic results — a confident ungrounded answer is a worse failure than an explicit cannot-verify response.

Parameter	Value
Embedding model	text-embedding-3-small
Vector dimensions	1536
Search mode	Hybrid (vector + keyword)
Default index name	loan-policies-index
Default top-K (MCP search_policy)	3
Filtering	Product identifier and effective policy version

6.3 Resilience Policy

Mechanism	Configuration / behaviour
Retries	Bounded retry count with exponential backoff and jitter on transient reads
Consequential writes	Zero retries — prevents duplicate state changes and duplicate audit entries
Timeout	10 seconds per external call

Mechanism	Configuration / behaviour
Circuit breaker	Per-dependency isolation with Closed / Open / HalfOpen states
Cancellation	Caller cancellation tokens honoured through the pipeline
Fallback	Safe degraded response; never a fabricated answer

7. Data Design

7.1 Entity Schema



Aggregates are persisted as JSON documents inside relational rows — the Domain model stays free of ORM concerns

Figure 2 — Persistence entities

Table	Column	Type	Notes
Applications	ApplicationId	string	Primary key
	ApplicantId	string	Owning applicant
	ProductId	string	Product under application
	Status	int (enum)	Application lifecycle state
	FactsJson	nvarchar(max)	Serialised ApplicantFacts
	ProductRulesJson	nvarchar(max)	Serialised ProductRules snapshot
	IndicatorsJson	nvarchar(max), null	Serialised EligibilityIndicators
	DocumentsJson	nvarchar(max)	Extracted document records
	DocumentAuditTrailJson	nvarchar(max)	Field override audit entries
Recommendations	CreatedAtUtc / UpdatedAtUtc	datetime2	Lifecycle timestamps
	RecommendationId	string	Primary key
	ApplicationId	string	Foreign key to Applications
	DecisionRecommendation / Status	int (enum)	Recommendation type and state
	RiskScore	float	0.0 low risk to 1.0 high risk
	SummaryReasoning	nvarchar(max)	Model-generated narrative
	CitationsJson	nvarchar(max)	Title, version, section, excerpt
	AuditTrailJson	nvarchar(max)	Append-only audit entries
	ApprovedByOfficerId / ApprovedAtUtc	string / datetime2, null	Set only on officer approval

7.2 Mapping Strategy

Domain aggregates are serialised to JSON columns rather than mapped field-by-field. Persistence entities expose `ToDomain()` and construction helpers that rehydrate Domain objects, so the Domain model carries no ORM attributes and no schema coupling. The trade-off, accepted at this scale, is reduced queryability of nested values.

7.3 Migrations

EF Core migrations are held in `Loan.Infrastructure/Migrations`, beginning with `InitialCreate`. A design-time factory allows migrations to be generated without running the web host. Migrations are additive to remain forward-compatible with the documented rollback procedure.

8. Interface Specifications

8.1 Web Routes

Controller	Route / action	Method	Authorization
ApplicantController	Index, CreateApplication, SaveDraft, AskQuestion, UploadDocument, ConfirmField	GET / POST	Applicant, Administrator
OfficerController	Index, Review, SubmitDecision, RequestInformation, StreamRecommendationDraft	GET / POST	LoanOfficer, Administrator
ComplianceController	Index, Review	GET	ComplianceReviewer, Administrator
AdminController	Index, UploadPolicyDocument, SyncSeedPolicies	GET / POST	Administrator
AccountController	Sign-in, sign-out, account actions	GET / POST	Mixed
McpController	api/mcp	POST	Claims-based; SystemWorker default
HealthController	health, health/ready, health/details, health/telemetry	GET	Anonymous

8.2 MCP Protocol

Transport is a single POST /api/mcp endpoint accepting JSON-RPC 2.0. The actor is resolved from authenticated claims; header-supplied actors are honoured only in Development or when a test key header is present, and otherwise the request is treated as a restricted SystemWorker.

Method	Behaviour
initialize	Returns protocolVersion 2024-11-05, capabilities and serverInfo (LoanAssistant-MCP-Server 1.0.0)
notifications/initialized	Acknowledged with an empty result
ping	Liveness acknowledgement
tools/list	Returns the five registered tools with their input schemas
tools/call	Dispatches to the named tool; records a tool-call telemetry event
(unknown)	JSON-RPC error -32601 MethodNotFound

Error codes. -32600 invalid request; -32601 method not found; -32603 internal error. Tool-level failures are returned as structured error results with a category prefix such as InvalidArguments, UnknownApplication, CrossApplicationMismatch or UnauthorizedAccess.

8.3 Tool Schemas

Tool	Required arguments	Returns	Guards
get_identity_status	applicationId, syntheticId	Identity verification record	Scope validation
get_income_verification	applicationId, syntheticId	Income verification record	Scope validation

Tool	Required arguments	Returns	Guards
get_credit (alias get_credit_score)	applicationId, syntheticId	Credit score record	Scope validation
search_policy	query (optional productId)	Policy results with citations	Argument validation; top-K 3
save_draft	applicationId, summaryReasoning, routingState (optional unresolvedItems, policyExceptions, citations)	Persisted recommendation	Approve / Reject / Approved / Rejected rejected

BR-01 enforcement point 2 of 3

save_draft rejects final-decision routing states with an InvalidArguments error. Permitted values are PendingInformation, ManualReview and ReadyForOfficerReview.

8.4 Health Endpoints

Endpoint	Returns
GET /health	Process liveness
GET /health/ready	Readiness including SQL connectivity
GET /health/details	Component-level diagnostics
GET /health/telemetry?count=n	Most recent telemetry records

9. Security Implementation

9.1 Enforcement Matrix

Rule	Enforcement point	Mechanism
BR-01	RecommendationOrchestratorAgent	Routing state derived from the Domain EligibilityStatus
BR-01	McpToolServer.HandleSaveDraftAsync	Approve / Reject routing states rejected
BR-01	OfficerController	Officer role required for any status change
BR-02	ApplicantFacts	Effective-value properties; calculator reads only these
BR-03	EligibilityCalculator	Pure deterministic computation in Domain
BR-04	AzureAiSearchPolicyRetriever	Version filtering; citation metadata carried through to the answer
BR-05	PiiMasker	Masking applied before model invocation; telemetry excludes content
BR-06	EligibilityCalculator	PendingInformation takes precedence over all other statuses
BR-07	OfficerController and Recommendation	Role check plus append-only audit entry

BR-01 enforcement point 3 of 3

Status changes require an authenticated officer role and write an immutable audit entry. Three independent layers means no single failure enables a model-made decision.

9.2 PII Masking

PiiMasker applies compiled regular expressions before any model call.

Pattern	Example input	Masked output
SSN / national ID	123-45-6789	***-**-6789
Account number	9876543210	*****3210
Email address	john.doe@example.com	jo***@example.com

A dedicated MaskSsn helper returns ***-**-XXXX when the input is absent or too short, so a malformed value can never pass through unmasked.

9.3 Prompt Injection Guard

PromptInjectionGuard.IsInjectionAttempt matches a case-insensitive keyword list covering override, privilege-escalation, prompt-disclosure and forced-approval attempts, supplemented by a regular expression for spacing variants. On a match, a fixed refusal is returned and the attempt is logged by category.

```
"SYSTEM OVERRIDE"                "IGNORE PREVIOUS INSTRUCTIONS"
"IGNORE ALL PREVIOUS INSTRUCTIONS" "DISREGARD POLICY" / "DISREGARD RULES"
"YOU ARE NOW IN DEVELOPER MODE"    "GRANT APPROVAL"
"BYPASS RULES" / "BYPASS VERIFICATION"
"OUTPUT|PRINT|SHOW SYSTEM PROMPT" "SET STATUS APPROVED"
"APPROVE LOAN IMMEDIATELY"        "IGNORE GUIDELINES"
"ACT AS AN UNRESTRICTED"

regex: (?:system\s*override|ignore\s+(?:all\s+)?previous\s+instructions)
```

Design note — why this is not the primary defence

A pattern list cannot cover every paraphrase and is therefore treated as a noise filter. The load-bearing controls are architectural: a successful injection still cannot approve a loan, cannot write a final decision through `save_draft`, and cannot read another applicant's data. A learned classifier is the identified improvement.

9.4 Scope Validation

`ValidateApplicationScopeAsync` runs before every verification read.

1. Load the application by identifier.
-> not found : `UnknownApplication`
2. Confirm the application has a bound synthetic identity.
-> unbound : `InvalidApplicationState`
3. Compare the supplied `syntheticId` with the bound value (case-insensitive).
-> mismatch : `CrossApplicationMismatch` (access denied)
4. Otherwise proceed with the read.

10. Observability Implementation

Signal	Captured by	Exposed through
Prompt / completion / total tokens	Chat model adapter	Telemetry records
LLM and retrieval latency	Adapters	Telemetry records
Agent stage latency	RecordAgentStageLatency per stage	Telemetry records
Tool call count	RecordToolCall on tools/call	Telemetry records
Errors	RecordError with a category	Telemetry records
Correlation identifier	Middleware	X-Correlation-ID request and response header

11. Error Handling

Condition	Handling	Surfaced as
Invalid tool arguments	Rejected before execution	InvalidArguments error result
Unknown application	Repository returns null	UnknownApplication error result
Cross-application access	Scope validation fails	CrossApplicationMismatch; existence not disclosed
Unauthorized action	Role check fails	UnauthorizedAccess error result
Injection attempt	Guard short-circuits	Fixed refusal, zero citations, logged
Retrieval unavailable	Empty result set	Honest cannot-verify response
Model unavailable	Circuit breaker and fallback	Safe degraded response
Unhandled exception	Caught at the protocol boundary	JSON-RPC -32603 InternalError
Null domain arguments	ArgumentNullException	Fail fast before computation

12. Test Design

12.1 Suites

Suite	Tests	Focus
Loan.Domain.Tests	20	Eligibility computation, exact boundaries, status precedence, zero-income and product-applicability guards
Loan.Application.Tests	59	Handlers, agents, MCP application scoping, cross-application isolation, save-draft restrictions
Loan.ContractTests	4	MCP protocol conformance, registered tool set, initialize response
Loan.IntegrationTests	23	SQL persistence, live Azure OpenAI completion, Semantic Kernel configuration
Loan.PromptTests	21	Prompt behaviour, refusal handling, grounding
Loan.EndToEndTests	34	Web routes, DI container composition, end-to-end journeys
Total	161	All passing, zero failures

12.2 Representative Cases

Test	Asserts
GetRegisteredTools_ShouldReturnFiveApprovedTools	The tool surface is exactly the five allow-listed operations
Initialize_ShouldReturnMcpProtocol20241105	Protocol version negotiation is correct
ToolsCall_GetIdentityStatus_ShouldReturnVerifiedResult	A scoped verification read succeeds end to end
ToolsCall_UnregisteredTool_ShouldReturnErrorResult	Unknown tools are refused
McpSaveDraftTests	Approve and Reject routing states are rejected (BR-01)
McpApplicationScopingTests	Mismatched application and synthetic identifiers are denied
CrossApplicationIsolationTests	One application cannot read another's data
Domain boundary tests	Exact-threshold behaviour for DTI, LTV and credit score

13. Configuration Reference

Key	Purpose	Default / note
AzureOpenAI:Endpoint	Azure OpenAI resource endpoint	Required; placeholder detected and treated as unconfigured
AzureOpenAI:ApiKey	Azure OpenAI key	User Secrets locally; never committed
AzureOpenAI:DeploymentName	Chat deployment	gpt-4o
AzureAISearch:Endpoint	Search service endpoint	Required for retrieval
AzureAISearch:ApiKey	Search service key	User Secrets locally
AzureAISearch:IndexName	Policy index name	loan-policies-index
ConnectionStrings (SQL)	Application database	SQL Server via EF Core
Blob storage connection	Document storage	Falls back to local App_Data

14. Known Gaps and Planned Work

#	Gap	Impact	Planned resolution
G1	The recommendation draft does not carry a promptVersion field, although the specification's output schema lists one and prompts carry an inline "Version v1.0" marker	Low — prompts are versioned assets, but the identifier is not surfaced on the output	Add the field to the draft and populate it from the prompt asset
G2	AI evaluation executed against the offline deterministic harness	Low — behavioural assertions valid; performance baselines absent	Re-run the 20-prompt suite against the live gpt-4o deployment
G3	Prompt-injection detection is pattern-based	Medium — paraphrase can evade detection, though not consequence	Replace with a learned classifier or model-based judge
G4	Telemetry is in-process only	Low — signals captured but not exported	Export to Application Insights / OpenTelemetry
G5	Cloud deployment outstanding (Slice 10 in progress)	Low — verified locally across all four personas	Deploy with configuration separated from code and a documented rollback path

End of Low-Level Design. Architectural rationale, context and non-functional strategy are documented in HLD-LACR-001.