1.Display all customers who live in 'Delhi'.

```
-- 1.Display all customers who live in 'Delhi'.
select * from customers
where city ='Delhi';
```

Result Grid | Filter Rows: | Edit: | Export/Import: | Wrap Cell Content:

customer_id	name	email	phone_number	city	address
2	Rohini Verma	rohini.verma@yahoo.com	9823456789	Delhi	B-23, Saket
5	Manish Kumar	NULL	9834567890	Delhi	D-45, Lajpat Nagar
18	Sonali Mishra	NULL	9878345678	Delhi	N-54, Karol Bagh
NULL	NULL	NULL	NULL	NULL	NULL

3.Find the average rating of all restaurants in 'Mumbai'.

```
5 •  select avg(rating) from restaurants
6    where city ='Mumbai';
```

Result Grid | Filter Rows:

avg(rating)
4.300000

3.List all customers who have placed at least one order

```sql
-- 3.List all customers who have placed at least one order.
select customers.name ,count(order_id) as total_order from orders
join customers
on customers.customer_id=orders.customer_id
group by customers.name
having count(order_id)>=1;
```

Result Grid | Filter Rows: | Export: | Wra

name	total_order
Amit Sharma	2
Rohini Verma	3
Rajesh Gupta	3
Sneha Mehta	2
Manish Kumar	4
Priya Singh	3
Vikas Reddy	3

Result 5

Output

4.Display the total number of orders placed by each customer.

```sql
-- 4.Display the total number of orders placed by each customer.
select customers.customer_id,customers.name ,count(order_id) as total_order from orders
join customers
on customers.customer_id=orders.customer_id
group by customers.customer_id,customers.name;
```

Result Grid | Filter Rows: | Export: | Wrap

customer_id	name	total_order
1	Amit Sharma	2
2	Rohini Verma	3
3	Rajesh Gupta	3
4	Sneha Mehta	2
5	Manish Kumar	4
6	Priya Singh	3
7	Vikas Reddy	3

Result 6

5.Find the total revenue generated by each restaurant

```
-- 5.Find the total revenue generated by each restaurant.
select restaurants.name,sum(amount_paid) as revenue from restaurants
join orders
on restaurants.restaurant_id=orders.restaurant_id
join payment on payment.order_id = orders.order_id
group by restaurants.name;
```

Result Grid | Filter Rows:

name	revenue
Biryani House	2700.00
Taste of Punjab	600.00
Spice of India	1250.00
Coastal Delight	1650.00
Tandoori Flames	1200.00
Curry Pot	1750.00
Veggie Delight	950.00

Result 7

Output

6.Find the top 5 restaurants with the highest average rating

```sql
-- 6.Find the top 5 restaurants with the highest average rating.
select name,avg(rating) from restaurants
group by name
order by avg(rating) desc
limit 5;
```

Result Grid | Filter Rows: | Export: | Wra

name	avg(rating)
Biryani House	4.800000
Paradise Biryani	4.800000
Lucknowi Nawabi	4.700000
Royal Biryani	4.700000
Flavours of Bengal	4.600000

7.Display all customers who have never placed an order.

```sql
-- 7.Display all customers who have never placed an order.
select customers.customer_id,customers.name,count(order_id) from customers
left join orders
on customers.customer_id=orders.customer_id
group by customers.customer_id,customers.name
having count(order_id)=0;
```

Result Grid | Filter Rows: | Export: | Wrap Cell Content:

customer_id	name	count(order_id)
24	Sonal Kaur	0
25	Vivek Malhotra	0
26	Divya Iyer	0
27	Rakesh Yadav	0
28	Mona Sharma	0
29	Sudha Pillai	0
30	Gaurav Khanna	0

Result 13

8.Find the number of orders placed by each customer in 'Mumbai'.

```
-- 8.Find the number of orders placed by each customer in 'Mumbai'.
select customers.name,count(order_id)as total_order from customers
join orders
on customers.customer_id=orders.customer_id
where city='Mumbai'
group by customers.name;
```

esult Grid | Filter Rows: | Export: | Wrap Cell Content:

name	total_order
Amit Sharma	2
Rajesh Gupta	3
Arjun Desai	2
Ravi Singh	2

9.Display all orders placed in the last 30 days.

```
-- 9.Display all orders placed in the last 30 days.
select * from orders
where order_date>=(select max(order_date)- interval 30 da
from orders);
```

Result Grid | Filter Rows: | Edit: | Export/Import: | Wrap Cell Content:

order_id	customer_id	restaurant_id	order_date	total_amount	status
1	1	3	2024-08-01 00:00:00	750.00	Completed
2	2	5	2024-08-02 00:00:00	600.00	Completed
3	3	1	2024-08-04 00:00:00	0.00	Cancelled
4	4	7	2024-08-01 00:00:00	850.00	Completed
5	5	2	2024-08-03 00:00:00	1200.00	Completed
6	1	4	2024-08-06 00:00:00	500.00	Processing
7	6	8	2024-08-03 00:00:00	950.00	Completed

orders 3

10.List all delivery partners who have completed more than 1 delivery

```sql
-- 10.List all delivery partners who have completed more than 1 delivery
select deliverypartners.name,count(order_id) as total_order from deliverypartners
join orderdelivery
on deliverypartners.partner_id= orderdelivery.partner_id
group by deliverypartners.name
having count(order_id)>1;
```

Result Grid | Filter Rows: | Export: | Wrap Cell Content:

name	total_order
Suresh Reddy	6
Anita Desai	4
Ravi Kumar	5
Rajesh Gupta	4
Priya Patel	3
Sneha Iyer	2
Amit Sharma	2

Result 4

11.Find the customers who have placed orders on exactly three different days

```sql
-- 11.Find the customers who have placed orders on exactly three different days
select c.customer_id ,c.name ,count(distinct o.order_date) as total_order from customers c
join orders o
on c.customer_id=o.customer_id
group by c.customer_id,c.name
having count(distinct o.order_date)=3;
```

sult Grid | Filter Rows: | Export: | Wrap Cell Content:

customer_id	name	total_order
2	Rohini Verma	3
6	Priya Singh	3
8	Anjali Patel	3
14	Nidhi Saxena	3
15	Ashok Kumar	3
18	Sonali Mishra	3

12.Find the delivery partner who has worked with the most different customers.

```sql
SELECT od.partner_id,
       dp.name,
       COUNT(DISTINCT o.customer_id) AS total_unique_customers
FROM orderdelivery od
JOIN orders o
    ON od.order_id = o.order_id
JOIN deliverypartners dp
    ON od.partner_id = dp.partner_id
GROUP BY od.partner_id, dp.name
ORDER BY total_unique_customers DESC
LIMIT 1;
```

Result Grid | Filter Rows: | Export: | Wrap Cell Content: | Fetch rows:

partner_id	name	total_unique_customers
4	Suresh Reddy	6

13.Identify customers who have the same city and have placed orders at the same restaurants, but on different dates.

```sql
-- 13.Identify customers who have the same city and have placed orders at the same restaurants, but on different dates.
SELECT
    c1.customer_id AS customer1,
    c2.customer_id AS customer2,
    c1.city,
    r.name,
    o1.order_date AS date1,
    o2.order_date AS date2
FROM customers c1
JOIN customers c2
    ON c1.city = c2.city
   AND c1.customer_id < c2.customer_id          -- avoid duplicates
JOIN orders o1 ON o1.customer_id = c1.customer_id
JOIN orders o2 ON o2.customer_id = c2.customer_id
JOIN restaurants r ON r.restaurant_id = o1.restaurant_id
                  AND r.restaurant_id = o2.restaurant_id
```

89

Result Grid | Filter Rows: | Export: | Wrap Cell Content:

customer1	customer2	city	name	date1	date2
5	18	Delhi	Biryani House	2024-08-04 00:00:00	2024-08-05 00:00:00
19	23	Mumbai	Veggie Delight	2024-08-03 00:00:00	2024-08-09 00:00:00
5	18	Delhi	Biryani House	2024-08-07 00:00:00	2024-08-05 00:00:00

esult 7 ×