

Environment Variable Audit Report

Next.js App Router + Supabase + PostgreSQL + Razorpay

Scope

All environment access found in application source, Next.js configuration, proxy/auth code, email/payment integrations, and deployment-related code. No files were modified and no secret values are included.

1. Executive Summary

Finding	Result
Variables identified	23 application/framework environment variables
Supabase service-role reference	Yes - referenced only by lib/supabase-admin.ts in application code
NEXT_PUBLIC_ secret exposure	No service-role, payment secret, webhook secret, scheduler secret, or email credential uses the NEXT_PUBLIC_ prefix
Razorpay build failure risk	Missing or blank Razorpay variables do not fail the Next.js/Vercel build; affected payment/webhook requests fail at runtime

2. Complete Variable Inventory

Exact variable	Files where referenced	Requirement	Public-safe?
NEXT_PUBLIC_SUPABASE_URL	lib/api-auth.ts lib/supabase.ts lib/supabase-admin.ts proxy.ts	Required for Supabase functionality. Build-time for client bundle and runtime for server/proxy use.	Yes
NEXT_PUBLIC_SUPABASE_ANON_KEY	lib/api-auth.ts lib/supabase.ts proxy.ts	Required for browser auth and API authentication. Build-time for client bundle and runtime use.	Yes
SUPABASE_SERVICE_ROLE_KEY	lib/supabase-admin.ts	Runtime-only. Required for trusted admin/server operations; optional for build.	NO
NEXT_PUBLIC_SITE_URL	app/api/email/events/route.ts app/api/jobs/publish-scheduled/route.ts app/forgot-password/page.tsx lib/auth-redirects.ts lib/email/templates.ts lib/seo.ts	Optional in code, but required in production for canonical URLs, metadata, sitemap, redirects and email links.	Yes
NEXT_PUBLIC_APP_URL	lib/seo.ts	Optional SEO URL fallback.	Yes
NEXT_PUBLIC_AUTH_CALLBACK_URL	lib/auth-redirects.ts	Optional authentication callback override.	Yes, if trusted
NEXT_PUBLIC_PASSWORD_RESET_REDIRECT_URL	app/forgot-password/page.tsx	Optional password-reset redirect override.	Yes, if trusted
VERCEL_PROJECT_PRODUCTION_URL	lib/email/templates.ts lib/seo.ts	Optional Vercel-provided production URL fallback.	Yes, non-secret
VERCEL_ENV	lib/seo.ts	Optional Vercel deployment metadata.	Yes, non-secret
RAZORPAY_KEY_ID	lib/razorpay-server.ts	Runtime-required for payment operations.	Yes in isolation; current code keeps it server-only
RAZORPAY_KEY_SECRET	lib/razorpay-server.ts	Runtime-required for Razorpay API requests and payment verification.	NO
RAZORPAY_WEBHOOK_SECRET	lib/razorpay-server.ts	Runtime-required for webhook signature verification.	NO

Exact variable	Files where referenced	Requirement	Public-safe?
JOB_SCHEDULER_SECRET	app/api/jobs/publish-scheduled/route.ts	Runtime-required when scheduled publishing is enabled.	NO
CRON_SECRET	app/api/email/process/route.ts app/api/jobs/publish-scheduled/route.ts	Optional fallback secret for scheduler/email endpoint authorization.	NO
EMAIL_QUEUE_SECRET	app/api/email/process/route.ts	Runtime-required when email queue processing is enabled.	NO
EMAIL_HTTP_ENDPOINT	lib/email/providers.ts	Optional runtime email-provider endpoint. Missing value selects the missing-provider adapter.	NO; keep server-only
EMAIL_HTTP_AUTH_HEADER_NAME	lib/email/providers.ts	Optional runtime email-provider header configuration.	NO; keep server-only
EMAIL_HTTP_AUTH_HEADER_VALUE	lib/email/providers.ts	Optional runtime provider credential.	NO
EMAIL_FROM_ADDRESS	lib/email/providers.ts	Optional runtime sender address; code has a fallback.	Yes, non-secret
EMAIL_REPLY_TO_ADDRESS	lib/email/providers.ts	Optional runtime reply-to address.	Yes, non-secret
EMAIL_LOGO_URL	lib/email/templates.ts	Optional runtime email branding URL.	Yes, non-secret
EMAIL_SUPPORT_ADDRESS	lib/email/templates.ts	Optional runtime support contact.	Yes, non-secret

3. NODE_ENV References

NODE_ENV is framework-provided and is not a manually managed secret. It is read for development-only logging, production cookie behavior, SEO/indexing behavior, production headers, and runtime checks.

Exact variable	Files where referenced	Requirement / exposure
NODE_ENV	app/api/admin/[section]/route.ts app/api/email/events/route.ts app/api/jobs/[slug]/view/route.ts app/api/jobs/publish-scheduled/route.ts app/api/recruiter/jobs/route.ts app/applications/candidate-applications.tsx app/applications/page.tsx app/applications/recruiter-applications.tsx app/auth/callback/page.tsx app/dashboard/use-dashboard-data.ts app/interviews/interview-schedule-dialog.tsx app/interviews/page.tsx app/interviews/recruiter-interviews.tsx app/jobs/[slug]/job-application-panel.tsx app/jobs/[slug]/job-view-tracker.tsx app/jobs/saved-jobs-state.tsx app/post-job/page.tsx lib/api-auth.ts lib/auth-errors.ts lib/candidate-dashboard.ts lib/dashboard-data.ts lib/dashboard-jobs.ts lib/email/client.ts lib/email/queue.ts lib/job-alerts.ts lib/notification-server.ts lib/public-company.ts lib/public-jobs.ts lib/saved-jobs.ts lib/seo.ts lib/sitemap-data.ts lib/supabase.ts next.config.ts	Framework-provided at build/runtime. No manual configuration required. Non-secret; do not create a custom NEXT_PUBLIC_NODE_ENV variable.

4. SUPABASE_SERVICE_ROLE_KEY Review

Referenced: Yes.

Application code: `lib/supabase-admin.ts`.

Behavior: The module is marked `server-only` and creates a privileged Supabase client only when both the Supabase URL and `service-role-key` are present.

Exposure assessment: Unsafe for `NEXT_PUBLIC_exposure`. It must remain a server-only Vercel environment variable and must never be serialized, logged, or returned to the browser.

5. Razorpay Blank/Missing Variable Behavior

Variable	Build behavior	Runtime behavior
<code>RAZORPAY_KEY_ID</code>	Does not fail the build.	Payment configuration becomes unavailable; order creation and verification return a runtime configuration error.
<code>RAZORPAY_KEY_SECRET</code>	Does not fail the build.	Razorpay API requests and checkout verification cannot run.
<code>RAZORPAY_WEBHOOK_SECRET</code>	Does not fail the build.	Webhook endpoint returns a runtime not-configured response and cannot verify signatures.

The current implementation reads Razorpay configuration when payment or webhook handlers execute rather than throwing at module import. A production build can therefore complete with missing values, but payment functionality will not be operational until the runtime variables are configured.

6. Configuration Notes

- The public Supabase URL and anon key are intentionally browser-safe and are required for client-side authentication to work.
- Production should set `NEXT_PUBLIC_SITE_URL` even though the code has safe fallbacks; otherwise canonical metadata, absolute email links and production indexing behavior are incomplete.
- Email provider variables are runtime-only. Without `EMAIL_HTTP_ENDPOINT`, the application selects its missing-provider adapter and email delivery does not occur.
- `JOB_SCHEDULER_SECRET`, `EMAIL_QUEUE_SECRET`, and the `CRON_SECRET` fallback must not be exposed to the client.
- The `.env.example` file documents the deployment/application variables. It contains placeholders only; this report intentionally reproduces no environment values.

Audit conclusion

The codebase references 23 environment variables. The only privileged Supabase key is `SUPABASE_SERVICE_ROLE_KEY`, used in one server-only module. Blank or missing Razorpay variables do not cause a Vercel build failure, but they disable payment and webhook operations at runtime.