Student Name: Abbas Abdelaziz Altunayan Student ID: 2240004112

Lab 3 — Image Manipulations using OpenCV

ARTI 404 – Image Processing

Task 1: Geometric transformations (resize, rotate 120°, shear) **Task 2:** Intensity transformations (negative, log transform, power-law / gamma)

The input image (`images/input.jpg`) is the `astronaut` sample image from `scikit-image` (https://scikit-image.org/docs/stable/auto_examples/data/plot_general.html), saved to disk so it can be read with `cv2.imread` like any other image.

In [1]:

```
import cv2
import numpy as np
import matplotlib.pyplot as plt
import skimage as ski
import os

os.makedirs('images', exist_ok=True)

# Get a sample image from scikit-image and save it as our input image
sample = ski.data.astronaut()                          # RGB array
bgr = cv2.cvtColor(sample, cv2.COLOR_RGB2BGR)
cv2.imwrite('images/input.jpg', bgr)

# Step 1: Read the image using OpenCV
img = cv2.imread('images/input.jpg')
print('Image shape:', img.shape)
print('Image dtype:', img.dtype)

def show(img_bgr, title):
    plt.figure(figsize=(5, 5))
    if len(img_bgr.shape) == 2:
        plt.imshow(img_bgr, cmap='gray')
    else:
        plt.imshow(cv2.cvtColor(img_bgr, cv2.COLOR_BGR2RGB))
    plt.title(title)
    plt.axis('off')
    plt.show()

show(img, 'Input Image')
```

```
Image shape: (512, 512, 3)
Image dtype: uint8
```



Task 1 — Geometric Transformations

1.1 Increase the size of the image


In [2]:

```
# Scale up the image by 1.5x using bicubic interpolation (better quality for
enlarging)
scale_factor = 1.5
resized = cv2.resize(img, None, fx=scale_factor, fy=scale_factor,
interpolation=cv2.INTER_CUBIC)

print('Original size:', img.shape[:2])
print('Resized size :', resized.shape[:2])

cv2.imwrite('images/task1_resized.jpg', resized)
show(resized, f'Resized ({scale_factor}x)')
```

```
Original size: (512, 512)
Resized size : (768, 768)
```



1.2 Rotate the image by 120 degrees

In [3]:

```
(h, w) = img.shape[:2]
center = (w // 2, h // 2)

angle = 120
M_rotate = cv2.getRotationMatrix2D(center, angle, 1.0)

# Compute new bounding dimensions so the rotated image isn't cropped
cos = np.abs(M_rotate[0, 0])
sin = np.abs(M_rotate[0, 1])
new_w = int((h * sin) + (w * cos))
new_h = int((h * cos) + (w * sin))

# Adjust the rotation matrix to account for translation
M_rotate[0, 2] += (new_w / 2) - center[0]
M_rotate[1, 2] += (new_h / 2) - center[1]

rotated = cv2.warpAffine(img, M_rotate, (new_w, new_h))

cv2.imwrite('images/task1_rotated_120.jpg', rotated)
show(rotated, 'Rotated 120 degrees')
```



1.3 Perform Shear operations over the image

In [4]:

```
# Shear along the x-axis using an affine transform
shear_factor = 0.3

M_shear = np.float32([[1, shear_factor, 0],
                      [0, 1,            0]])

# Widen the output canvas so the sheared content isn't cut off
new_w = int(w + abs(shear_factor) * h)
sheared = cv2.warpAffine(img, M_shear, (new_w, h))

cv2.imwrite('images/task1_sheared.jpg', sheared)
show(sheared, f'Sheared (factor={shear_factor})')
```




Task 1 — Summary

In [5]:

```
fig, axs = plt.subplots(1, 4, figsize=(20, 5))
titles = ['Original', 'Resized (1.5x)', 'Rotated 120°', 'Sheared']
images_t1 = [img, resized, rotated, sheared]

for ax, im, t in zip(axs, images_t1, titles):
    ax.imshow(cv2.cvtColor(im, cv2.COLOR_BGR2RGB))
    ax.set_title(t)
    ax.axis('off')

plt.tight_layout()
plt.savefig('images/task1_summary.jpg')
plt.show()
```



Task 2 — Intensity Transformations

In [6]:

```
# Work in grayscale for intensity transformations
gray = cv2.cvtColor(img, cv2.COLOR_BGR2GRAY)
show(gray, 'Grayscale (base for intensity transforms)')
```



2.1 Create a Negative Image

In [7]:

```
# Negative transformation: s = (L-1) - r, where L = 256 for 8-bit images
negative = 255 - gray

cv2.imwrite('images/task2_negative.jpg', negative)
show(negative, 'Negative Image')
```



2.2 Log Transformation

In [8]:

```
# Log transformation: s = c * log(1 + r)
# c is chosen so the output maps to the full 0-255 range
# (cast to float first -- 1 + uint8(255) would overflow to 0)
c = 255 / np.log(1 + float(np.max(gray)))
log_transformed = c * np.log(1 + gray.astype(np.float64))
log_transformed = np.array(log_transformed, dtype=np.uint8)

cv2.imwrite('images/task2_log.jpg', log_transformed)
show(log_transformed, f'Log Transform (c={c:.2f})')
```



2.3 Power-Law (Gamma) Transformation

In [9]:

```
# Power-law transformation: s = c * r^gamma
# gamma < 1 increases contrast in the dark regions (brightens shadows)
gamma = 0.4
gamma_corrected = np.array(255 * (gray / 255.0) ** gamma, dtype=np.uint8)

cv2.imwrite('images/task2_gamma.jpg', gamma_corrected)
show(gamma_corrected, f'Power-Law Transform (gamma={gamma})')
```



Task 2 — Summary

In [10]:

```
fig, axs = plt.subplots(1, 4, figsize=(20, 5))
titles2 = ['Grayscale (Original)', 'Negative', 'Log Transform', f'Power-Law
(gamma={gamma})']
images_t2 = [gray, negative, log_transformed, gamma_corrected]

for ax, im, t in zip(axs, images_t2, titles2):
    ax.imshow(im, cmap='gray')
    ax.set_title(t)
    ax.axis('off')

plt.tight_layout()
plt.savefig('images/task2_summary.jpg')
plt.show()
```

