

AtlasMap Design Time Service API Reference

Version 1.39.0-SNAPSHOT, 2018-11-21

Design Time Service

1. Core	1
1.1. Paths	1
1.1.1. List FieldActions	1
1.1.2. Upload Library	1
1.1.3. Remove All Mappings	1
1.1.4. Process Mapping	2
1.1.5. Validate Mapping	3
1.1.6. Create Mapping	3
1.1.7. Get Mapping	4
1.1.8. Update Mapping	4
1.1.9. Remove Mapping	5
1.1.10. List Mappings	6
1.1.11. Ping	6
1.2. Definitions	7
1.2.1. ActionDetail	7
1.2.2. ActionDetails	8
1.2.3. ActionParameter	8
1.2.4. ActionParameters	8
1.2.5. Actions	9
1.2.6. AtlasLibraryLoader	9
1.2.7. AtlasMapping	9
1.2.8. AtlasMappingResult	9
1.2.9. Audit	10
1.2.10. Audits	10
1.2.11. BaseMapping	10
1.2.12. ClassLoader	11
1.2.13. Constant	11
1.2.14. Constants	11
1.2.15. DataSource	11
1.2.16. Field	12
1.2.17. FieldGroup	13
1.2.18. LookupEntry	14
1.2.19. LookupTable	14
1.2.20. LookupTables	15
1.2.21. Mapping	15
1.2.22. Mappings	16
1.2.23. ProcessMappingResponse	16
1.2.24. Properties	16

1.2.25. Property	16
1.2.26. StringMap	17
1.2.27. StringMapEntry	17
1.2.28. TargetDocument	17
1.2.29. Validation	17
1.2.30. Validations	18
2. Java	19
2.1. Paths	19
2.1.1. Inspect Class	19
2.1.2. Inspect Class	19
2.1.3. Generate Maven Classpath	20
2.1.4. Simple	20
2.2. Definitions	21
2.2.1. Actions	21
2.2.2. JavaClass	21
2.2.3. JavaEnumField	23
2.2.4. JavaEnumFields	25
2.2.5. JavaField	25
2.2.6. JavaFields	27
2.2.7. MavenClasspathResponse	27
2.2.8. ModifierList	27
2.2.9. StringList	27
3. JSON	28
3.1. Paths	28
3.1.1. Inspect JSON	28
3.1.2. Inspect JSON via URI	28
3.1.3. Simple	29
3.2. Definitions	29
3.2.1. Actions	29
3.2.2. Field	30
3.2.3. Fields	31
3.2.4. JsonDocument	31
3.2.5. JsonInspectionResponse	31
4. XML	32
4.1. Paths	32
4.1.1. Inspect XML	32
4.1.2. Inspect XML via URI	32
4.1.3. Simple	33
4.2. Definitions	33
4.2.1. Actions	33
4.2.2. Field	33

4.2.3. Fields	34
4.2.4. XmlDocument	35
4.2.5. XmlInspectionResponse	35
4.2.6. XmlNamespace	35
4.2.7. XmlNamespaces	36

Chapter 1. Core

1.1. Paths

1.1.1. List FieldActions

GET /fieldActions

Description

Retrieves a list of available field action

Responses

HTTP Code	Description	Schema
200	Return a list of field action detail	ActionDetails

Produces

- `application/json`

1.1.2. Upload Library

POST /library

Description

Upload library jar files

Responses

HTTP Code	Description	Schema
200	Succeeded to upload library	No Content

Consumes

- `multipart/mixed`

1.1.3. Remove All Mappings

DELETE /mapping/RESET

Description

Remove all mapping files saved on the server

Responses

HTTP Code	Description	Schema
200	All mapping files were removed successfully	No Content
204	Unable to remove all mapping files	No Content

Produces

- `application/json`

1.1.4. Process Mapping

PUT /mapping/process

Description

Process Mapping by feeding input data

Responses

HTTP Code	Description	Schema
200	Return a mapping result	ProcessMappingResponse
204	Skipped empty mapping execution	No Content

Consumes

- `application/json`

Produces

- `application/json`

1.1.5. Validate Mapping

PUT /mapping/validate

Description

Validate mapping file

Responses

HTTP Code	Description	Schema
200	Return a validation result	Validations

Consumes

- `application/json`

Produces

- `application/json`

1.1.6. Create Mapping

PUT /mapping/{mappingFormat}

Description

Save a mapping file on the server

Parameters

Type	Name	Description	Schema
Path	mappingFormat at <i>required</i>	Mapping Format	string

Responses

HTTP Code	Description	Schema
200	Succeeded	No Content

Consumes

- `application/json`
- `application/xml`
- `application/octet-stream`

Produces

- `application/json`

1.1.7. Get Mapping

```
GET /mapping/{mappingFormat}/{mappingId}
```

Description

Retrieve a mapping file saved on the server

Parameters

Type	Name	Description	Schema
Path	mappingFormat <i>required</i>	Mapping Format	string
Path	mappingId <i>required</i>	Mapping ID	string

Responses

HTTP Code	Description	Schema
200	Return a mapping file content	AtlasMapping
204	Mapping file was not found	No Content

Produces

- `application/json`
- `application/xml`
- `application/octet-stream`

1.1.8. Update Mapping

POST /mapping/{mappingId}

Description

Update existing mapping file on the server

Parameters

Type	Name	Description	Schema
Path	mappingId <i>required</i>	Mapping ID	string

Responses

HTTP Code	Description	Schema
200	Succeeded	No Content

Consumes

- `application/json`

Produces

- `application/json`

1.1.9. Remove Mapping

DELETE /mapping/{mappingId}

Description

Remove a mapping file saved on the server

Parameters

Type	Name	Description	Schema
Path	mappingId <i>required</i>	Mapping ID	string

Responses

HTTP Code	Description	Schema
200	Specified mapping file was removed successfully	No Content
204	Mapping file was not found	No Content

Produces

- `application/json`

1.1.10. List Mappings

GET /mappings

Description

Retrieves a list of mapping file name saved on the server

Parameters

Type	Name	Schema
Query	filter <i>optional</i>	string

Responses

HTTP Code	Description	Schema
200	Return a list of a pair of mapping file name and content	StringMap

Produces

- `application/json`

1.1.11. Ping

GET /ping

Description

Simple liveness check method used in liveness checks. Must not be protected via authentication.

Responses

HTTP Code	Description	Schema
200	Return 'pong'	string

1.2. Definitions

1.2.1. ActionDetail

Name	Schema
className <i>optional</i>	string
custom <i>optional</i>	boolean
method <i>optional</i>	string
name <i>optional</i>	string
parameters <i>optional</i>	ActionParameters
sourceCollectionType <i>optional</i>	enum (ALL, ARRAY, LIST, MAP, NONE)
sourceType <i>optional</i>	enum (ANY, ANY_DATE, BIG_INTEGER, BOOLEAN, BYTE, BYTE_ARRAY, CHAR, COMPLEX, DATE, DATE_TIME, DATE_TIME_TZ, DATE_TZ, DECIMAL, DOUBLE, FLOAT, INTEGER, LONG, NONE, NUMBER, SHORT, STRING, TIME, TIME_TZ, UNSIGNED_BYTE, UNSIGNED_INTEGER, UNSIGNED_LONG, UNSIGNED_SHORT, UNSUPPORTED)
targetCollectionType <i>optional</i>	enum (ALL, ARRAY, LIST, MAP, NONE)

Name	Schema
targetType <i>optional</i>	enum (ANY, ANY_DATE, BIG_INTEGER, BOOLEAN, BYTE, BYTE_ARRAY, CHAR, COMPLEX, DATE, DATE_TIME, DATE_TIME_TZ, DATE_TZ, DECIMAL, DOUBLE, FLOAT, INTEGER, LONG, NONE, NUMBER, SHORT, STRING, TIME, TIME_TZ, UNSIGNED_BYTE, UNSIGNED_INTEGER, UNSIGNED_LONG, UNSIGNED_SHORT, UNSUPPORTED)

1.2.2. ActionDetails

Name	Schema
actionDetail <i>optional</i>	< ActionDetail > array

1.2.3. ActionParameter

Name	Schema
description <i>optional</i>	string
displayName <i>optional</i>	string
fieldType <i>optional</i>	enum (ANY, ANY_DATE, BIG_INTEGER, BOOLEAN, BYTE, BYTE_ARRAY, CHAR, COMPLEX, DATE, DATE_TIME, DATE_TIME_TZ, DATE_TZ, DECIMAL, DOUBLE, FLOAT, INTEGER, LONG, NONE, NUMBER, SHORT, STRING, TIME, TIME_TZ, UNSIGNED_BYTE, UNSIGNED_INTEGER, UNSIGNED_LONG, UNSIGNED_SHORT, UNSUPPORTED)
name <i>optional</i>	string
values <i>optional</i>	< string > array

1.2.4. ActionParameters

Name	Schema
parameter <i>optional</i>	< ActionParameter > array

1.2.5. Actions

Type : object

1.2.6. AtlasLibraryLoader

Name	Schema
empty <i>optional</i>	boolean
parent <i>optional</i>	ClassLoader

1.2.7. AtlasMapping

Name	Schema
constants <i>optional</i>	Constants
dataSource <i>required</i>	< DataSource > array
lookupTables <i>optional</i>	LookupTables
mappings <i>required</i>	Mappings
name <i>optional</i>	string
properties <i>optional</i>	Properties

1.2.8. AtlasMappingResult

Name	Schema
audits <i>optional</i>	Audits
targetDocuments <i>optional</i>	< TargetDocument > array

1.2.9. Audit

Name	Schema
docId <i>optional</i>	string
message <i>optional</i>	string
path <i>optional</i>	string
status <i>optional</i>	enum (ALL, INFO, WARN, ERROR, NONE)
value <i>optional</i>	string

1.2.10. Audits

Name	Schema
audit <i>optional</i>	< Audit > array

1.2.11. BaseMapping

Name	Schema
alias <i>optional</i>	string
description <i>optional</i>	string

Name	Schema
mappingType <i>optional</i>	enum (ALL, COLLECTION, COMBINE, LOOKUP, MAP, SEPARATE, NONE)

1.2.12. ClassLoader

Name	Schema
parent <i>optional</i>	ClassLoader

1.2.13. Constant

Name	Schema
fieldType <i>optional</i>	enum (ANY, ANY_DATE, BIG_INTEGER, BOOLEAN, BYTE, BYTE_ARRAY, CHAR, COMPLEX, DATE, DATE_TIME, DATE_TIME_TZ, DATE_TZ, DECIMAL, DOUBLE, FLOAT, INTEGER, LONG, NONE, NUMBER, SHORT, STRING, TIME, TIME_TZ, UNSIGNED_BYTE, UNSIGNED_INTEGER, UNSIGNED_LONG, UNSIGNED_SHORT, UNSUPPORTED)
name <i>optional</i>	string
value <i>optional</i>	string

1.2.14. Constants

Name	Schema
constant <i>optional</i>	< Constant > array

1.2.15. DataSource

Name	Schema
dataSourceType <i>optional</i>	enum (SOURCE, TARGET)

Name	Schema
id <i>optional</i>	string
uri <i>optional</i>	string

1.2.16. Field

Name	Schema
actions <i>optional</i>	Actions
arrayDimensions <i>optional</i>	integer (int32)
arraySize <i>optional</i>	integer (int32)
collectionType <i>optional</i>	enum (ALL, ARRAY, LIST, MAP, NONE)
docId <i>optional</i>	string
fieldType <i>optional</i>	enum (ANY, ANY_DATE, BIG_INTEGER, BOOLEAN, BYTE, BYTE_ARRAY, CHAR, COMPLEX, DATE, DATE_TIME, DATE_TIME_TZ, DATE_TZ, DECIMAL, DOUBLE, FLOAT, INTEGER, LONG, NONE, NUMBER, SHORT, STRING, TIME, TIME_TZ, UNSIGNED_BYTE, UNSIGNED_INTEGER, UNSIGNED_LONG, UNSIGNED_SHORT, UNSUPPORTED)
format <i>optional</i>	string
index <i>optional</i>	integer (int32)
path <i>optional</i>	string

Name	Schema
required <i>optional</i>	boolean
status <i>optional</i>	enum (SUPPORTED, UNSUPPORTED, CACHED, ERROR, NOT_FOUND, BLACK_LIST)
value <i>optional</i>	object

1.2.17. FieldGroup

Name	Schema
actions <i>optional</i>	Actions
arrayDimensions <i>optional</i>	integer (int32)
arraySize <i>optional</i>	integer (int32)
collectionType <i>optional</i>	enum (ALL, ARRAY, LIST, MAP, NONE)
docId <i>optional</i>	string
field <i>optional</i>	< Field > array
fieldType <i>optional</i>	enum (ANY, ANY_DATE, BIG_INTEGER, BOOLEAN, BYTE, BYTE_ARRAY, CHAR, COMPLEX, DATE, DATE_TIME, DATE_TIME_TZ, DATE_TZ, DECIMAL, DOUBLE, FLOAT, INTEGER, LONG, NONE, NUMBER, SHORT, STRING, TIME, TIME_TZ, UNSIGNED_BYTE, UNSIGNED_INTEGER, UNSIGNED_LONG, UNSIGNED_SHORT, UNSUPPORTED)
format <i>optional</i>	string

Name	Schema
index <i>optional</i>	integer (int32)
path <i>optional</i>	string
required <i>optional</i>	boolean
status <i>optional</i>	enum (SUPPORTED, UNSUPPORTED, CACHED, ERROR, NOT_FOUND, BLACK_LIST)
value <i>optional</i>	object

1.2.18. LookupEntry

Name	Schema
sourceType <i>optional</i>	enum (ANY, ANY_DATE, BIG_INTEGER, BOOLEAN, BYTE, BYTE_ARRAY, CHAR, COMPLEX, DATE, DATE_TIME, DATE_TIME_TZ, DATE_TZ, DECIMAL, DOUBLE, FLOAT, INTEGER, LONG, NONE, NUMBER, SHORT, STRING, TIME, TIME_TZ, UNSIGNED_BYTE, UNSIGNED_INTEGER, UNSIGNED_LONG, UNSIGNED_SHORT, UNSUPPORTED)
sourceValue <i>optional</i>	string
targetType <i>optional</i>	enum (ANY, ANY_DATE, BIG_INTEGER, BOOLEAN, BYTE, BYTE_ARRAY, CHAR, COMPLEX, DATE, DATE_TIME, DATE_TIME_TZ, DATE_TZ, DECIMAL, DOUBLE, FLOAT, INTEGER, LONG, NONE, NUMBER, SHORT, STRING, TIME, TIME_TZ, UNSIGNED_BYTE, UNSIGNED_INTEGER, UNSIGNED_LONG, UNSIGNED_SHORT, UNSUPPORTED)
targetValue <i>optional</i>	string

1.2.19. LookupTable

Name	Schema
description <i>optional</i>	string
lookupEntry <i>optional</i>	< LookupEntry > array
name <i>optional</i>	string

1.2.20. LookupTables

Name	Schema
lookupTable <i>optional</i>	< LookupTable > array

1.2.21. Mapping

Name	Schema
alias <i>optional</i>	string
delimiter <i>optional</i>	string
delimiterString <i>optional</i>	string
description <i>optional</i>	string
id <i>optional</i>	string
inputField <i>optional</i>	< Field > array
inputFieldGroup <i>optional</i>	FieldGroup
lookupTableName <i>optional</i>	string

Name	Schema
mappingType <i>optional</i>	enum (ALL, COLLECTION, COMBINE, LOOKUP, MAP, SEPARATE, NONE)
outputField <i>optional</i>	< Field > array
strategy <i>optional</i>	string
strategyClassName <i>optional</i>	string

1.2.22. Mappings

Name	Schema
mapping <i>optional</i>	< BaseMapping > array

1.2.23. ProcessMappingResponse

Name	Schema
atlasMappingResult <i>optional</i>	AtlasMappingResult
audits <i>optional</i>	Audits
mapping <i>optional</i>	Mapping

1.2.24. Properties

Name	Schema
property <i>optional</i>	< Property > array

1.2.25. Property

Name	Schema
fieldType <i>optional</i>	enum (ANY, ANY_DATE, BIG_INTEGER, BOOLEAN, BYTE, BYTE_ARRAY, CHAR, COMPLEX, DATE, DATE_TIME, DATE_TIME_TZ, DATE_TZ, DECIMAL, DOUBLE, FLOAT, INTEGER, LONG, NONE, NUMBER, SHORT, STRING, TIME, TIME_TZ, UNSIGNED_BYTE, UNSIGNED_INTEGER, UNSIGNED_LONG, UNSIGNED_SHORT, UNSUPPORTED)
name <i>optional</i>	string
value <i>optional</i>	string

1.2.26. StringMap

Name	Schema
stringMapEntry <i>optional</i>	< StringMapEntry > array

1.2.27. StringMapEntry

Name	Schema
name <i>optional</i>	string
value <i>optional</i>	string

1.2.28. TargetDocument

Name	Schema
body <i>optional</i>	string
docId <i>optional</i>	string

1.2.29. Validation

Name	Schema
id <i>optional</i>	string
message <i>optional</i>	string
scope <i>optional</i>	enum (ALL, DATA_SOURCE, MAPPING, LOOKUP_TABLE, CONSTANT, PROPERTY)
status <i>optional</i>	enum (ALL, INFO, WARN, ERROR, NONE)

1.2.30. Validations

Name	Schema
validation <i>optional</i>	< Validation > array

Chapter 2. Java

2.1. Paths

2.1.1. Inspect Class

POST /java/class

Description

Inspect a Java Class with specified fully qualified class name and return a Document object

Responses

HTTP Code	Description	Schema
200	Return a Document object represented by JavaClass	JavaClass

Consumes

- `application/json`

Produces

- `application/json`

2.1.2. Inspect Class

GET /java/class

Description

Inspect a Java Class with specified fully qualified class name and return a Document object

Parameters

Type	Name	Description	Schema
Query	className <i>optional</i>	The fully qualified class name to inspect	string

Responses

HTTP Code	Description	Schema
200	Return a Document object represented by JavaClass	JavaClass

Produces

- `application/json`

2.1.3. Generate Maven Classpath

POST /java/mavenclasspath

Description

Retrieve a maven classpath string

Responses

HTTP Code	Description	Schema
200	Return a MavenClasspathResponse object which contains classpath string	MavenClasspathResponse

Consumes

- `application/json`

Produces

- `application/json`

2.1.4. Simple

GET /java/simple

Description

Simple hello service

Parameters

Type	Name	Description	Schema
Query	from <i>optional</i>	From	string

Responses

HTTP Code	Description	Schema
200	Return a response	string

Produces

- `text/plain`

2.2. Definitions

2.2.1. Actions

Type : object

2.2.2. JavaClass

Name	Schema
actions <i>optional</i>	Actions
anonymous <i>optional</i>	boolean
annotation <i>optional</i>	boolean
annotations <i>optional</i>	StringList
arrayDimensions <i>optional</i>	integer (int32)
arraySize <i>optional</i>	integer (int32)
canonicalClassName <i>optional</i>	string
className <i>optional</i>	string

Name	Schema
collectionClassName <i>optional</i>	string
collectionType <i>optional</i>	enum (ALL, ARRAY, LIST, MAP, NONE)
docId <i>optional</i>	string
enumeration <i>optional</i>	boolean
fieldType <i>optional</i>	enum (ANY, ANY_DATE, BIG_INTEGER, BOOLEAN, BYTE, BYTE_ARRAY, CHAR, COMPLEX, DATE, DATE_TIME, DATE_TIME_TZ, DATE_TZ, DECIMAL, DOUBLE, FLOAT, INTEGER, LONG, NONE, NUMBER, SHORT, STRING, TIME, TIME_TZ, UNSIGNED_BYTE, UNSIGNED_INTEGER, UNSIGNED_LONG, UNSIGNED_SHORT, UNSUPPORTED)
format <i>optional</i>	string
getMethod <i>optional</i>	string
index <i>optional</i>	integer (int32)
interface <i>optional</i>	boolean
javaEnumFields <i>required</i>	JavaEnumFields
javaFields <i>required</i>	JavaFields
localClass <i>optional</i>	boolean
memberClass <i>optional</i>	boolean

Name	Schema
modifiers <i>required</i>	ModifierList
name <i>optional</i>	string
packageName <i>optional</i>	string
parameterizedTypes <i>optional</i>	StringList
path <i>optional</i>	string
primitive <i>optional</i>	boolean
required <i>optional</i>	boolean
setMethod <i>optional</i>	string
status <i>optional</i>	enum (SUPPORTED, UNSUPPORTED, CACHED, ERROR, NOT_FOUND, BLACK_LIST)
synthetic <i>optional</i>	boolean
uri <i>optional</i>	string
value <i>optional</i>	object

2.2.3. JavaEnumField

Name	Schema
actions <i>optional</i>	Actions

Name	Schema
arrayDimensions <i>optional</i>	integer (int32)
arraySize <i>optional</i>	integer (int32)
className <i>optional</i>	string
collectionType <i>optional</i>	enum (ALL, ARRAY, LIST, MAP, NONE)
docId <i>optional</i>	string
fieldType <i>optional</i>	enum (ANY, ANY_DATE, BIG_INTEGER, BOOLEAN, BYTE, BYTE_ARRAY, CHAR, COMPLEX, DATE, DATE_TIME, DATE_TIME_TZ, DATE_TZ, DECIMAL, DOUBLE, FLOAT, INTEGER, LONG, NONE, NUMBER, SHORT, STRING, TIME, TIME_TZ, UNSIGNED_BYTE, UNSIGNED_INTEGER, UNSIGNED_LONG, UNSIGNED_SHORT, UNSUPPORTED)
format <i>optional</i>	string
index <i>optional</i>	integer (int32)
name <i>optional</i>	string
ordinal <i>optional</i>	integer (int32)
path <i>optional</i>	string
required <i>optional</i>	boolean
status <i>optional</i>	enum (SUPPORTED, UNSUPPORTED, CACHED, ERROR, NOT_FOUND, BLACK_LIST)

Name	Schema
value <i>optional</i>	object

2.2.4. JavaEnumFields

Name	Schema
javaEnumField <i>optional</i>	< JavaEnumField > array

2.2.5. JavaField

Name	Schema
actions <i>optional</i>	Actions
annotations <i>optional</i>	StringList
arrayDimensions <i>optional</i>	integer (int32)
arraySize <i>optional</i>	integer (int32)
canonicalClassName <i>optional</i>	string
className <i>optional</i>	string
collectionClassName <i>optional</i>	string
collectionType <i>optional</i>	enum (ALL, ARRAY, LIST, MAP, NONE)
docId <i>optional</i>	string

Name	Schema
fieldType <i>optional</i>	enum (ANY, ANY_DATE, BIG_INTEGER, BOOLEAN, BYTE, BYTE_ARRAY, CHAR, COMPLEX, DATE, DATE_TIME, DATE_TIME_TZ, DATE_TZ, DECIMAL, DOUBLE, FLOAT, INTEGER, LONG, NONE, NUMBER, SHORT, STRING, TIME, TIME_TZ, UNSIGNED_BYTE, UNSIGNED_INTEGER, UNSIGNED_LONG, UNSIGNED_SHORT, UNSUPPORTED)
format <i>optional</i>	string
getMethod <i>optional</i>	string
index <i>optional</i>	integer (int32)
modifiers <i>required</i>	ModifierList
name <i>optional</i>	string
parameterizedTypes <i>optional</i>	StringList
path <i>optional</i>	string
primitive <i>optional</i>	boolean
required <i>optional</i>	boolean
setMethod <i>optional</i>	string
status <i>optional</i>	enum (SUPPORTED, UNSUPPORTED, CACHED, ERROR, NOT_FOUND, BLACK_LIST)
synthetic <i>optional</i>	boolean

Name	Schema
value <i>optional</i>	object

2.2.6. JavaFields

Name	Schema
javaField <i>optional</i>	< JavaField > array

2.2.7. MavenClasspathResponse

Name	Schema
classpath <i>optional</i>	string
errorMessage <i>optional</i>	string
executionTime <i>optional</i>	integer (int64)

2.2.8. ModifierList

Name	Schema
modifier <i>optional</i>	< enum (ALL, ABSTRACT, FINAL, INTERFACE, NATIVE, PACKAGE_PRIVATE, PUBLIC, PROTECTED, PRIVATE, STATIC, STRICT, SYNCHRONIZED, TRANSIENT, VOLATILE, NONE) > array

2.2.9. StringList

Name	Schema
string <i>optional</i>	< string > array

Chapter 3. JSON

3.1. Paths

3.1.1. Inspect JSON

POST /json/inspect

Description

Inspect a JSON schema or instance and return a Document object

Responses

HTTP Code	Description	Schema
200	Return a Document object represented by JsonDocument	JsonInspectionResponse

Consumes

- `application/json`

Produces

- `application/json`

3.1.2. Inspect JSON via URI

GET /json/inspect

Description

NOT IMPLEMENTED Inspect a JSON schema or instance located at specified URI and return a Document object

Parameters

Type	Name	Description	Schema
Query	<code>type</code> <i>optional</i>		string

Type	Name	Description	Schema
Query	uri <i>optional</i>	URI for JSON schema or instance	string

Responses

HTTP Code	Description	Schema
200	Return a Document object represented by JsonDocument	JsonDocument

Produces

- `application/json`

3.1.3. Simple

```
GET /json/simple
```

Description

Simple hello service

Parameters

Type	Name	Description	Schema
Query	from <i>optional</i>	From	string

Responses

HTTP Code	Description	Schema
200	Return a response	string

Produces

- `text/plain`

3.2. Definitions

3.2.1. Actions

Type : object

3.2.2. Field

Name	Schema
actions <i>optional</i>	Actions
arrayDimensions <i>optional</i>	integer (int32)
arraySize <i>optional</i>	integer (int32)
collectionType <i>optional</i>	enum (ALL, ARRAY, LIST, MAP, NONE)
docId <i>optional</i>	string
fieldType <i>optional</i>	enum (ANY, ANY_DATE, BIG_INTEGER, BOOLEAN, BYTE, BYTE_ARRAY, CHAR, COMPLEX, DATE, DATE_TIME, DATE_TIME_TZ, DATE_TZ, DECIMAL, DOUBLE, FLOAT, INTEGER, LONG, NONE, NUMBER, SHORT, STRING, TIME, TIME_TZ, UNSIGNED_BYTE, UNSIGNED_INTEGER, UNSIGNED_LONG, UNSIGNED_SHORT, UNSUPPORTED)
format <i>optional</i>	string
index <i>optional</i>	integer (int32)
path <i>optional</i>	string
required <i>optional</i>	boolean
status <i>optional</i>	enum (SUPPORTED, UNSUPPORTED, CACHED, ERROR, NOT_FOUND, BLACK_LIST)
value <i>optional</i>	object

3.2.3. Fields

Name	Schema
field <i>optional</i>	< Field > array

3.2.4. JsonDocument

Name	Schema
fields <i>required</i>	Fields

3.2.5. JsonInspectionResponse

Name	Schema
errorMessage <i>optional</i>	string
executionTime <i>optional</i>	integer (int64)
jsonDocument <i>optional</i>	JsonDocument

Chapter 4. XML

4.1. Paths

4.1.1. Inspect XML

POST /xml/inspect

Description

Inspect a XML schema or instance and return a Document object

Responses

HTTP Code	Description	Schema
200	Return a Document object represented by XmlDocument	XmlInspectionResponse

Consumes

- `application/json`

Produces

- `application/json`

4.1.2. Inspect XML via URI

GET /xml/inspect

Description

Inspect a XML schema or instance located at specified URI and return a Document object

Parameters

Type	Name	Schema
Query	type <i>optional</i>	string
Query	uri <i>optional</i>	string

Responses

HTTP Code	Description	Schema
200	Return a Document object represented by XmlDocument	XmlDocument

Produces

- `application/json`

4.1.3. Simple

GET /xml/simple

Description

Simple hello service

Parameters

Type	Name	Schema
Query	from <i>optional</i>	string

Responses

HTTP Code	Description	Schema
200	Return a response	string

Produces

- `text/plain`

4.2. Definitions

4.2.1. Actions

Type : object

4.2.2. Field

Name	Schema
actions <i>optional</i>	Actions
arrayDimensions <i>optional</i>	integer (int32)
arraySize <i>optional</i>	integer (int32)
collectionType <i>optional</i>	enum (ALL, ARRAY, LIST, MAP, NONE)
docId <i>optional</i>	string
fieldType <i>optional</i>	enum (ANY, ANY_DATE, BIG_INTEGER, BOOLEAN, BYTE, BYTE_ARRAY, CHAR, COMPLEX, DATE, DATE_TIME, DATE_TIME_TZ, DATE_TZ, DECIMAL, DOUBLE, FLOAT, INTEGER, LONG, NONE, NUMBER, SHORT, STRING, TIME, TIME_TZ, UNSIGNED_BYTE, UNSIGNED_INTEGER, UNSIGNED_LONG, UNSIGNED_SHORT, UNSUPPORTED)
format <i>optional</i>	string
index <i>optional</i>	integer (int32)
path <i>optional</i>	string
required <i>optional</i>	boolean
status <i>optional</i>	enum (SUPPORTED, UNSUPPORTED, CACHED, ERROR, NOT_FOUND, BLACK_LIST)
value <i>optional</i>	object

4.2.3. Fields

Name	Schema
field <i>optional</i>	< Field > array

4.2.4. XmlDocument

Name	Schema
fields <i>required</i>	Fields
xmlNamespaces <i>required</i>	XmlNamespaces

4.2.5. XmlInspectionResponse

Name	Schema
errorMessage <i>optional</i>	string
executionTime <i>optional</i>	integer (int64)
xmlDocument <i>optional</i>	XmlDocument

4.2.6. XmlNamespace

Name	Schema
alias <i>optional</i>	string
locationUri <i>optional</i>	string
targetNamespace <i>optional</i>	boolean
uri <i>optional</i>	string

4.2.7. XmlNamespaces

Name	Schema
xmlNamespace <i>optional</i>	< XmlNamespace > array