

# Lecture Questions

## 1 Language Model 1

### 1.1 Question (time: 6:17)

Say we have a vocabulary  $\mathcal{V} = \{\text{the}\}$  and a constant  $N \geq 1$ .

For any  $x_1 \dots x_n$  such that  $x_i \in \mathcal{V}$  for  $i = 1 \dots (n-1)$  and  $x_n = \text{STOP}$ , we define  $p(x_1, \dots, x_n) = \begin{cases} \frac{1}{N} & \text{if } n \leq N \\ 0 & \text{otherwise} \end{cases}$

Is this a valid language model?

- (a) True
- (b) False

### 1.2 Question (time: 6:17)

Say we have a vocabulary  $\mathcal{V} = \{\text{the}, \text{dog}\}$ .

For any  $x_1 \dots x_n$  such that  $x_i \in \mathcal{V}$  for  $i = 1 \dots (n-1)$  and  $x_n = \text{STOP}$ , we define  $p(x_1, \dots, x_n) = \begin{cases} \frac{1}{2} & \text{if } n = 2 \\ 0 & \text{otherwise} \end{cases}$

Is this a valid language model?

- (a) True
- (b) False

## 2 Markov Process 1

### 2.1 Question (time: 2:47)

Consider a Markov process with states  $\mathcal{V} = \{0, 1, 2\}$  and length  $n = 10$ .

How many different sequences can be generated by this process?

- (a)  $2^{10}$
- (b)  $10^2$
- (c)  $3^{10}$
- (d)  $10^3$

### 3 Trigram

#### 3.1 Question (time: 5:12)

Say we have a language model with  $\mathcal{V} = \{\text{the, dog, runs}\}$ , and the following parameters:

- $q(\text{the}|\ast, \ast) = 1$
- $q(\text{dog}|\ast, \text{the}) = 0.5$
- $q(\text{STOP}|\ast, \text{the}) = 0.5$
- $q(\text{runs}|\text{the, dog}) = 0.5$
- $q(\text{STOP}|\text{the, dog}) = 0.5$
- $q(\text{STOP}|\text{dog, runs}) = 1$

How many sentences have non-zero probability under this model?

#### 3.2 Question (time: 7:01)

Consider the following corpus of sentences:

- the dog walks STOP
- walks the dog STOP
- dog walks fast STOP

Let  $q_{\text{ML}}$  be the maximum-likelihood parameters of a trigram language model trained on this corpus. Which of the following parameters have a value that is both well-defined and non zero?

- (a)  $q_{\text{ML}}(\text{walks}|\text{dog, the})$
- (b)  $q_{\text{ML}}(\text{fast}|\text{dog, the})$
- (c)  $q_{\text{ML}}(\text{walks}|\ast, \text{dog})$
- (d)  $q_{\text{ML}}(\text{STOP}|\text{walks, dog})$
- (e)  $q_{\text{ML}}(\text{dog}|\text{walks, the})$
- (f)  $q_{\text{ML}}(\text{walks}|\text{the, dog})$

## 4 Perplexity

### 4.1 Question (time: 6:37)

Define a trigram language model with the following parameters:

- $q(\text{the}|\ast, \ast) = 1$ ,  $q(\text{dog}|\ast, \text{the}) = 0.5$
- $q(\text{cat}|\ast, \text{the}) = 0.5$ ,  $q(\text{walks}|\text{the}, \text{cat}) = 1$
- $q(\text{STOP}|\text{cat}, \text{walks}) = 1$ ,  $q(\text{runs}|\text{the}, \text{dog}) = 1$
- $q(\text{STOP}|\text{dog}, \text{runs}) = 1$

Now consider a test corpus with the following sentences:

- the dog runs STOP, the cat walks STOP, the dog runs STOP

What is the perplexity of the language model on this test corpus to three decimal places? (Note: use  $\log_2$  for your calculations. Note that the number of words in this corpus,  $M$ , is equal to 12)

## 5 Linear Interpolation 2

### 5.1 Question (time: 2:21)

We are given the following corpus:

- the green book STOP
- my blue book STOP
- his green house STOP
- book STOP

Assume we compute a language model based on this corpus using linear interpolation with  $\lambda_i = 1/3$  for all  $i \in \{1, 2, 3\}$ .

What is the value of the parameter  $q_{\text{LI}}(\text{book}|\text{the}, \text{green})$  in this model to three decimal places?

(Note: please include STOP words in your unigram model.)

## 5.2 Question (time: 5:07)

Say that we train a language model using linear interpolation with  $\lambda_1 = -0.5$ ,  $\lambda_2 = 0.5$ , and  $\lambda_3 = 1.0$ . Note that these values satisfy the constraint  $\sum_i \lambda_i = 1$  but violate the constraint  $\lambda_i \geq 0$ .

What problems might occur in the resulting language model? Check all that apply.

- (a) we may have a bigram  $u, v$  such that  $\sum_{w \in \mathcal{V}} q(w|u, v) \neq 1$
- (b) we may have a trigram  $u, v, w$  such that  $q(w|u, v) < 0$
- (c) we may have a trigram  $u, v, w$  such that  $q(w|u, v) > 1$

## 6 Discounting Methods 1

### 6.1 Question (time: 6:09)

Assume that we are given a corpus with the following properties:

- $\text{Count}(\text{the}) = 70$
- $|\{w : c(\text{the}, w) > 0\}| = 15$ , i.e. there are 15 different words that follow "the".

Furthermore assume that discounted counts are defined as  $c^*(\text{the}, w) = c(\text{the}, w) - 0.3$ .

Under this corpus, what is the missing probability mass,  $\alpha(\text{the})$ , to three decimal places?

### 6.2 Question (time: 9:27)

Let's return to a smaller version of our corpus.

- the book STOP
- his house STOP

This time we compute a bigram language model using Katz back-off with  $c^*(v, w) = c(v, w) - 0.5$ .

What is the value of  $q_{\text{BO}}(\text{book}|\text{his})$  estimated from this corpus?

## A Answers

- (1.1) a
- (1.2) a
- (2.1) c
- (3.1) 3
- (3.2) c e f
- (4.1) 1.189
- (5.1) 0.571
- (5.2) b c
- (6.1) 0.064
- (6.2) 0.1