Notes 6 – Linux Commands

1. mkdir

Definition

The **mkdir** command stands for **make directory**. It is used to create a new directory (folder) in Linux.

Usage/Formula

```
mkdir directory_name
```

Examples

Create a directory named `projects`:

```
mkdir projects
```

Create multiple directories at once:

```
mkdir school work personal
```

2. touch

Definition

The **touch** command is used to create an empty file. If the file already exists, it updates the file's timestamp without deleting its contents.

Usage/Formula

```
touch file_name
```

Examples

Create an empty file named `notes.txt`:

```
touch notes.txt
```

Create multiple files at once:

```
touch notes1.txt notes2.txt notes3.txt
```

3. rm

Definition

The **rm** command stands for **remove**. It is used to delete files and directories in Linux.

Usage/Formula

```
rm file_name
```

Examples

Delete a file named `notes.txt`:

```
rm notes.txt
```

Delete a directory and everything inside it:

```
rm -r projects
```

4. cp

Definition

The **cp** command stands for **copy**. It is used to make a copy of a file or directory and place it in another location. The original file stays where it is.

Usage/Formula

```
cp source destination
```

Examples

Copy a file and give the copy a new name:

```
cp notes.txt notes_backup.txt
```

Copy a file into another directory:

```
cp notes.txt documents/
```

5. mv

Definition

The **mv** command stands for **move**. It is used to move files or directories to another location. It can also be used to rename files and directories.

Usage/Formula

```
mv source destination
```

Examples

Rename a file from `notes.txt` to `linux_notes.txt`:

```
mv notes.txt linux_notes.txt
```

Move a file into another directory:

```
mv linux_notes.txt documents/
```