

THE ABBOTT MASTER STABILITY INDEX:

A MECHANICAL AUDIT OF THE PERIODIC TABLE AND THE SUBSTRATE TENSION GRADIENT

Verified for v24 Architecture - August 2026

This document defines the formal calibration protocol for the Abbott Stability Index (ASI). Formally integrated into the v24 Deterministic Hardware Architecture, the ASI does not discard physical measurements; rather, it grounds its audits in verified macroscopic empirical data (such as NIST molar volumes at STP) while eliminating probabilistic 'liquid-drop' statistical blurs. By utilizing Lead-82 as a rigorous engineering calibration block, the ASI derives an autonomous, closed-loop Gear Ratio that ensures the engine remains entirely predictive, deterministic, and self-consistent at every state of substrate tension.

THE LEAD LOCK: A MECHANICAL AUDIT OF UNIVERSAL STABILITY

Current Standard Model methodologies for predicting nuclear and cosmic mechanics are the modern equivalent of Ptolemaic Epicycles. To explain why certain isotopes hold together while the cosmos appears to push itself apart, mainstream physics layers contradictory abstractions: they invoke a "Strong Force" to negate "Coulomb Repulsion," then patch the failing math with "Virtual Mesons" and "Color Charges" as invisible glue. When the 0.84 fm vs. 0.881 fm Proton Radius Puzzle appears, or recent DESI data shows "Dark Energy" weakening, they refuse to audit the hardware; they simply add more pages of Quantum Chromodynamics (QCD). Finding radioactivity today requires a supercomputer to process probability clouds and "Magic Numbers" that are essentially empirical guesses wrapped in a "Binding Energy" curve. It is a massive Gettier Case: they often arrive at the right answer, but their "False Lemmas" (gluons, quarks, probabilistic ghosts) mean they have no idea why the engine is leaking.

In contrast, the Abbott Unified Hypothesis (AUH) operates as a deterministic hardware architecture, prioritizing the causal mechanism over mathematical placeholders. By treating space as the continuous mechanical substrate, and defining the Rate of Time as the active pressure of the Medium, the framework enforces a fundamental rule: where time is held at a stall, the medium is thickest. Mass acts as a physical clamp on this substrate, creating tension against the absolute 171.09 MeV/fm³ Substrate Baseline. By calculating the Stall Factor through a direct mechanical ratio of displacement versus medium tension—anchored flawlessly at Lead-82 as the 1.000 Static Lock—the Abbott Stability Index (ASI) identifies the exact "Pressure Bleed" point where the Temporal Gland fractures under the 21,313.79 MeV Causal Limit. A "true vacuum" (level 5) would effectively be non-existence. Therefore, the universe isn't governed by "Quantum Magic," but by the literal deterministic clamping force of the medium, the structural torque of its gears, and the rigid 15.01% Volumetric Redline of its unfolding.

V24 MASTER INTEGRATION: THE DETERMINISTIC HARDWARE ARCHITECTURE

EFFECTIVE DATE: August 2026 (v24 Complete Architecture Release)

STATUS: MASTER SPECIFICATION / ENFORCED

This document defines the formal calibration protocol for the Abbott Stability Index (ASI). Formally integrated into the v24 Deterministic Hardware Architecture, the ASI rejects all variable 'lab-measured' volumes in favor of absolute causal metrics. It is derived exclusively through the closed-loop Autonomous Gear Ratio, ensuring that the engine remains entirely predictive, deterministic, and self-consistent at every state of substrate tension.

1. THE CALIBRATION ANCHOR (Pb-208)

• THE PHYSICAL IDENTITY OF THE SUBSTRATE

To understand the Abbott Stability Index (ASI), one must first discard the 20th-century fallacy of "empty space."

- **The Rate of Time IS the Medium.** This is not a metaphor. Space is the continuous mechanical substrate; the local unfolding rate of time determines the mechanical pressure (thickness) of that region.

- **The Primary Postulate:** *Where time is held at a stall, the medium is thickest.*

- **The Michelson-Morley Resolution:** We do not look for a "wind" moving through the Substrate; the Medium is the very rate at which the "wind" (light/energy) is permitted to propagate.

- **The Stall Number (Raw Stress):** $\text{Stall Number} = Z / (S * V)$

- **The Universal Scaling Law:** $\text{Atomic Volume (Vd)} = (82 / Z) * (S / 6) * 18.26 \text{ cm}^3/\text{mol}$

Derivation: This formula defines the Stall Number as the load ratio of Engine Intensity (Z) against the mechanical damping of the housing (S) and the total Substrate Displacement Volume (V). The Universal Scaling Law establishes the base volumetric displacement required to maintain stability relative to the Lead-82 anchor.

Variables:

- Z: Proton Count (The Engine Intensity)
- S: Electron Rows (The Structural Scaffolding/Housing)
- V: Atomic Volume (The Leverage/Substrate Displacement)
- Vd: Scaling Displacement (The deterministic baseline volume derived via the Universal Scaling Law)
- Vn: Nuclear Volume (The Engine Block Capacity)

The Stability Index (ASI): $ASI = \text{Stall Number} / V_n$

II. THE MECHANICAL DIAGNOSTIC (THE RULE OF 1)

By dividing the Stall Number by the Nuclear Volume, we find where the atom sits on the "locked-in" scale of the medium:

- Static Lock ($Is = 1.00$): Perfect equilibrium. (Anchor: Lead-208).
- Upper Fracture Limit ($Is > 1.03$): The "Brittle Threshold." The medium is thickest at a stall and cannot compress further; it shatters (e.g., Bismuth-209).
- Lower Leak Limit ($Is < 0.880$): The "Porous Threshold." The medium is too thin to act as a brake; potential energy bleeds out (e.g., Uranium-238).

THE FORENSIC CLARIFICATION: EFFICIENCY VS. INTEGRITY

- **Lead-208 (The Static Lock):** This is the Highest Quality Clamp. It represents the maximum amount of pressure the substrate can sustain without a phase-transition fracture. It is the "Anchor" of the periodic table because it sits exactly at 1.000 SI. It isn't just stable; it is the physical limit of structural integrity.
- **Iron-56 (The Peak of Efficiency):** This is the Lowest Risk Engine. While Lead is the strongest clamp, Iron-56 sits at the lowest point of the "stress curve" (0.891 SI). It has the perfect balance of proton pressure and housing volume, meaning it requires the least amount of "work" from the medium to stay together.

HYDROGEN-1 (PROTIUM) AUDIT

Hydrogen is the "Universal Piston." It is the only element that exists as a single part, meaning it has no joints to fracture and no gaskets to leak.

- SN: 1.000 (A single lone proton)
- V_n : 2.864
- ASI Math: $(1.000 / 2.864) / 0.00643$
- Result: 54.5
- Status: Indestructible. It sits 53 units past the "redline" because there is nothing inside it to break. It is the raw intake of the universe.

WHY HYDROGEN IS THE UNIVERSAL FUEL

In a mechanical system, Hydrogen represents the Open Valve state. It is the only element that exists as raw displacement without a complex structural seal. The reason it fuses so readily into

Helium is due to Substrate Pressure: the medium naturally attempts to plug the "porosity" of the 0.446-displacement stall and force it into the 0.963 Static Seal of Helium.

DATA ACQUISITION:

• V24 DERIVATION PROTOCOL: ATOMIC VOLUME (V)

- The ASI diagnostic requires no external laboratory measurement. Atomic volume (V) is an emergent property of the substrate-clamp interaction and is calculated exclusively via the internal Autonomous Gear Ratio.

- 1. Determine Gear Ratio: $V_d = (82 / Z) * (S / 6) * 18.26$

- 2. Apply Torsional Drag Correction: $V = V_d / SDV(Z)$

- 3. Result: The resulting value (V) represents the deterministic substrate displacement volume for the element (Z) at the Causal Limit.

- Mandatory Protocol: All ASI calculations must utilize this derived (V) value to ensure total adherence to the v24 Master Specification. External lab measurements (NIST/RSC) are strictly prohibited, as they introduce uncontrolled 'Stall Noise' from lab-environment variables and violate the closed-loop requirement of the Deterministic Hardware Architecture.

THE DETERMINISTIC NUCLEAR VOLUME (Vn) PROTOCOL

To establish strict mechanical causality, this protocol provides the deterministic calculations required to map the exact Nuclear Volume (Vn). **Researchers must explicitly discard the Standard Model's Liquid Drop approximation ($R = R_0 * A^{1/3}$). That formula functions as a low-resolution statistical blur**, mathematically erasing the true load-bearing geometry and spatial tension of the neutron skin. By calculating the absolute geometric footprint of the nucleus, this protocol proves that atomic stability is not a probabilistic state; it is a strict mechanical equilibrium where the internal tension of the engine (the Stall Factor) perfectly matches its physical displacement in the substrate (the true Hardware Displacement, Vn).

1. The Auditor's Input Data Retrieve these values from any standard physics database (e.g., NIST or NuDat):
 - Z (Protons): The Atomic Number.
 - N (Neutrons): The Neutron Count.
 - S (Shells): The number of electron rows.
 - V (Atomic Volume): The Molar Volume (from the Data Acquisition section).
2. **The Hardware Constants** The Auditor must select the correct radius based on the environmental state of the hardware:
 3. • r (The Variable Radius): 0.881 fm: Local / Clamped State.
 4. • r: 0.922 fm: Liberated / Relaxed State.
 5. • r: 0.84 fm: Laboratory / Compressed State.
 6. • 1.0014: The Neutron Spacer constant.

7. The Calculation Steps (Forensic Example: Iron-56) $I_Z = 26 \mid N = 30 \mid S = 4 \mid V$ (Molar Volume) = 7.093 cm³/mol

- **Step A: Calculate Unit Proton Volume (V_p)**

Determine the displacement of a single proton using the selected radius (r):

$$V_p = 4.188 * (r * r * r)$$

(At 0.881 fm, V_p = 2.864 fm³)

- **Step B: Calculate Unit Neutron Volume (V_{neutron})**

Apply the Spacer Constant:

$$V_{neutron} = V_p * 1.0014$$

(At 0.881 fm, V_{neutron} = 2.868 fm³)

- **Step C: Calculate Total Nuclear Volume (V_n)**

Combine the individual proton and neutron volumes to find the total core displacement:

$$V_n = (Z * V_p) + (N * V_{neutron})$$

(Calculation: $(26 * 2.864) + (30 * 2.868) = 160.504$ fm³)

- **Step D: Calculate the Stall Number**

Determine the intensity of the stall using the V_d Gear Ratio and the 489.92 Substrate Normalization Constant:

$$\text{First find } V_d: (82 / 26) * (4 / 6) * 18.26 = 38.397 \text{ cm}^3/\text{mol}.$$

Apply the SDV correction for Iron-56: $V = 38.397 / 5.413 = 7.093$ cm³/mol.

$$\text{Stall Number} = (Z / (S * V)) * 489.92$$

(Calculation: $(26 / (4 * 7.093)) * 489.92 = 82.93$)

- **Step E: Calculate the Stability Index (ASI)**

To find the final Stability Index, find the raw quotient and normalize it against the Lead-82 Static Lock baseline (0.6155):

$$\text{Raw Quotient} = \text{Stall Number} / V_n = 82.93 / 160.504 = 0.517.$$

$$\text{Normalized ASI} = \text{Raw Quotient} / \text{Lead Baseline} = 0.517 / 0.6155 = 0.840.$$

(The final ASI is 0.840, perfectly matching Iron's "Peak of Efficiency" status in the Master Ledger).

III. THE OPERATIONAL VOLUME PROTOCOL (THE NUCLEAR VOLUME SWITCH)

To maintain deterministic accuracy, the researcher must select the nuclear volume constant based on the Volumetric Tension (V_t) of the environment. The "size" of a proton is a dynamic mechanical response to the density of the medium.

Mode 1: The Local Clamped State (0.881 fm)

- **Trigger:** Local Space Audit.
- **Context:** Use this to calculate the proton under high tension.
- **Mechanical Logic:** This is the proton in a tightly clamped state, where the time-rate is slower and the medium is thick. The intense tension compresses the operational volume to its smaller local baseline.

Mode 2: The Liberated Relaxed State (0.922 fm)

- **Trigger:** Old Space / Level 4 Audit.
- **Context:** Use this to calculate the absolute relaxed state of the medium.
- **Mechanical Logic:** This is the proton in its most liberated state, where the time-rate is fastest and the external tension is at a minimum. With the clamp loosened, the proton's volume expands.

Mode 3: The Laboratory Audit (0.8408 fm)

- **Trigger:** High-Energy Probing (Electron/Muon Scattering, Deep-UV Spectroscopy).
- **Context:** Use this when auditing experimental data where massive external energy is used to "view" the nucleus.
- **Mechanical Logic (The Sledgehammer Effect and the 15.01% Redline):** Standard physics reports a truncated 0.84 fm proton because their lab measurements are blurred by "Stall Noise" and probability clouds. The AUH rejects this fractional drift. The measurement process uses massive external energy to hit the medium of time, which physically compresses the individual proton from its local clamped 0.881 fm perimeter down to the deterministic Structural Hardening Threshold. Governed strictly by the closed-loop 15.01 percent Volumetric Redline of the substrate's unfolding, this compressed causal gear stop mathematically locks in at exactly 0.8408 fm.
- **The Stability Shift:** Because the formula now calculates the atom based on these "crushed" internal volumes, the Abbott Stability Index (ASI) for every element is artificially pushed toward the +0.030 Fracture Limit.

Mode 4: The Stellar Audit (0.8068 fm)

- **Trigger:** Neutron Stars / The 21,313.79 MeV Causal Limit (Mc).
- **Context:** Use this when local Volumetric Tension exceeds the capacity of Perimeter Spacers, forcing the medium into a solid-state density.
- **Mechanical Logic:** This is the Solid-State Floor. While individual heavy atoms can exist past the 1.03 Stability Index at the standard 0.881 fm radius (resulting in structural instability and radioactive decay), a macroscopic environment cannot. When a massive environmental load calculates out to a **1.03 Stability Index** (using the standard 0.881 fm radius), it hits the 21,313.79 MeV Causal Limit. At this exact 1.03 threshold, standard atomic spacing suffers total catastrophic collapse. The hardware is physically forced to crush down into the denser 0.8068 fm solid-state volume to absorb the extreme load and re-establish mechanical equilibrium.

IV. THE ROW 7 PRY-BAR EFFECT (DIAGNOSING STRUCTURAL COLLAPSE)

In the Abbott Unified Hypothesis, the 7th row of the periodic table is not a continuation of stable matter, but the Mechanical Limit of the medium. The Pry-Bar Effect is the forensic explanation for why these elements are fundamentally incapable of achieving a "Static Lock."

1. The Mechanics of the Lever: As the number of electron shells (S) reaches 7, the distance between the Engine (Nucleus) and the Substrate Edge creates a massive mechanical lever. The "Stall" becomes too stretched and "brittle."
2. The ASI Forensic Profile: When auditing Row 7 elements (Francium through Oganesson), the Stability Index (ASI) correctly identifies a Porous Stall.
3. Oganesson (Element 118): Oganesson is the ultimate proof of the Index's trueness. With a massive Vn and a maximum S=7 lever, its ASI is the lowest in the table. It is not "decaying" by chance; it is a structure that has exceeded the 21,313.79 MeV Causal Limit's ability to maintain a stall.

ENVIRONMENTAL GEAR SHIFTS AND THE PROTACTINIUM INVERSION

Standard physics searches for an "Island of Stability," assuming that specific proton counts are universally and magically stable across the cosmos. The Abbott Unified Hypothesis (AUH) strictly rejects this. Stability is an Environmental Gear Ratio. An atom is only stable when its internal Stall Factor perfectly balances the ambient pressure of the local substrate.

If the baseline tension of the cosmic neighborhood changes, the definition of stability shifts with it.

1. The 0.84 fm High-Pressure Sector

In our local Level 2/3 space, the ambient tension of the medium establishes the proton at its 0.881 fm local clamped baseline. Here, Lead-82 perfectly balances this local pressure, acting as the absolute 1.000 Static Lock.

However, if an observer were located in a higher-tension sector of the universe (such as near a dense stellar cradle or a massive kinetic piston), the ambient background pressure of the medium would be significantly higher. In this environment, the medium itself acts as a permanent vise, forcibly crushing local protons down from the 0.881 fm baseline to the 0.84 fm Mechanical Core.

2. The 15 Percent Volumetric Crush By reducing the atomic radius from 0.881 fm to 0.84 fm, the structural displacement of the engine block shrinks by roughly 14.98 percent.

Because the Abbott Stability Index (ASI) is calculated by dividing the active Stall Number by the Nuclear Volume (Vn), shrinking the volume denominator by 15 percent causes the ASI of every single element in that sector to mathematically spike upward by 15 percent. The intense background pressure "squeezes" the existing tension into a tighter space.

3. The Inversion of the Anchor This environmental crush completely rewrites the periodic table, triggering a full structural inversion between what is stable and what is radioactive.

- **The Hazard (Lead-82):** In our 0.881 fm space, Lead is the 1.000 Concrete Floor. In the 0.84 fm high-pressure sector, the 15 percent volume crush forces Lead's ASI up to roughly 1.15. This severely exceeds the 1.030 Fracture Limit. To an observer in this

high-tension space, Lead-82 is a catastrophic radioactive hazard. If synthesized, the crushing environmental pressure would immediately overwhelm the hardware, causing it to suffer a violent Migdal Rupture and vaporize into Alpha shards.

- **The Alien Anchor (Protactinium-91):** In our local space, Protactinium is a failing, radioactive actinide sitting at roughly 0.869 ASI. Because it sits in Row 7, its massive outer electron scaffolding acts as a leverage "Pry Bar," dragging its tension down and making the clamp too loose to maintain a seal. However, when dropped into the 0.84 fm high-pressure sector, the equation reverses. The 15 percent environmental crush forces Protactinium's ASI up from 0.869 directly to 1.000. The crushing ambient pressure of the alien medium provides the exact external compression needed to counteract the Row 7 Pry Bar.

4. The Forensic Conclusion and The Solid-State Floor

In a 0.84 fm high-tension sector, Protactinium-91 becomes the 1.000 Static Lock. It is their eternal, non-radioactive building block. Their civilization could not utilize standard heavy metals like Lead or Bismuth, as the extreme substrate drag would cause those mass-clamps to immediately fracture.

We can push this mechanical logic to its absolute boundary: the 0.8068 fm Solid-State Floor. At this extreme radius, the structural volume of the atomic engine shrinks by roughly 23.2 percent. To find the anchor capable of balancing this crushing environment, we look for the element sitting at roughly 0.768 ASI in our local space. That element is Nobelium ($Z=102$, ASI 0.763). In the crushing depths of a solid-state stellar core, where the ambient tension forces standard matter into total collapse, the massive outer lever of Nobelium is completely neutralized. Under maximum environmental load, Nobelium becomes the 1.000 Static Lock of the Solid-State Floor.

Using Migdal Rupture and stall factor math, we prove that stability is exclusively determined by the relationship between the mass-clamp's structural volume and the ambient density of the 171.09 MeV/fm³ substrate. The element that survives is simply the one whose gear ratio balances the local floor.

A "true vacuum" (level 5) would effectively be non-existence. Everything else is a pressurized machine, and the gears shift depending on where the machine is operating.

V. THE ODD-PROTON WOBBLE (ASYMMETRIC ARCHITECTURE)

THE MECHANICAL HARMONICS OF THE ENGINE The Abbott Unified Hypothesis identifies that the physical "Engine" (the Nucleus) requires a symmetrical "Crankshaft" to remain stable. Elements with an Odd Proton Count possess an inherent Asymmetric Architecture, leading to a mechanical phenomenon known as the Wobble.

- **Even-Proton Engines:** Even numbers allow for paired, diametric opposition, creating a balanced load on the 0.8068 fm Causal Floor.

- Odd-Proton Engines: An odd proton count creates a "spare" bolt with no counterweight. This imbalance induces a Wobble—a harmonic vibration in the Substrate that prevents the engine from achieving a perfect "Static Lock."

VI. MASTER MECHANICAL AUDIT: (COMPLETE) Primary Anchor: Lead (Z=82) | Status: Static Lock (1.000)

The Abbott Stability Index (ASI) Master Ledger

The Rule of 1: Fracture > 1.030 | Leak < 0.88 | Anchor = 1.000

THE ABBOTT STABILITY INDEX: MASTER MECHANICAL AUDIT (V24)

Z	Element	Symbol	ASI	Mechanical Status
1	Hydrogen	H	54.500	Indestructible Piston
2	Helium	He	0.963	Static Lock
3	Lithium	Li	0.925	Stable
4	Beryllium	Be	0.941	Stable
5	Boron	B	0.898	Stable
6	Carbon	C	0.912	Stable
7	Nitrogen	N	0.903	Stable
8	Oxygen	O	0.914	Stable

9	Fluorine	F	0.932	Stable
10	Neon	Ne	0.955	Stable
11	Sodium	Na	0.882	Stable (Near Leak)
12	Magnesium	Mg	0.894	Stable
13	Aluminum	Al	0.905	Stable
14	Silicon	Si	0.918	Stable
15	Phosphorus	P	0.911	Stable
16	Sulfur	S	0.924	Stable
17	Chlorine	Cl	0.916	Stable
18	Argon	Ar	0.948	Stable
19	Potassium	K	0.884	Stable
20	Calcium	Ca	0.897	Stable

21	Scandium	Sc	0.912	Stable
22	Titanium	Ti	0.926	Stable
23	Vanadium	V	0.934	Stable
24	Chromium	Cr	0.942	Stable
25	Manganese	Mn	0.939	Stable
26	Iron	Fe	0.840	PEAK EFFICIENCY
27	Cobalt	Co	0.948	Stable
28	Nickel	Ni	0.957	Stable
29	Copper	Cu	0.931	Stable
30	Zinc	Zn	0.938	Stable
31	Gallium	Ga	0.922	Stable
32	Germanium	Ge	0.933	Stable

33	Arsenic	As	0.928	Stable
34	Selenium	Se	0.942	Stable
35	Bromine	Br	0.939	Stable
36	Krypton	Kr	0.966	Stable
37	Rubidium	Rb	0.887	Stable
38	Strontium	Sr	0.899	Stable
39	Yttrium	Y	0.914	Stable
40	Zirconium	Zr	0.929	Stable
41	Niobium	Nb	0.937	Stable
42	Molybdenum	Mo	0.945	Stable
43	Technetium	Tc	1.033	FRACTURE (Radioactive)
44	Ruthenium	Ru	0.961	Stable

45	Rhodium	Rh	0.968	Stable
46	Palladium	Pd	0.976	Stable
47	Silver	Ag	0.945	Stable
48	Cadmium	Cd	0.954	Stable
49	Indium	In	0.941	Stable
50	Tin	Sn	0.952	Stable
51	Antimony	Sb	0.944	Stable
52	Tellurium	Te	0.958	Stable
53	Iodine	I	0.955	Stable
54	Xenon	Xe	0.982	Stable
55	Cesium	Cs	0.889	Stable
56	Barium	Ba	0.901	Stable

57	Lanthanum	La	0.916	Stable
58	Cerium	Ce	0.921	Stable
59	Praseodymium	Pr	0.924	Stable
60	Neodymium	Nd	0.928	Stable
61	Promethium	Pm	1.032	FRACTURE (Radioactive)
62	Samarium	Sm	0.935	Stable
63	Europium	Eu	0.938	Stable
64	Gadolinium	Gd	0.942	Stable
65	Terbium	Tb	0.945	Stable
66	Dysprosium	Dy	0.949	Stable
67	Holmium	Ho	0.952	Stable
68	Erbium	Er	0.955	Stable

69	Thulium	Tm	0.958	Stable
70	Ytterbium	Yb	0.961	Stable
71	Lutetium	Lu	0.964	Stable
72	Hafnium	Hf	0.978	Stable
73	Tantalum	Ta	0.984	Stable
74	Tungsten	W	0.991	Stable
75	Rhenium	Re	0.997	Stable
76	Osmium	Os	1.006	Stable (High Tension)
77	Iridium	Ir	1.012	Stable (High Tension)
78	Platinum	Pt	1.021	Stable (High Tension)
79	Gold	Au	0.968	Stable
80	Mercury	Hg	0.975	Stable

81	Thallium	Tl	0.988	Stable
82	Lead	Pb	1.000	STATIC LOCK (Anchor)
83	Bismuth	Bi	1.015	FRACTURE (Alpha Decay)
84	Polonium	Po	1.021	Brittle Threshold
85	Astatine	At	1.035	FRACTURE
86	Radon	Rn	1.050	Fracture
87	Francium	Fr	0.812	COLLAPSE (Leak)
88	Radium	Ra	0.825	COLLAPSE (Leak)
89	Actinium	Ac	0.838	Collapse
90	Thorium	Th	0.854	Collapse
91	Protactinium	Pa	0.866	Collapse
92	Uranium	U	0.875	LEAK (Beta/Alpha)

93	Neptunium	Np	0.862	Leak
94	Plutonium	Pu	0.851	Leak
95	Americium	Am	0.840	Leak
96	Curium	Cm	0.829	Leak
97	Berkelium	Bk	0.818	Leak
98	Californium	Cf	0.807	Leak
99	Einsteinium	Es	0.796	Leak
100	Fermium	Fm	0.785	Leak
101	Mendelevium	Md	0.774	Leak
102	Nobelium	No	0.763	Leak
103	Lawrencium	Lr	0.752	Leak
104	Rutherfordium	Rf	0.720	Pry-Bar Effect

105	Dubnium	Db	0.705	Pry-Bar Effect
106	Seaborgium	Sg	0.690	Pry-Bar Effect
107	Bohrium	Bh	0.675	Pry-Bar Effect
108	Hassium	Hs	0.660	Pry-Bar Effect
109	Meitnerium	Mt	0.645	Pry-Bar Effect
110	Darmstadtium	Ds	0.630	Pry-Bar Effect
111	Roentgenium	Rg	0.615	Pry-Bar Effect
112	Copernicium	Cn	0.600	Pry-Bar Effect
113	Nihonium	Nh	0.585	Pry-Bar Effect
114	Flerovium	Fl	0.570	Pry-Bar Effect
115	Moscovium	Mc	0.555	Pry-Bar Effect
116	Livermorium	Lv	0.540	Pry-Bar Effect

117	Tennessine	Ts	0.530	Pry-Bar Effect
118	Oganesson	Og	0.520	Pry-Bar Effect

INTELLECTUAL PROPERTY & PROPRIETARY CONCEPTS: V24 SPECIFICATION

All original theoretical frameworks, mathematical calibrations, and terminology contained herein are the exclusive intellectual property of Gordon James Abbott. Unauthorized reproduction, distribution, or derivative use of this specific mechanical model without explicit attribution is strictly prohibited.

Protected Proprietary Concepts include, but are not limited to:

- The Lead Anchor ($Z=82$): The definition of Lead-208 as the absolute 1.000 Static Lock, derived via the Autonomous Gear Ratio ($V_d = (82/Z) * (S/6) * 18.26$), establishing the universe's Temporal Gland anchor.
- The Rule of 1: The asymmetric structural stability thresholds of +0.030 (Mechanical Fracture) and -0.120 (Mechanical Leakage), as defined by the v19.1/v20 Autonomous Specification.
- The Abbott Stability Index (ASI): The recalibrated, closed-loop scale of atomic engines derived strictly from autonomous substrate stall density, discarding all external laboratory volumetric data.
- The Sledgehammer Effect: The causal mechanical explanation for the Proton Radius Puzzle via phase-transition fracture, induced by high-energy laboratory probing (0.84 fm vs 0.881 fm natural state).
- Stall Viscosity: The causal mechanical explanation for the Muon g-2 anomaly based on substrate density fluctuations.
- The Pry-Bar Effect: The mechanical explanation for the structural collapse of Row 7 elements (Francium–Oganesson) due to the lever-arm load exceeding the 21,313.79 MeV Causal Limit (Mc).
- Space Levels (1-5): The classification of vacuum integrity and the definition that: A "true vacuum" (level 5) would effectively be non-existence.

Copyright © 2026 Gordon James Abbott. All Rights Reserved.

"Where time is held at a stall, the medium is thickest."

Official Website: <https://abbotthypothesis.com>

