

Memorial University of Newfoundland
Department of Mathematics and Statistics

DSCI 6607 – Programmatic Data Analysis Using Python and R – Fall 2024

Instructor: Dr. Armin Hatefi

Thursday, December 12, 2024

Final Exam

Student Number: _____

Family Name: _____

First Name: _____

Instructions:

2. There are 5 questions (100 points).
3. Marks are shown in brackets.
4. Show all your mathematical and computational work.
7. This exam has 4 pages, including this page.

1. Consider generating random observations from the following distribution

$$f(x) = \frac{1}{c(1+x)^{3/2}}, \quad x > 0$$

- a) Find constant c such that $f(x)$ is a legitimate probability density function (pdf).
- b) Find the cumulative density function (cdf) corresponding to the pdf $f(x)$?
- c) Use part (b), and apply the inverse cdf method to generate data from the distribution. Show you mathematical calculations.
- d) Use **python**, and write a function which takes $N = 2000$ and generates N observations from the distribution.
- e) Plot the histogram of the generated data and plot the curve of the $f(x)$ on top of them. Explain if your simulated data follow the corresponding distribution or not. **[20 points]**

2. In this question, we plan to develop a maximum likelihood estimation using **R**. Let X follow probability density function $f(x; \theta)$, where θ denotes the unknown parameter(s). The maximum likelihood function of θ based on n observations $\mathbf{x} = (x_1, \dots, x_n)$ is calculated by

$$L(\theta|\mathbf{x}) = \prod_{i=1}^n f(x_i; \theta)$$

Hence the maximum likelihood estimate of θ is given by

$$\hat{\theta} = \arg \max_{\theta} \ell(\theta|\mathbf{x})$$

where $\ell(\theta|\mathbf{x})$ is the logarithm of the $L(\theta|\mathbf{x})$.

- a) Consider X follows normal distribution with pdf

$$f(x; \mu, \sigma^2) = \frac{1}{\sqrt{2\pi\sigma^2}} \exp\left(-\frac{(x-\mu)^2}{2\sigma^2}\right),$$

find the loglikelihood function of $\theta = (\mu, \sigma^2)$ based on n observations.

- b) Write an R function called 'loglike.function' which takes two arguments, including data and params (as a vector of two arguments). Then the function returns the loglikelihood function. Then, evaluate the log-likelihood function based on params as $(\mu = 5, \sigma^2 = 1)$ and data

$$5.1, 3.2, 5.8, 6.1, 6.2, 6.8, 5.2, 5.01, 6.5, 6.8$$

- c) Write function(s) which takes data and returns the MLE of parameters μ and σ^2 by maximizing the loglikelihood function using the numerical optimization function 'optim' in R.

- d) Recall the above function, initialize the optim function by starting point (mean(data), var(data)) and find the MLE of the parameters based on the above data in part (b). **[20 points]**

3. We want to implement an introduction to gradient descent optimisation with Python in this question. Consider the quadratic equation **[20 points]**

$$f(x) = ax^2 + bx + c$$

- a) Write a python function, 'quadratic.function' that takes a,b,c as three inputs and computes the function.
- b) Write the gradient function 'grad.function' which computes

$$f'(x) = 2ax + b$$

- c) Write a functional program to find the minimum value of the $f(x)$ using the numerical optimization through a customized gradient descent. To do that, write a function which takes a,b,c and 'learning.rate' (default 0.1), 'tol' (default 10^{-5}) and 'max.iter' (default 1000). The function iterates, updating the gradient using 'grad.function' and updating x by ' $x - learning.rate * grad$ '. These two iterative steps are alternated until either the gradient becomes less than the 'tol' or the number of iterations reaches the 'max.iter'.
- d) Test your program with the values a=3, b=-12, c=9.
- e) Explain your solution and whether your numerical optimization converged or not. Why?

4. Import the 'diamond' data set from the repository. Use R to analyze and explain how the price of a diamond varies by clarity and cut. We plan to use the ggplot2 package to answer this question.

- a) Focus on the diamond observations whose carat is greater than 0.5 and whose price is less than 5000.
- b) Use ggplot and study the relationship between the two variables of price and carat from part (a) data. Explain which graphical display should be used and why.
- c) Facet the plot by 'cut' so that each facet corresponds to a different diamond cut.
- d) Color the points by 'clarity'. Carefully add the labels for the x-axis, y-axis, title and legend. **[20 points]**

5. Import the 'sales' data set from the repository. Use Python to analyze and explain sales data, which contains monthly sales information for different regions.

- a) Load the dataset as a data frame. Convert the 'Date' column to a datetime object and extract the year.
 - b) Group the data by 'Region' and calculate the total sales for each year.
 - c) Create a line plot to show the yearly sales trend for each region. Then, add appropriate labels for the x-axis and y-axis and a title for the plot.
 - d) Highlight the region with the highest total sales across all years in the plot using a thicker line width or a different line style.
- [20 points]**

Good luck!