

UNIVERSITÉ LIBRE DE BRUXELLES

Faculté des Sciences

Département d'Informatique

Characterization and complexity of
Thin Strip Graphs

Abdeslam El-Haman Abdeslam

Promotor : Prof. Jean Cardinal
Master Thesis in Computer Sciences

Academic year 2018 - 2019

*You may want
to write a dedication here*

” *Science isn’t about why – it’s about **why not**.*

— **Cave Johnson**
(Portal 2)

Acknowledgment

I want to thank ...

Contents

1	Introduction	1
2	Background	4
2.1	Graph theory	4
2.1.1	Intersection graphs	6
2.2	Order and set theory	6
2.2.1	Comparability graphs	7
2.3	Complexity	7
2.4	Geometry	8
3	Interval graphs	9
3.1	Interval graphs	10
3.2	Mixed unit interval graphs	10
3.2.1	Characterization	13
3.3	Unfettered unit interval graphs	16
3.3.1	Recognition	20
4	Thin strip graphs	22
4.1	c -strip graphs	23
4.2	Thin strip graphs	23
4.2.1	Interval graphs	24
4.3	Characterization of thin strip graphs	27
4.3.1	Mixed unit interval graph forbidden subgraphs	27
4.4	Recognition	32

5 Thin two-level graphs	34
5.1 Thin two-level graph	34
5.1.1 Relation with interval graphs	36
Appendices	39
A Graph classes hierarchy	40
B Problems in inclusion	42
C Problems in forbidden induced subgraph characterization	43
D Problems in complexity	44

Chapter 1

Introduction

” *There’s no such thing in the world as absolute reality. Most of what they call real is actually fiction; what you think you see is only as real as your brain tells you it is. It’s not whether you were right or wrong, but how much faith you were willing to have, that decides the future.*

— **Solid Snake**
(Metal Gear Solid 2)

This work is mainly focused on the characterization and complexity of variants of unit disk graphs, where the domain of possible locations for the disks is limited. We are also going to see their close relation to a certain family of interval graphs. In this chapter, we will overview the open questions we will focus on and our main results. Further details about the results discussed in this chapter will be introduced later in the thesis as well as a background in Chapter 2.

Interval graphs

In Chapter 3 we introduce the concept of interval graphs and some of their use cases. An *interval graph* is a graph in which each one of its vertices is a closed interval on the real line and they are adjacent if they overlap; interval graphs where the length of its intervals is the same is called *unit interval graphs (UIG)*.

Moreover, we introduce two new subclasses of graphs. *Mixed unit interval graphs (MUIG)* [15] can be seen as unit interval graphs but the endpoints of each interval can be open or closed. Another variant are *unfettered unit interval graphs (UUIG)* [13], where we can chose whether two touching intervals (so that one of their endpoints are in the same position) are adjacent or not.

Joos describes the class MUIG [15] with a list of graphs that cannot be MUIGs. Also, Hayashi et al. describe the class UUIG with the next theorem.

Theorem. *A graph is an UUIG if and only if it has a level structure such that each level is a clique.*

Finally, we take an algorithmic approach to study these classes of graphs. A graph recognition problem for a class of graphs is the problem to guess whether a given graph is of a certain class. The recognition of MUIG is of $\mathcal{O}(n^2)$ [22] and the recognition of UUIG is only overviewed. For the moment, we know that recognition of UUIG is in \mathcal{NP} .

Strip graphs

In Chapter 4 we introduce the main class of graphs of this thesis. *Unit disk graphs (UDG)* are intersection graphs of disks on a plane when the diameter of the disks are unitary. *c-strip graphs (SG(c))* [5] is a subclass of UDG, where the center of the disks can only be located between two horizontal lines with a separation of c . More formally, for each disk v in the graph G , $v_y \in [0, c]$. Breu [5] defined this class of graphs and studied early phases of its charaterization and recognition. However, this is not complete as there is still no answer to the complexity of TSG recognition.

Thin strip graphs

Thin strip graphs (TSG) is a subclass of UDG that can be defined as the intersection of every $SG(c)$ with $c > 0$. This is equivalent to say that $TSG = SG(\varepsilon)$ with ε an arbitrarily small number. Hayashi et al. [13] present this class of graphs in their work and found some interesting properties about them.

Theorem. *There is no constant t such that $TSG = SG(t)$.*

More importantly, TSG is well located in the hierarchy of the graphs seen until now. We know that $MUIG \subsetneq TSG \subsetneq UUG$. This helps us to find a characterization for TSG because we know that the characterization of MUIG is complete. We also see that every forbidden graph for MUIG is also forbidden in TSG except for one of them.

Two-level graphs

to add or not? we'll see in the end

Chapter 2

Background

” *The right man in the wrong place can make all the difference in the world.*

— G-Man
(Half-Life 2)

In this chapter we review some definitions and notations used in this thesis. We limit ourselves to the basic notations used during the work. However, the bibliography of each subject will be referenced for further details about the topic.

2.1 Graph theory

A **graph** is defined as a tuple $G = (V, E)$ where V is the set of **vertices** and E is a set of **edges** where $E \subseteq \binom{V}{2}$. An **orientation** of a graph G is an assignment of a direction to each edge, we denote the orientation of the edges by \vec{E} . An orientation is **transitive** if $uv \in \vec{E}$ and $vw \in \vec{E}$, then $uw \in \vec{E}$. If two vertices share the same edge e they are called **adjacent** and also the **endpoints** of e . The **neighbourhood** of a vertex v is the subset of V of vertices that are adjacent to v and is denoted by $N(v)$. A **subgraph** $H = (V', E')$ of a graph G is a graph such that $V' \subseteq V$ and $E' \subseteq E$. An




Figure 2.1: Realization of a UDG (unit disk graph).

induced subgraph of a graph is a subgraph H of a graph G such that for every edge of G is also in H if its two endpoints are in V' . A **clique** is a subgraph such that every vertex is adjacent to each other. A graph that is also a clique is called a **complete graph** and it is denoted as K_n . A graph is **bipartite** if there exist two disjoint subsets of the vertex set $A \cup B = V$ such that two vertices of the same subset are not adjacent. A **complete bipartite graph** $K_{n,m}$ is a bipartite graph such that $v \in A$ and $w \in B$ implies $vw \in E$ where n and m are the size of each bipartition.

A **path** $P_n = v_1 \dots v_{n+1}$ of a graph is a sequence of pairwise distinct n vertices such that two consequent vertices are adjacent. A **cycle** is a path $C_n = v_1 \dots v_n v_{n+1}$ such that $v_1 = v_{n+1}$. A graph is **connected** if there exists a path between every pair of vertices. A **chord** of a cycle C_n with $n \geq 4$ is an edge that connects two non adjacent vertices of the cycle. A graph is **chordal** if there is a chord in every cycle bigger than four.

Some graphs can be characterized with properties. An **isomorphism** between two graphs $G = (V, E)$ and $H = (V', E')$ is a bijection $f : V \rightarrow V'$ between the two vertex sets such that u, v are adjacent in G if and only if $f(u), f(v)$ are adjacent in H . A graph **property** is a property of the graph that is preserved in all its isomorphisms; this will help us to set properties that are based on the abstraction of the graph and not only its drawings. A property is **hereditary** if it is also preserved under all taking subgraphs.

For notation in this thesis, sometimes the class of a certain type of graphs is denoted by its initials (*e.g.* the class of unit interval graphs is denoted by **UIG**) to avoid extreme repetition.




Figure 2.2: On the left, Hasse diagram of a poset of the power set of 2 elements ordered by inclusion. On the right, the comparability graph of this poset.

2.1.1 Intersection graphs

An *intersection graph* is a graph $G = (\zeta, E)$ of a collection of objects ζ is a graph such that $v, w \in \zeta$ and $v \cup w \neq \emptyset$ implies that $vw \in E$. An *interval graph* is an intersection graph of intervals on the plane; when the size of the intervals is equal they are called *unit interval graphs*. A *unit disk graph* is an intersection graph of disks on a plane that have the same diameter - you can find an example in Figure 2.1.

For more details about graph theory we recommend the reading of *Graph Theory* by Diestel [2], *Graph Classes: A Survey* by Brändstadt *et al.* [4] and *Topics in Intersection Graph Theory* by McKee *et al.* [16].

2.2 Order and set theory

The *powerset* $\mathcal{O}(S)$ of a set S is the set of subsets of S . A *partial order* is a binary relation \leq over a set A satisfying three axioms:

- if $a \leq b$ and $b \leq a$ then $a = b$ (*antisymmetry*).
- if $a \leq b$ and $b \leq c$ then $a \leq c$ (*transitivity*).
- $a \leq a$ (*reflexivity*).

On the other side, a *total order* is a partial order where the reflexivity order is replaced by the *connexity* property – $a \leq b$ or $b \leq a$. A *partially*

ordered set (or **poset**) (S, \leq) is a set such that the elements of S are partially ordered by the relation \leq . A good way to represent a poset is the **Hasse diagram** (Figure 2.2).

2.2.1 Comparability graphs

A **spanning order** $(V, <)$ on a graph $G = (V, E)$ is a total order on V such that for any three vertices $u < v < w$:

$$uw \in E \Rightarrow uv \in E \text{ or } vw \in E$$

The class of comparability graphs are built on the ideas of order theory. A graph G is a **comparability graph** if there exists a partial order \leq such that $uv \in E \Leftrightarrow v \leq w \text{ or } w \leq v$. The complement of comparability graphs are called **co-comparability graphs**.

2.3 Complexity

Complexity theory has the objective to establish lower bounds on how efficient an algorithm can be for a given problem. This approach let us have a reference point to establish the difficulty of a problem. A **decision problem** is a problem where we have to decide if a statement is true or false. A **decider** of a decision problem is defined as the deterministic machine that solves this problem. The problem is **polynomially decidable** if it has a polynomial time decider. A **verifier** of a decision problem is a deterministic machine that verifies whether an answer to the decision problem is true or false. Equally, a problem is **polynomially verifiable** if it has a polynomial time verifier. The problem of **recognition** is the problem to decide whether a graph G is in a class of graphs. We denote by \mathcal{P} the class of polynomially decidable problems. On the other hand, \mathcal{NP} denotes the class of polynomially verifiable problems. We can see that $\mathcal{P} \subseteq \mathcal{NP}$.

A **reduction** of a problem L to a problem M is a mapping of an instance of L (I_L) to an instance of M (I_M) such that I_L is true for the problem L

if and only if I_M is true for the problem M . This is denoted by $L \leq M$ and $L \leq_P M$ if the reduction is done in polynomial time. We usually prove bounds of complexity for an unknown problem L by reducing it to another problem with an already known complexity. Thus, we can define the class **\mathcal{NP} -hard** as the set of problems such that we can reduce every \mathcal{NP} problem to one of them. The set of problems that are both \mathcal{NP} and \mathcal{NP} -hard are called **\mathcal{NP} -complete**. For more details about complexity we recommend the reading of *Introduction to the Theory of Computation* by Sipser [21].

2.4 Geometry

We must recall some really basic definitions of geometry. Every geometrical object of this thesis is located in \mathbb{R}^2 if it is not otherwise specified. The **distance** between two points as $\text{dist}(a, b)$. An object S is **convex** if for every point p, q the segment between the two points is also contained in S . More formally:

$$\forall \lambda \in [0, 1] : (1 - \lambda)p + \lambda q \in S$$

A **stabbing** is a point that traverses a set of intersecting objects. A lot of research has been done [18] on the minimal amount of stabblings to cover every object in a set. If instead of points we use more complex object, we denote it by a **covering**. The **Helly** theorem says that:

Theorem (Helly ([14])). *Given a set S of objects in \mathbb{R}^d , if for each subset of S of size $d + 1$ their intersection is non empty, then $\bigcap_{s \in S} s \neq \emptyset$.*

We say that a set S satisfies the **Helly property** if every subfamily of S composed of pairwise intersecting objects has also a non-empty intersection. For more details about algorithmic geometry, we recommend the reading of *Computational Geometry: algorithms and applications* by de Berg *et al.* [9].

Chapter 3

Interval graphs

” *If you like easy, my program isn’t for you.
Nothing great comes from easy.*

— Robert Callaghan
(Big Hero 6)

The goal of this chapter is to present the family of classes of interval graphs that are related to the class of thin strip graphs. We introduce the class of interval graphs, which is one of the most used classes of intersection graphs. There are multiple types of interval graphs and those that are the most relevant for the thesis are going to be defined below.

First, we recall the basic definition of an interval graphs and their multiple characterizations. Also, we present unit interval graphs, where we see their characterization and complexity such as Robert’s characterization [17]. Then, we see some characterizations such as Joos’s paper about mixed unit interval graphs [15] and the paper from Hayashi *et al.* [13] where the unfettered unit interval graphs are defined and also characterized as well as some equivalences with *unit disk graphs* are presented. Also, the complexity of the recognition for each one of the classes presented will be discussed.

3.1 Interval graphs

First we present the main characterizations of interval graphs. In the next sections we present some other subclasses of interval graphs that will help us characterize the thin strip graphs on Chapter 4. There are multiple characterizations of interval graphs that are equivalent, in this thesis we present Gilmore and Hoffman's characterization described in Theorem 3.1.1. From this theorem it is clear that *IG* class is a subclass of the *CO-CO* class.

Theorem 3.1.1 (Gilmore and Hoffman [12]). *G is an interval graph if and only if G does not contain C_4 as an induced subgraph and \overline{G} can be ordered partially, in other words, \overline{G} is a comparability graph.*

The first interesting subclass of IG is the class of ***unit interval graphs*** which is defined by the interval graphs that have intervals with the same length (or equal to one). This class of graphs is equivalent to the class of ***proper interval graph*** which is the class of intervals where no interval is a strict subset of another. This statement is powerful because the study of unit interval graphs can be more comfortable because of the simplicity of its definition and characterization as seen in Theorem 3.1.2.


Theorem 3.1.2 (Roberts [17]). *An interval graph is a unit interval graph if and only if it has no induced subgraph $K_{1,3}$* ¹.

In terms of recognition, interval graphs as long as unit interval graphs can be recognized in ***linear time***. Interval graph linear time recognition was discovered by Booth *et al.* by doing so with a ***breadth-first search*** [3]. UIG recognition has also been proven to be linear [7].

3.2 Mixed unit interval graphs

We can define a new class of graphs that is related to UIG by its definition. This class is closely related to thin strip graphs as we will see in Chapter 4. ***Mixed unit interval graphs*** are graphs where the intervals have the same

¹ $K_{1,3}$ is also called ***claw***.

Figure 3.1: Representation of $K_{1,3}$ as a MUIG.

size as the unit interval graphs. However, in this class, the endpoints of the intervals can be open or closed - or one of each.

Formally, MUIG is defined by using the next classes of graphs:

$$\mathcal{U}^{++} = \{[x, y] : x, y \in \mathbb{R}, x \leq y\}$$

$$\mathcal{U}^{--} = \{(x, y) : x, y \in \mathbb{R}, x \leq y\}$$

$$\mathcal{U}^{+-} = \{[x, y) : x, y \in \mathbb{R}, x \leq y\}$$

$$\mathcal{U}^{-+} = \{(x, y] : x, y \in \mathbb{R}, x \leq y\}$$

where \mathcal{U}^{xx} is the class of unit interval graphs where its intervals can be open or closed depending on their sign. For exemple, $\mathcal{U}^{++} = \text{UIG}$.

Dourado, by defining these classes of unit interval graphs with open/closed intervals also found that, for unit interval graphs, it does not matter if the endpoints are open, closed, or closed open (Theorem 3.2.1).

Theorem 3.2.1 (Dourado et al. [10]). *The classes of the graphs \mathcal{U}^{--} , \mathcal{U}^{++} , \mathcal{U}^{-+} , \mathcal{U}^{+-} , and $\mathcal{U}^{-+} \cup \mathcal{U}^{+-}$ are the same.*

However, MUIG is defined as $\mathcal{U}^{++} \cup \mathcal{U}^{--} \cup \mathcal{U}^{+-} \cup \mathcal{U}^{-+}$ which is also denoted as \mathcal{U} . In this case it is clear that this class is not equivalent to UIG. As we have seen in Theorem 3.1.2, a UIG can be seen as a $K_{1,3}$ -free IG. Nevertheless, MUIG can accept this graph as seen in Proposition 3.2.2.

Proposition 3.2.2 (Dourado et al. [11]). *MUIG has a $K_{1,3}$ representation. Also, for every MUIG representation $\phi : V(K_{1,3}) \rightarrow \mathcal{U}$ such that $\phi(V(K_{1,3}))$ contains:*

- $a = [x, x + 1]$
- $b = (x, x + 1)$
- $c = [x + 1, x + 2]$ or $[x + 1, x + 2)$
- $d = [x - 1, x]$ or $[x - 1, x)$

Proof. Let $\phi : V(K_{1,3}) \rightarrow \mathcal{U}$ be the representation of $K_{1,3}$ as a mixed unit interval intersection diagram as illustrated in Figure 3.1. Let $V(K_{1,3}) = \{v_1, v_2, v_3, v_4\}$ and $E(K_{1,3}) = \{v_1v_4, v_2v_4, v_3v_4\}$. Let $x(v_1) = I(v_1) \cap I(v_4)$, $x(v_2) = I(v_2) \cap I(v_4)$ and $x(v_3) = I(v_3) \cap I(v_4)$. Because v_1, v_2 and v_3 are not adjacent, we can assume that $x(v_1) < x(v_2) < x(v_3)$. Since $x(v_1) \in I(v_4)$ and $x(v_3) \in I(v_4)$, then $x(v_3) - x(v_1) \leq 1$. Since $I(v_1), I(v_2)$ and $I(v_3)$ are disjoint, $I(v_2)$ must be a proper subset of $(x(v_1), x(v_3))$. Since $I(v_2)$ is a mixed unit interval, then it implies that $x(v_3) = x(v_1) + 1$, $I(v_2) = (x(v_1), x(v_1 + 1))$, $I(v_4) = [x(v_1), x(v_1) + 1]$, $I(v_1) = \{(x(v_1) - 1, x(v_1)], [x(v_1) - 1, x(v_1)]\}$ and $I(v_3) = \{[x(v_3) - 1, x(v_3)), [x(v_3) - 1, x(v_3)]\}$. \square

Theorem 3.2.3 (Dourado *et al.* [11]). $UIG \subsetneq MUIG$.

Proof. The strict inclusion is straightforward: we know that $UIG = \mathcal{U}^{++} \subset MUIG$ by definition. For the inequality, we prove it by Proposition 3.2.2, as $K_{1,3}$ is not realizable in UIG . \square

Nevertheless, $MUIG$ still shares some properties with UIG . In the previous section we mentioned that the class of unit interval graphs is the same as the class of proper interval graphs. In our case, mixed unit interval graphs is also exactly the same as the mixed proper interval graphs – where no mixed interval can be a proper subset of another one.

Theorem 3.2.4. *For a graph G , the following two statements are equivalent.*

- G is a mixed proper interval graph.
- G is a mixed unit interval graph.

Schuchat *et al.* [19] describe an algorithm to recognize mixed unit interval graphs in polynomial time with a characterization. Proof and details about the algorithm will not be provided but we encourage the reading of their paper.

Theorem 3.2.5 (Schuchat et al. [19]). *The MUIG recognition problem is in \mathcal{P} . Moreover, there is an algorithm that solves it in $O(|V|^2)$ for V the vertex set of a graph.*

3.2.1 Characterization

A complete characterization by induced forbidden subgraphs have been found independently by A. Schuchat et al. [20] and F. Joos [15]. In this section we will present briefly the characterization of MUIG given by Joos with forbidden subgraphs. We will also review each one of these forbidden subgraphs and discuss the properties compared of one of them that will be relevant in the next chapter. However, the proof of this characterization will not be given in this thesis because of its length. His work follows Dourado *et al.* [11] where they characterized **diamond-free** mixed unit interval graphs.

Theorem 3.2.6 (Joos [15]). *G is a MUIG if and only if it is a $\{F\} \cup \mathcal{R} \cup \mathcal{S} \cup \mathcal{S}'' \cup \mathcal{T}$ -free interval graph.*

The forbidden families can be seen in Figures 3.3, 3.4, 3.5, 3.6, 3.7. You can notice that, without including F , every family of forbidden graphs of MUIG is infinite and is defined recursively by its predecessor. Our only goal in this section is to focus in the properties of \mathcal{R} because, as we will see in Chapter 4, it is the only forbidden graph family for MUIG that is also forbidden for thin strip graphs.

We know that \mathcal{R} is a family of forbidden subgraph for mixed unit interval graphs. If we look up in the graph classes hierarchy 3.2 we find that $\text{MUIG} \subsetneq \text{CO-CO}$. The first step to see if \mathcal{R} is a family of proper forbidden subgraph for MUIG is to prove if $\mathcal{R} \subsetneq \text{CO-CO}$. In the first place, we present a characterization of cocomparability graphs.




Figure 3.2: The hierarchy of the classes between *UIG* and *CO-CO*. The arrows represent a relation of \subsetneq .

Theorem 3.2.7 (Damaschke [8]). *A graph G is a co-comparability graph if and only if it has a spanning order.*





Figure 3.3: The class \mathcal{R} . [15]

Lemma 3.2.8. *\mathcal{R} is a family of co-comparability graphs.*

Proof. If we recall Theorem 3.2.7, in order to prove that \mathcal{R} is a family of co-comparability graphs we will have to find a spanning order for every R_i with $i \geq 0$. We will proceed to label our vertices with a mapping function $f : V \rightarrow \mathbb{N}$ such that $f(v) \in \{1, \dots, |V|\}$. This mapping will give us a spanning order by induction:

- $i = 0$: We assign the number 1 to the vertex with maximum degree v_1 . We assign then the rest of the numbers to the other vertices. We see

Figure 3.4: The class \mathcal{S} [15].


then that $\forall u < v < w : uw \in E \rightarrow uv \in E$ because every vertex is adjacent to v_1 .



- $i = i + 1$: We define $\lambda_i = 5 + 2i$ where $\lambda_i = |V(R_i)|$. We add two vertices on each graph, where their labels are $\lambda_i + 1$ and $\lambda_i + 2$ and we also add three new edges: $v_{\lambda_i}v_{\lambda_i-1}, v_{\lambda_i}v_{\lambda_i+1}, v_{\lambda_i}v_{\lambda_i+2} \in E$.

By induction we only have to see if it holds with the new edges. We can say that it still holds with $v_{\lambda_i}v_{\lambda_i-1}$ and $v_{\lambda_i}v_{\lambda_i+1}$ because:

$$\nexists k \in \mathbb{N} : i < k < i + 1$$

Finally, we see that $v_{\lambda_i}v_{\lambda_i+2}$ is a valid edge because $v_{\lambda_i}v_{\lambda_i+1} \in E$. \square

Figure 3.5: The class \mathcal{S}'' . [15]

Figure 3.6: The graph F . [15]Figure 3.7: The class \mathcal{T} . [15]

3.3 Unfettered unit interval graphs

In this section we detail the properties of unfettered . An unfettered unit interval graph can be defined as an unit interval graph such that for every touching endpoints we can chose either if they are adjacent or not. We remark that by definition, every unit interval graph is feasible in UIG. This class is a minimal superclass of TSG, *i.e.* $\text{TSG} \subsetneq \text{UIG}$.

This class has a characterization by levels done by Hayashi *et al.* where levels are used. A **level structure** of a graph $G = (V, E)$ is a partition $L = \{L_i : i \in [1, t]\}$ of V such that

$$v \in L_k \Rightarrow N(v) \subseteq L_{k-1} \cup L_k \cup L_{k+1}$$

where $L_0 = L_{t+1} = \emptyset$.

Theorem 3.3.1 (Hayashi et al. [13]). *A graph G is an unfettered unit interval graph if and only if it has a level structure where each level is a clique.*

Proof. We begin by proving the if-part. Let G be a graph with levels L_1, \dots, L_t where every level is a clique. For every vertex $v \in L_i$, we assign an interval $[i - 1, i]$. We see that every interval within a level is in the same position, so they are all adjacent. Then, for L_i we have its adjacent levels L_{i-1} and L_{i+1} . The right endpoints of the intervals L_{i-1} match the left endpoints of L_i . On the other side, the left endpoints of L_{i+1} match the right endpoints of L_i . As we know, we can chose whether the endpoints touch or not between levels. This will construct its respective UUIG.

Now we prove the only-if. Let G be a UUIG and $I(v)$ the interval representation of $v \in V(G)$ and $\ell(I(v))$ the left side of an interval. Let $I'(v) = [\lfloor \ell(I(v)) \rfloor, \lfloor \ell(I(v)) \rfloor + 1]$. This gives us exactly the same graph because the following holds:

$$\begin{aligned} \ell(I(v)) - \ell(I(v)) \leq 1 &\Rightarrow \lfloor \ell(I(v)) \rfloor - \lfloor \ell(I(v)) \rfloor \leq 1 \\ \ell(I(v)) - \ell(I(v)) \geq 1 &\Rightarrow \lfloor \ell(I(v)) \rfloor - \lfloor \ell(I(v)) \rfloor \geq 1 \end{aligned} \tag{3.1}$$

We can have a partition $L_i = \{v : \ell(I'(v)) = i\}$ where every L_i is a clique. Also, this partition is a level structure because the endpoints of L_i meet the endpoints of L_{i-1} and L_{i+1} . \square

We can clearly see that $\text{MUIG} \in \text{UUIG}$. However, we still have to see what is the location of UUIG in the higher graph classes hierarchy:

Proposition 3.3.2. *UUIG \subset co-comparability.*

Proof. This proposition is equivalent to say that if a graph G is a UUIG, then it also has a spanning order.

For each vertex of a partition L_k of UUIG (Theorem 3.3.1) we assign arbitrarily a number $i \in [\max(V(L_{k-1})) + 1, \max(V(L_{k-1})) + |V(L_k)| + 1]$; intuitively, we assign every available number from the beginning in increasing order ($|V(L_1)|$ first numbers on the first partition and consecutively).

Because we know that each partition L_k is a clique, we can say that for each three vertices $u < v < w$, if $vw \in E \Rightarrow uv \in E$ or $vw \in E$. We know this because given $u \in L_i$ and $w \in L_j$: if $uw \in E$ it means that levels L_i and L_j are adjacent, which means that $v \in L_i$ or $v \in L_j$ so v will be adjacent

either to u or w . This is a spanning order. \square

In the other hand, we can find a graph in UIG that is not an UDG. This theorem will be used in Chapter 4.

Proof. We can define $T = (L_1 \cup L_2, E)$ a UIG with two levels $L_1 = \{v_1, v_2, v_3, v_4\}$ and $L_2 = \wp(L_1)$ and $E = \binom{L_1}{2} \cup \binom{L_2}{2} \cup \{vw : w \in L_2, v \in w\}$. For a better visualisation, you can find in Figure 3.8 the representation as an UDG in the case where $L_1 = \{v_1, v_2, v_3\}$.

We can see the UDG representation of G as a Venn diagram of four disks (L_1) where there is a disk of L_2 that intersects only with its subset associated. We know by instance that a Venn diagram cannot be constructed with disks if the number of sets is bigger than four [23] as you can see in Figure 3.9. Thus,




Figure 3.9: A disk Venn diagram of four sets. Each circle of color represent a set. You may notice that some subsets are not represented here (*e.g.* v_2v_4 or v_1v_3). So a disk that touches v_4 and v_2 in this representation is not possible without intersecting also v_3 or v_1 .




Figure 3.10: Extension of the graph classes diagram from Figure 3.2 with *UUIG*.

there will be at least one disk that is not able to intersect with its associated subset because there is at least one subset that is not representable by a disk Venn Diagram. Which means that $G \notin \text{UDG}$. \square

3.3.1 Recognition

As we mentioned in the previous section, UUIG is a class of graphs very relevant to define TSG and that is why we are interested in knowing how this class of graphs is recognized.

Lemma 3.3.4. *Let G be a connected UUIG with a level structure with levels L_1, \dots, L_n . $G \setminus L_i$ is a graph where each connected component is also an UUIG and the number of connected components is not bigger than two.*

Proof. By definition for a graph with a level structure, if $v \in L_i$, $N(v) = L_{i-1} \cup L_i \cup L_{i+1}$. This said, if we delete a level L_i , L_{i-1} and L_{i+1} are disconnected, but they are still connected to the other consecutive levels (L_{i-1} is connected to L_{i-2} , which is connected to L_{i-3} ... and viceversa with L_{i+1}).

And because a level is only adjacent to two other levels, we only have two connected components, only one if $L_i = L_1$ or $L_i = L_n$. \square

By this lemma we can suppose that the input graph G is a connected graph. This observation reduces the complexity of the problem for a graph G from $O(f(|V(G)|))$ to $O(f(|V(H)|))$ where $H \subseteq G$ the biggest component of G .

Theorem 3.3.5. *UUIG recognition is in \mathcal{NP} .*

Proof. The UUIG recognition of a graph G is in \mathcal{NP} because we can build a ***polynomial time verifier*** that takes a level structure of G and check whether each level is a clique or not. Viceversa, we can build another one that takes a partition and check whether each clique is a level of a level structure. \square

Future work on the recognition of unfettered unit interval graphs would be to adapt this algorithm to avoid combinatorial complexity. In our case we are interested in seeing the recognition of UUIG for unit disk graphs. We know that the CLIQUE problem is in \mathcal{P} for unit disk graphs [6] and the first hypothesis was that given an UUIG G , at least one level of G is a maximal clique of the graph. Nevertheless, we have a counterexample in $T_{0,0}$ (Fig. 3.7) where the levels of the graph are $\{K_1, K_2, K_2, K_1\}$ while $\omega(T_{0,0}) = 3$.

Observation 3.3.6. *Given an UUIG G , a level of G does not have to be necessarily a maximal clique.*

Chapter 4

Thin strip graphs

” *Sometimes it is the people no one imagines anything of who do the things that no one can imagine.*

— **Alan Turing**
(The Imitation Game)

The goal of this chapter is to introduce the main subject of this thesis. is a class of graphs that lie between unit disk graphs and mixed interval graphs. We can define formally a as a unit disk graph such that the centers of the disks belong to $\{(x, y) : -\infty < x < \infty, 0 \leq y \leq c\}$, more intuitively we can see this as a unit disk graph where the centers of the disks lie between two parallel horizontal lines with a distance of c between them. We denote this class by $\text{SG}(c)$. We have then that $\text{SG}(0) = \text{UIG}$ and $\text{SG}(\infty) = \text{UDG}$.

The definition and main work for this class comes from Breu in his thesis [5]. However, Hayashi et al. [13] expand his work by defining the class of thin strip graphs.




Figure 4.1: A construction of $K_{1,3}$ with a disk realization, being this graph a TSG.

4.1 c -strip graphs

4.2 Thin strip graphs

A thin strip graph can be intuitively defined as a c -strip graph where c is an arbitrarily little ε . Also, we can see that $\text{SG}(k) \subseteq \text{SG}(l)$ with $k < l$. A more strict definition emerges from this observation:

Definition 4.2.1. Thin strip graphs are defined as $\text{TSG} = \bigcap_{c>0} \text{SG}(c)$.

Remark 4.2.2. $\text{SG}(0) \neq \text{TSG}$. We can construct a $K_{1,3}$ such that we have 3 vertices with the coordinates $(1, 0)$, $(0, 0)$, $(1, 0)$ and a last one $(0, \varepsilon)$ with $\varepsilon > 0$ and arbitrarily small as seen in Figure 4.1.

Theorem 4.2.3 (Hayashi et al. [13]). *There is no constant t such that $\text{SG}(t) = \text{TSG}$.*

Theorem 4.2.4 (Hayashi et al. [13]). *There is no constant t such that $SG(t) = UDG$.*

Hayashi et al. left some open problems. We try to expand the knowledge around some of these problems to understand them better, largely for the recognition of this class of graphs. Before that, we see where this class lays in the hierarchy of classes. We know by definition that $TSG \subsetneq UDG$.

4.2.1 Interval graphs

Thin strip graphs shares their geometrical structure with interval graphs (remember $SG(0) = UIG$). In this subsection, we overview the results of Hayashi et al. [13] where they find maximal and minimal superclasses for TSG in the interval graphs presented in chapter 3. The following theorem will be proven by taking the proof written by Hayashi et al. in order to use their mapping in other theorems (e.g. 5).

Theorem 4.2.5 (Hayashi et al. [13]). *$MUIG \subsetneq TSG$.*

Proof. First, we prove that $MUIG \neq TSG$. This can be proven because $C_4 \in TSG$ if we take as points $(0, 0), (0, \varepsilon), (1, 0), (1, \varepsilon)$ with $1 > \varepsilon > 0$ and $C_4 \notin MUIG$ because it is a chordal graph.

Then, we have to prove that $MUIG \subseteq TSG$. Let $G = (V, E) \in MUIG$ where each vertex is a unit mixed interval denoted as I_v . We define $t = \min\{|I_u \cap I_v| : |I_u \cap I_v| > 0, \{I_u, I_v\} \subseteq V\}$ and $s = \min\{\ell(I_v) - r(I_u) : \ell(I_v) > r(I_u), \{I_u, I_v\} \subseteq V\}$. We have then t being the minimum length of an intersection bigger than zero (that is, not endpoint-adjacent) and s is the minimum distance between non-adjacent vertices (also not endpoint-adjacent). We also define $c(I_v) = \frac{\ell(I_v) + r(I_v)}{2}$ as the center of the interval and $p(I_v) = (-1)^{\lfloor c(I_v) \rfloor}$.

Let d be a real such that $0 < d < \frac{2}{3}$, $d \leq \frac{t}{4}$, $d < \frac{s}{2}$ and $\varepsilon \geq 2\sqrt{d - d^2}$. If we let $h = \sqrt{d - d^2}$, then we can create a $2h$ -realization of G with the following mapping:

$$\phi(v) = \begin{cases} (c(I_v), 0) & \text{if } I_v \text{ is a closed interval} \\ (c(I_v), hp(I_v)) & \text{if } I_v \text{ is an open interval} \\ (c(I_v) - d, hp(I_v)) & \text{if } I_v \text{ is a closed-open interval} \\ (c(I_v) + d, hp(I_v)) & \text{if } I_v \text{ is an open-closed interval} \end{cases}$$

For two vertices u and v of G such that $u \leq v$, we have the three following cases:

1. $r(I_u) < \ell(I_v)$:

I_u and I_v are not adjacents, which means that $\text{dist}(\phi(u), \phi(v)) > 1$. If we minimize the distance between them we have $\phi(u) = (c(I_u) + d, hp(I_u))$ and $\phi(v) = (c(I_v) - d, hp(I_v))$ with $p(I_u) = p(I_v)$. Therefore, we only have to compare their x -coordinates:

$$\text{dist}(\phi(u), \phi(v)) \geq (c(I_v) - d) - (c(I_u) + d) = c(I_v) - c(I_u) - 2d$$

By definition, $s \leq l(I_v) - r(I_u)$. If we take the centers, then $s \leq c(I_v) - c(I_u) - 1$, which means finally that $s + 1 \leq c(I_v) - c(I_u)$

$$\text{dist}(\phi(u), \phi(v)) \geq s + 1 - 2d > 1$$

2. $r(I_u) > \ell(I_v)$: In this case u and v are adjacent. We maximize $\text{dist}(\phi(u), \phi(v))$ when $\phi(u) = (c(I_u) - d, hp(I_u))$ and $\phi(v) = (c(I_v) + d, hp(I_v))$ with $p(I_u) \neq p(I_v)$. Therefore,

$$\begin{aligned} \text{dist}(\phi(u), \phi(v)) &\leq \sqrt{((c(I_v) + d) - (c(I_u) - d))^2 + (h + h)^2} \\ &\text{with the same reasoning as before } c(I_v) - c(I_u) \leq 1 - t \\ &\leq \sqrt{(1 - t + 2d)^2 + 4h^2} \\ &\leq \sqrt{(1 - 4d + 2d)^2 + 4(d - d^2)} \\ &= \sqrt{1 - 4d + 4d^2 + 4d - 4d^2} = 1 \end{aligned}$$

3. $r(I_u) = \ell(I_v)$:

In this case, u and v are adjacent only if $r(I_u)$ and I_v are closed. We know that $c(I_v) = c(I_u) + 1$ and $p(I_u) \neq p(I_v)$. Without loss of generality, we suppose that $p(I_u) = 1$ and $p(I_v) = -1$. We have two cases:

- (a) Both ends are closed. So we have this set of possible assignments for each one of the vertices:

$$\begin{aligned}\phi(u) &\in \{(c(I_u), 0), (c(I_u) + d, h)\} \\ \phi(v) &\in \{(c(I_u) + 1, 0), (c(I_u) + 1 - d, -h)\}\end{aligned}$$

This gives us a rectangle with its diagonal smaller than one.

- (b) One of the ends is closed, we suppose $r(I_u)$ is open. In this case, we have these solutions:

$$\begin{aligned}\phi(u) &\in \{(c(I_u) - d, h), (c(I_u), h)\} \\ \phi(v) &\in \{(c(I_u) + 1, 0), (c(I_u) + 1, -h), (c(I_u) + 1 \pm d, -h)\}\end{aligned}$$

Every distance between every points is greater than 1 if we take into consideration the domain of d . \square

From this theorem, $\text{UIG} \subsetneq \text{TSG}$. Actually, there exists a stronger connection between these two classes:

Theorem 4.2.6 (Breu [5]). *Let G a c -strip graph with $c \in \mathbb{R}_0^+$. G has an induced $K_{1,3}$ or C_4 if and only if G is not an unit interval graph.*

Thin strip graphs can also be seen as unfettered unit interval graphs, which means that if a graph is a thin strip graph, then we can partition this graph with a level structure where each level is a clique. This information will be relevant in the next section.

Theorem 4.2.7 (Hayashi et al. [13]). *$\text{TSG} \subsetneq \text{UUIG}$.*

Proof. See [13].




Figure 4.2: Extension of the graph classes diagram from Figure 4.2 with *TSG* and *UDG*.

4.3 Characterization of thin strip graphs

One of the main goals of this thesis is to characterize thin strip graphs by forbidden induced subgraphs. We know that TSG is an hereditary class, then a way to characterize this class of graphs is by looking for its forbidden subgraphs the same way as MUIG has been characterized by Joos. Furthermore, $\text{MUIG} \subsetneq \text{TSG}$ by Theorem 4.2.5, so the first we can do is to check if the forbidden subgraphs of MUIG are also for TSG.

4.3.1 Mixed unit interval graph forbidden subgraphs

In the previous section we have shown that $\text{MUIG} \subsetneq \text{TSG}$ 4.2.5. We have even shown every forbidden induced subgraph of MUIG in Chapter 3. Here we are going to overview these forbidden induced subgraphs and we their inclusion in TSG. Moreover, we will verify if one of these families is at least in UUIG.

In this subsection, we are going to see the relationship between thin strip graphs and mixed unit interval graphs.



Figure 4.3: Every possible clique partition of R_0 . You may notice that any of the partitions is a level structure.




Figure 4.4: The graph R_{i+1} . You can see that the red edges and vertices are what differ from R_i .

Theorem 4.3.1 (Hayashi et al. [13]). \mathcal{R} is a forbidden induced subgraph family of *UIG*.

Proof. We can prove this by induction on i .

- **Case $i = 0$:** $R_0 \notin \text{UIG}$ because there is no clique partition of R_0 that is also a level structure as seen in Figure 4.3.
- **Case $i = i + 1$:** We suppose that every valid clique partition of R_i is not a level structure. See in Figure 4.4 the edges and vertices that we add to generate R_{i+1} . We call a, b the vertices that were disjoint in R_i and c, d the new vertices. These two vertices are adjacent to b .

Let $\{b, c\}$ or $\{b, d\}$ be a level of our clique partition. By the hypothesis of induction we know that this partition is not a level structure because this partition is a valid partition of R_i because a and b are in different levels. The only way to create a new partition that is not a valid clique partition of R_i is if $\{a, b\}$ is a level. In this case, however, the clique level $\{a, b\}$ will be adjacent to three cliques $\{c\}, \{d\}$ and $\{e, \dots\}$ so this clique partition is not a level structure either.




Figure 4.5: The graph F where each level is represented by a different color.




Figure 4.6: Realization of F as a thin strip graph.

This proves that R_i for every $i \in \mathbb{N}_0$ has not a clique level structure; thus, it is not an UUIG. \square

We see that \mathcal{R} is a family of forbidden subgraphs of TSG. Nevertheless, the rest of the forbidden subgraphs for MUIG are thin strip graphs. The main reason is because they are unfettered unit interval graphs. We see our first example with the forbidden graph for MUIG F .

Theorem 4.3.2. $F \in TSG$.

Proof. To prove this we have to find an ε -realization for our graph $F = (V, E)$ with ε arbitrarily small. Let $\phi(v)$ be the mapping of our vertices on the plane. F has a level structure $L = \{\{u_0, u_1\}, \{v_0, v_1, v_2\}, \{w\}\}$ as shown in Figure 4.5.

We begin to construct the representation as a thin strip graph by placing the vertices v_0, v_1, v_2 on the plane. Simply, we place them on the same x coordinate with an equal distance from v_0 to v_1 and v_1 to v_2 such that they are all adjacent, being those on a y coordinate smaller than ε :

$$\phi(v_k) = \left(0, \varepsilon \frac{k}{2}\right)$$

for $k \in \{0, 1, 2\}$.

We continue with w ; w has to be adjacent to v_0 and v_1 , but not v_2 . We pursue to place it on a y coordinate that is located in the middle between 0 and $\frac{\varepsilon}{2}$ (the y coordinates of v_0 and v_1), which is $\frac{\varepsilon}{4}$. Now we have to find a x coordinate for w such that it touches both v_0 and v_1 but does not intersect with v_2 . By symmetry, we only have to check the adjacency of v_0 and v_2 . We can calculate a point such that the distance between w and v_0 equals one:

$$\begin{aligned} \sqrt{\phi(w)_y^2 + \left(\frac{\varepsilon}{4}\right)^2} &= 1 \\ \phi(w)_x^2 + \left(\frac{\varepsilon}{4}\right)^2 &= 1 \\ \phi(w)_x^2 &= 1 - \left(\frac{\varepsilon}{4}\right)^2 \\ \phi(w)_x &= \sqrt{1 - \left(\frac{\varepsilon}{4}\right)^2} \\ \phi(w)_x &= \sqrt{\frac{16 - \varepsilon^2}{16}} \\ \phi(w)_x &= \frac{\sqrt{16 - \varepsilon^2}}{4} \end{aligned}$$

and by symmetry, $-\frac{\sqrt{16 - \varepsilon^2}}{4}$ is also a candidate. We only have to see if it touches v_2 for every ε :

$$\begin{aligned}
\sqrt{\left(\frac{\sqrt{16-\varepsilon^2}}{4}\right)^2 + \varepsilon^2} &> 1 \\
\sqrt{\frac{16-\varepsilon^2}{16} + \varepsilon^2} &> 1 \\
\sqrt{\frac{16-\varepsilon^2+16\varepsilon}{16}} &> 1 \\
\sqrt{\frac{16+15\varepsilon^2}{16}} &> 1 \\
\frac{1}{4}\sqrt{16+15\varepsilon^2} &> 1
\end{aligned}$$

the expression of the left will always be bigger than one if $\varepsilon \neq 0$, which means that w will never be adjacent to v_2 .

$$\phi(w) = \left(\frac{\sqrt{16-\varepsilon^2}}{4}, \frac{\varepsilon}{4} \right)$$

Finally, we have to place u_0, u_1 . We can remark that the neighbours of u_1 in the second level correspond to the neighbours of w , so it will be placed symmetrically with respect to 0 with the same y coordinate, as we have proven before. Finally, u_0 has to be adjacent to v_0 . We can place it at $(-1, 0)$ with the same argument as the construction of $K_{1,3}$ (see Figure 4.1). The other vertices of the second level v_1 and v_2 will not be adjacent to u_0 unless their y coordinate is 0, which is not the case.

$$\phi(u_1) = \left(-\frac{\sqrt{16-\varepsilon^2}}{4}, \frac{\varepsilon}{4} \right)$$

$$\phi(u_2) = (-1, 0)$$

You can find a visual representation of this graph in Figure 4.6. □

Add drawings for S and S'' like Figure 4.7 and the actual proofs (similar to proof of F , only have to write them!).




Figure 4.7: The graph $T_{4,2}$ with the diamond in red and the arms in green. The $K_{1,3}$ bis from previous lemma is in blue.

4.4 Recognition

The recognition of this class of graphs is approached by Breu in his thesis [5]. He gives a polynomial-time algorithm to recognise strip graphs for a given input with an assignment of y -coordinates for each vertex of the graph and an orientation of the edges of its complement.

Theorem 4.4.1 (Breu [5]). *Let $G = (V, E, \gamma, \vec{E})$ a graph where $\gamma : V \rightarrow [0, c]$ is a function associating a y -coordinate (or a level) to each vertex and \vec{E} an orientation of the complement of the graph. The recognition of c -strip graphs with this input is in \mathcal{P} .*

Observation 4.4.2. *Recognition of c -strip graphs without a given \vec{E} is in \mathcal{NP} .*

Proof. Given an polynomial-time algorithm with a complexity of $O(f(n))$ to solve recognition of $G = (V, E, \gamma, \vec{E})$, we can run again this algorithm by testing every possible orientation of its complement. This algorithm would take $O(f(n))2^{|E|-1} = O(f(n)2^{|E|})$ time to execute. \square

We would like to have an algorithm that solves this problem without knowing the y -coordinates of the vertices. Nevertheless, further research would concentrate on recognition of UIGs. We know that $\text{TSG} \subsetneq \text{UIG}$, and recognition of UIGs is \mathcal{NP} . If we the problem of recognising TSG given a UIG and is solved in polynomial time, then TSG recognition would be \mathcal{NP} . However, given the observations in the end of chapter 3, there may be a polynomial-time algorithm for UIG.




Figure 4.8: A realization as a thin strip graph of $T_{4,2}$ from Figure 4.7. The distance between the disks diminishes with the value of ε , but the disks designated by the black points will never touch.

Chapter 5

Thin two-level graphs

Breu [5] has presented in his thesis a similar class of constrained unit disk graphs where the disks are placed on k horizontal parallel lines. More formally: a disk (x, y) can be placed in $x \in (-\infty, \infty)$ and $y \in L$ with $|L| = k$.

In this chapter we define thin two-level graphs as a two-level graph where $L = \{0, \varepsilon\}$ and ε is an arbitrarily small real number.

5.1 Thin two-level graph

A two-level graph can be defined intuitively as a strip graph such that the disks are placed only on the horizontal lines. In the same way, we can define also

This class of graphs is close to our main class TSG. But we have to know at what point we can rely in this class of graphs to study TSG:

Lemma 5.1.1 (Breu [5]). *Let $abcd$ be a chordless 4-cycle in a two-level graph $G = (V, E)$. Then ad and bc are level edges (they are adjacent in the*




Figure 5.1: Forbidden graph in TTLG

same level), and the others are cross edges for every realization ϕ of G for which $\phi(a)_x < \phi(c)_x$ and $\phi(b)_x < \phi(d)_x$.

With this preliminary result, we proceed to one of our main result:

Theorem 5.1.2. $TTLG \subsetneq TSG$

Proof. By definition, we know that $TTLG \subset TSG$ because the area where the disks can be placed in $TTLG$ is included in the area in TSG .

We can prove that $TTLG \neq TSG$ because we can construct a graph G such that $G \in TSG$ and $G \notin TTLG$. This graph D is a net* graph as described in Figure 5.1.

Part 1. D is a TSG because we can realize it as a TSG if we take as center of disks $(0, 0)$, $(0, z)$, $(0, \epsilon)$, $(1, 0)$, $(1, z)$, $(1, \epsilon)$ such that $0 < z < \epsilon$.

Part 2. Now we have to prove that D is a forbidden induced subgraph of $TTLG$. We will try to construct it by taking an induced subgraph that is realizable: we take $D_{-1} = D - x$ with $x \in V(D)$. We notice that $V(D_{-1})$ is a chordless C_4 ($abcd$) with a vertex e adjacent to any two consecutive vertices $x, y \in V(C_4)$ creating the triangle xye .

By Lemma 5.1.1 we know that $abcda$ is a cycle if ab and cd are level edges. We can classify these vertices in two sets: $\ell(V) = a, d$ and $r(V) = b, c$ where $\forall u \in \ell(V) v \in r(V) : u_x < v_x$.

To realize D_{-1} we have to add a vertex i to C_4 . We can either put it between two line-vertices or put it between two vertices with different level. In the case where we want to put it between two line vertices a and b we have:

$$b_x < d_x < c_x$$

In this case, we have d_x that is adjacent to at least one vertex of the other level. The only way to do this is to put it adjacent to two different level vertices (a and b). Now that we have a realization of D_{-1} , we should add a last vertex j adjacent to i , c and d . If we put j on the right of the cycle, then i has to be on the left to be able to touch c and d . However, it is impossible for j to reach i because between because at each level there is a region $a \cap d$ and $b \cap c$ that neither of these disks can breach, so they will always be disjoint. \square

5.1.1 Relation with interval graphs

The relationship between two-level graphs and interval graphs is clear: a k -two-level graph with $k > 1$ gives us a disconnected graph where every connected component is a unit interval graph. Here we could say that a two-level graph $G = F \cup H$ being F and H unit interval graphs.

Furthermore, this relationship between unit interval graphs and two-level graphs is even stronger:

Theorem 5.1.3 (Breu [5]). *For any value of k , a k -two-level-graph is an union of two unit interval graphs.*

Before proving this, we have to define:

Definition 5.1.4. A short edge τ -two-level graph is a τ -two-level graph $G(V, E)$ such that given $vw \in E$, then $|v_x - w_x| \leq \sqrt{1 - \tau^2}$.

Claim 5.1.5. *A short edge two-level graph is a unit interval graph.*

Proof. See [5].

Proof of theorem. Let $G = (V, E)$ be a two-level graph. Let have $G_S = (V, E_S)$ the graph induced on the short edges and $G_L = (V, E_L)$ a graph induced on the line-edges (between points in the same line). Both of these graphs are unit interval graphs.

We can see that $E_S \cup E_L \subseteq E$, we only have to prove that $E \subseteq E_S \cup E_L$. Given an edge $vw \in E$, if $|v_x - w_x| > \alpha$, then $vw \in E_L$ because two graphs on different levels cannot touch. In the other case, when $|v_x - w_x| \leq \alpha$, v and w can be either in the same level or in different levels.

This shows that every edge of E is in either E_L or E_S , so $E \subseteq E_L \cup E_S$. Which means that $G = G_L \cup G_S$.




Figure 5.2: A representation of a $TL(c)$

Conclusions

The conclusions are to be written with care, because it will be sometimes the part that could convince a potential reader to read the whole document.

Appendices

Appendix A

Graph classes hierarchy




Figure A.1: A hierarchy of every relevant graph of this document. The relation $\text{class}_1 \rightarrow \text{class}_2$ means that $\text{class}_1 \subset \text{class}_2$.

Appendix B

Problems in inclusion

- **MUIG \subsetneq TSG \subsetneq UUIG** : Hayashi [13]
- **MUIG \neq TTLG (Open)**: To prove that MUIG \subsetneq TSG, Hayashi [13] could simulate MUIGs with 4 different levels. Having only two levels, I conjecture that this is not possible. However, MUIG can have C_4 , so an inclusion between these two classes is impossible (it has to be rewritten).
- **TTLG \subsetneq TSG (Open)**: This problem has been solved in my thesis by finding a forbidden graph for TTLG, theorem 4.1.3.
- **TLG \subset TSG (Open)**: This is a plausible stronger statement than the one before. However, this result could make the study of TTLG less relevant. Thus, this result would imply:

$$G \in \text{TLG}(j) \rightarrow G \in \text{SG}(k) : j, k \in \mathbb{R}$$

Appendix C

Problems in forbidden induced subgraph characterization

- **MUIG**: Joos [15] gives us a complete characterization of forbidden graphs.
- **TSG (Open)**: Hayashi [13] says that MUIG's forbidden induced subgraphs also are in TSG. He claims that finding a graph $F \in (\text{UDG} \cap \text{UUIG}) \setminus \text{TSG}$ could be a good starting point. In my thesis I show that a forbidden induced subgraph for MUIG is in $\text{UDG} \cap \text{UUIG}$.
- **TTLG (Open)**: There are many properties about these graphs in Breu's thesis [5].
- **UDG (Open)**: There is no complete characterization of UDG. Can the results of this thesis help find new ones?U

Appendix D

Problems in complexity

- **UIG/IG recognition:** Both of these problems are polynomial.
- **MUIG recognition:** Schuchat et al. give a linear algorithm ($O(|V|^2)$) to recognise MUIGs [19].
- **UDG recognition:** $\exists\mathbb{R}$ -complete [1].
- **SG(c) recognition (Open):** Breu [5] states that SG(c) recognition is polynomial if a complement edge orientation and a mapping $\phi : V \rightarrow [0, c]$ is polynomial as an input of the decision problem.
- **TSG recognition (Open):** Can we get rid of the mapping as input to recognise TSGs? In that case the problem would be at least NP.
- **UUIG recognition (Open):** Informally the recognition of this class of graphs **cannot** be polynomial because we have to find all the cliques of the graph; the CLIQUE problem is NP-complete.

Index

c -strip graph, 22

Care, 38

Thin strip graphs, 22

unfettered unit interval graphs, 16

Bibliography

- [1] Existential Theory of the Reals. In *Algorithms in Real Algebraic Geometry*, volume 10, pages 505–532. Springer Berlin Heidelberg, 2006.
- [2] *Graph Theory*. Springer Berlin Heidelberg, New York, NY, 2017.
- [3] Kellogg S. Booth and George S. Lueker. Testing for the consecutive ones property, interval graphs, and graph planarity using PQ-tree algorithms. *Journal of Computer and System Sciences*, 13(3):335–379, December 1976.
- [4] Andreas Brandstädt, Van Bang Le, and Jeremy P. Spinrad. *Graph Classes: A Survey*. Society for Industrial and Applied Mathematics, January 1999.
- [5] Heinz Breu. *Algorithmic Aspects of Constrained Unit Disk Graphs*. PhD thesis, National Library of Canada = Bibliothèque nationale du Canada, Ottawa, 1996. OCLC: 46501382.
- [6] Brent N. Clark, Charles J. Colbourn, and David S. Johnson. Unit Disk Graphs. *Discrete Mathematics*, 86(1):165–177, 1990.
- [7] Derek G Corneil. Extensions of permutation and interval graphs. In *Proc. 18th Southeastern Conference on Combinatorics, Graph Theory and Computing*, pages 267–276, 1987.
- [8] Peter Damaschke. Distances in cocomparability graphs and their powers. *Discrete Applied Mathematics*, 35(1):67–72, January 1992.

- [9] Mark de Berg, editor. *Computational Geometry: Algorithms and Applications*. Springer, Berlin, 3rd ed edition, 2008.
- [10] Mitre C. Dourado, Van Bang Le, Fábio Protti, Dieter Rautenbach, and Jayme L. Szwarcfiter. Mixed unit interval graphs. *Discrete Mathematics*, 312(22):3357–3363, 2012.
- [11] Mitre C. Dourado, Van Bang Le, Fábio Protti, Dieter Rautenbach, and Jayme L. Szwarcfiter. Mixed unit interval graphs. *Discrete Mathematics*, 312(22):3357–3363, November 2012.
- [12] P. C. Gilmore and A. J. Hoffman. A characterization of comparability graphs and of interval graphs. *Canadian Journal of Mathematics*, 16(0):539–548, January 1964.
- [13] Takashi Hayashi, Akitoshi Kawamura, Yota Otachi, Hidehiro Shinohara, and Koichi Yamazaki. Thin Strip Graphs. *Special Graph Classes and Algorithms — in Honor of Professor Andreas Brandstädt on the Occasion of His 65th Birthday*, 216:203–210, January 2017.
- [14] E. Helly. Über Mengen konvexer Körper mit gemeinschaftlichen Punkten. *Jahresber. Deutsch. Math.-Verein.*, 32:175–176, 1923. cited By 187.
- [15] Felix Joos. A Characterization of Mixed Unit Interval Graphs. *arXiv:1312.0729 [math]*, December 2013.
- [16] Terry A McKee, F. R McMorris, and Society for Industrial and Applied Mathematics. *Topics in Intersection Graph Theory*. Society for Industrial and Applied Mathematics (SIAM, 3600 Market Street, Floor 6, Philadelphia, PA 19104), Philadelphia, Pa., 1999. OCLC: 697895279.
- [17] Fred S Roberts. *Representations of Indifference Relations*. Department of Mathematics, Stanford University., 1968.
- [18] L.M. Schlipf. *Stabbing and Covering Geometric Objects in the Plane*. 2013.

- [19] Alan Shuchat, Randy Shull, Ann N. Trenk, and Lee C. West. Unit Mixed Interval Graphs. *arXiv:1405.4247 [math]*, May 2014.
- [20] Alan Shuchat, Randy Shull, Ann N. Trenk, and Lee C. West. Unit Mixed Interval Graphs. *arXiv:1405.4247 [math]*, May 2014.
- [21] Michael Sipser. *Introduction to the Theory of Computation*. Course Technology, second edition, 2006.
- [22] Alexandre Talon and Jan Kratochvíl. Completion of the mixed unit interval graphs hierarchy. *arXiv:1412.0540 [cs, math]*, December 2014.
- [23] J. Venn. I. ***On the diagrammatic and mechanical representation of propositions and reasonings***. *The London, Edinburgh, and Dublin Philosophical Magazine and Journal of Science*, 10(59):1–18, July 1880.

Todo list

to add or not? we'll see in the end	3
Add drawings for S and S'' like Figure 4.7 and the actual proofs (similar to proof of F , only have to write them!).	31