RENAULT PN	TYPE	YAZAKI PN	INSULATION CODE	LINE STYLE
R100263281	SPOT TAPE	430H31930	7B	
R100269413	SPOT TAPE	430211570	Y	
241A05073R	SPOT TAPE	430Q81940	BE1	
241A01667R	SPOT TAPE	4304X1930	6E	
241A01667R	BREAKOUT TAPE	4304X1930	6F	
241A01667R	BREAKOUT TAPE	4304X1930	6D	
242974057R	FIXED TUBE	45022R09730	TXTX4-R-08	
242976726R	FIXED TUBE	45022R04830	TXTX4-R-05	
242971604R	FIXED TUBE	45020N01834	COT-9	
242973253R	FIXED TUBE	45020N10034	COT-6	
R100215499	FIXED TUBE	45020N02134	COT-13	
R100215495	FIXED TUBE	45020N01634	COT-4.5	

MULTI-CORE	YAZ PN	CUST PN	WIRES	SPEC	ASSEMBLY	ASSEMBLY INTERNAL PN
CBL$4200	181CT6001ZZ	85120380D	10,11	DC302B	FAKRA 1024227 (210-42A-2385AA)	74757734
CBL$4776			39,40	25130		
CBL$7182	181CT6001ZZ	85120380D	100,101	DC302B	FAKRA 1024227 (210-42A-2385CA)	74757734

243408002R:[7298250930]:FEMALE CONN 12P RH 0.64 CPA SLD B

266-42A
HBT/_BCLR
F005E 2AN
C016

PIN	LIAI	WIRE/PLUG	COL	TYPE	MAT	OPTION	TO	PIN2	CABLE
1	35A	25	P	COFLRYB-0.5	SN	(ITP15 || ITP17)	E35A-A	L	
2	35B	26	GY	COFLRYB-0.5	SN	(ITP15 || ITP17)	E35B-A	L	
3	35C	13	BR/W	A3ZP-0.35	SN	(BCB && EPER0) && (ITP15 || ITP17)	1637AA	2	
3	35C	113	BR/W	A3ZP-0.35	SN	(BCB && (EPER3 || EPER4)) && (ITP15 || ITP17)	1637BA	2	
4	35D	14	P/W	A3ZP-0.35	SN	(BCB && EPER0) && (ITP15 || ITP17)	1635AA	2	
4	35D	114	P/W	A3ZP-0.35	SN	(BCB && (EPER3 || EPER4)) && (ITP15 || ITP17)	1635BA	2	
5	47EH	40	G/W	COFLRYB-0.35	SN	ALL	2373AA	4	CBL$4776
6	BT5	34	R/W	COFLRYB-0.35	SN	ALL	2373AA	8	
7		8200299691							
8	35G	16	BE/W	A3ZP-0.35	SN	(BCB && EPER0) && (ITP15 || ITP17)	1634AA	2	
8	35G	116	BE/W	A3ZP-0.35	SN	(BCB && (EPER3 || EPER4)) && (ITP15 || ITP17)	1634CA	2	
9	188M	28	LG/W	A3ZP-0.35	SN	(BCB && EPER0) && (ITP15 || ITP17)	2411AA	2	
9	188M	128	LG/W	A3ZP-0.35	SN	(BCB && (EPER3 || EPER4)) && (ITP15 || ITP17)	2411CA	2	
10	188J	27	DL/W	A3ZP-0.35	SN	(BCB && EPER0) && (ITP15 || ITP17)	2412AA	2	
10	188J	127	DL/W	A3ZP-0.35	SN	(BCB && (EPER3 || EPER4)) && (ITP15 || ITP17)	2412BA	2	
11	47EL	39	BR/W	COFLRYB-0.35	SN	ALL	2373AA	3	CBL$4776
12	35H	15	G/W	A3ZP-0.35	SN	(BCB && EPER0) && (ITP15 || ITP17)	1636AA	2	
12	35H	115	G/W	A3ZP-0.35	SN	(BCB && (EPER3 || EPER4)) && (ITP15 || ITP17)	1636CA	2	

210-42A
PDB/_BCLR
2AN
C010

PIN	LIAI	Wire/Plug	COL	Type	MAT	Option	TO	PIN2	Cable
1	47AR	11	W	ZDC302B-0.4	SN	(BCB && EPER0) && AVCAM	2385AA	1	CBL$4200
1	47AR	101	W	ZDC302B-0.4	SN	(BCB && (EPER3 || EPER4)) && (M3CAM || AVCAM)	2385CA	1	CBL$7182
2	TB1S	10	SI	AMISEN-0.75	SN	(BCB && EPER0) && AVCAM	2385AA	2	CBL$4200
2	TB1S	100	SI	AMISEN-0.75	SN	(BCB && (EPER3 || EPER4)) && (M3CAM || AVCAM)	2385CA	2	CBL$7182

243408516R:[ASSY_R197117A55]:1P - PART OF ASSY CABLE
243655951R:[ASSY_R280197330]: COVER FAKRA (ASSY PA...
74757734: 2P ASSY FAKRA WP COD A-FAKRA WP COD A 1540MM
74757734: 2P ASSY FAKRA WP COD A-FAKRA WP COD A 1540MM

243406186R:[7298228030]:FEMALE CONN 4P RH025 0.635 SLD CPA B

E35A-A
EPISSURE

PIN	LIAI	WIRE	COL	TYPE	OPTION	CONN2	PIN2
L	35A	17	P	A3ZP-0.5	(BCB && EPER0) && (ITP15 || ITP17)	1634AA	1
L	35A	25	P	COFLRYB-0.5	(ITP15 || ITP17)	266-42A	1
L	35A	29	P	A3ZP-0.5	(BCB && EPER0) && (ITP15 || ITP17)	2411AA	1
L	35A	129	P	A3ZP-0.5	(BCB && (EPER3 || EPER4)) && (ITP15 || ITP17)	2411CA	1
L	35A	117	P	A3ZP-0.5	(BCB && (EPER3 || EPER4)) && (ITP15 || ITP17)	1634CA	1
R	35A	19	P	A3ZP-0.5	(BCB && EPER0) && (ITP15 || ITP17)	1635AA	1
R	35A	21	P	A3ZP-0.5	(BCB && EPER0) && (ITP15 || ITP17)	1636AA	1
R	35A	23	P	A3ZP-0.5	(BCB && EPER0) && (ITP15 || ITP17)	1637AA	1
R	35A	31	P	A3ZP-0.5	(BCB && EPER0) && (ITP15 || ITP17)	2412AA	1
R	35A	119	P	A3ZP-0.5	(BCB && (EPER3 || EPER4)) && (ITP15 || ITP17)	1635BA	1
R	35A	123	P	A3ZP-0.5	(BCB && (EPER3 || EPER4)) && (ITP15 || ITP17)	1637BA	1
R	35A	131	P	A3ZP-0.5	(BCB && (EPER3 || EPER4)) && (ITP15 || ITP17)	2412BA	1
R	35A	121	P	A3ZP-0.5	(BCB && (EPER3 || EPER4)) && (ITP15 || ITP17)	1636CA	1

4501020609:[KS7478-0150]:ULTRASONIC WELD:
242439271R:[70393210]: SHRINK TUBE NR1 L=50MM : 1 :

E35B-A
EPISSURE

PIN	LIAI	WIRE	COL	TYPE	OPTION	CONN2	PIN2
L	35B	18	GY	A3ZP-0.5	(BCB && EPER0) && (ITP15 || ITP17)	1634AA	3
L	35B	26	GY	COFLRYB-0.5	(ITP15 || ITP17)	266-42A	2
L	35B	30	GY	A3ZP-0.5	(BCB && EPER0) && (ITP15 || ITP17)	2411AA	3
L	35B	130	GY	A3ZP-0.5	(BCB && (EPER3 || EPER4)) && (ITP15 || ITP17)	2411CA	3
L	35B	118	GY	A3ZP-0.5	(BCB && (EPER3 || EPER4)) && (ITP15 || ITP17)	1634CA	3
R	35B	20	GY	A3ZP-0.5	(BCB && EPER0) && (ITP15 || ITP17)	1635AA	3
R	35B	22	GY	A3ZP-0.5	(BCB && EPER0) && (ITP15 || ITP17)	1636AA	3
R	35B	24	GY	A3ZP-0.5	(BCB && EPER0) && (ITP15 || ITP17)	1637AA	3
R	35B	32	GY	A3ZP-0.5	(BCB && EPER0) && (ITP15 || ITP17)	2412AA	3
R	35B	120	GY	A3ZP-0.5	(BCB && (EPER3 || EPER4)) && (ITP15 || ITP17)	1635BA	3
R	35B	124	GY	A3ZP-0.5	(BCB && (EPER3 || EPER4)) && (ITP15 || ITP17)	1637BA	3
R	35B	132	GY	A3ZP-0.5	(BCB && (EPER3 || EPER4)) && (ITP15 || ITP17)	2412BA	3
R	35B	122	GY	A3ZP-0.5	(BCB && (EPER3 || EPER4)) && (ITP15 || ITP17)	1636CA	3

4501020609:[KS7478-0150]:ULTRASONIC WELD:
242439271R:[70393210]: SHRINK TUBE NR1 L=50MM : 1 :

NOTE 6
7B SPOT TAPE USED TO CLOSE ENDS OF COT TUBES INSTEAD OF 7C (ACCORDING TO CUSTOMER RULE) BY CUSTOMER REQUEST. YAZAKI DOES NOT ACCEPT ANY CLAIMS RELATED.

NOTE 5
COT-13 BETWEEN N74730 AND N74764
COT-6 INSULATION ON 1635AA/BA AND 1637AA/BA BRANCHES CANNOT BE CHANGED
SAME CONFIGURATION MUST BE KEPT IN THE FUTURE

NOTE 7: 6E CROSS TAPING APPLICATION FOR FX20

NOTE 77
INSULATION FILLING RATE OVER %80 FOR N18-N74767
YAZAKI DOES NOT ACCEPT ANY CLAIMS RELATED.

NOTE 1: GENERAL REQUIREMENTS

1.1. PRODUCTION AND SUPPLY OF PRODUCTS ACCORDING TO THE STANDARD 00-10-415--S
1.2. PROHIBITED OR RESTRICTED SUBSTANCES IN PARTS ACCORDING TO STANDARD GDN-1903-2024-0002 V3.0
1.3. PART HAS TO BE COMPLIANT WITH STANDARD 36-05-013 --N (CDC WIRING)
1.4. PART HAS TO BE COMPLIANT WITH GDN-0120-2024-0001 V2.0 (WIRING MEASUREMENT AND TOLERANCE)
1.5. PART HAS TO BE COMPLIANT WITH GDN-3605-2024-0007 V2.0 (FOR HIGH SPEED COAXIAL)

NOTE 2: MARKING

2.1. MARKING ACCORDING TO THE STANDARD 00-10-501--E
2.2. MARKING ACCORDING TO THE STANDARD 03-00-002---
    2.2.1. LOGOTYPE TYPE 1
    2.2.2. RENAULT PART REFERENCE, 10 CHARACTERS
    2.2.3. RENAULT PART INDEX, 3 CHARACTERS
    2.2.4. DATER
    2.2.5. SUPPLIER'S COMPANY NAME AND MANUFACTURING SITE
    2.2.6. TEAM CODE
    2.2.7. ELECTRICAL CONTROL CERTIFICATION
2.3. VISUALIZATION OF THE MARKING LABEL : SEE SHEET 1
2.4. LOCATION OF THE LABEL ON THE PART : SEE SHEET 1

2.2.5
2.2.1
2.2.2
2.2.3
2.2.4
2.2.6
2.2.7

NOTE 3: HARNESS METIER SPECIFICATION

3.1. UNLESS OTHERWISE SPECIFIED, THE CONNECTOR BOLTS WILL BE SHIPPED CLOSED AND THE LEVERS OPEN, NOT GUARANTEED FOR DELIVERY
3.2. DO NOT MANAGE EXTRA-LENGTH OF WIRES OR SPLICES IN DYNAMIC LOOPS
3.3. LENGTHS OF INTERNAL WIRES INSIDE DUCTS AND COVERS ARE MANAGED BY THE SUPPLIER
3.4. NOTE PACKAGING DYNAMIC LOOP:
HARNESSES WILL NOT BE BENDED MORE THAN 45° OR HOOKED DURING ASSEMBLY, HANDLING AND PACKAGING IN THE AREA WHERE THE DYNAMIC LOOP IS DEFINED
3.5. PASSIVE SAFETY: ANY MODIFICATION OF THE ROUTING OR OF THE NATURE AND ARRANGEMENT OF MECHANICAL PROTECTION (CRASH TUBE) MUST BE APPROUVED BY THE PASSIVE SAVETY PPC OF VEHICULE
3.6. TOLERANCES OF MANUFACTURING:
- GENERAL STANDARD TOLERANCE ON LENGTHS:
  - L ≤ 1000mm TOLERANCE = -5mm / + 5mm
  - L ≤ 1000mm TOLERANCE (BRANCH END)= -0mm / + 10mm
  - L > 1000mm TOLERANCE = -0 / + 1%
- MINIMAL TOLERANCE (CONTRAINT CASE):
  - L ≤ 1000mm TOLERANCE = -3mm / + 3mm
  - L ≤ 1000mm TOLERANCE (BRANCH END) = -0mm / + 5mm
- STANDARD TOLERANCE BETWEEN REFERENTIAL
  - L ≤ 1000mm TOLERANCE = -0mm / + 10mm
  - L > 1000mm TOLERANCE = -0 / + 1%
- MINIMUM TOLERANCE BETWEEN REFERENTIAL
  - L ≤ 1000mm TOLERANCE = -0mm / + 5mm
- MAXIMUM TOLERANCE (SLACK AND EXCESS LENGTH):
  - L ≤ 1000mm TOLERANCE = -15mm / + 15mm
- TOLERANCE OF OUTER COVER LENGTH:
  - L ≤ 1000mm = -5mm / + 5mm
  - L > 1000mm = -0.5% / + 0.5%
- ANGULAR TOLERANCE:
  - α = -15° / + 15 °

3.7. ELECTROMAGNETIC COMPATIBILITY: ANY MODIFICATION OF THE TECHNICAL DEFINITION OF THE HARNESS THAT AFFECTS THE EMC REGULATORY PERFORMANCE BY ADDING OR REMOVING A FERRITE OR SHIELDING MUST BE VALIDATED BY RENAULT ENGINEERING IN CONJUNCTION WITH THE ECM RRSH
3.8 IDENTIFICATION OF HIGH VOLTAGE HARNESS BY ORANGE COLOUR : ANY CHANGE OF THE TECHNICAL DEFINITION OF THE HARNESS THAT AFFECTS ITS IDENTIFICATION USING THE CORANGE COLOUR MUST BE VALIDATED BY RENAULT ENGINEERING IN CONJUCTION WITH THE "ELECTRIC SAFETY" RRSH

YAZAKI ADDITIONS TO GDN-0120-2024-0001:

-THE MINIMUM TOLERANCES BELOW, WILL BE PREVIOUSLY SUBMITTED TO YAZAKI PLANT FEASIBILITY AGREEMENT VIA DFS SUBMITTED BY THE CUSTOMER
L ≤ 1000mm TOLERANCE= -3mm +3mm/ L ≤ 1000mm TOLERANCE (BRANCHE END) = 0mm +5mm / L ≤ 1000mm BETWEEN REFERENTIAL = 0mm +5mm
-SPECIFIC ANGULAR DIMENSIONS WILL BE PREVIOUSLY SUBMITTED TO YAZAKI PLANT FEASIBILITY AGREEMENT VIA DFS SUBMITTED BY THE CUSTOMER
- CLIP FIXATIONS MUST RESPECT THE ORIENTATIONS REQUIRED ON THE CUSTOMER DRAWING
- BRANCH ORIENTATION IS ONLY GUARANTEED ON PRODUCTION TABLES
- PACKAGING TOLERANCES ARE CONSTRAINT TO MAXIMAL TOLERANCES EXCEPT SPECIFIC NOTES -15mm +15mm

CONFORMEMENT A LA NORME LISTE VISAMAT ANNEXE 1 *CONSISTENLY WITH STANDARD VISAMAT LIST IN APPENDIX 1*	01-00-510 --H	
M : METALLIQUE/*METALLIC* P : POLYMERE/*POLYMER*	M	P
PLAN SOUMIS A LA SIGNATURE *DRAWING SUBJECTED TO SIGNATURE*		
PLAN NON SOUMIS A LA SIGNATURE *DRAWING NOT SUBJECTED TO SIGNATURE*	☒	☒

ISO GPS

SPECIFICATION DIMENSIONNELLE, GEOMETRIQUE ET D'ETATS DE SURFACE SELON L'ISO 8015:2011 ET CONFORMEMENT A LA NORME RENAULT : 00-10-039 --A

DIMENSIONAL, GEOMETRICAL AND SURFACE TEXTURE SPECIFICATIONS ACCORDING TO ISO 8015:2011 AND WITH ACCORDANCE TO THE RENAULT STANDARD 00-10-039 --A

OPERATEUR DE SPECIFICATION DE TAILLE PAR DEFAUT/ *DEFAULT SPECIFICATION OPERATOR FOR SIZE :*

TAILLE LINEAIRE ISO 14405 Ⓔ ☐ OUI/*YES*
LINEAR SIZE ISO 14405 Ⓔ ☒ NON/*NO*

COTATION ET TOLERANCEMENT DES PIECES NON RIGIDES SELON / *DIMENSIONNING AND TOLERANCING OF THE NON-RIGID PARTS IS CARRIED OUT IN ACCORDING TO :*

ISO10579 ☒ OUI/*YES* (1)
☐ NON/*NO*

(1) ASSUREZ VOUS QUE LES CONDITIONS DE CONTRAINTE A APPLIQUER SONT SPECIFIEES / *MAKE SURE THAT THE CONSTRAINT CONDITIONS TO BE APPLIED ARE SPECIFIED*

HIERARCHISATION DES CARACTERISTIQUES NORME 01-33-301
CLASSIFICATION OF REQUIREMENTS STANDARD 01-33-301

TOTALE
TOTAL

TOUTE CARACTERISTIQUE NON HIERARCHISEE EST DE NIVEAU 3
ANY CHARACTERISTIC NOT CLASSIFIED BELONGS TO LEVEL 3

WAVE : INCI	TCC :TCC_XCB_BCB_YAZAKI_TR0526_--R_EXCEL	17/03/2026

FIS : FIS595303-1
MODIFICATIONS APPLYED AFTER THE FICHINIT :

DFS APPLIED BY FICHINIT:
DFS580913-1, DFS584174-1, DFS587982-1, DFS594995-1, DFS595048-1, DFS600352-1

CUSTOMER PN	CUSTOMER REV	WEIGHT Kg	CIRCUITS	ALL	AVCAM	BCB	EPER3	EPER4	ITP17	M3CAM
253A95853R	---	0.296	13	X		X	X	X		
253A99285R	---	0.53	35	X	X	X	X	X	X	X

YAZAKI

YAZAKI SYSTEMS TECHNOLOGIES FRANCE SAS
2 RUE RENÉ CAUDRON,BÂTIMENT E
78960 VOISINS LE BRETONNEUX FRANCE

CABLAGE BOUCLIER AVANT

FRONT BUMPER HARNESS

DRAWN BY M.ALKAN	DATE 09/01/2026	DRAWING REALIZED WITH HXC SIEMENS	
CHECKED BY U.KARACA	PROJECT BCB	3D PART NUMBER OCIE754777	3D REV 028
HARNESS STATUS Released	WAVE INCI	PEI NUMBER 2D0051833P	PEI REV --K
THIS DRAWING IS THE EXCLUSIVE PROPERTY OF YAZAKI SYSTEMS TECHNOLOGIES FRANCE SAS WHICH TRANSFER IT TO RENAULT GROUP FOR THE PROGRAM NEEDS ON STRICTLY CONFIDENTIAL BASE	FORMAT 2xA0	HARNESS WEIGHT	SHEET 1/2