C014 | 264-68A
HBT/_HAYON_D
PART OF ASSY
C020 | 589-68A
HBT_/_BCLR_A
RENAULT
100 / R1
210 / R1
R1
R5
N13701
N74276
N13807
C016 | 2688AA
RDR_LAT_ARG
N7429
N57400
N74256
N13805
177 / R4
251 / R3
480 / R5
587 / R5
R6
B
R7
275 / R6
N36401
N74280
C009 | 1778AA
CAMERA_AR
C010 | 1778BA
CAMERA_AR
C006 | 167BA
ECL_PLQ_G_PO
N13704
N13705
N13714
CLIP CHECKER
C011 | 2413AA
CPTR_DTCN_LT
R4
C001 | 1218AA
CPTR_ARG_EXT
R3
N57402
N9200
PACKAGING NOTE 4
BE1 BE1
N74282
C005 | 166BA
ECL_PLQ_D_PO
N13706
C013 | 259-68A
RAC_HBT/_BCL
R15
N13804
241 / R15
C
N74255
239 / R8
147 / R10
N33203
N9202
N57408
N13803
C015 | 2687AA
RDR_LAT_ARD
N13707
N57412
C002 | 1219AA
CPTR_ARD_EXT
R8
N13708
C012 | 2414AA
CPTR_DTCN_LT
R10
C007 | 174AA
F/B_ARD
C017 | 2757CA
F/MA_D_BCLR
N13709
N13710
488 / R13
C003 | 1220AA
CPTR_ARD_INT
N13711
D
R13
566 / R12
365 / R12
205 / R12
N74273
N74272
N74275
C004 | 1221AA
CPTR_ARG_INT
N13712
N74274
R12
273 / R11
110 / R11
C008 | 175AA
F/B_ARG
R11
N13713
C018 | 2758CA
F/MA_G_BCLR
N13700
N74277
COT-6
COT-9
COT-13
COT-4.5
COT-11
M5TX4-E
FX1 FX2 FX3 FX4 FX5 FX6 FX7 FX8 FX9 FX10 FX11 FX12 FX13 FX15
242104093R [7047055330] TIE CLIP:1.0:
242715845R [7247003430] TIE CLIP:1.0:
242712089R [7047798230] TIE CLIP:1.0:
242710329R [7047798330] TIE CLIP:1.0:
4501020608:[7490Q19405] IDENT. LABEL 75X45:1.0: ID LABEL RENAULT
4501020608:[7490Q19405] IDENT. LABEL 75X45:1.0: CLIP CHECKER

RENAULT PN	TYPE	YAZAKI PN	INSULATION CODE	LINE STYLE
R100269413	SPOT TAPE	430211570	Y	
241A05073R	SPOT TAPE	430Q81940	BE1	
R100269409	SPOT TAPE	430211540	W	
241A06924R	SPOT TAPE	430FF1930	1E	
241A06924R	SPOT TAPE	430FF1930	1B	
241A06924R	BREAKOUT TAPE	430FF1930	1C	
241A06924R	BREAKOUT TAPE	430FF1930	1D	
R100263281	OVERLAP TAPE	430H31930	M5TX4-E	▨
242971604R	FIXED TUBE	45020N01834	COT-9	⌇
R100215495	FIXED TUBE	45020N01634	COT-4.5	⌇
R100215499	FIXED TUBE	45020N02134	COT-13	⌇
242973253R	FIXED TUBE	45020N10034	COT-6	⌇
R100215498	FIXED TUBE	45020N03234	COT-11	⌇

MULTI-CORE	YAZ PN	CUST PN	WIRES	SPEC	ASSEMBLY	ASSEMBLY INTERNAL PN
CBL$1719			34,35	25130		
CBL$545	181FQ5002ZZ	241A17625R	59,60,61,62	FLRMYMY		
CBL$1998			36,37	25130		
CBL$6794	181CT6001ZZ	85120380D	21,20	DC302B	FAKRA 1021374 (264-68A-1778BA)	74750965

264-68A
HBT/_HAYON_D
2AN
C014

PIN	LIAI	Wire/Plug	COL	Type	MAT	Option	TO	PIN2	Cable
1	34KL	20	W	ZDC302B-0.4	SN	BCB && (AVCAM || M3CAM || RRCA2)	1778BA	1	CBL$6794
2	TB34	21	SI	AMISEN-0.75	SN	BCB && (AVCAM || M3CAM || RRCA2)	1778BA	2	CBL$6794

264-68A

243408516R:[ASSY_R197117A55]:1P - PART OF ASSY CABLE
243655951R:[ASSY_R280197330]: COVER FAKRA (ASSY PA...
74750965:2P ASSY FAKRA - FAKRA SLD 990MM

589-68A
HBT_/_BCLR_A
F005E 2AN
C020

PIN	LIAI	WIRE/PLUG	COL	TYPE	MAT	OPTION	TO	PIN2	CABLE
1	LPH	14	BR	COFLRYB-0.5	SN	BCB	ELPH-A	L	
2	47FH	35	BR/W	COFLRYB-0.35	SN	BCB && (BSD00 || BSD02)	2688AA	1	CBL$1719
3	188D	32	LG/W	COFLRYB-0.35	SN	BCB && (BSD00 || BSD02)	2688AA	6	
4	34KI	60	BR	ZFLRMYBY-0.35		BCB && RRCAM	1778AA	1	CBL$545
5	34KJ	59	B	PDRAIN-0.35		BCB && RRCAM	1778AA	3	CBL$545
6	66H	3	GY	COFLRYB-0.5	SN	BCB	E66H-A	L	
7		8200299691							
8	47FL	34	P/W	COFLRYB-0.35	SN	BCB && (BSD00 || BSD02)	2688AA	2	CBL$1719
9	NAU	15	B	COFLRYB-0.5	SN	BCB	ENAU-A	L	
10	34KL	61	R	ZFLRMYBY-0.35		BCB && RRCAM	1778AA	2	CBL$545
11	34KK	62	Y	ZFLRMYBY-0.35		BCB && RRCAM	1778AA	4	CBL$545
12	9P	16	G	COFLRYB-0.5	SN	BCB	E9P-A	L	

Ⓟ Ⓢ 589-68A

243408002R:[7298250930]:FEMALE CONN 12P RH 0.64 CPA SLD B

2688AA
RDR_LAT_ARG
F005E 2AN
C016

PIN	LIAI	WIRE/PLUG	COL	TYPE	MAT	OPTION	TO	PIN2	CABLE
1	47FH	35	BR/W	COFLRYB-0.35	SN	BCB && (BSD00 || BSD02)	589-68A	2	CBL$1719
2	47FL	34	P/W	COFLRYB-0.35	SN	BCB && (BSD00 || BSD02)	589-68A	8	CBL$1719
3		8200299691							
4		8200299691							
5		8200299691							
6	188D	32	LG/W	COFLRYB-0.35	SN	BCB && (BSD00 || BSD02)	589-68A	3	
7		8200299691							
8		8200299691							
9		8200299691							
10	NAU	30	B/W	COFLRYB-0.35	SN	BCB && (BSD00 || BSD02)	ENAU-B	L	
11	NAU	31	B/W	COFLRYB-0.35	SN	BCB && (BSD00 || BSD02)	ENAU-B	L	
12	BPT8	23	R	COFLRYB-0.5	SN	BSD00 || BSD02	EBPT8-B	L	

Ⓟ Ⓢ 2688AA

243408002R:[7298250930]:FEMALE CONN 12P RH 0.64 CPA SLD B

ELPH-A
EPISSURE

PIN	LIAI	WIRE	COL	TYPE	OPTION	CONN2	PIN2
L	LPH	14	BR	COFLRYB-0.5	BCB	589-68A	1
R	LPH	4	BR	COFLRYB-0.5	BCB	166BA	1
R	LPH	6	BR	COFLRYB-0.5	BCB	167BA	1

4501020609:[KS7478-0150]:ULTRASONIC WELD:
[242439271R] : SHRINK TUBE NR1 L=50MM:1.0

EBPT8-B
EPISSURE

PIN	LIAI	WIRE	COL	TYPE	OPTION	CONN2	PIN2
L	BPT8	23	R	COFLRYB-0.5	BSD00 || BSD02	2688AA	12
R	BPT8	22	R	COFLRYB-0.5	BSD00 || BSD02	2687AA	12
R	BPT8	24	R	COFLRYB-0.5	BCB && (BSD00 || BSD02)	259-68A	12

4501020609:[KS7478-0150]:ULTRASONIC WELD:
[242439271R] : SHRINK TUBE NR1 L=50MM:1.0

Ⓟ 1778AA

243407133R:[7289417530]:4P CONN MCON MSLD FEMALE B

1778AA
CAMERA_AR
2AN
C009

PIN	LIAI	Wire/Plug	COL	Type	MAT	Option	TO	PIN2	Cable
1	34KI	60	BR	ZFLRMYBY-0.35		BCB && RRCAM	589-68A	4	CBL$545
2	34KL	61	R	ZFLRMYBY-0.35		BCB && RRCAM	589-68A	10	CBL$545
3	34KJ	59	B	PDRAIN-0.35		BCB && RRCAM	589-68A	5	CBL$545
4	34KK	62	Y	ZFLRMYBY-0.35		BCB && RRCAM	589-68A	11	CBL$545

1778BA
PART OF ASSY

243408516R:[ASSY_R197117A55]:1P - PART OF ASSY CABLE
243655951R:[ASSY_R280197330]: COVER FAKRA (ASSY PA...

1778BA
CAMERA_AR
2AN
C010

PIN	LIAI	Wire/Plug	COL	Type	MAT	Option	TO	PIN2	Cable
1	34KL	20	W	ZDC302B-0.4	SN	BCB && (AVCAM || M3CAM || RRCA2)	264-68A	1	CBL$6794
2	TB34	21	SI	AMISEN-0.75	SN	BCB && (AVCAM || M3CAM || RRCA2)	264-68A	2	CBL$6794

74750965:2P ASSY FAKRA - FAKRA SLD 990MM

ENAU-B
EPISSURE

PIN	LIAI	WIRE	COL	TYPE	OPTION	CONN2	PIN2
L	NAU	30	B/W	COFLRYB-0.35	BCB && (BSD00 || BSD02)	2688AA	10
L	NAU	31	B/W	COFLRYB-0.35	BCB && (BSD00 || BSD02)	2688AA	11
R	NAU	25	B/W	COFLRYB-0.35	BCB && (BSD00 || BSD02)	ENAU-A	L
R	NAU	27	B/W	COFLRYB-0.35	BCB && (BSD00 || BSD02)	2687AA	10
R	NAU	28	B/W	COFLRYB-0.35	BCB && (BSD00 || BSD02)	2687AA	11
R	NAU	29	B/W	COFLRYB-0.35	BCB && (BSD00 || BSD02)	2687AA	5

4501020609:[KS7478-0150]:ULTRASONIC WELD:
[242439271R] : SHRINK TUBE NR1 L=50MM:1.0

Ⓟ Ⓢ 167BA

243404638R:[7298186530]:FEMALE CONN 2P RH 0.64 CPA SLD B

167BA
ECL_PLQ_G_PO
F005E 2AN
C006

PIN	LIAI	WIRE/PLUG	COL	TYPE	MAT	OPTION	TO	PIN2
1	LPH	6	BR	COFLRYB-0.5	SN	BCB	ELPH-A	R
2	NAU	7	B	COFLRYB-0.5	SN	BCB	ENAU-A	L

Ⓟ Ⓢ 2413AA

243402127R:[7298691130]:FEMALE CONN 3P MLK1.2 CPA SLD B

2413AA
CPTR_DTCN_LT
FM1T1 2AN
C011

PIN	LIAI	WIRE/PLUG	COL	TYPE	MAT	OPTION	TO	PIN2
1	151U	52	GY/W	A3ZP-0.35	SN	BCB && (ITP14 || ITP15 || ITP17)	E151U-A	L
2	188S	57	P/W	A3ZP-0.35	SN	BCB && (ITP14 || ITP15 || ITP17)	259-68A	10
3	151V	53	DL/W	A3ZP-0.35	SN	BCB && (ITP14 || ITP15 || ITP17)	E151V-A	L

Ⓟ Ⓢ 1218AA

243402127R:[7298691130]:FEMALE CONN 3P MLK1.2 CPA SLD B

1218AA
CPTR_ARG_EXT
FM1T1 2AN
C001

PIN	LIAI	WIRE/PLUG	COL	TYPE	MAT	OPTION	TO	PIN2
1	151U	38	GY/W	A3ZP-0.35	SN	(ITP14 || ITP15 || ITP17 || ITPK0)	E151U-A	L
2	151C	51	BR/W	A3ZP-0.35	SN	BCB && (ITP14 || ITP15 || ITP17 || ITPK0)	259-68A	1
3	151V	39	DL/W	A3ZP-0.35	SN	(ITP14 || ITP15 || ITP17 || ITPK0)	E151V-A	L

Ⓟ Ⓢ 175AA

243404638R:[7298186530]:FEMALE CONN 2P RH 0.64 CPA SLD B

175AA
F/B_ARG
F005E 2AN
C008

PIN	LIAI	WIRE/PLUG	COL	TYPE	MAT	OPTION	TO	PIN2
1	9P	10	G	COFLRYB-0.5	SN	BCB	E9P-A	R
2	NAU	11	B	COFLRYB-0.5	SN	BCB	ENAU-A	R

Ⓟ Ⓢ 2758CA

243406054R:[7298186710]:FEMALE CONN 2P RH 0.64 CPA SLD DGY

2758CA
F/MA_G_BCLR
F005E 2AN
C018

PIN	LIAI	WIRE/PLUG	COL	TYPE	MAT	OPTION	TO	PIN2
1	66H	18	GY	COFLRYB-0.5	SN	BCB	E66H-A	R
2	NAU	13	B	COFLRYB-0.5	SN	BCB	ENAU-A	R

1221AA
CPTR_ARG_INT
FM1T1 2AN
C004

PIN	LIAI	WIRE/PLUG	COL	TYPE	MAT	OPTION	TO	PIN2
1	151U	44	GY/W	A3ZP-0.35	SN	BCB && (ITP14 || ITP15 || ITP17 || ITPK0)	E151U-A	R
2	151M	49	G/W	A3ZP-0.35	SN	BCB && (ITP14 || ITP15 || ITP17 || ITPK0)	259-68A	7
3	151V	45	DL/W	A3ZP-0.35	SN	BCB && (ITP14 || ITP15 || ITP17 || ITPK0)	E151V-A	R

Ⓟ Ⓢ 1221AA

243402127R:[7298691130]:FEMALE CONN 3P MLK1.2 CPA SLD B

NOTE 6: 1E CROSS TAPING APPLICATION FOR FX8,FX2,FX9.FX13

Ⓟ Ⓢ 166BA

243404638R:[7298186530]:FEMALE CONN 2P RH 0.64 CPA SLD B

166BA
ECL_PLQ_D_PO
F005E 2AN
C005

PIN	LIAI	WIRE/PLUG	COL	TYPE	MAT	OPTION	TO	PIN2
1	LPH	4	BR	COFLRYB-0.5	SN	BCB	ELPH-A	R
2	NAU	5	B	COFLRYB-0.5	SN	BCB	ENAU-A	L

ENAU-A
EPISSURE

PIN	LIAI	WIRE	COL	TYPE	OPTION	CONN2	PIN2
L	NAU	5	B	COFLRYB-0.5	BCB	166BA	2
L	NAU	7	B	COFLRYB-0.5	BCB	167BA	2
L	NAU	15	B	COFLRYB-0.5	BCB	589-68A	9
L	NAU	25	B/W	COFLRYB-0.35	BCB && (BSD00 || BSD02)	ENAU-B	R
R	NAU	9	B	COFLRYB-0.5	BCB	174AA	2
R	NAU	11	B	COFLRYB-0.5	BCB	175AA	2
R	NAU	12	B	COFLRYB-0.5	BCB	2757CA	2
R	NAU	13	B	COFLRYB-0.5	BCB	2758CA	2

4501020609:[KS7478-0150]:ULTRASONIC WELD:
[242439271R] : SHRINK TUBE NR1 L=50MM:1.0

E66H-A
EPISSURE

PIN	LIAI	WIRE	COL	TYPE	OPTION	CONN2	PIN2
L	66H	3	GY	COFLRYB-0.5	BCB	589-68A	6
R	66H	17	GY	COFLRYB-0.5	BCB	2757CA	1
R	66H	18	GY	COFLRYB-0.5	BCB	2758CA	1

4501020609:[KS7478-0150]:ULTRASONIC WELD:
[242439271R] : SHRINK TUBE NR1 L=50MM:1.0

E151V-A
EPISSURE

PIN	LIAI	WIRE	COL	TYPE	OPTION	CONN2	PIN2
L	151V	39	DL/W	A3ZP-0.35	(ITP14 || ITP15 || ITP17 || ITPK0)	1218AA	3
L	151V	41	DL/W	A3ZP-0.35	(ITP14 || ITP15 || ITP17 || ITPK0)	1219AA	3
L	151V	50	DL/W	COFLRYB-0.35	BCB && (ITP14 || ITP15 || ITP17 || ITPK0)	259-68A	9
L	151V	53	DL/W	A3ZP-0.35	BCB && (ITP14 || ITP15 || ITP17)	2413AA	3
L	151V	55	DL/W	A3ZP-0.35	BCB && (ITP14 || ITP15 || ITP17)	2414AA	3
R	151V	43	DL/W	A3ZP-0.35	BCB && (ITP14 || ITP15 || ITP17 || ITPK0)	1220AA	3
R	151V	45	DL/W	A3ZP-0.35	BCB && (ITP14 || ITP15 || ITP17 || ITPK0)	1221AA	3

4501020609:[KS7478-0150]:ULTRASONIC WELD:
[242439271R] : SHRINK TUBE NR1 L=50MM:1.0

2757CA
F/MA_D_BCLR
F005E 2AN
C017

PIN	LIAI	WIRE/PLUG	COL	TYPE	MAT	OPTION	TO	PIN2
1	66H	17	GY	COFLRYB-0.5	SN	BCB	E66H-A	R
2	NAU	12	B	COFLRYB-0.5	SN	BCB	ENAU-A	R

E151U-A
EPISSURE

PIN	LIAI	WIRE	COL	TYPE	OPTION	CONN2	PIN2
L	151U	38	GY/W	A3ZP-0.35	(ITP14 || ITP15 || ITP17 || ITPK0)	1218AA	1
L	151U	40	GY/W	A3ZP-0.35	(ITP14 || ITP15 || ITP17 || ITPK0)	1219AA	1
L	151U	46	GY/W	COFLRYB-0.35	BCB && (ITP14 || ITP15 || ITP17 || ITPK0)	259-68A	3
L	151U	52	GY/W	A3ZP-0.35	BCB && (ITP14 || ITP15 || ITP17)	2413AA	1
L	151U	54	GY/W	A3ZP-0.35	BCB && (ITP14 || ITP15 || ITP17)	2414AA	1
R	151U	42	GY/W	A3ZP-0.35	BCB && (ITP14 || ITP15 || ITP17 || ITPK0)	1220AA	1
R	151U	44	GY/W	A3ZP-0.35	BCB && (ITP14 || ITP15 || ITP17 || ITPK0)	1221AA	1

4501020609:[KS7478-0150]:ULTRASONIC WELD:
[242439271R] : SHRINK TUBE NR1 L=50MM:1.0

Ⓟ Ⓢ 2757CA

243406054R:[7298186710]:FEMALE CONN 2P RH 0.64 CPA SLD DGY

174AA
F/B_ARD
F005E 2AN
C007

PIN	LIAI	WIRE/PLUG	COL	TYPE	MAT	OPTION	TO	PIN2
1	9P	8	G	COFLRYB-0.5	SN	BCB	E9P-A	R
2	NAU	9	B	COFLRYB-0.5	SN	BCB	ENAU-A	R

Ⓟ Ⓢ 174AA

243404638R:[7298186530]:FEMALE CONN 2P RH 0.64 CPA SLD B

Ⓟ Ⓢ 1220AA

243402127R:[7298691130]:FEMALE CONN 3P MLK1.2 CPA SLD B

1220AA
CPTR_ARD_INT
FM1T1 2AN
C003

PIN	LIAI	WIRE/PLUG	COL	TYPE	MAT	OPTION	TO	PIN2
1	151U	42	GY/W	A3ZP-0.35	SN	BCB && (ITP14 || ITP15 || ITP17 || ITPK0)	E151U-A	R
2	151Q	48	L/W	A3ZP-0.35	SN	BCB && (ITP14 || ITP15 || ITP17 || ITPK0)	259-68A	2
3	151V	43	DL/W	A3ZP-0.35	SN	BCB && (ITP14 || ITP15 || ITP17 || ITPK0)	E151V-A	R

E9P-A
EPISSURE

PIN	LIAI	WIRE	COL	TYPE	OPTION	CONN2	PIN2
L	9P	16	G	COFLRYB-0.5	BCB	589-68A	12
R	9P	8	G	COFLRYB-0.5	BCB	174AA	1
R	9P	10	G	COFLRYB-0.5	BCB	175AA	1

4501020609:[KS7478-0150]:ULTRASONIC WELD:
[242439271R] : SHRINK TUBE NR1 L=50MM:1.0

259-68A
RAC_HBT/_BCL
F005E 2AN
C013

PIN	LIAI	WIRE/PLUG	COL	TYPE	MAT	OPTION	TO	PIN2	CABLE
1	151C	51	BR/W	A3ZP-0.35	SN	BCB && (ITP14 || ITP15 || ITP17 || ITPK0)	1218AA	2	
2	151Q	48	L/W	A3ZP-0.35	SN	BCB && (ITP14 || ITP15 || ITP17 || ITPK0)	1220AA	2	
3	151U	46	GY/W	COFLRYB-0.35	SN	BCB && (ITP14 || ITP15 || ITP17 || ITPK0)	E151U-A	L	
4	188P	56	BE/W	A3ZP-0.35	SN	BCB && (ITP14 || ITP15 || ITP17)	2414AA	2	
5	47FH	37	P/W	COFLRYB-0.35	SN	BCB && (BSD00 || BSD02)	2687AA	1	CBL$1998
6	188F	33	G/W	COFLRYB-0.35	SN	BCB && (BSD00 || BSD02)	2687AA	6	
7	151M	49	G/W	A3ZP-0.35	SN	BCB && (ITP14 || ITP15 || ITP17 || ITPK0)	1221AA	2	
8	151H	47	BR/W	A3ZP-0.35	SN	BCB && (ITP14 || ITP15 || ITP17 || ITPK0)	1219AA	2	
9	151V	50	DL/W	COFLRYB-0.35	SN	BCB && (ITP14 || ITP15 || ITP17 || ITPK0)	E151V-A	L	
10	188S	57	P/W	A3ZP-0.35	SN	BCB && (ITP14 || ITP15 || ITP17)	2413AA	2	
11	47FL	36	BR/W	COFLRYB-0.35	SN	BCB && (BSD00 || BSD02)	2687AA	2	CBL$1998
12	BPT8	24	R	COFLRYB-0.5	SN	BCB && (BSD00 || BSD02)	EBPT8-B	R	

Ⓟ Ⓢ 259-68A

243408002R:[7298250930]:FEMALE CONN 12P RH 0.64 CPA SLD B

Ⓟ Ⓢ 2687AA

243408002R:[7298250930]:FEMALE CONN 12P RH 0.64 CPA SLD B

2687AA
RDR_LAT_ARD
F005E 2AN
C015

PIN	LIAI	WIRE/PLUG	COL	TYPE	MAT	OPTION	TO	PIN2	CABLE
1	47FH	37	P/W	COFLRYB-0.35	SN	BCB && (BSD00 || BSD02)	259-68A	5	CBL$1998
2	47FL	36	BR/W	COFLRYB-0.35	SN	BCB && (BSD00 || BSD02)	259-68A	11	CBL$1998
3		8200299691							
4		8200299691							
5	NAU	29	B/W	COFLRYB-0.35	SN	BCB && (BSD00 || BSD02)	ENAU-B	R	
6	188F	33	G/W	COFLRYB-0.35	SN	BCB && (BSD00 || BSD02)	259-68A	6	
7		8200299691							
8		8200299691							
9		8200299691							
10	NAU	27	B/W	COFLRYB-0.35	SN	BCB && (BSD00 || BSD02)	ENAU-B	R	
11	NAU	28	B/W	COFLRYB-0.35	SN	BCB && (BSD00 || BSD02)	ENAU-B	R	
12	BPT8	22	R	COFLRYB-0.5	SN	BSD00 || BSD02	EBPT8-B	R	

Ⓟ Ⓢ 1219AA

243402127R:[7298691130]:FEMALE CONN 3P MLK1.2 CPA SLD B

1219AA
CPTR_ARD_EXT
FM1T1 2AN
C002

PIN	LIAI	WIRE/PLUG	COL	TYPE	MAT	OPTION	TO	PIN2
1	151U	40	GY/W	A3ZP-0.35	SN	(ITP14 || ITP15 || ITP17 || ITPK0)	E151U-A	L
2	151H	47	BR/W	A3ZP-0.35	SN	BCB && (ITP14 || ITP15 || ITP17 || ITPK0)	259-68A	8
3	151V	41	DL/W	A3ZP-0.35	SN	(ITP14 || ITP15 || ITP17 || ITPK0)	E151V-A	L

Ⓟ Ⓢ 2414AA

243402127R:[7298691130]:FEMALE CONN 3P MLK1.2 CPA SLD B

2414AA
CPTR_DTCN_LT
FM1T1 2AN
C012

PIN	LIAI	WIRE/PLUG	COL	TYPE	MAT	OPTION	TO	PIN2
1	151U	54	GY/W	A3ZP-0.35	SN	BCB && (ITP14 || ITP15 || ITP17)	E151U-A	L
2	188P	56	BE/W	A3ZP-0.35	SN	BCB && (ITP14 || ITP15 || ITP17)	259-68A	4
3	151V	55	DL/W	A3ZP-0.35	SN	BCB && (ITP14 || ITP15 || ITP17)	E151V-A	L

NOTE 1: GENERAL REQUIREMENTS

1.1. PRODUCTION AND SUPPLY OF PRODUCTS ACCORDING TO THE STANDARD 00-10-415--S
1.2. PROHIBITED OR RESTRICTED SUBSTANCES IN PARTS ACCORDING TO STANDARD GDN-1903-2024-0002 V3.0
1.3. PART HAS TO BE COMPLIANT WITH STANDARD 36-05-013 --N (CDC WIRING)
1.4. PART HAS TO BE COMPLIANT WITH GDN-0120-2024-0001 V2.0 (WIRING MEASUREMENT AND TOLERANCE)
1.5. PART HAS TO BE COMPLIANT WITH GDN-3605-2024-0007 V2.0 (FOR HIGH SPEED COAXIAL)

NOTE 2: MARKING

2.1. MARKING ACCORDING TO THE STANDARD 00-10-501--E
2.2. MARKING ACCORDING TO THE STANDARD 03-00-002---
  2.2.1. LOGOTYPE TYPE 1
  2.2.2. RENAULT PART REFERENCE, 10 CHARACTERS
  2.2.3. RENAULT PART INDEX, 3 CHARACTERS
  2.2.4. DATER
  2.2.5. SUPPLIER'S COMPANY NAME AND MANUFACTURING SITE
  2.2.6. TEAM CODE
  2.2.7. ELECTRICAL CONTROL CERTIFICATION
2.3. VISUALIZATION OF THE MARKING LABEL : SEE SHEET 1
2.4. LOCATION OF THE LABEL ON THE PART : SEE SHEET 1

2.2.5
2.2.1
2.2.2
2.2.3
2.2.4
2.2.6
2.2.7

NOTE 3: HARNESS METIER SPECIFICATION

3.1. UNLESS OTHERWISE SPECIFIED, THE CONNECTOR BOLTS WILL BE SHIPPED CLOSED AND THE LEVERS OPEN, NOT GUARANTEED FOR DELIVERY
3.2. DO NOT MANAGE EXTRA-LENGTH OF WIRES OR SPLICES IN DYNAMIC LOOPS
3.3. LENGTHS OF INTERNAL WIRES INSIDE DUCTS AND COVERS ARE MANAGED BY THE SUPPLIER
3.4. NOTE PACKAGING DYNAMIC LOOP:
HARNESSES WILL NOT BE BENDED MORE THAN 45° OR HOOKED DURING ASSEMBLY,
HANDLING AND PACKAGING IN THE AREA WHERE THE DYNAMIC LOOP IS DEFINED
3.5. PASSIVE SAFETY: ANY MODIFICATION OF THE ROUTING OR OF THE NATURE AND ARRANGEMENT OF MECHANICAL PROTECTION (CRASH TUBE) MUST BE APPROUVED BY THE PASSIVE SAVETY PPC OF VEHICULE
3.6. TOLERANCES OF MANUFACTURING:
- GENERAL STANDARD TOLERANCE ON LENGTHS:
  - $L \le 1000$mm TOLERANCE = -5mm / + 5mm
  - $L \le 1000$mm TOLERANCE (BRANCH END)= -0mm / + 10mm
  - $L > 1000$mm TOLERANCE = -0 / + 1%
- MINIMAL TOLERANCE (CONTRAINT CASE):
  - $L \le 1000$mm TOLERANCE = -3mm / + 3mm
  - $L \le 1000$mm TOLERANCE (BRANCH END) = -0mm / + 5mm
- STANDARD TOLERANCE BETWEEN REFERENTIAL
  - $L \le 1000$mm TOLERANCE = -0mm / + 10mm
  - $L > 1000$mm TOLERANCE = -0 / + 1%
- MINIMUM TOLERANCE BETWEEN REFERENTIAL
  - $L \le 1000$mm TOLERANCE = -0mm / + 5mm
- MAXIMUM TOLERANCE (SLACK AND EXCESS LENGTH):
  - $L \le 1000$mm TOLERANCE = -15mm / + 15mm
- TOLERANCE OF OUTER COVER LENGTH:
  - $L \le 1000$mm = -5mm / + 5mm
  - $L > 1000$mm = -0.5% / + 0.5%
- ANGULAR TOLERANCE:
  - $\alpha = -15° / + 15°$

3.7. ELECTROMAGNETIC COMPATIBILITY: ANY MODIFICATION OF THE TECHNICAL DEFINITION OF THE HARNESS THAT AFFECTS THE EMC REGULATORY PERFORMANCE BY ADDING OR REMOVING A FERRITE OR SHIELDING MUST BE VALIDATED BY RENAULT ENGINEERING IN CONJUNCTION WITH THE ECM RRSH
3.8 IDENTIFICATION OF HIGH VOLTAGE HARNESS BY ORANGE COLOUR : ANY CHANGE OF THE TECHNICAL DEFINITION OF THE HARNESS THAT AFFECTS ITS IDENTIFICATION USING THE CORANGE COLOUR MUST BE VALIDATED BY RENAULT ENGINEERING IN CONJUCTION WITH THE "ELECTRIC SAFETY" RRSH

YAZAKI ADDITIONS TO GDN-0120-2024-0001:

-THE MINIMUM TOLERANCES BELOW, WILL BE PREVIOUSLY SUBMITTED TO YAZAKI PLANT FEASIBILITY AGREEMENT VIA DFS SUBMITTED BY THE CUSTOMER
$L \le 1000$mm TOLERANCE= -3mm +3mm/ $L \le 1000$mm TOLERANCE (BRANCHE END) = 0mm +5mm / $L \le 1000$mm BETWEEN REFERENTIAL = 0mm +5mm
-SPECIFIC ANGULAR DIMENSIONS WILL BE PREVIOUSLY SUBMITTED TO YAZAKI PLANT FEASIBILITY AGREEMENT VIA DFS SUBMITTED BY THE CUSTOMER
- CLIP FIXATIONS MUST RESPECT THE ORIENTATIONS REQUIRED ON THE CUSTOMER DRAWING
- BRANCH ORIENTATION IS ONLY GUARANTEED ON PRODUCTION TABLES
- PACKAGING TOLERANCES ARE CONSTRAINT TO MAXIMAL TOLERANCES EXCEPT SPECIFIC NOTES -15mm +15mm

CONFORMEMENT A LA NORME LISTE VISAMAT ANNEXE 1 *CONSISTENLY WITH STANDARD VISAMAT LIST IN APPENDIX 1*	01-00-510 --H	
M : METALLIQUE/*METALLIC* P : POLYMERE/*POLYMER*	M	P
PLAN SOUMIS A LA SIGNATURE *DRAWING SUBJECTED TO SIGNATURE*		
PLAN NON SOUMIS A LA SIGNATURE *DRAWING NOT SUBJECTED TO SIGNATURE*	☒	☒

ISO GPS

SPECIFICATION DIMENSIONNELLE, GEOMETRIQUE ET D'ETATS DE SURFACE SELON l'ISO 8015:2011 ET CONFORMEMENT A LA NORME RENAULT : 00-10-039 --A

DIMENSIONAL,GEOMETRICAL AND SURFACE TEXTURE SPECIFICATIONS ACCORDING TO ISO 8015:2011 AND WITH ACCORDANCE TO THE RENAULT STANDARD 00-10-039 --A

OPERATEUR DE SPECIFICATION DE TAILLE PAR DEFAUT/ *DEFAULT SPECIFICATION OPERATOR FOR SIZE :*

TAILLE LINEAIRE ISO 14405 Ⓔ ☐ OUI/*YES*
LINEAR SIZE ISO 14405 Ⓔ ☒ NON/*NO*

COTATION ET TOLERANCEMENT DES PIECES NON RIGIDES SELON / *DIMENSIONNING AND TOLERANCING OF THE NON-RIGID PARTS IS CARRIED OUT IN ACCORDING TO :*

ISO10579 ☒ OUI/*YES* (1)
☐ NON/*NO*

(1) ASSUREZ VOUS QUE LES CONDITIONS DE CONTRAINTE A APPLIQUER SONT SPECIFIEES / *MAKE SURE THAT THE CONSTRAINT CONDITIONS TO BE APPLIED ARE SPECIFIED*

HIERARCHISATION DES CARACTERISTIQUES NORME 01-33-301
CLASSIFICATION OF REQUIREMENTS STANDARD 01-33-301

TOTALE
TOTAL

TOUTE CARACTERISTIQUE NON HIERARCHISEE EST DE NIVEAU 3
ANY CHARACTERISTIC NOT CLASSIFIED BELONGS TO LEVEL 3

CUSTOMER PN	CUSTOMER REV	WEIGHT Kg	CIRCUITS	ALL	AVCAM	BCB	BSD02	EPER4	ITP17	ITPK0	M3CAM	RRCA2
240151748R	---	0.389	32	X		X		X		X		X
240155239R	---	0.533	53	X	X	X	X	X	X		X	

WAVE : INCI	TCC : TCC_XCB_BCB_YAZAKI_TR0526_--R_EXCEL	17/03/2026

FIS : FIS595307-1
MODIFICATIONS APPLYED AFTER THE FICHINIT :
DFS604464-1, DFS607862-1

DFS APPLIED BY FICHINIT:
DFS573262-1, DFS580916-1, DFS584253-1, DFS585076-1, DFS594999-1, DFS598814-1, DFS598843-1, DFS602650-1

YAZAKI

YAZAKI SYSTEMS TECHNOLOGIES FRANCE SAS
2 RUE RENÉ CAUDRON,BÂTIMENT E
78960 VOISINS LE BRETONNEUX FRANCE

CABLAGE BOUCLIER ARRIERE

REAR BUMPER HARNESS

DRAWN BY M.ALKAN	DATE 09/02/2026	DRAWING REALIZED WITH HXC SIEMENS	
CHECKED BY B.KAR	PROJECT BCB	3D PART NUMBER OCIE753462	3D REV 031
HARNESS STATUS Released	WAVE INCI	PEI NUMBER 2D0051835P	PEI REV --K
FORMAT 2xA0	HARNESS WEIGHT	SHEET 1/2	

THIS DRAWING IS THE EXCLUSIVE PROPERTY OF YAZAKI SYSTEMS TECHNOLOGIES FRANCE SAS WHICH TRANSFER IT TO RENAULT GROUP FOR THE PROGRAM NEEDS ON STRICTLY CONFIDENTIAL BASE