NOTE 1: GENERAL REQUIREMENTS

1.1. PRODUCTION AND SUPPLY OF PRODUCTS ACCORDING TO THE STANDARD 00-10-415--U
1.2. PROHIBITED OR RESTRICTED SUBSTANCES IN PARTS ACCORDING TO STANDARD GDN-1903-2024-0002 V3.0
1.3. PART HAS TO BE COMPLIANT WITH STANDARD 36-05-013 --P (CDC WIRING)
1.4. PART HAS TO BE COMPLIANT WITH GDN-0120-2024-0001 V3.0 (WIRING MEASUREMENT AND TOLERANCE)
1.5. PART HAS TO BE COMPLIANT WITH GDN-3605-2024-0007 V2.0 (FOR HIGH SPEED COAXIAL)

NOTE 2: MARKING

2.1. MARKING ACCORDING TO THE STANDARD 00-10-501--G
2.2. MARKING ACCORDING TO THE STANDARD 03-00-002---
  2.2.1. LOGOTYPE TYPE 1
  2.2.2. RENAULT PART REFERENCE, 10 CHARACTERS
  2.2.3. RENAULT PART INDEX, 3 CHARACTERS
  2.2.4. DATER
  2.2.5. SUPPLIER'S COMPANY NAME AND MANUFACTURING SITE
  2.2.6. TEAM CODE
  2.2.7. ELECTRICAL CONTROL CERTIFICATION
2.3. VISUALIZATION OF THE MARKING LABEL : SEE SHEET 1
2.4. LOCATION OF THE LABEL ON THE PART : SEE SHEET 1

2.2.5
2.2.1
2.2.2
2.2.3
2.2.4
2.2.6
2.2.7

NOTE 3: HARNESS METIER SPECIFICATION

3.1. UNLESS OTHERWISE SPECIFIED, THE CONNECTOR BOLTS WILL BE SHIPPED CLOSED AND THE LEVERS OPEN, NOT GUARANTEED FOR DELIVERY
3.2. DO NOT MANAGE EXTRA-LENGTH OF WIRES OR SPLICES IN DYNAMIC LOOPS
3.3. LENGTHS OF INTERNAL WIRES INSIDE DUCTS AND COVERS ARE MANAGED BY THE SUPPLIER
3.4. NOTE PACKAGING DYNAMIC LOOP:
HARNESSES WILL NOT BE BENDED MORE THAN 45° OR HOOKED DURING ASSEMBLY,
HANDLING AND PACKAGING IN THE AREA WHERE THE DYNAMIC LOOP IS DEFINED
3.5. PASSIVE SAFETY: ANY MODIFICATION OF THE ROUTING OR OF THE NATURE AND ARRANGEMENT OF MECHANICAL PROTECTION (CRASH TUBE) MUST BE APPROUVED BY THE PASSIVE SAVETY PPC OF VEHICULE
3.6. TOLERANCES OF MANUFACTURING:
- GENERAL STANDARD TOLERANCE ON LENGTHS:
  - $L \leq 1000mm$ TOLERANCE = -5mm / + 5mm
  - $L \leq 1000mm$ TOLERANCE (BRANCH END)= -0mm / + 10mm
  - $L > 1000mm$ TOLERANCE = -0 / + 1%
- MINIMAL TOLERANCE (CONTRAINT CASE):
  - $L \leq 1000mm$ TOLERANCE = -3mm / + 3mm
  - $L \leq 1000mm$ TOLERANCE (BRANCH END) = -0mm / + 5mm
- STANDARD TOLERANCE BETWEEN REFERENTIAL
  - $L \leq 1000mm$ TOLERANCE = -0mm / + 10mm
  - $L > 1000mm$ TOLERANCE = -0 / + 1%
- MINIMUM TOLERANCE BETWEEN REFERENTIAL
  - $L \leq 1000mm$ TOLERANCE = -0mm / + 5mm
- MAXIMUM TOLERANCE (SLACK AND EXCESS LENGTH):
  - $L \leq 1000mm$ TOLERANCE = -15mm / + 15mm
- TOLERANCE OF OUTER COVER LENGTH:
  - $L \leq 1000mm$ = -5mm / + 5mm
  - $L > 1000mm$ = -0.5% / + 0.5%
- ANGULAR TOLERANCE:
  - α = -15° / + 15 °

3.7. ELECTROMAGNETIC COMPATIBILITY: ANY MODIFICATION OF THE TECHNICAL DEFINITION OF THE HARNESS THAT AFFECTS THE EMC REGULATORY PERFORMANCE BY ADDING OR REMOVING A FERRITE OR SHIELDING MUST BE VALIDATED BY RENAULT ENGINEERING IN CONJUNCTION WITH THE ECM RRSH
3.8 IDENTIFICATION OF HIGH VOLTAGE HARNESS BY ORANGE COLOUR : ANY CHANGE OF THE TECHNICAL DEFINITION OF THE HARNESS THAT AFFECTS ITS IDENTIFICATION USING THE CORANGE COLOUR MUST BE VALIDATED BY RENAULT ENGINEERING IN CONJUCTION WITH THE "ELECTRIC SAFETY" RRSH

CONFORMEMENT A LA NORME LISTE VISAMAT ANNEXE 1 *CONSISTENLY WITH STANDARD* *VISAMAT LIST IN APPENDIX 1*	01-00-510 --H	
M : METALLIQUE/*METALLIC* P : POLYMERE/*POLYMER*	M	P
PLAN SOUMIS A LA SIGNATURE *DRAWING SUBJECTED TO SIGNATURE*		
PLAN NON SOUMIS A LA SIGNATURE *DRAWING NOT SUBJECTED TO SIGNATURE*	☒	☒

ISO GPS

SPECIFICATION DIMENSIONNELLE, GEOMETRIQUE ET D'ETATS DE SURFACE SELON l'ISO 8015:2011 ET CONFORMEMENT A LA NORME RENAULT : 00-10-039 --B

DIMENSIONAL,GEOMETRICAL AND SURFACE TEXTURE SPECIFICATIONS ACCORDING TO ISO 8015:2011 AND WITH ACCORDANCE TO THE RENAULT STANDARD 00-10-039 --B

OPERATEUR DE SPECIFICATION DE TAILLE PAR DEFAUT/ *DEFAULT SPECIFICATION OPERATOR FOR SIZE :*

TAILLE LINEAIRE ISO 14405 Ⓔ ☐ OUI/*YES*
LINEAR SIZE ISO 14405 Ⓔ ☒ NON/*NO*

COTATION ET TOLERANCEMENT DES PIECES NON RIGIDES SELON / *DIMENSIONNING AND TOLERANCING OF THE NON-RIGID PARTS IS CARRIED OUT IN ACCORDING TO :*

ISO10579 ☒ OUI/*YES* (1)
☐ NON/*NO*

(1) ASSUREZ VOUS QUE LES CONDITIONS DE CONTRAINTE A APPLIQUER SONT SPECIFIEES / *MAKE SURE THAT THE CONSTRAINT CONDITIONS TO BE APPLIED ARE SPECIFIED*

HIERARCHISATION
DES CARACTERISTIQUES
NORME 01-33-301
CLASSIFICATION
OF REQUIREMENTS
STANDARD 01-33-301

TOTALE
TOTAL

TOUTE CARACTERISTIQUE
NON HIERARCHISEE EST
DE NIVEAU 3
ANY CHARACTERISTIC
NOT CLASSIFIED BELONGS
TO LEVEL 3

WAVE : DEFNE	TCC : TCC_XCB_HCB_YAZAKI_TR0526_--V_EXCEL	FIS595230-1

FIS : DFS577604-1 / DFS577607-1 / DFS580225-1 / DFS580229-1 / DFS580969-1 / DFS580974-1 / DFS580986-1 / DFS580993-1 / DFS580997-1 / DFS581000-1 / DFS581403-1 / DFS581415-1 / DFS582035-1 / DFS586438-1 / DFS586444-1 / DFS586890-1 / DFS586893-1 / DFS586909-1 / DFS588454-1 / DFS588459-1 / DFS591020-1 / DFS591022-1 / DFS593717-1 / DFS593719-1 / DFS598323-1 / DFS598325-1 / DFS598327-1 / DFS598329-1 / DFS598625-1 / DFS598628-1 / DFS598640-1 / DFS598745-1 / DFS598779-1 / DFS601762-1 / DFS601764-1 / DFS601951-1 / DFS601953-1

APPLIED AFTER THE FI : DFS602353-1 / DFS602358-1

YAZAKI

YAZAKI SYSTEMS TECHNOLOGIES FRANCE SAS
2 RUE RENÉ CAUDRON,BÂTIMENT E
78960 VOISINS LE BRETONNEUX FRANCE

CABLAGE PDB DG

LHD DASHBOARD

DRAWN BY E.UCAR	DATE 06/02/2026	DRAWING REALIZED WITH HXC SIEMENS	
CHECKED BY M.GIRGIN	PROJECT HCB	3D PART NUMBER OCCM07NNDL.	3D REV 024
HARNESS STATUS Released	WAVE DEFNE	PEI NUMBER 2D0070257P	PEI REV --J
THIS DRAWING IS THE EXCLUSIVE PROPERTY OF YAZAKI SYSTEMS TECHNOLOGIES FRANCE SAS WHICH TRANSFER IT TO RENAULT GROUP FOR THE PROGRAM NEEDS ON STRICTLY CONFIDENTIAL BASE	FORMAT 2xA0	HARNESS WEIGHT	SHEET 1/14