RENAULT PN	TYPE	YAZAKI PN	INSULATION CODE	LINE STYLE
241A01667R	SPOT TAPE	4304X1930	6C	
241A05073R	SPOT TAPE	430Q81940	BE1	
241A01667R	BREAKOUT TAPE	4304X1930	6H	
241A01667R	BREAKOUT TAPE	4304X1930	6G	
241A01667R	BREAKOUT TAPE	4304X1930	6F	
241A01667R	BREAKOUT TAPE	4304X1930	6D	
242974057R	FIXED TUBE	45022R09730	TXTX4-R-08	
242976726R	FIXED TUBE	45022R04830	TXTX4-R-05	
242977221R	FIXED TUBE	45022R04430	TXTX4-R-10	
242971604R	FIXED TUBE	45020N01834	COT-9	
R100215499	FIXED TUBE	45020N02134	COT-13	
R100215495	FIXED TUBE	45020N01634	COT-4.5	
242973253R	FIXED TUBE	45020N10034	COT-6	
R100215510	FIXED TUBE	45063401636	COTX-4.5	
242978698R	FIXED TUBE	45063410036	COTX-6	
241A06924R	SPIRAL TAPE	430FF1930	TA-D	

MULTI-CORE	YAZ PN	CUST PN	WIRES	SPEC	ASSEMBLY	ASSEMBLY INTERNAL PN
CBL$4200			15,16		FAKRA 1024224 (210-42A - 2385AA)	74757738
CBL$7853			3,4	25130		
CBL$4201			1500,1600		FAKRA 1024225 210-42A 2385BA	74757737

C012 | 266-42A PSG_COMPART/
C013 | 210-42A PASSENGER_CO
C007 | 1758AA LH_FR_DAY_LI
C003 | 1635AA PARKING_AID_
C009 | 2385AA FR_CAMERA
C0085 | 2385BA FR_CAMERA
C005 | 1637AA PARKING_AID_
C001 | 106-42A FR/_FR_SHIEL
C004 | 1636AA PARKING_AID_
C033 | 1636BA PARKING_AID_
C011 | 2412AA PARKING_AID_
C035 | 1757BA RH_FR_DAY_LI
C006 | 1757AA RH_FR_DAY_LI
C008 | 2373AA FRONT_COLLIS
C032 | 1634BA PARKING_AID_
C002 | 1634AA PARKING_AID_
C031 | 1758BA LH_FR_DAY_LI
C030 | 2411BA PARKING_AID_
C010 | 2411AA PARKING_AID_
E35B-A EPISSURE
E35A-A EPISSURE
ENU-C EPISSURE
PACKAGING BE1
ID LABEL RENAULT
CLIP CHECKER
PART OF ASSY
R1 R2 R3 R4 R5 R6 R7 R8 R9 R10 R11 R13 R14 R15 R16 R17

NOTE 6

INSULATION FILLING RATE OVER %80 FOR C-N531552 YAZAKI DOES NOT ACCEPT ANY CLAIMS RELATED.

NOTE 1: GENERAL REQUIREMENTS

1.1. PRODUCTION AND SUPPLY OF PRODUCTS ACCORDING TO THE STANDARD 00-10-415--U
1.2. PROHIBITED OR RESTRICTED SUBSTANCES IN PARTS ACCORDING TO STANDARD GDN-1903-2024-0002 V3.0
1.3. PART HAS TO BE COMPLIANT WITH STANDARD 36-05-013 --P (CDC WIRING)
1.4. PART HAS TO BE COMPLIANT WITH GDN-0120-2024-0001 V3.0 (WIRING MEASUREMENT AND TOLERANCE)
1.5. PART HAS TO BE COMPLIANT WITH GDN-3605-2024-0007 V2.0 (FOR HIGH SPEED COAXIAL)

NOTE 2: MARKING

2.1. MARKING ACCORDING TO THE STANDARD 00-10-501--G
2.2. MARKING ACCORDING TO THE STANDARD 03-00-002---
    2.2.1. LOGOTYPE TYPE 1
    2.2.2. RENAULT PART REFERENCE, 10 CHARACTERS
    2.2.3. RENAULT PART INDEX, 3 CHARACTERS
    2.2.4. DATER
    2.2.5. SUPPLIER'S COMPANY NAME AND MANUFACTURING SITE
    2.2.6. TEAM CODE
    2.2.7. ELECTRICAL CONTROL CERTIFICATION
2.3. VISUALIZATION OF THE MARKING LABEL : SEE SHEET 1
2.4. LOCATION OF THE LABEL ON THE PART : SEE SHEET 1

2.2.5
2.2.1
2.2.2
2.2.3
2.2.4
2.2.6
2.2.7

NOTE 3: HARNESS METIER SPECIFICATION

3.1. UNLESS OTHERWISE SPECIFIED, THE CONNECTOR BOLTS WILL BE SHIPPED CLOSED AND THE LEVERS OPEN, NOT GUARANTEED FOR DELIVERY
3.2. DO NOT MANAGE EXTRA-LENGTH OF WIRES OR SPLICES IN DYNAMIC LOOPS
3.3. LENGTHS OF INTERNAL WIRES INSIDE DUCTS AND COVERS ARE MANAGED BY THE SUPPLIER
3.4. NOTE PACKAGING DYNAMIC LOOP:
HARNESSES WILL NOT BE BENDED MORE THAN 45° OR HOOKED DURING ASSEMBLY, HANDLING AND PACKAGING IN THE AREA WHERE THE DYNAMIC LOOP IS DEFINED
3.5. PASSIVE SAFETY: ANY MODIFICATION OF THE ROUTING OR OF THE NATURE AND ARRANGEMENT OF MECHANICAL PROTECTION (CRASH TUBE) MUST BE APPROUVED BY THE PASSIVE SAVETY PPC OF VEHICULE
3.6. TOLERANCES OF MANUFACTURING:
- GENERAL STANDARD TOLERANCE ON LENGTHS:
    - L ≤ 1000mm TOLERANCE = -5mm / + 5mm
    - L ≤ 1000mm TOLERANCE (BRANCH END)= -0mm / + 10mm
    - L > 1000mm TOLERANCE = -0 / + 1%
- MINIMAL TOLERANCE (CONTRAINT CASE):
    - L ≤ 1000mm TOLERANCE = -3mm / + 3mm
    - L ≤ 1000mm TOLERANCE (BRANCH END) = -0mm / + 5mm
- STANDARD TOLERANCE BETWEEN REFERENTIAL
    - L ≤ 1000mm TOLERANCE = -0mm / + 10mm
    - L > 1000mm TOLERANCE = -0 / + 1%
- MINIMUM TOLERANCE BETWEEN REFERENTIAL
    - L ≤ 1000mm TOLERANCE = -0mm / + 5mm
- MAXIMUM TOLERANCE (SLACK AND EXCESS LENGTH):
    - L ≤ 1000mm TOLERANCE = -15mm / + 15mm
- TOLERANCE OF OUTER COVER LENGTH:
    - L ≤ 1000mm = -5mm / + 5mm
    - L > 1000mm = -0.5% / + 0.5%
- ANGULAR TOLERANCE:
    - α = -15° / + 15 °

3.7. ELECTROMAGNETIC COMPATIBILITY: ANY MODIFICATION OF THE TECHNICAL DEFINITION OF THE HARNESS THAT AFFECTS THE EMC REGULATORY PERFORMANCE BY ADDING OR REMOVING A FERRITE OR SHIELDING MUST BE VALIDATED BY RENAULT ENGINEERING IN CONJUNCTION WITH THE ECM RRSH
3.8 IDENTIFICATION OF HIGH VOLTAGE HARNESS BY ORANGE COLOUR : ANY CHANGE OF THE TECHNICAL DEFINITION OF THE HARNESS THAT AFFECTS ITS IDENTIFICATION USING THE CORANGE COLOUR MUST BE VALIDATED BY RENAULT ENGINEERING IN CONJUCTION WITH THE "ELECTRIC SAFETY" RRSH

YAZAKI ADDITIONS TO GDN-0120-2024-0001:

-THE MINIMUM TOLERANCES BELOW, WILL BE PREVIOUSLY SUBMITTED TO YAZAKI PLANT FEASIBILITY AGREEMENT VIA DFS SUBMITTED BY THE CUSTOMER
L ≤ 1000mm TOLERANCE= -3mm +3mm/ L ≤ 1000mm TOLERANCE (BRANCHE END) = 0mm +5mm / L ≤ 1000mm BETWEEN REFERENTIAL = 0mm +5mm
-SPECIFIC ANGULAR DIMENSIONS WILL BE PREVIOUSLY SUBMITTED TO YAZAKI PLANT FEASIBILITY AGREEMENT VIA DFS SUBMITTED BY THE CUSTOMER
- CLIP FIXATIONS MUST RESPECT THE ORIENTATIONS REQUIRED ON THE CUSTOMER DRAWING
- BRANCH ORIENTATION IS ONLY GUARANTEED ON PRODUCTION TABLES
- PACKAGING TOLERANCES ARE CONSTRAINT TO MAXIMAL TOLERANCES EXCEPT SPECIFIC NOTES -15mm +15mm

CONFORMEMENT A LA NORME LISTE VISAMAT ANNEXE 1 *CONSISTENLY WITH STANDARD VISAMAT LIST IN APPENDIX 1*	01-00-510 --H	
M : METALLIQUE/*METALLIC* P : POLYMERE/*POLYMER*	M	P
PLAN SOUMIS A LA SIGNATURE *DRAWING SUBJECTED TO SIGNATURE*		
PLAN NON SOUMIS A LA SIGNATURE *DRAWING NOT SUBJECTED TO SIGNATURE*	☒	☒

ISO GPS

SPECIFICATION DIMENSIONNELLE, GEOMETRIQUE ET D'ETATS DE SURFACE SELON l'ISO 8015:2011 ET CONFORMEMENT A LA NORME RENAULT : 00-10-039 --B

DIMENSIONAL,GEOMETRICAL AND SURFACE TEXTURE SPECIFICATIONS ACCORDING TO ISO 8015:2011 AND WITH ACCORDANCE TO THE RENAULT STANDARD 00-10-039 --B

OPERATEUR DE SPECIFICATION DE TAILLE PAR DEFAUT/ *DEFAULT SPECIFICATION OPERATOR FOR SIZE :*

TAILLE LINEAIRE ISO 14405 Ⓔ ☐ OUI/*YES*
LINEAR SIZE ISO 14405 Ⓔ ☒ NON/*NO*

COTATION ET TOLERANCEMENT DES PIECES NON RIGIDES SELON / *DIMENSIONNING AND TOLERANCING OF THE NON-RIGID PARTS IS CARRIED OUT IN ACCORDING TO :*

ISO10579 ☒ OUI/*YES* (1)
☐ NON/*NO*

(1) ASSUREZ VOUS QUE LES CONDITIONS DE CONTRAINTE A APPLIQUER SONT SPECIFIEES / *MAKE SURE THAT THE CONSTRAINT CONDITIONS TO BE APPLIED ARE SPECIFIED*

HIERARCHISATION DES CARACTERISTIQUES NORME 01-33-301

CLASSIFICATION OF REQUIREMENTS STANDARD 01-33-301

TOTALE
TOTAL

TOUTE CARACTERISTIQUE NON HIERARCHISEE EST DE NIVEAU 3

ANY CHARACTERISTIC NOT CLASSIFIED BELONGS TO LEVEL 3

CUSTOMER PN	CUSTOMER REV	WEIGHT Kg	CIRCUITS	ALL	AVCAM	EPEM0	EPEM3	EPEM4	EPER2	EPER3	EPER4	HCB	ITP15	ITP17	M3CAM
253A91898R	---	0.522	35	X	X				X	X	X	X		X	X
253A92485R	---	0.296	13	X		X	X	X				X			
253A92955R	--D	0.278	13	X					X			X			
253A94545R	---	0.464	33	X					X	X	X	X	X		
253A94691R	---	0.478	33	X		X	X	X				X	X		
253A97911R	---	0.53	35	X	X	X	X	X				X		X	X

WAVE : DEFNE	TCC :TCC_XCB_HCB_YAZAKI_TR0526_--V_EXCEL	13/03/2026

FIS : FIS595300-1
MODIFICATIONS APPLYED AFTER THE FICHINIT :

DFS APPLIED BY FICHINIT:
DFS585901-1 DFS591013-1 DFS580864-1 DFS575609-1 DFS584176-1 DFS584180-1 DFS598819-1 DFS598272-1 DFS598864-1

YAZAKI

YAZAKI SYSTEMS TECHNOLOGIES FRANCE SAS
2 RUE RENÉ CAUDRON,BÂTIMENT E
78960 VOISINS LE BRETONNEUX FRANCE

CABLAGE BOUCLIER AVANT

FRONT BUMPER HARNESS

DRAWN BY A.SAYGI	DATE 09/02/2026	DRAWING REALIZED WITH HXC SIEMENS			
CHECKED BY B.KAR	PROJECT HCB	3D PART NUMBER OCCM07NPLQ			3D REV 023
HARNESS STATUS Released	WAVE DEFNE	PEI NUMBER 2D0070260P			PEI REV --J
THIS DRAWING IS THE EXCLUSIVE PROPERTY OF YAZAKI SYSTEMS TECHNOLOGIES FRANCE SAS WHICH TRANSFER IT TO RENAULT GROUP FOR THE PROGRAM NEEDS ON STRICTLY CONFIDENTIAL BASE		FORMAT 2xA0	HARNESS WEIGHT	SHEET 1/2	