

Register ↗



Search

CTRL K



Table of Contents >

nuxi add

```
npx nuxi add [--cwd] [--force] <TEMPLATE> <NAME>
```

Option	Default	Description
TEMPLATE	-	Specify a template of the file to be generated.
NAME	-	Specify a name of the file that will be created.
--cwd	.	The directory of the target application.
--force	false	Force override file if it already exists.

Modifiers:

Some templates support additional modifier flags to add a suffix (like `.client` or `.get`) to their name.

Example: `npx nuxi add plugin sockets --client` generates `/plugins/sockets.client.ts`.

nuxi add component

- Modifier flags: `--mode client|server` or `--client` or `--server`

Example:

```
> # Generates `components/TheHeader.vue`  
> npx nuxi add component TheHeader
```

nuxi add composable

Example:

```
> # Generates `composables/foo.ts`  
> npx nuxi add composable foo
```

nuxi add layout

Example:

```
> # Generates `layouts/custom.vue`  
> npx nuxi add layout custom
```

nuxi add plugin

- Modifier flags: `--mode client|server` or `--client` or `--server`

Example:

```
> # Generates `plugins/analytics.ts`  
> npx nuxi add plugin analytics
```

nuxi add page

Example:

```
> # Generates `pages/about.vue`  
> npx nuxi add page about
```

```
> # Generates `pages/category/[id].vue`  
> npx nuxi add page "category/[id]"
```

nuxi add middleware

- Modifier flags: `--global`

Example:

```
> # Generates `middleware/auth.ts`  
> npx nuxi add middleware auth
```

nuxi add api

- Modifier flags: `--method` (can accept `connect` , `delete` , `get` , `head` , `options` , `patch` , `post` , `put` or `trace`) or alternatively you can directly use `--get` , `--post` , etc.

Example:

```
> # Generates `server/api/hello.ts`  
> npx nuxi add api hello
```

[Edit on Github](#)



© 2016-2023 Nuxt - MIT
License

Enterprise

Design Kit
Nuxt Studio

NuxtLabs

