



Table of Contents >

Sourcemaps

Sourcemaps are enabled for your server build by default, and for the client build in dev mode, but you can enable them more specifically in your configuration.

```
export default defineNuxtConfig({
  // or sourcemap: true
  sourcemap: {
    server: true,
    client: true
  }
})
```

Debugging in Your IDE

It is possible to debug your Nuxt app in your IDE while you are developing it.

Example VS Code Debug Configuration

You may need to update the config below with a path to your web browser. For more information, visit the [VS Code documentation about debug configuration](#).

```
{
  // Use IntelliSense to learn about possible attributes.
  // Hover to view descriptions of existing attributes.
  "version": "0.2.0",
```

```

"configurations": [
  {
    "type": "chrome",
    "request": "launch",
    "name": "client: chrome",
    "url": "http://localhost:3000",
    "webRoot": "${workspaceFolder}"
  },
  {
    "type": "node",
    "request": "launch",
    "name": "server: nuxt",
    "outputCapture": "std",
    "program": "${workspaceFolder}/node_modules/nuxi/bin/nuxi.mjs",
    "args": [
      "dev"
    ],
  }
],
"compounds": [
  {
    "name": "fullstack: nuxt",
    "configurations": [
      "server: nuxt",
      "client: chrome"
    ]
  }
]
}

```

If you prefer your usual browser extensions, add this to the *chrome* configuration above:

```
"userDataDir": false,
```

Example JetBrains IDEs Debug Configuration

You can also debug your Nuxt app in JetBrains IDEs such as IntelliJ IDEA, WebStorm, or PhpStorm.

1. Create a new file in your project root directory and name it `nuxt.run.xml` .
2. Open the `nuxt.run.xml` file and paste the following debug configuration:

```
<component name="ProjectRunConfigurationManager">
  <configuration default="false" name="client: chrome" type="JavascriptDebugType" uri="http://localhost:5986">
    <method v="2" />
  </configuration>

  <configuration default="false" name="server: nuxt" type="NodeJSConfigurationType" application-pa
    <method v="2" />
  </configuration>

  <configuration default="false" name="fullstack: nuxt" type="CompoundRunConfigurationType">
    <toRun name="client: chrome" type="JavascriptDebugType" />
    <toRun name="server: nuxt" type="NodeJSConfigurationType" />
    <method v="2" />
  </configuration>
</component>
```

Other IDEs

If you have another IDE and would like to contribute sample configuration, feel free to [open a PR!](#)

 [Edit on Github](#)



© 2016-2023 Nuxt - MIT
License

Enterprise

Design Kit
Nuxt Studio

NuxtLabs

