



# Runtime Config

When using `runtimeConfig` option, nitro must have been configured.

## Update Runtime Config

Nuxt 3 approaches runtime config differently than Nuxt 2, using a new combined `runtimeConfig` option.

First, you'll need to combine your `publicRuntimeConfig` and `privateRuntimeConfig` properties into a new one called `runtimeConfig`, with the public config within a key called `public`.

```
// nuxt.config.js
- privateRuntimeConfig: {
-   apiKey: process.env.NUXT_API_KEY || 'super-secret-key'
- },
- publicRuntimeConfig: {
-   websiteURL: 'https://public-data.com'
- }
+ runtimeConfig: {
+   apiKey: process.env.NUXT_API_KEY || 'super-secret-key',
+   public: {
+     websiteURL: 'https://public-data.com'
+   }
+ }
```

This also means that when you need to access public runtime config, it's behind a property called `public`. If you use public runtime config, you'll need to update your code.

```
// MyWidget.vue
```

```
- <div>Website: {{ $config.websiteURL }}</div>
+ <div>Website: {{ $config.public.websiteURL }}</div>
```

[Edit on Github](#)



© 2016-2023 Nuxt - MIT  
License

Enterprise

Design Kit  
Nuxt Studio

NuxtLabs

