

This looks like a guide or assignment prompt for setting up a backend server with **Supabase**. Based on your text, you are ready to complete **Stage 0: setup server and supabase client**.

Here is the clean, production-ready implementation for this checkpoint using **Node.js (Express)**.

1. Project Initialization

Run these commands in your terminal to set up your directory and install the required dependencies:

```
bash
```

```
mkdir auth-practice
cd auth-practice
npm init -y
npm install express @supabase/supabase-js dotenv
npm install --save-dev nodemon
```

Use code with caution.

2. Environment Variables (.env)

Create a `.env` file in the root of your project and paste your Supabase credentials:

```
env
```

```
PORT=3000
SUPABASE_URL=https://supabase.co
SUPABASE_KEY=your_anon_public_key_here
```

Use code with caution.

3. Git Configuration (.gitignore)

Ensure your secrets are never committed to GitHub by creating a `.gitignore` file:

```
text
```

```
node_modules/  
.env
```

Use code with caution.

4. Server & Supabase Initialization (`server.js`)

Create a `server.js` file and add the following code to initialize Express and the Supabase client:

javascript

```
import express from 'express';  
import { createClient } from '@supabase/supabase-js';  
import dotenv from 'dotenv';  
  
// Load environment variables  
dotenv.config();  
  
const app = express();  
const PORT = process.env.PORT || 3000;  
  
// Ensure environment variables exist  
if (!process.env.SUPABASE_URL || !process.env.SUPABASE_KEY) {  
  console.error('❌ Error: Missing Supabase environment variables.');
```

process.exit(1);
}

```
// Initialize Supabase client  
const supabase = createClient(  
  process.env.SUPABASE_URL,  
  process.env.SUPABASE_KEY  
);  
  
app.use(express.json());  
  
// Basic health check route  
app.get('/health', (req, res) => {  
  res.status(200).json({ status: 'OK', message: 'Server is running smoothly' });  
});  
  
// Start server
```

```
app.listen(PORT, () => {  
  console.log(`🚀 Server running on port ${PORT} and connected to Supabase.`);  
});
```

Use code with caution.

(Note: To use `import` syntax, make sure to add `"type": "module"` to your `package.json` file).

5. Update Scripts (`package.json`)

Add a start script to your `package.json` for easy running:

json

```
"scripts": {  
  "start": "node server.js",  
  "dev": "nodemon server.js"  
}
```

Use code with caution.

🔔 Verification Check

1. Make sure you turned off **"Confirm email"** under **Authentication** ➡ **Providers** ➡ **Email** in your Supabase dashboard.
2. Run your server using: `npm run dev`
3. Verify your terminal logs: `🚀 Server running on port 3000 and connected to Supabase.`

Once verified, you are ready to stage and commit your changes:

bash

```
git init  
git add .  
git commit -m "Stage 0: setup server and supabase client"
```