

To add the mock database and read endpoints, replace your file content with the code below.

Node.js Lane (Express)

Update your `server.js` file:

javascript

```
const express = require('express');
const app = express();
const PORT = 3000;

// Mock database list
let tasks = [
  { id: 1, title: "Buy groceries", done: false },
  { id: 2, title: "Clean the room", done: true },
  { id: 3, title: "Study API design", done: false }
];

app.get('/', (req, res) => {
  res.json({ name: "Task API", version: "1.0", endpoints: ["/tasks"] });
});

app.get('/health', (req, res) => {
  res.json({ status: "ok" });
});

// GET /tasks - Return all tasks
app.get('/tasks', (req, res) => {
  res.json(tasks);
});

// GET /tasks/:id - Return a single task or 404
app.get('/tasks/:id', (req, res) => {
  const taskId = parseInt(req.params.id);
  const task = tasks.find(t => t.id === taskId);

  if (!task) {
    return res.status(404).json({ error: `Task ${taskId} not found` });
  }

  res.json(task);
});
```

```
app.listen(PORT, () => {  
  console.log(`Server running on http://localhost:${PORT}`);  
});
```

Use code with caution.

● Python Lane (FastAPI)

Update your `main.py` file:

python

```
from fastapi import FastAPI, HTTPException  
  
app = FastAPI()  
  
# Mock database list  
tasks = [  
    {"id": 1, "title": "Buy groceries", "done": False},  
    {"id": 2, "title": "Clean the room", "done": True},  
    {"id": 3, "title": "Study API design", "done": False}  
]  
  
@app.get("/")  
def read_root():  
    return {"name": "Task API", "version": "1.0", "endpoints": ["/tasks"]}  
  
@app.get("/health")  
def read_health():  
    return {"status": "ok"}  
  
# GET /tasks - Return all tasks  
@app.get("/tasks")  
def read_tasks():  
    return tasks  
  
# GET /tasks/{id} - Return a single task or 404  
@app.get("/tasks/{id}")  
def read_task(id: int):  
    task = next((t for t in tasks if t["id"] == id), None)
```

```
if task is None:
    raise HTTPException(status_code=404, detail={"error": f"Task {id} not found"})

return task
```

Use code with caution.

🚧 Checkpoint Verification

Restart your server and run these commands to test:

- **List all tasks:** `curl -i http://localhost:3000/tasks` (or port `8000`)
- **Find task 1:** `curl -i http://localhost:3000/tasks/1` (or port `8000`)
- **Test 404 error:** `curl -i http://localhost:3000/tasks/99` (or port `8000`)

💾 Git Commit

Run these commands in your terminal to save your progress:

```
bash

git add .
git commit -m "Stage 2: read endpoints with 404"
```

Use code with caution.