

Wasfa (meal-planner)

One-page repo summary generated from code, configs, migrations, and docs in this repository.

WHAT IT IS

Wasfa is an Expo/React Native mobile app for saving and organizing cooking recipes. It combines social-link recipe import, folders, grocery-list generation, onboarding, and English/Arabic support with guest mode or Google sign-in.

WHO IT'S FOR

Primary persona: home cooks who save recipes from Instagram or TikTok and want them organized in a bilingual mobile app with shopping-list support.

WHAT IT DOES

- Supports guest mode plus Google sign-in, with persisted Supabase sessions.
- Runs an onboarding flow for diet, allergies, referral source, age, measurement system, and nutrition-display preferences.
- Accepts shared or pasted recipe links and creates import jobs from the app.
- Polls import status, applies localized recipe text, and confirms recipe drafts into saved recipes.
- Organizes saved recipes into folders and searchable recipe-library views.
- Shows recipe details with ingredients, steps, source link, delete action, and add-to-shopping-list action.
- Builds a grocery list from recipe ingredients, groups similar items, and lets users check or remove entries.

HOW IT WORKS

- UI and navigation: Expo Router screens under app/ with tabs for recipes, grocery, planner, profile, plus import and recipe-detail routes.
- Cross-cutting providers: Root layout wires ShareIntentProvider, LanguageProvider, and AuthProvider before navigation.
- Local state and persistence: AsyncStorage stores auth session, language, onboarding progress/answers, and import client ID.
- Backend data access: Supabase JS clients read/write recipes, recipe_folders, shopping_list_items, and onboarding_profiles.
- Import pipeline: share or paste flow calls Supabase Edge functions import-create, import-share, import-status, and import-confirm.
- Data flow: import_jobs -> recipe_drafts -> recipes/job_events in Postgres; functions README says drafts store localized en/ar text and use OpenRouter plus Apify fallback.

HOW TO RUN

- npm install
- Add EXPO_PUBLIC_SUPABASE_URL and EXPO_PUBLIC_SUPABASE_ANON_KEY in .env; without real values the repo warns that auth will not work, but guest mode remains usable.
- If you want the import pipeline/backend too: run supabase db push and deploy the four import functions documented in supabase/functions/README.md.
- npm start, then npm run ios or npm run android

NOT FOUND IN REPO

- Production deployment workflow beyond local/dev setup: Not found in repo.