Basic classic

Fine sandblasting unit

Space-saving fine sandblasting unit with 1-2 blasting tanks.

tool included

perfect view



Advantages

- Cost-effective operation through special mixing chamber technology (Venturi-Principle).
- Precise sandblasting due to excellent illumination of the blasting chamber with LED technology
- Large sandblasting chamber (14 l) allows good freedom of movement.

Details

- Tool-free extension to 2 tanks.



Four times longer service life compared to conventional nozzles thanks to highly resistant boron carbide

Technical data

Permissible mains voltage	220–240 V | 100–120 V
Permissible mains frequency	50/60 Hz
Working pressure	1–6 bar // 14.5–87 psi
Max. connection pressure	6–8 bar // 87–116 psi
Air consumption	98 l/min (6 bar) // 3.46 cfm (87 psi)
Intensity of lighting	4800 lx
Lamp power	16 W
Dimensions (W x H x D)	355 x 270 x 415 mm // 14.0 x 10.6 x 16.3"
Tank capacity	1000 ml // 34 fl.oz.
Number of tanks	1–2
Blasting chamber volume	14 l // 3.7 gal
Weight (empty, 2-tanks)	~6,5 kg // ~14.3 lbs
Weight (empty, 1-tank)	~5,4 kg // ~11.9 lbs

Ordering information

Basic classic, 25-70 µm, 220-240 V	No. 29471050
Basic classic, 70-250 µm, 220-240 V	No. 29471250
Basic classic, 25-70 µm/25-70 µm, 220-240 V	No. 29472000
Basic classic, 25-70 µm/70-250 µm, 220-240 V	No. 29472025
Basic classic, 70-250 µm/70-250 µm, 220-240 V	No. 29472250
Basic classic, 25-70 µm/25-70 µm, 100-120 V	No. 29474000
Basic classic, 25-70 µm/70-250 µm, 100-120 V	No. 29474025
Retrofit tank, 25–70 µm, 1 x 25–70 µm, incl. nozzle 0.8 mm	No. 29470050
Retrofit tank, 70–250 µm, 1 x 70–250 µm, incl. nozzle 1.2 mm	No. 29470250
Cobra	Page 45
Rolloblast	Page 46
Sandblasting nozzles	Page 46

Further product data at: www.renfert.com/p/item number