Basic eco

Fine sandblasting unit

Compact, fine sandblasting unit with 1 or 2 blasting tanks.



tool included

perfect view

compact

Advantages

- Great cost efficiency through special mixing chamber technology (Venturi-Principle).
- Precise sandblasting due to excellent illumination of the blasting chamber with LED technology
- Sufficient freedom of movement in the large sandblasting chamber (10 l).

Details

- Tool-free extension to 2 tanks.



Pin-point accurate and cost-effective sandblasting. Above: Renfert focused jet, below: focused jet of a competitor

Technical data

Permissible mains voltage	220–240 V | 120 V | 100 V
Permissible mains frequency	50/60 Hz
Working pressure	1–6 bar // 14.5–87 psi
Max. connection pressure	6–8 bar // 87–116 psi
Air consumption	98 l/min (6 bar) // 3.46 cfm (87 psi)
Intensity of lighting	4800 lx
Lamp power	9 W
Dimensions (W x H x D)	350 x 275 x 400 mm // 13.8 x 10.8 x 15.7"
Tank capacity	1000 ml // 34 fl.oz.
Number of tanks	1–2
Blasting chamber volume	10 l // 2.64 gal
Weight (empty, 2-tanks)	~5,5 kg // ~12.1 lbs
Weight (empty, 1-tank)	~4,4 kg // ~9.7 lbs

Ordering information

Basic eco, 25-70 µm, 230 V	No. 29491050
Basic eco, 70-250 µm, 230 V	No. 29491250
Basic eco, 25-70 µm/70-250 µm, 230 V	No. 29492025
Basic eco, 25-70 µm, 120 V	No. 29493050
Basic eco, 70-250 µm/70-250 µm, 120 V	No. 29494250
Basic eco, 25-70 µm/70-250 µm, 120 V	No. 29494025
Basic eco, 25-70 µm/70-250 µm, 100 V	No. 29495025
Basic eco, 25-70 µm, 100 V	No. 29495050
Basic eco, 70-250 µm, 100 V	No. 29495250
Cobra	Page 45
Rolloblast	Page 46
Sandblasting nozzles	Page 46