Basic master

Fine sandblasting unit

tool included

perfect view

Fine sandblasting unit with 2 blasting tanks and large blasting chamber.



Advantages

- Homogeneous and tension-free surfaces thanks to the special mixing chamber technology (Venturi principle), regardless of the fill level of the sandblasting tank.
- High economic efficiency as there is no unnecessary after-flow of sandblasting material.
- Targeted, precise sandblasting due to excellent illumination of the blasting chamber with LED technology.

Details

- Large sandblasting chamber (20 l) allows ample freedom of movement.
- Good, long-lasting visibility of the objects through silicone-coated glass panel (10x longer service life).



High contrast and high contour detail due to excellent illumination ("perfect view" concept)

Technical data

Permissible mains voltage	220–240 V | 100–120 V
Permissible mains frequency	50/60 Hz
Working pressure	1–6 bar // 14.5–87 psi
Max. connection pressure	6–8 bar // 87–116 psi
Air consumption	98 l/min (6 bar) // 3.46 cfm (87 psi)
Intensity of lighting	4800 lx
Lamp power	16 W
Dimensions (W x H x D)	395 x 285 x 460 mm // 15.6 x 11.2 x 18.1"
Tank capacity	1000 ml // 34 fl.oz.
Number of tanks	2
Blasting chamber volume	20 l // 5.3 gal
Weight (empty, 2-tanks)	~8,1 kg // ~17.9 lbs

Ordering information

Basic master, 25-70 µm/25-70 µm, 220-240 V	No. 29482000
Basic master, 25-70 µm/70-250 µm, 220-240 V	No. 29482025
Basic master, 70-250 µm/70-250 µm, 220-240 V	No. 29482250
Basic master, 25-70 µm/25-70 µm, 100-120 V	No. 29484000
Basic master, 25-70 µm/70-250 µm, 100-120 V	No. 29484025
Retrofit tank, 25–70 µm, 1 x 25–70 µm, incl. nozzle 0.8 mm	No. 29470050
Retrofit tank, 70–250 µm, 1 x 70–250 µm, incl. nozzle 1.2 mm	No. 29470250
Cobra	Page 45
Rolloblast	Page 46
Sandblasting nozzles	Page 46