Basic quattro IS

Fine sandblasting unit

Professional fine sandblasting unit with 2-4 blasting tanks and the "IS" (= **I**mmediate **S**top) technology for controlled sandblasting without an after-flow of sandblasting material.



tool included

easy use

perfect view

Advantages

- Saves up to 80% sandblasting material thanks to the air-sand mixture and the integrated "IS" immediate stop technology.
- Enables pin-point precision while working, for example when sandblasting grooves or devesting intricate items.
- Quick and safe operation with the help of individual pressure adjustment and indicator for each tank.

Details

- Large sandblasting chamber (20 l) allows maximum freedom of movement.
- Easy, tool-free tank extension via the quick-coupling and color-coded system.
- Precise sandblasting due to excellent illumination of the blasting chamber with LED technology.
- Good, long-lasting visibility of the objects through silicone-coated glass panel (10x longer service life).

Making work easy

When sandblasting intricate items such as press ceramics and fissures, the flow of abrasives must start and stop instantly. The integrated quick stop technology does exactly that, reducing the consumption of abrasives at the same time.



Thanks to the "Immediate Stop (IS)" function, very fine and intricate tasks as such sandblasting pits and occlusal grooves are possible

Technical data

Permissible mains voltage	220–240 V | 100–120 V
Permissible mains frequency	50/60 Hz
Working pressure	1–6 bar // 14.5–87 psi
Max. connection pressure	6–8 bar // 87–116 psi
Air consumption	98 l/min (6 bar) // 3.46 cfm (87 psi)
Intensity of lighting	4800 lx
Lamp power	16 W
Dimensions (W x H x D) (1-2 tank version)	395 x 320 x 510 mm // 15.6 x 12.6 x 20.1"
Dimensions (W x H x D) (3-4 tank version)	395 x 320 x 610 mm // 15.6 x 12.6 x 24.0"
Tank capacity	1000 ml // 34 fl.oz.
Number of tanks	2–4
Blasting chamber volume	20 l // 5.3 gal
Weight (empty, 2-tanks)	~11,5 kg // ~25.4 lbs

Ordering information

Basic quattro IS, 25-70 µm/70-250 µm, 220-240 V	No. 29590000
Basic quattro IS, 25-70 µm/70-250 µm, 100-120 V	No. 29591000
Additional tank, 25–70 µm, 1 x 25–70 µm, incl. nozzle 0.8 mm	No. 29590050
Additional tank, 70–250 µm, 1 x 70–250 µm, incl. nozzle 1.2 mm	No. 29590250
Cobra	Page 45
Rolloblast	Page 46
Sandblasting nozzles	Page 46