Basic mobil

Fine sandblasting unit



Renfert blasting technology has been reduced to a basic design in the Basic mobil sandblasters. Mobile use only requires connection to the compressed air.

Advantages

- Ideal use with existing abrasive chamber.
- Control using pneumatic foot switch.
- Individual blasting pressure of 1–6 bar. Pressure display via manometer.

Technical data

Working pressure	1–6 bar // 14.5–87 psi
Max. connection pressure	6–8 bar // 87–116 psi
Air consumption	98 l/min (6 bar) // 3.46 cfm (87 psi)
Dimensions (W x H x D)	220 x 260 x 130 mm // 8.7 x 10.2 x 5.1"
Tank capacity	1000 ml // 34 fl.oz.
Number of tanks	1
Weight (empty)	~2,5 kg // ~5.5 lbs

Ordering information

Basic mobil with foot switch, 25–70 µm	No. 29143050
Basic mobil with foot switch, 70–250 µm	No. 29143250
Cobra	Page 45
Rolloblast	Page 46
Sandblasting nozzles	Page 46

High performance compressed air filter



No more problems in compressed air supply systems due to condensation water, oil, color residue or rust particles from compressors. The compressed air filter prevents clumping of the sandblasting abrasive and blockage of the fine channels of compressed air units.

Advantages

- Three-step filter system: Prefilter, fine filter and active carbon filter.
- Three users can be connected to one filter.
- All filters can be easily exchanged.

Technical data

Working pressure	10 bar // 145 psi
Air quality	ISO 8573-1, Class 1.7.1
Flow rate	420 l/min (6,3 bar) // 14.8 cfm (91 psi)
Dimensions (W x H x D)	210 x 280 x 70 mm // 8.3 x 11.0 x 2.8 "

Ordering information

High performance compressed air filter	No. 29400000

Further product data at: www.renfert.com/p/item number