hotty LED

Wax dipping pot

easy use



The reliable wax dipping pot with LED display and membrane keypad for the even and accurate heating temperature of dipping waxes.

Advantages

- Suitable for all dipping waxes due to the temperature setting of 60 – 110°C (140 – 230°F).
- Uniform wax layer thickness of the coping due to even temperature distribution.
- Making ideal use of the wax properties thanks to the true temperature value in the area where the dies are dipped.

Details

- Saves working time due to fast and consistent heating phase.

Features

The membrane keypad of the hotty LED enables the temperature to be set accurately to within a degree. The temperature status is permanently indicated by the LED display.

Technical data

Permissible mains voltage	220–240 V | 100–120 V
Permissible mains frequency	50/60 Hz
Power consumption	25 W
Working temperature min./ max.	60–110 °C // 140–230 °F
Dimensions (W x H x D)	90 x 65 x 98 mm // 3.54 x 2.56 x 3.86"
Weight	~400 g // ~14.1 oz

Ordering information

hotty LED, 220-240 V	No. 14610000
hotty LED, 100-120 V	No. 14611000
GEO Dip	Page 141

hotty

Wax dipping pot

easy use



Reliable wax dipping pot with a potentiometer for uniform heating of dipping waxes.

Advantages

- Suitable for all dipping waxes due to infinitely variable temperature setting from 60 to 110°C (140 – 230°F).
- Uniform wax layer thickness due to even temperature distribution.
- Saves time during working thanks to the quick and consistent heating up phase.

Details

- Actual value indication in the dipping area of the dies.
- Ergonomically contoured housing provides optimal support for the fingers.
- No contamination of the unit by wax residue thanks to the specially designed wax runback pot.
- The integrated lid provides protection against dirt and dust.

Features

The hotty allows for temperature input and display via a potentiometer.

Technical data

Permissible mains voltage	220–240 V | 100–120 V
Permissible mains frequency	50/60 Hz
Power consumption	25 W
Working temperature min./ max.	60–110 °C // 140–230 °F
Dimensions (W x H x D)	90 x 65 x 98 mm // 3.54 x 2.56 x 3.86"
Weight	~360 g // ~12.7 oz

Ordering information

hotty, 220-240 V	No. 14600000
hotty, 100-120 V	No. 14601000
GEO Dip	Page 141