Safety burner eco

Safety burner

easy use



The eco safety burner is a single tube safety burner for use with liquid gas and natural gas E.

Details

- High degree of safety due to automatic shut-off of the gas supply if the flame is extinguished unintentionally.
- Quick cleaning of the easily detachable collector tray.
- Tested quality and safety thanks to the DVGW type-examination certificate according to DIN 30665–1.

Note

Always use the liquid gas Bunsen burner with a pressure reducer at a fixed setting (50 mbar).

Technical data

Rated output	650 W | 450 W
Connection hose (norm)	DIN 30664
Connection pressure	50 mbar | 20 mbar
Ø (Nozzle)	0,34 mm | 0,55 mm // 13.4 mil | 21.7 mil
Consumption	50 g/h | 48 l/h // 1.76 oz/h | 1.7 ft³/h
Ambient temperature max.	40 °C // 104 °F
Dimensions (W x H x D)	141 x 102 x 121 mm // 5.6 x 4.0 x 4.8"
Weight	~460 g // ~16.2 oz

Ordering information

Safety burner eco, Liquid gas	No. 9340100
Safety burner eco, Natural gas E	No. 9350100

Bijou 90

Bunsen burner

easy use



Bijou 90 is a two-tube burner for use with liquid gas and natural gas E.

Details

- Two riser tubes provide the choice of flame intensity.
- Individual adjustment of the gas supply (rocker lever) and oxygen supply (adjustment wheel).
- Tested quality and safety thanks to the DIN-DVGW type-examination certificate according to DIN 30665–1.

Note

Always use the liquid gas Bunsen burner with a pressure reducer at a fixed setting (50 mbar).

Technical data

Height (depending on the angle)	102–109 mm // 4.02–4.29 "
Rated output	660 W
Connection hose (norm)	DIN 30664
Connection pressure	50 mbar | 20 mbar
Ø (Nozzle)	0,34 mm | 0,55 mm // 13.4 mil | 21.7 mil
Consumption	48 g/h | 63 l/h // 1.69 oz/h | 2.2 ft³/h
Ambient temperature max.	40 °C // 104 °F
Dimensions (W x H x D)	100 x 109 x 60 mm // 3.94 x 4.29 x 2.36"
Weight	~530 g // ~18.7 oz

Ordering information

Bijou 90, Liquid gas	No. 9600000
Bijou 90, Natural gas E	No. 9610000