SILENT compact

Single workbench extraction

silent

compact

Compact, dustbag-free suction with automatic filter cleaning and durable collector motor.



Advantages

- No follow-up costs due to bag-free dust collection.
- Low operating noise of max. 55 dB (A).
- 3x longer service life in comparison to conventional collector motors (1000 operating hours guaranteed).

Details

- Comfortable operation of the switch-on function through key combination.
- Working without interruption due to uncomplicated motor change within minutes.



Bag-free system with automatic filter cleaning

Technical data

Permissible mains voltage	220–240 V | 120 V | 100 V
Permissible mains frequency	50/60 Hz
Power consumption	490 W (230 V) | 480 W (120 V) | 480 W (100 V)
Volume flow (max.)	2500 l/min // 1.47 ft³/s
Max. depression	219 hPa // 3.2 psi
Filter quality	Class M according to EN 60335-2-69
Max. permitted connected load of the plug-in socket	1350 W (230 V) | 480 W (120 V) | 320 W (100 V)
Number of suction hoses	1
Sound pressure level (LpA) (at max. volume flow)	55 dB (A)
Weight (empty)	~13,2 kg // ~29.1 lbs
Dimensions (W x H x D)	245 x 440 x 500 mm // 9.6 x 17.3 x 19.7"
Ø suction fittings interior	35 mm // 1.38 "
Ø suction fittings exterior	40 mm // 1.57 "
Fill level dust collector	~2,6 l // ~0.69 gal

Ordering information

SILENT compact, 220-240 V	No. 29340000
SILENT compact, 120 V	No. 29341000
SILENT compact, 100 V	No. 29341500
Further accessories	Page 33
Hoses, mufflers and adapters	Page 33