SILENT TC

Single workbench extraction

Powerful, bag-free extraction unit with automatic filter cleaning and long-lasting collector motor.

silent



Advantages

- No follow-up costs due to bag-free dust collection.
- Low operating noise of max. 54.3 dB (A).
- 3x longer service life in comparison to conventional collector motors (1000 operating hours guaranteed).

Details

- Comfortable operation of the switch-on function through key combination.
- Working without interruption due to uncomplicated motor change within minutes.



Intuitive, convenient operation and programming

Technical data

Permissible mains voltage	220–240 V
Permissible mains frequency	50/60 Hz
Power consumption	850 W (230 V) | 850 VA (230 V)
Volume flow (max.)	3980 l/min // 2.34 ft³/s
Max. depression	281 hPa // 4.1 psi
Filter quality	Class M according to EN 60335-2-69
Max. permitted connected load of the plug-in socket	2000 W (230 V)
Total connected power	2850 W (230 V)
Number of suction hoses	1
Sound pressure level (LpA)	54.3 dB (A)
Weight (empty)	~22 kg // ~48.5 lbs
Dimensions (W x H x D)	275 x 535 x 540 mm // 10.8 x 21.1 x 21.3 "
Ø suction fittings interior	45 mm // 1.77 "
Ø suction fittings exterior	50 mm // 1.97 "
Fill level dust collector	~7 l // ~1.85 gal

Ordering information

SILENT TC, 220-240 V	No. 29350000
SILENT TC, 100-120 V	No. 29351000
Starter kit waste bag for SILENT TC, TC2, EC2 & powerCAM EC / TC	No. 29340015
External ventilation SILENT TC / TC2 / EC2 / powerCAM EC, Adapter incl. Ø100 mm plastic tube, 2 m	No. 29370002
Further accessories	Page 33
Hoses, mufflers and adapters	Page 33

Further product data at: www.renfert.com/p/item number