SILENT TC2

Two workbench extraction

silent



Powerful, bag-free extraction unit with two independently controlled suction ports, automatic filter cleaning and long-lasting collector motor.

Advantages

- Consistent suction power thanks to automatic re-adjustment.
- 3x longer service life in comparison to conventional collector motors (1000 operating hours guaranteed).
- Low operating noise of max. 55 dB (A).

Details

- No follow-up costs due to bag-free dust collection.
- Working without interruption due to an uncomplicated motor change within minutes.
- Effective dust reduction using a high volume flow (approx. 4000 l/min.).



No follow-up costs thanks to bag-free system

Technical data

Permissible mains voltage	220–240 V
Power consumption	850 W (230 V)
Volume flow (max.)	3980 l/min // 2.34 ft³/s
Max. depression	281 hPa // 4.1 psi
Filter quality	Class M according to EN 60335-2-69
Max. permitted connected load of the plug-in socket	2000 W (230 V)
Min./ max. connection pressure external	4,5–8 bar // 65–116 psi
Total connected power	2850 W (230 V)
Number of suction hoses	2
Sound pressure level (LpA)	55 dB (A)
Weight (empty)	~23 kg // ~50.7 lbs
Dimensions (W x H x D)	285 x 535 x 540 mm // 11.2 x 21.1 x 21.2"
Ø suction fittings interior	45 mm // 1.77 "
Ø suction fittings exterior	50 mm // 1.97 "
Fill level dust collector	~7 l // ~1.85 gal

Ordering information

SILENT TC2, 220-240 V	No. 29360000
SILENT TC2, 100-120 V	No. 29361000
Starter kit waste bag for SILENT TC, TC2, EC2 & powerCAM EC / TC	No. 29340015
External ventilation SILENT TC / TC2 / EC2 / powerCAM EC, Adapter incl. Ø100 mm plastic tube, 2 m	No. 29370002
Pinch valve straight, 1 piece	No. 900021526
Further accessories	Page 33
Hoses, mufflers and adapters	Page 33