SILENT TS

Single workbench extraction

silent



High performance extraction unit with durable collector motor and double filter system.

Advantages

- Low operating noise of max. 63 dB (A).
- 3x longer service life in comparison to conventional collector motors (1000 operating hours guaranteed).
- High level of health protection due to double filter system, optional H/HEPA filter available.

Details

- Working without interruption due to an uncomplicated motor change within minutes.
- Effective dust reduction using a high volume flow (approx. 3300 l/min.).

Workflow guarantee

Renfert provides a guarantee of 1000 operating hours of motor running time for SILENT TS motors. The tests even showed service lives of over 2400 working hours in extreme cases.



Reliable collection in a large dust bag and easy, dust-free disposal

Technical data

Permissible mains voltage	220–240 V | 100–120 V
Permissible mains frequency	50/60 Hz
Power consumption	1400 W (230 V) | 1400 W (120 V) | 1000 W (100 V)
Volume flow (max.)	3300 l/min (230 V) | 3300 l/min (120 V) | 2900 l/min (100 V) // 1.94 ft³/s (230 V) | 1.94 ft³/s (120 V) | 1.7 ft³/s (100 V)
Max. depression	200 hPa // 2.9 psi
Filter quality	Class M according to EN 60335-2-69
Max. permitted connected load of the plug-in socket	2000 W (230 V) | 360 W (120 V) | 500 W (100 V)
Total connected power	3400 W (230 V) | 1800 W (120 V) | 1500 W (100 V)
Number of suction hoses	1
Sound pressure level (LpA) (at max. volume flow)	63 dB (A)
Weight (empty)	~26 kg // ~57 lbs
Dimensions (W x H x D)	224 x 591 x 564 mm // 8.8 x 23.3 x 22.2"
Ø suction fittings interior	32 mm // 1.26 "
Ø suction fittings exterior	40 mm // 1.57 "
Fill level dust collector	7,5 l // 2 gal

Ordering information

SILENT TS, 220-240 V	No. 29210050
SILENT TS, 100-120 V	No. 29211050
Adapter for external exhaust air duct SILENT TS / TS2, 1 piece	No. 29210004
Filters and bags	Page 33
Further accessories	Page 33
Hoses, mufflers and adapters	Page 33

Further product data at: www.renfert.com/p/item number