SILENT TS2

Two workbench extraction

silent



Powerful extraction unit with two separately controlled suction ports, durable collector motor and double filter system.

Advantages

- Consistant suction power thanks to automatic re-adjustment.
- Low operating noise of max. 59 dB (A).
- 3x longer service life in comparison to conventional collector motors (1000 operating hours guaranteed).

Details

- Intuitive operation incl. handpice calibration with large multifunctional display.
- High degree of health protection through double filter system, optional H/HEPA filter available.
- Working without interruption due to an uncomplicated motor change within minutes.



Simple operation and programming of both independent suction ports

Technical data

Permissible mains voltage	220–240 V | 120 V
Permissible mains frequency	50/60 Hz | 60 Hz
Power consumption	1400 W (230 V) | 1400 W (120 V)
Volume flow (max.)	3300 l/min (230 V) | 3300 l/min (120 V) | 1.94 ft³/s (230 V) | 1.94 ft³/s (120 V)
Max. depression	200 hPa // 2.9 psi
Filter quality	Class M according to EN 60335-2-69
Max. permitted connected load of the plug-in socket	2000 W (230 V) | 360 W (120 V)
Min./ max. connection pressure external	4,5–8 bar // 65–116 psi
Total connected power	3400 W (230 V) | 1800 W (120 V)
Number of suction hoses	2
Sound pressure level (LpA) (at max. volume flow)	59 dB (A)
Weight (empty)	~27 kg // ~59.5 lbs
Dimensions (W x H x D)	224 x 591 x 584 mm // 8.8 x 23.3 x 23.0"
Ø suction fittings interior	45 mm // 1.77 "
Ø suction fittings exterior	50 mm // 1.97 "
Fill level dust collector	7,5 l // 2 gal

Ordering information

SILENT TS2, 220-240 V	No. 29300050
SILENT TS2, 120 V	No. 29301050
Adapter for external exhaust air duct SILENT TS / TS2, 1 piece	No. 29210004
Pinch valve straight, 1 piece	No. 900021526
Filters and bags	Page 33
Further accessories	Page 33
Hoses, mufflers and adapters	Page 33