Waxlectric I

Electric wax knife

easy use



Waxlectric I is the professional introduction to the electric wax knife range.

Advantages

- Temperature setting to a precise degree ensures controlled working processes.
- Direct access of preferred working temperatures using the programming function.
- Fast heat-up rate and low heat transfer to the handle thanks to the heating element integrated in the tip.

Details

- Integrated holders provide ergonomic access to the handpiece and exchange tips.
- Direct setting of the maximum or minimum temperature.
- Daylight operable 3-figure LED display.
- Color-coded for controlled management of the handpiece.

Technical data

Permissible mains voltage	100–240 V
Permissible mains frequency	50/60 Hz
Supply voltage	12 V DC
Output power	5 W
Transformer input voltage	100–240 V AC (50 Hz) | 100–120 V AC (50 Hz)
Transformer output voltage	12 V DC (1 A)
Working temperature min./ max.	50–200 °C // 122–392 °F
Handpiece cable length	85 cm // 33.5 "
Dimensions (W x H x D)	120 x 60 x 98 mm // 4.72 x 2.36 x 3.86 "
Weight (with mains unit)	~430 g // ~15.2 oz
Weight (without mains unit)	~240 g // ~8.5 oz

Ordering information

Waxlectric I, 220-240 V	No. 21560000
Waxlectric I, 100-120 V	No. 21561000
Sculpting tips	Page 78

Waxlectric II

Electric wax knife

easy use



Waxlectric II is the professional device in the electric wax knife range which can be operated with two handpieces simultaneously.

Advantages

- Temperature setting to a precise degree ensures controlled working processes.
- Direct access of preferred working temperatures using the programming function.
- Fast heat-up rate and low heat transfer to the handle thanks to the heating element integrated in the tip.

Details

- Integrated holders provide ergonomic access to the handpieces and exchange tips.
- Direct setting of the maximum or minimum temperature.
- Daylight operable 3-figure LED display.
- Both channels can be set separately with the Waxlectric II.
- Color-coded for controlled management of the handpieces.

Technical data

Permissible mains voltage	100–240 V
Permissible mains frequency	50/60 Hz
Supply voltage	12 V DC
Output power	10 W
Transformer input voltage	100–240 V AC (50 Hz)
Transformer output voltage	12 V DC (1 A)
Working temperature min./ max.	50–200 °C // 122–392 °F
Handpiece cable length	85 cm // 33.5 "
Dimensions (W x H x D)	150 x 60 x 98 mm // 5.91 x 2.36 x 3.86 "
Weight (with mains unit)	~460 g // ~16.2 oz
Weight (without mains unit)	~270 g // ~9.5 oz

Ordering information

Waxlectric II, 220-240 V	No. 21570000
Waxlectric II, 100-120 V	No. 21571000
Sculpting tips	Page 78