DIGITAL LABORATORY COLLECTION

LS SERIES

Precision begins with a clear digital model.

Three desktop scanners. Open file formats.
Built for dental laboratory workflows.



LS2



LS3



LS4

STL / PLY / OBJ

Open system

True colour

Texture capture

Blue light

Scanning technology

SPECTRA CERAM TRADING L.L.C.

ONE CONNECTED WORKFLOW

Capture. Colour. Create.

High-resolution 3D scanning for digitising dental laboratory stone models, with support for a broad range of laboratory scan types.

01	02	03
CAPTURE	**VISUALISE**	**EXPORT**
Blue-light acquisition	True-colour texture	STL / PLY / OBJ

Colour reproduction

Capture model colours and surface texture. The source describes algorithms that reduce data volume while preserving colour information.

Open architecture

STL, PLY and OBJ output supports data exchange with compatible CAD systems, keeping the laboratory workflow flexible.

Electronic authorisation

Software authorisation is electronic. A physical licence dongle is not required.

Broad scan support

Scan gypsum models, impressions, dies, articulators and wax-ups, with texture capture for supported workflows.

Applications include prosthodontics, orthodontics and implantology. These are laboratory scanners; the supplied intended use is digitisation of stone models.

DENTAL LABORATORY SCANNER

LS2

A practical start to digital scanning.



Everyday model digitisation

11 s

Full-arch scan

2 × 2.4 MP

Camera configuration

6 µm* | 9 kg

Stated accuracy / Weight

01

11-second full-arch scan

A listed full-arch scan time of 11 seconds, with 27 seconds for a full-arch impression.

02

Dual-camera capture

Two 2.4 MP cameras combine with blue-light scanning and true-colour texture capture.

03

Open digital output

Export STL, PLY or OBJ files to continue working in compatible CAD software.

Full specifications and comparison: page 6. Computer requirements: page 7. * See LS2 accuracy note in the specifications.

DENTAL LABORATORY SCANNER

LS3

More camera detail. Refined precision.



High-resolution model capture

13 s

Full-arch scan

2 × 5.0 MP

Camera configuration

≤5 µm | 9 kg

Stated accuracy / Weight

01

Two 5.0 MP cameras

The highest camera resolution in this LS-series selection, supporting detailed model acquisition.

02

Accuracy stated at ≤5 µm

The source specifies accuracy against ISO 12836, with a full-arch scan time of 13 seconds.

03

Colour with open output

True-colour texture scanning and STL, PLY and OBJ output support an open digital workflow.

Full specifications and comparison: page 6. Computer requirements: page 7.

DENTAL LABORATORY SCANNER

LS4

Faster scans. A lighter footprint.



Speed-focused laboratory scanning

9 s

Full-arch scan

2 × 2.4 MP

Camera configuration

≤6 µm | 6 kg

Stated accuracy / Weight

01

9-second full-arch scan

The shortest listed full-arch scan time in the range, with 19 seconds for a full-arch impression.

02

6 kg scanner weight

The lightest scanner in this selection, with a listed body size of 393 × 271 × 264 mm.

03

A complete open workflow

Blue-light scanning, true-colour textures and STL, PLY and OBJ export in one platform.

Full specifications and comparison: page 6. Computer requirements: page 7.

THE RANGE AT A GLANCE

Choose by the numbers.

A clear comparison of the three LS models in the supplied catalogue.

Performance parameters	LS2	LS3	LS4
Camera configuration	2 × 2.4 MP	2 × 5.0 MP	2 × 2.4 MP
Accuracy (ISO 12836)	6 µm*	≤5 µm	≤6 µm
Full-arch scan	11 s	13 s	9 s
Full-arch impression scan	27 s	29 s	19 s
Scan area	60 × 84 × 106 mm	94 × 89 × 60 mm	96 × 82 × 60 mm
Scanner dimensions	393 × 271 × 274 mm	393 × 271 × 274 mm	393 × 271 × 264 mm
Scanner weight	9 kg	9 kg	6 kg
Package dimensions	40 × 40 × 50 cm	50 × 40 × 40 cm	50 × 40 × 40 cm

SHARED ACROSS ALL THREE MODELS

Output formats	STL / PLY / OBJ
Light source	Blue light
Texture scanning	True colour
Power supply	DC 24 V
Interface	USB 3.0
Articulator scanning	Dynamic / static; articulator transfer

* LS2: the source prints the inequality after the 6 µm value. The numeric value is retained; the direction of the limit requires supplier confirmation.

Dimension order is retained as listed in the supplied catalogue. Scan times are nominal.

PREPARE YOUR WORKSTATION

Give scanning room to perform.

The configurations below reproduce the minimum and recommended specifications in the supplied LS-series catalogue.

MINIMUM Source-listed configuration	RECOMMENDED For the preferred experience
PROCESSOR Intel Core i7-10700 or above	PROCESSOR Intel Core i7-13700 or above
MEMORY 16 GB or above	MEMORY 32 GB or above
GRAPHICS NVIDIA GeForce GTX 1660 6 GB or above	GRAPHICS NVIDIA GeForce RTX 2060 SUPER 8 GB or above
OPERATING SYSTEM Windows 10 (64-bit)	OPERATING SYSTEM Windows 11 (64-bit)
CONNECTION USB 3.0	CONNECTION USB 3.0

BEFORE INSTALLATION

Use the recommended configuration when planning a new workstation. The Windows 10 entry is retained from the source minimum specification; confirm current operating-system and driver support with the supplier before installation.

FROM PHYSICAL MODELS TO DIGITAL DESIGN

Made for the laboratory.

A shared platform for restorative, orthodontic and implant-related laboratory scanning workflows.

01 **Gypsum models**

Stone model digitisation

02 **Impressions**

Full-arch impression scanning

03 **Dies**

Individual preparation capture

04 **Articulators**

Dynamic / static scanning

05 **Wax-ups**

Wax-up digitisation

06 **Textures**

Model colour information

SPECTRA CERAM TRADING L.L.C.

Spectra Scanner by Denpark

Denpark product information

denpark3d.com | info@denpark3d.com

TECHNICAL BASIS

Primary source: supplied “Spectra Scanner” catalogue, page 4 (LS model specifications), page 5 (computer configuration), and page 2 (shared features and intended use). Model names and model-specific values follow this source.

Denpark’s official L-series page was consulted for general platform context only. Its L3 / L6 / L9 model names are not treated as a verified cross-reference for LS2 / LS3 / LS4. denpark3d.com/list/1.html

Accuracy and scan times are supplier-stated values from the supplied catalogue, not independent test results. Actual scan times may vary with the case and computer configuration.