

Regression

Abdelrahman
Khaled and
Amr Khalil

What is
Reinforcement
Learning?

Terminology

Terminology

Deep
Reinforcement
Learning

Applications

References

Deep Reinforcement Learning: An Introduction

Abdelrahman Khaled and Amr Khalil

Machine Learning Community
German University in Cairo

August 1, 2019

Outline

Regression

Abdelrahman
Khaled and
Amr Khalil

What is
Reinforcement
Learning?

Terminology

Terminology

Deep
Reinforcement
Learning

Applications

References

1 What is Reinforcement Learning?

2 Terminology

3 Terminology

4 Deep Reinforcement Learning

5 Applications

6 References

Reinforcement Learning

Regression

Abdelrahman
Khaled and
Amr Khalil

What is
Reinforcement
Learning?

Terminology

Terminology

Deep
Reinforcement
Learning

Applications

References




Figure: Venn Diagram from David Silver's UCL slides

Reinforcement Learning

Regression

Abdelrahman
Khaled and
Amr Khalil

What is
Reinforcement
Learning?

Terminology

Terminology


Deep
Reinforcement
Learning

Applications

References

Definition

Reinforcement learning is a training method based on rewarding desired behaviors and/or punishing undesired ones.
-Search Enterprise AI



Reinforcement Learning

Regression

Abdelrahman
Khaled and
Amr Khalil

What is
Reinforcement
Learning?

Terminology

Terminology

Deep
Reinforcement
Learning

Applications

References




Figure: The agent-environment cycle. *Image source*

Reinforcement Learning

Regression

Abdelrahman
Khaled and
Amr Khalil

What is
Reinforcement
Learning?

Terminology

Terminology

Deep
Reinforcement
Learning

Applications

References

A typical reinforcement learning problem is different from a traditional machine learning problem in the sense that:

- 1 There is no predefined data set.
- 2 Sequence of inputs and time between inputs matters.
- 3 Agent's actions often affect the upcoming inputs.
- 4 Pre-processing of data is done online.

Reinforcement Learning

Regression

Abdelrahman
Khaled and
Amr Khalil

What is
Reinforcement
Learning?

Terminology

Terminology

Deep
Reinforcement
Learning

Applications

References

A typical reinforcement learning problem is different from a traditional machine learning problem in the sense that:

- 1 There is no predefined data set.
- 2 Sequence of inputs and time between inputs matters.
- 3 Agent's actions often affect the upcoming inputs.
- 4 Pre-processing of data is done online.

Offline RL

Reinforcement Learning can be done offline by collecting data about the environment over a set period of time to create a dataset. However this loses the effect of the agent learning as it experiences the environment.

Frozen Lake

Regression

Abdelrahman
Khaled and
Amr Khalil

What is
Reinforcement
Learning?

Terminology

Terminology

Deep
Reinforcement
Learning

Applications

References

the game consists of a grid, some cells in the grid are terminal nodes that will reward you or punish you if you step in them. each time you can take action of moving up,down,left,right and depending on your action you will either move in the direction you choose or as the grid is a frozen lake you will move perpendicular on the direction you choose depending on some noise variable.




Figure: Frozen Lake

Environment

Regression

Abdelrahman
Khaled and
Amr Khalil

What is
Reinforcement
Learning?

Terminology

Terminology

Deep
Reinforcement
Learning

Applications

References




Figure: The agent-environment cycle. *Image source*

Environment

Regression

Abdelrahman
Khaled and
Amr Khalil

What is
Reinforcement
Learning?

Terminology

Terminology

Deep
Reinforcement
Learning

Applications

References

Definition

Markov Decision Processes a mathematical framework for modeling decision making in situations where outcomes are partly random.

Markov Decision Processes can be considered as a tuple

Definition

Markov Decision Processes a mathematical framework for modeling decision making in situations where outcomes are partly random.

Markov Decision Processes can be considered as a tuple

- 1 Set of states S

Definition

Markov Decision Processes a mathematical framework for modeling decision making in situations where outcomes are partly random.

Markov Decision Processes can be considered as a tuple

- 1 Set of states S
- 2 Set of actions A

Definition

Markov Decision Processes a mathematical framework for modeling decision making in situations where outcomes are partly random.

Markov Decision Processes can be considered as a tuple

- 1 Set of states S
- 2 Set of actions A
- 3 Transition function $T \ P(s'|s, a)$

Definition

Markov Decision Processes a mathematical framework for modeling decision making in situations where outcomes are partly random.

Markov Decision Processes can be considered as a tuple

- 1 Set of states S
- 2 Set of actions A
- 3 Transition function $T \ P(s'|s, a)$
- 4 Reward function $R(s, a, s')$

Definition

Markov Decision Processes a mathematical framework for modeling decision making in situations where outcomes are partly random.

Markov Decision Processes can be considered as a tuple

- 1 Set of states S
- 2 Set of actions A
- 3 Transition function $T \ P(s'|s, a)$
- 4 Reward function $R(s, a, s')$
- 5 Start state s_0

Definition

Markov Decision Processes a mathematical framework for modeling decision making in situations where outcomes are partly random.

Markov Decision Processes can be considered as a tuple

- 1 Set of states S
- 2 Set of actions A
- 3 Transition function $T \ P(s'|s, a)$
- 4 Reward function $R(s, a, s')$
- 5 Start state s_0
- 6 Discount factor γ

Frozen Lake

Regression

Abdelrahman
Khaled and
Amr Khalil

What is
Reinforcement
Learning?

Terminology

Terminology

Deep
Reinforcement
Learning

Applications

References

Markov Decision Processes

- 1 Set of states S
- 2 Set of actions A
- 3 Transition function $T \ P(s'|s, a)$
- 4 Reward function $R(s, a, s')$
- 5 Start state s_0
- 6 Discount factor γ



Figure: Frozen Lake

Frozen Lake

Regression

Abdelrahman
Khaled and
Amr Khalil

What is
Reinforcement
Learning?

Terminology


Terminology

Deep
Reinforcement
Learning

Applications

References

frozen lake




probability

$$P(S|s, a)$$

$$P(2|1, R) = 80\%$$

if the noise = 0, 2

States



Transition function

$$T(1, R) = \begin{cases} 2, & 80\% \\ 5, & 10\% \\ 1, & 10\% \end{cases}$$

$$T(11, \text{Exit}) = T$$

discount factor $0 < \gamma < 1$

actions

→ Right
← Left
↑ Up
↓ down
○ Exit

Reward function

$$R(11, \text{Exit}, T) = 1$$

$$R(10, R, 11) = 0$$

$$R(7, \text{Exit}, T) = -1$$

Terminology

Regression

Abdelrahman
Khaled and
Amr Khalil

What is
Reinforcement
Learning?

Terminology

Terminology

Deep
Reinforcement
Learning

Applications

References

Terminology

Regression

Abdelrahman
Khaled and
Amr Khalil

What is
Reinforcement
Learning?

Terminology

Terminology

Deep
Reinforcement
Learning

Applications

References

Definition

A reward R_t is a number the environment provides to the agent at timestep t . It can either be positive (positive reward) or negative (punishment or negative reward). A reward of 0 is the same as no reward.

Terminology

Regression

Abdelrahman
Khaled and
Amr Khalil

What is
Reinforcement
Learning?

Terminology

Terminology

Deep
Reinforcement
Learning

Applications

References

Definition

A reward R_t is a number the environment provides to the agent at timestep t . It can either be positive (positive reward) or negative (punishment or negative reward). A reward of 0 is the same as no reward.

Definition

An episode E is everything involved in the agent-environment cycle from start until termination.

Value Iteration

Regression

Abdelrahman
Khaled and
Amr Khalil

What is
Reinforcement
Learning?

Terminology

Terminology

Deep
Reinforcement
Learning

Applications

References

Value Iteration

Regression

Abdelrahman
Khaled and
Amr Khalil

What is
Reinforcement
Learning?

Terminology

Terminology

Deep
Reinforcement
Learning

Applications

References

Definition

A policy π is a function that maps a state to an action.
($\pi : \mathcal{S} \longrightarrow \mathcal{A}$). An optimal policy is usually denoted as π^* .

Value Iteration

Regression

Abdelrahman
Khaled and
Amr Khalil

What is
Reinforcement
Learning?

Terminology

Terminology

Deep
Reinforcement
Learning

Applications

References

Definition

A policy π is a function that maps a state to an action.
($\pi : \mathcal{S} \rightarrow \mathcal{A}$). An optimal policy is usually denoted as π^* .

Definition

A value function V maps a state to a real number that signifies the intrinsic goodness of that state. ($V : \mathcal{S} \rightarrow \mathbb{R}$). An optimal value function is usually denoted as V^* .

$$V^*(s_t) = \text{Max}_{\pi} E\left[\sum_{t=0}^{\infty} \gamma^t R(s_t, a_t, s_{t+1}) \mid \pi, s_t = s_0\right]$$

Frozen Lake

Regression

Abdelrahman
Khaled and
Amr Khalil

What is
Reinforcement
Learning?

Terminology

Terminology

Deep
Reinforcement
Learning

Applications

References

Reward function as
a Look up table

0	0	0	+1
0		0	-1
0	0	0	0

with noise = 0
and $\gamma = 1$

$$V(3,4) = 1$$

$$V(3,3) = 1$$

$$V(2,3) = 1$$

$$V(1,1) = 1$$

State-Value as
a Look up table

3	$V(3,1)$	$V(3,2)$	$V(3,3)$	$V(3,4)$
2	$V(2,1)$		$V(2,3)$	$V(2,4)$
1	$V(1,1)$	$V(1,2)$	$V(1,3)$	$V(1,4)$
	1	2	3	4

with noise = 0
and $\gamma = 0.9$

$$V(3,4) = 1$$

$$V(3,3) = 0.9$$

$$V(2,3) = 0.9 * 0.9$$

$$V(1,1) = 0.9 * 0.9 * 0.9 * 0.8 * 0.9$$

with noise = 0.2
and $\gamma = 0.9$

$$V(3,3) = 1 * 0.8 + 0.2 * V(2,3)$$

$\uparrow + 0.1 * V(3,3)$
 \downarrow
problem

Value Iteration

Regression

Abdelrahman
Khaled and
Amr Khalil

What is
Reinforcement
Learning?

Terminology

Terminology

Deep
Reinforcement
Learning

Applications

References

```
 $\forall s, V_0^*(s) = 0;$   
for  $k = 1, 2, \dots, H$  do  
    for Each  $s$  in  $S$  do  
         $V_k^*(s) = \max_a \sum_{s'} P(s'|s, a)(R(s, a, s')) + \gamma V_{k-1}^*(s');$   
         $\pi_k^*(s) =$   
             $\operatorname{argmax}_a \sum_{s'} P(s'|s, a)(R(s, a, s')) + \gamma V_{k-1}^*(s');$   
    end  
end
```

Value Iteration

Regression

Abdelrahman
Khaled and
Amr Khalil

What is
Reinforcement
Learning?

Terminology

Terminology

Deep
Reinforcement
Learning

Applications

References

Value Iteration

$$V_2(s) \leftarrow \max_a \sum_{s'} P(s'|s, a)(R(s, a, s') + \gamma V_1(s'))$$

k = 2

0.00	0.00	0.72	1.00
0.00		0.00	-1.00
0.00	0.50	0.00	0.50

VALUES AFTER 2 ITERATIONS

Noise = 0.2
Discount = 0.9

Video Time

<https://youtu.be/qaMdN6LS9rA?t=1517>

Q Learning

Regression

Abdelrahman
Khaled and
Amr Khalil

What is
Reinforcement
Learning?

Terminology

Terminology

Deep
Reinforcement
Learning

Applications

References

Definition

A quality function Q combines both the policy and value functions together. It maps a state and action pair to a real number that signifies how good it is to take the action in that state. ($Q : \mathcal{S} \times \mathcal{A} \rightarrow \mathbb{R}$). An optimal quality function is usually denoted as Q^* .

Q Learning

Regression

Abdelrahman
Khaled and
Amr Khalil

What is
Reinforcement
Learning?

Terminology

Terminology

Deep
Reinforcement
Learning

Applications

References

Definition

Bellman Equation

$$Q^*(s, a) = \sum_{s'} P(s'|s, a)(R(s, a, s')) + \gamma \max_{a'} Q^*(s', a')$$

Q Learning

Regression

Abdelrahman
Khaled and
Amr Khalil

What is
Reinforcement
Learning?

Terminology

Terminology

Deep
Reinforcement
Learning

Applications

References

Definition

Bellman Equation

$$Q^*(s, a) = \sum_{s'} P(s'|s, a)(R(s, a, s')) + \gamma \max_{a'} Q^*(s', a)$$

Definition

Iteration Equation

$$Q_{k+1}^*(s, a) = \sum_{s'} P(s'|s, a)(R(s, a, s')) + \gamma \max_{a'} Q_k^*(s', a)$$

Q Learning

Regression

Abdelrahman
Khaled and
Amr Khalil

What is
Reinforcement
Learning?

Terminology

Terminology

Deep
Reinforcement
Learning

Applications

References

In the end, all that really matters is the quality function. If we know Q , then we can get both V and π .

$$V(S_t) = \max_{A_t} Q(S_t, A_t)$$

$$\pi(S_t) = \arg \max_a Q(S_t, a)$$

Q Learning (sampling or tabular)

Regression

Abdelrahman
Khaled and
Amr Khalil

What is
Reinforcement
Learning?

Terminology

Terminology

Deep
Reinforcement
Learning

Applications

References

```
for  $s$  in  $S$  do
    for  $a$  in  $A$  do
        |  $Q(s,a)$ =initialization;
    end
end
 $s=s_0$ ;
for  $k=1,2,\dots,convergence$  do
     $a=sampleAction()$ ;
     $s'=runAction(a)$ ;
    if  $s' = TERMINAL$  then
        |  $Q(s,a) = R(s,a,s')$ ;
        |  $s=s_0$ ;
    else
        |  $Q(s, a) =$ 
        |  $Q(s, a) + \alpha[R(s, a, s') + \gamma \max_a Q(s', a) - Q(s, a)]$ ;
    end
end
```


Q Learning (sampling or tabular)

Regression

Abdelrahman
Khaled and
Amr Khalil

What is
Reinforcement
Learning?


Terminology

Terminology

Deep
Reinforcement
Learning

Applications

References



Video Time

<https://youtu.be/q0-HUo0Ls04?t=1916>

Exploration vs Exploitation

Regression

Abdelrahman
Khaled and
Amr Khalil

What is
Reinforcement
Learning?

Terminology

Terminology

Deep
Reinforcement
Learning

Applications

References

initalize

$\epsilon = 1;$

$\epsilon_{min} = 0.01;$

$\lambda = 0.001;$

Function sampleAction():

if $\epsilon < \epsilon_{min}$ **then**

$\epsilon = \epsilon_{min};$

end

$r = \text{random}();$

if $r < \epsilon$ **then**

$\epsilon -= \lambda;$

 return randomAction();

else

 return $\arg \max_a Q(S_t, a);$

end

End Function

Deep Q-Learning

Regression

Abdelrahman
Khaled and
Amr Khalil

What is
Reinforcement
Learning?

Terminology

Terminology

Deep
Reinforcement
Learning

Applications

References

Q-learning is a technique in reinforcement learning where the agent attempts to fill a table with the correct value for each state-action pair. It's usually initialized at 0s and filled using the following formula:

$$Q(S_t, A_t) = Q(S_t, A_t) + \alpha[R + \gamma \max_a Q(S_{t+1}, a) - Q(S_t, A_t)]$$

Deep Q-Learning

Regression

Abdelrahman
Khaled and
Amr Khalil

What is
Reinforcement
Learning?

Terminology

Terminology

Deep
Reinforcement
Learning

Applications

References

Sometimes regular Q -learning is just not feasible, but that's mainly because of the fact that the state space can become extremely large. For example:

Deep Q-Learning

Regression

Abdelrahman
Khaled and
Amr Khalil

What is
Reinforcement
Learning?

Terminology

Terminology

Deep
Reinforcement
Learning

Applications

References

Sometimes regular Q-learning is just not feasible, but that's mainly because of the fact that the state space can become extremely large. For example:

- Chess has about 10^{20} possible states. If each state only took 10 bytes of data, the table would be more than 800 exabytes large. All of the memory space in existence currently cannot hold that much data.

Deep Q-Learning

Regression

Abdelrahman
Khaled and
Amr Khalil

What is
Reinforcement
Learning?

Terminology

Terminology

Deep
Reinforcement
Learning

Applications

References

Sometimes regular Q -learning is just not feasible, but that's mainly because of the fact that the state space can become extremely large. For example:

- Chess has about 10^{20} possible states. If each state only took 10 bytes of data, the table would be more than 800 exabytes large. All of the memory space in existence currently cannot hold that much data.
- Tetris has about 10^{64} possible states. (These can be reduced down to around 10^{22} states, but that is still a large number).

Deep Q-Learning

Regression

Abdelrahman
Khaled and
Amr Khalil

What is
Reinforcement
Learning?

Terminology

Terminology

Deep
Reinforcement
Learning

Applications

References

Sometimes regular Q -learning is just not feasible, but that's mainly because of the fact that the state space can become extremely large. For example:

- Chess has about 10^{20} possible states. If each state only took 10 bytes of data, the table would be more than 800 exabytes large. All of the memory space in existence currently cannot hold that much data.
- Tetris has about 10^{64} possible states. (These can be reduced down to around 10^{22} states, but that is still a large number).
- A self-driving car has a *continuous* state space, and thus the number of states is possibly infinite.

Deep Q-Learning

Deep Q-learning uses a neural network as a function approximator for learning the Q function.




Figure: A deep Q-network

Regression

Abdelrahman
Khaled and
Amr Khalil

What is
Reinforcement
Learning?

Terminology

Terminology

Deep
Reinforcement
Learning

Applications

References

Success Stories in RL

Regression

Abdelrahman
Khaled and
Amr Khalil

What is
Reinforcement
Learning?

Terminology

Terminology

Deep
Reinforcement
Learning

Applications

References

Probably the best known success story in RL is Google's deepmind team.

In 2013 they published a paper detailing their experiment where they used a DQN along with a few convolution layers to read input directly from the frames of a few different Atari games.




Success Stories in RL

Regression

Abdelrahman
Khaled and
Amr Khalil

In 2015, they published their improved results where their agent either achieved or surpassed human-level control on upwards of 20 different games.



RL Algorithms

Regression

Abdelrahman
Khaled and
Amr Khalil

What is
Reinforcement
Learning?


Terminology

Terminology

Deep
Reinforcement
Learning

Applications

References



References

Regression

Abdelrahman
Khaled and
Amr Khalil

What is
Reinforcement
Learning?

Terminology

Terminology

Deep
Reinforcement
Learning

Applications

References

- UCL. Advanced Topics 2015. (COMPM050/COMPGI13) *Reinforcement Learning*. David Silver. [link](#)
- Mnih et al. (2013). *Playing Atari with Deep Reinforcement Learning*.
- Mnih et al. (2015). *Human-level control through deep reinforcement learning*.
- AI Prism's Deep Reinforcement Learning Bootcamp