Ain Shams University — Faculty of Engineering
Computer Engineering and Software Systems

From Pixels to Language

Milestone 1: Data Understanding, Classification and Encoder Training

CSE485 / CSE488 — Deep Learning

Team **16**

Name	Student ID
Abdelrahman Mohamed Zayed	23P0094
Ahmed ElSayed	23P0019
Saeed Mohamed Negm	23P0255
Yehya ElAbyad	23P0067
Hassan Hazem	23P0415

Instructors: Dr. Mahmoud Khalil, Eng. Seif Yasser

Code: `https://github.com/Abdelrahmanzay/cub-pixels-to-language`
Experiment tracking (W&B):
`https://forge.coreweave.com/wandb/23p0094-ain-shams-university/cub-pixels-to-language`

November 2026

Contents

1 Introduction **2**

2 Data: EDA, Cleaning, Preprocessing and Augmentation **2**

2.1 Splits . . . 2
2.2 Class distribution . . . 3
2.3 Image sizes and quality . . . 4
2.4 Duplicates and leakage . . . 5
2.5 Captions: analysis and cleaning . . . 6
2.6 Augmentation strategy . . . 7
2.7 How the EDA informed modelling . . . 9

3 Models **9**

4 Experiments **9**

4.1 From scratch vs. transfer learning . . . 10
4.2 Architecture comparison . . . 11

5 Hyper-parameter tuning **12**

6 Experiment tracking **14**

7 Evaluation **14**

8 Explainability (Grad-CAM) **15**

9 Benchmarking **18**

10 Improving the models **19**

10.1 Bird-crop preprocessing (bounding boxes) . . . 19
10.2 Resolution . . . 20
10.3 Augmentation ablation . . . 20
10.4 Loss function: cosine loss vs. cross-entropy . . . 21
10.5 Scratch CNN: combining the improvements . . . 22
10.6 Test-time augmentation (TTA) . . . 23
10.7 Hyper-parameter tuning v2 . . . 23
10.8 Summary of single changes (ConvNeXt-Tiny) . . . 24
10.9 Final combined runs and model selection . . . 24
10.10 Grad-CAM of the final models . . . 26

11 Final selection **28**

12 Failures and limitations **28**

13 Reproducibility and interface **29**

14 Team contributions **29**

1 Introduction

The project builds one multimodal system on a single visual encoder: the encoder is first trained as a fine-grained image classifier (Milestone 1, this report), and will later be reused as the backbone of an image-colorization network and of an image-captioning model (Milestone 2).

Dataset. We use the default dataset, Caltech-UCSD Birds-200-2011 (CUB-200-2011) [1] with the natural-language descriptions of Reed et al. [2], loaded from Hugging Face (`Multimodal-Fatima/CUB_train` / `CUB_test`). It contains 11,788 photographs of 200 bird species (5,994 train / 5,794 test), each with ten human-written captions. We kept it because it satisfies all three tasks with one dataset: a discrete label per image (classification), good-quality colour photographs from which grayscale/colour pairs can be generated (colorization), and ten captions per image (captioning). It is also small enough (≈1.1 GB) for free Kaggle/Colab T4 GPUs.

Why it is hard. CUB is a *fine-grained* problem: classes are species of the same families (25 warblers, 21 sparrows, 8 gulls, 7 terns, . . . ; Fig. 3) that differ in small details such as a wing bar or the colour of the bill, while only ∼30 training images exist per class.

Summary of results. In the baseline experiments our from-scratch residual CNN reached **52.5%** test accuracy and transfer learning raised this to **82.4%** (ResNet-50) and **84.6%** (ConvNeXt-Tiny). We then improved the models one change at a time (Section 10): cropping to the bird, Mixup/CutMix, the cosine loss, higher resolution, test-time augmentation and a second tuning round. Our **final model**, a full-image ConvNeXt-Tiny at 384 px, reaches **87.0%** test accuracy (**87.3%** with test-time augmentation) without any annotation at test time, and our improved scratch CNN reaches **66.8%** (67.5% with TTA). Random search beat grid search with the same budget; the first tuning round did not survive a full-length run, which led to a better second tuning protocol.

2 Data: EDA, Cleaning, Preprocessing and Augmentation

All numbers below are produced by `python -m src.cli eda` and stored in `outputs/eda/eda_summary.json`; figures are in `outputs/eda/figures/`.

2.1 Splits

CUB provides no validation split, and tuning on the test set would make the reported test scores optimistic. We therefore carve a **stratified 10% validation split** (3 images per class, seed 42) out of the official training set. The official test set is left untouched so that our numbers remain comparable with published results (Section 9).

Split	Images	Per class	Used for
train	5,392	26–27	gradient updates
val	598	2–3	early stopping, model selection, hyper-parameter tuning
test (official)	5,794	11–30	final evaluation only

Table 1: Splits after duplicate removal (Section 2.4).



Figure 1: Random training images with their label and the first of their ten captions.

2.2 Class distribution

The training split is almost perfectly balanced (26–27 images per class), but the **test split is not**: most classes have 30 images, while a few have far fewer (Least Auklet 11, Crested Auklet 14, Spotted Catbird 15; max/min ratio 2.7). Plain accuracy is therefore dominated by the large classes, which is why we also report **macro**-averaged precision, recall and F1 (Section 7).



Figure 2: Top: images per class and split (sorted by test count). Bottom: distribution of class sizes.



Figure 3: Number of species per family word. Large groups of visually similar species are the core difficulty of fine-grained classification.

2.3 Image sizes and quality

Images have 1,152 distinct sizes; the median is 500×375 (aspect ratio 1.33, range 0.38–3.60). 148 images have a shorter side below 224 px and are slightly upsampled at training time. Brightness, contrast, colourfulness and sharpness distributions of train and test overlap closely (Fig. 4), so there is no visible domain shift between the splits. **Preprocessing decision:** every image is resized *once* (shorter side 256 px) and cached as JPEG. Decoding full-size images every epoch was the main bottleneck on small GPUs; the cache made each epoch several times faster. Models then use 224×224 crops.



Figure 4: Image sizes (top) and per-image statistics of train vs. test (bottom).

Grayscale images. 8 images (4 train, 4 test) are stored in grayscale mode. They are kept for classification (converted to 3 channels), but they have no colour target and are flagged (`is_grayscale`) so that they are excluded from colorization in Milestone 2.



Figure 5: The eight grayscale images in the dataset.

2.4 Duplicates and leakage

Exact pixel hashing found one duplicated training image. To find re-encoded or resized copies we computed a 64-bit perceptual hash (pHash) of every image and compared all ≈69 million pairs. Of the 12 pairs within Hamming distance 4, **8 pairs at distance ≤ 2 are the same photograph** (red in Fig. 6); the pairs at distance 3–4 are different photographs with a similar composition. The 8 duplicates include:

- **2 validation↔test leaks** (Bronzed Cowbird, Prothonotary Warbler): the same image in both splits would inflate validation accuracy;
- 2 duplicates inside the training set (Pigeon Guillemot, Swainson Warbler);
- **1 label conflict**: the same photograph is labelled *Chuck-will's-widow* and *Whip-poor-will* (both in test) — a sign of annotation noise between two very similar nightjars;
- 3 same-class duplicates inside the test set.

Cleaning decision: the 4 train/val copies are dropped automatically by `prepare`; the official test set is never modified (so published numbers stay comparable), and its duplicates are only reported.



Figure 6: Duplicate candidates by perceptual hash. Red titles: true duplicates (distance ≤ 2).

2.5 Captions: analysis and cleaning

The `description` field is one string per image that holds the ten captions separated by `\n` (always 11 lines: ten captions and a trailing empty line). Our analysis found:

- **Encoding corruption:** 1,700 Unicode replacement characters (U+FFFD), almost always in pairs, standing in for spaces ("this??bird??has…") — most likely non-breaking spaces that were decoded with the wrong encoding.

- **Duplicates:** 1,306 captions repeat another caption of the same image (in 1,183 images).
- **Templated captions:** some sentences are reused across hundreds of images, e.g. "this bird has wings that are brown and has a white belly" appears 971 times. This matters for captioning: a decoder can reach a decent BLEU score by producing such generic sentences.
- **Typos and merged words:** 679 rare words are not in an English dictionary (e.g. "abdoment", "ahwite", "baclk", "ablack", "andthe"); they are only 0.09% of all tokens.
- **Uninformative captions:** 84 captions mention neither a colour nor a body part ("a bird that lives by the ocean. it eats anything."); conversely 98.7% of captions contain a colour word, confirming that colour is central to how humans describe birds.
- **Formatting noise:** spaces before punctuation ("neck , except"), missing spaces after commas ("breast,vent"), slashes and stray symbols.

Cleaning pipeline (`src/data/text.py`), applied to every line: (1) Unicode NFKC normalisation and lower-casing; (2) replace every character outside `[a-z0-9 ,.'-]` — including U+FFFD — by a space; (3) fix spacing around commas and periods; (4) collapse whitespace; (5) drop empty lines and exact duplicates within an image, keeping order. The result is **116,574 captions**: 10 per image for 10,605 images, 9 for 1,064, 8 for 115 and 7 for 4. Typos are deliberately *not* auto-corrected: automatic spell-checkers mis-correct domain words (e.g. "tarsus", "rectrices"); instead the vocabulary frequency cut-off (below) maps rare misspellings to `<unk>`.

Statistics. Captions have 15.3 words on average (median 14, 95th percentile 24, 99th percentile 32, max 66). The train+val vocabulary has 4,078 words, of which 1,872 appear only once. A minimum frequency of 5 keeps 1,243 words yet covers 99.5% of all tokens (Fig. 7); we will use this cut-off and a maximum length of ≈32 tokens for the Milestone-2 caption decoder.



Figure 7: Caption length, captions per image after cleaning, vocabulary size vs. frequency cut-off, and the most frequent content words (red: colour words, blue: body parts).

2.6 Augmentation strategy

Augmentation targets the real nuisance factors of CUB: the bird's scale and position in the frame (RandomResizedCrop), left/right pose (horizontal flip), small camera tilt (rotation ±15°), lighting (brightness/contrast ±20%, saturation ±10%) and partial occlusion by branches (RandomErasing,

$p = 0.25$). **We never use hue jitter or random grayscale**: colour is one of the most discriminative cues between species (e.g. Scarlet vs. Summer Tanager), so changing it would create training images whose label is wrong. Three levels were implemented (Fig. 8); the *strong* level sometimes crops the bird out of the image entirely (row 3, first sample), so *standard* is the default and *light* is used for the linear probe, which has few trainable parameters.

Figure 8: Light / standard / strong augmentation on three training images.

2.7 How the EDA informed modelling

- Imbalanced test set ⇒ report macro-F1 and balanced accuracy, not only accuracy.
- Only ∼27 images per class ⇒ strong regularisation (label smoothing, weight decay, dropout, augmentation) and an expectation that transfer learning will dominate training from scratch.
- Colour is discriminative ⇒ no hue/grayscale augmentation.
- Small, fine details ⇒ higher resolution would help; we use 224 px for GPU budget reasons and discuss this in Section 12.
- Duplicates and label conflict ⇒ leak-free validation, and an explanation for one of the most confused class pairs (Section 7).

3 Models

All encoders implement one interface (`BaseEncoder` in `src/models/encoders.py`): `forward_features(x)` returns four feature maps at strides 4, 8, 16 and 32 (56, 28, 14 and 7×7 for a 224 px input), together with their channel counts and the layer used by Grad-CAM. Encoders are created through a registry, so any encoder can be selected from the config without touching the training code. The multi-scale output is designed for Milestone 2: the colorization U-Net uses all four maps as skip connections, and the caption decoder attends over the last 7×7 grid. The classifier is *encoder → global average pooling → dropout → linear layer (200 classes).*

Encoder	Params	Initialisation	Notes
Scratch CNN (ours)	11.3M	random (Kaiming)	residual, 4 stages $64-128-256-512$, 2 blocks each
Scratch CNN, no skips	11.1M	random	ablation: same CNN without residual connections
ResNet-50 [3]	23.9M	ImageNet	bottleneck residual network
EfficientNet-B0 [4]	4.3M	ImageNet	depthwise convs + squeeze-excitation, compound scaling
ConvNeXt-Tiny [5]	28.0M	ImageNet	modernised ResNet: 7×7 depthwise convs, LayerNorm, GELU

Table 2: Encoders (parameter counts include the 200-class head).

Our from-scratch CNN. Stem: 3×3 conv (stride 2) → 3×3 conv → max-pool; then four stages of two residual blocks (3×3 conv–BN–ReLU–3×3 conv–BN, plus an identity or 1×1 projection shortcut). Every stage after the first halves the resolution and doubles the channels. Weights use Kaiming initialisation, and the last BatchNorm of every residual branch is initialised to zero so that each block starts as an identity mapping, which stabilises early training.

Transfer-learning strategies. (a) *Linear probe*: the ImageNet backbone is frozen (including its BatchNorm statistics) and only the linear head is trained. (b) *Full fine-tuning*: all layers are trained, with *discriminative learning rates* — the head uses the base LR and the pretrained backbone uses $0.1\times$ that LR, so the useful ImageNet features are adapted gently instead of being overwritten.

4 Experiments

Common setup. AdamW, linear warm-up then cosine decay (per step), label smoothing 0.1, mixed precision (FP16), batch size 32 (64 for the scratch CNNs), 224×224 inputs, ImageNet normalisation for pretrained models and dataset statistics (mean $[0.485, 0.499, 0.432]$) for the scratch models, early stopping on validation accuracy with the best checkpoint restored. Hardware: one NVIDIA Tesla T4 (Kaggle). One run per configuration, seed 42.

Run	LR (head)	Weight decay	Aug.	Epochs (best)	Time	s/epoch
Scratch CNN	2e-3	0.05	standard	80 (64)	23.8 min	17.8
Scratch CNN, no skips	2e-3	0.05	standard	40 (37)	11.8 min	17.7
ResNet-50 linear probe	3e-3	1e-4	light	15 (11)	5.1 min	20.2
ResNet-50 fine-tune	1e-3	1e-4	standard	30 (27)	9.9 min	19.7
ResNet-50 fine-tune, tuned	2.09e-3	3.4e-5	standard	30 (23)	11.7 min	23.4
EfficientNet-B0 fine-tune	1e-3	1e-4	standard	30 (29)	10.4 min	20.8
ConvNeXt-Tiny fine-tune	1e-3	1e-4	standard	28 (20)	13.5 min	28.8

Table 3: Settings of every training run. Pretrained backbones use 0.1× the head LR.

Model	Accuracy	Top-5	Precision	Recall	F1	Best val acc
Scratch CNN, no skips	36.5	67.0	35.5	36.7	35.0	36.0
Scratch CNN (ours)	52.5	76.7	53.2	52.5	52.1	51.7
ResNet-50 linear probe	67.6	91.2	69.0	68.0	67.7	66.4
EfficientNet-B0 fine-tune	79.8	94.4	80.3	80.0	79.8	79.1
ResNet-50 fine-tune	82.4	95.2	82.8	82.5	82.3	81.6
ResNet-50 fine-tune, tuned	82.4	95.3	82.8	82.6	82.3	81.8
ConvNeXt-Tiny fine-tune	**84.6**	**96.0**	**85.0**	**84.8**	**84.5**	**84.3**

Table 4: Test-set results (%, official CUB test split, 5,794 images). Precision/recall/F1 are macro-averaged.



Figure 9: Validation accuracy per epoch for all runs.

4.1 From scratch vs. transfer learning

Transfer learning wins by a wide margin: the best fine-tuned model is **32 points** more accurate than our scratch CNN, converges in 20 epochs instead of 64, and is already at ∼75% validation accuracy after 3 epochs (Fig. 9). With only ∼27 images per class, a network trained from scratch must learn edges, textures and bird parts from about 5,400 images; ImageNet pretraining provides these generic features for free.

The scratch CNN also shows the clearest **overfitting** (Fig. 10): training accuracy reaches 96% while validation accuracy plateaus at 51%, and the validation loss stops improving after epoch ∼45 while the training loss keeps falling. Strong regularisation (weight decay 0.05, dropout 0.3, label

smoothing, RandomErasing) reduced but could not close this gap. The pretrained models also fit the training set ($> 98\%$), but their gap is much smaller because their features generalise.

Linear probe vs. fine-tuning. Frozen ImageNet features already give 67.6%, i.e. they are informative about birds; but fine-tuning the whole backbone adds **+14.8 points**. ImageNet features are tuned to separate e.g. "bird vs. dog", not "California Gull vs. Western Gull", so adapting the deeper layers to fine-grained cues is essential.

Ablation: residual connections. With the same 11M-parameter CNN, removing the skip connections lowers validation accuracy at epoch 40 from 45.8% to 35.3%. Crucially the no-skip network does *not* overfit — its training accuracy is only 44% — it is harder to *optimise*. This is the degradation problem described by He et al. [3]: residual connections give gradients a short path through the 18-layer network.



Figure 10: Training vs. validation loss and accuracy. Top: scratch CNN with and without residual connections. Bottom: fine-tuned ResNet-50 and ConvNeXt-Tiny.

4.2 Architecture comparison

Among pretrained backbones, ConvNeXt-Tiny is best (84.6%), ResNet-50 second (82.4%) and EfficientNet-B0 third (79.8%), which matches their ordering on ImageNet and the finding of Kornblith et al. [8] that better ImageNet architectures transfer better. EfficientNet-B0 is the most parameter-efficient (79.8% with 4.3M parameters, 6.6× fewer than ConvNeXt), while ConvNeXt costs about 45% more time per epoch than ResNet-50.



Figure 11: Test accuracy, macro-F1 and top-5 accuracy of all models.

5 Hyper-parameter tuning

Setup. We tuned the two hyper-parameters with the largest expected effect for fine-tuning, the **learning rate** (head LR; backbone = 0.1×) and **weight decay**, on ResNet-50 full fine-tuning. Each trial is a short 8-epoch run (enough to rank configurations); selection uses only the validation set.

- **Grid search:** LR $\in \{3\times10^{-4}, 10^{-3}, 3\times10^{-3}\}$ × WD $\in \{10^{-5}, 10^{-4}, 10^{-3}\}$ = 9 trials.
- **Random search [7]:** 9 trials (same budget), LR $\sim$ log-uniform$[2\times10^{-4}, 5\times10^{-3}]$, WD $\sim$ log-uniform$[10^{-5}, 10^{-2}]$, i.e. the same ranges.

Method	Trials	Best val acc	Total time	Best found at
Grid	9	79.3% (LR 3e-3, WD 1e-4)	25.3 min	trial 8
Random	9	**80.4%** (LR 2.09e-3, WD 3.4e-5)	24.3 min	trial 8

Table 5: Comparison of tuning methods with the same budget.



Figure 12: Top: best validation accuracy so far vs. trial number and wall-clock time. Bottom: where each method sampled (colour = validation accuracy).

Findings.

1. **Learning rate dominates; weight decay barely matters.** In the grid, the mean accuracy per LR row is 75.6%, 78.0% and 78.9% for LR 3×10^{-4}, 10^{-3} and 3×10^{-3}, while changing WD by 100× moves accuracy by less than 0.7 points.
2. **Random search was better with the same budget** (80.4% vs. 79.3%, and ahead after every trial). Grid search spends three trials on each LR value; random search tries 9 different LR values, which is more useful when only one of the two dimensions is important [7]. The grid's best LR is also on the edge of its range, a sign the grid was too narrow; random search covered more of the LR axis.
3. **Caveat: noise.** With 598 validation images one image is 0.17%, and the standard error of an accuracy near 80% is about $\sqrt{0.8 \cdot 0.2/598} \approx 1.6\%$. Differences of ∼1 point between trials are within noise.

Baseline vs. tuned model. Retraining ResNet-50 for the full 30 epochs with the best random-search configuration gave 82.40% test accuracy vs. 82.38% for the default configuration — **no meaningful improvement**. The short 8-epoch proxy rewards hyper-parameters that converge *fast* (a higher LR), but with a full cosine schedule the default LR catches up. We report this honestly as a limitation of low-fidelity tuning: the proxy should be closer to the real schedule (e.g. 15–20 epochs) or combined with a multi-fidelity method such as Hyperband.

6 Experiment tracking

Every run is logged with Weights & Biases [20] through a small `Tracker` interface (`src/tracking/trackers.py`); a local tracker additionally writes `config.yaml`, `history.jsonl`, `summary.json` and the plots to each run folder, so all figures can be regenerated offline. For each run we log: the full configuration (all hyper-parameters, encoder, augmentation, seed), per-epoch train/validation loss and accuracy, validation macro-F1 and top-5, learning rate and epoch time, the final test metrics, parameter counts, the device, and the path of the best checkpoint. Tuning trials are grouped (`tune-grid-*`, `tune-random-*`) and tagged, so the two searches can be compared side by side. In total Milestone 1 contains 53 runs: 7 baseline training runs, 18 tuning-v1 trials, 16 improvement runs, 8 tuning-v2 trials and 4 final runs.



Figure 13: W&B: all runs of Milestone 1.



Figure 14: W&B: learning curves of the training runs.



Figure 15: W&B: hyper-parameter search trials.

7 Evaluation

Metrics.

- **Accuracy**: fraction of test images whose top-1 prediction is correct. Simple, but dominated by the larger classes of the imbalanced test set.
- **Top-5 accuracy**: the true class is among the five most probable. In fine-grained tasks the top-2/3 are often sibling species, so top-5 shows whether the model at least narrows the answer to the right group.
- **Macro precision / recall / F1**: computed per class and averaged with equal weight, so the small classes (e.g. Least Auklet, 11 images) count as much as the large ones. Precision: of the

images predicted as class c, how many are c; recall: of the images of class c, how many were found; F1: their harmonic mean.
- **Balanced accuracy**: mean per-class recall.
- **Confusion matrix** and the list of the most confused class pairs.

Interpretation. For every model, macro-F1 is within 0.5 points of accuracy (Table 4), so the test imbalance does not hide a failure on small classes. ConvNeXt's top-5 accuracy of 96.0% means that for 96% of images the correct species is among five candidates — the remaining errors are mostly between siblings. Its per-class accuracy ranges from 100% (e.g. the woodpeckers with distinctive patterns) down to 23% (California Gull, Common Tern).



Figure 16: Most confused (true → predicted) pairs of ConvNeXt-Tiny on the test set.

The most confused pairs (Fig. 16) are exactly the hard fine-grained cases: terns (Caspian/Elegant, Common/Forster's/Arctic), gulls (California/Western), *Empidonax* flycatchers (Acadian/Least/Yellow-bellied) and jaegers — species that birders separate by size, voice or subtle bill and wing-tip details that are hard to see at 224 px. The top pair, **Chuck-will's-widow → Whip-poor-will** (11 of 26 test images), is the same pair for which the EDA found an identical photograph labelled as both species — evidence that the labels of these two nightjars are themselves noisy.

8 Explainability (Grad-CAM)

We implemented Grad-CAM [6] (`src/visualization/gradcam.py`) with forward/backward hooks on the last stage of each encoder. For the target class c, the weight of channel k is the spatial mean of $\partial y^c / \partial A^k$, and the map is $\mathrm{ReLU}(\sum_k \alpha_k^c A^k)$, upsampled to the image size. The same test images are shown for the scratch CNN, ResNet-50 and ConvNeXt; images are selected from the scratch model's predictions (6 random correct ones and its 6 most confident mistakes).



Figure 17: Grad-CAM on images the scratch CNN classified correctly (green: correct, red: wrong; confidence in brackets).



Figure 18: Grad-CAM on the scratch CNN's most confident mistakes.

Analysis.

- **Correct predictions** (Fig. 17): all models mostly look at the bird, typically the head and breast, where most field marks are (e.g. the Wilson's Warbler's head, the Cedar Waxwing's face and crest). The pretrained models produce tighter, part-focused maps (ResNet-50 on the hummingbird's red throat), while the scratch CNN's maps are broader.
- **Right for the wrong reason:** on the Ruby-throated Hummingbird the scratch CNN's attention is on the *red feeder*, not on the bird (and its confidence is only 0.27). It has learned a context

shortcut — red objects near hummingbirds — that will not generalise; the pretrained models attend to the bird itself.

- **Scratch mistakes are confident and coarse** (Fig. 18): it predicts Blue Jay for a Florida Jay with 0.99 confidence while attending to the whole body; the fine-tuned models, attending to the same region but with better features, get it right. For the Herring Gull the scratch CNN looks at the ground and legs.
- **Mistakes shared by all models are informative:** American Crow → Common Raven is wrong for all three: the two are separated mainly by size and bill thickness, which a single cropped image does not show reliably. The Red-headed Woodpecker is predicted as Red-bellied Woodpecker by all models, whose attention lies on the barred back/belly — shared by both species — rather than on the fully red head that distinguishes it.

9 Benchmarking

We compare against published results on the same benchmark: the official CUB-200-2011 test split (5,794 images, which we did not modify) and the same metric (top-1 accuracy). The open-source pretrained backbones are additionally evaluated by us on our split with our metrics (Table 4).

Method	Backbone (pretraining)	Input	Top-1 (%)	Source
Trained from scratch				
ResNet-50, 300 epochs†	ResNet-50 (none)	–	66.7	[12]
ResNet-50 + cross-entropy	ResNet-50 (none)	448	51.9	[14]
ResNet-50 + cosine loss + cross-entropy	ResNet-50 (none)	448	68.0	[14]
Ours, scratch CNN, 80 epochs (baseline)	11M CNN (none)	224	52.5	
Ours, scratch CNN, final‡	11M CNN (none)	224	**66.8**	
Fine-tuned ImageNet backbones				
ResNet-50 (+2 FC layers)	ResNet-50 (IN-1k)	224	77.5	[11]
ResNet-50 baseline	ResNet-50 (IN-1k)	448	84.5	[9]
ResNet-50 baseline	ResNet-50 (IN-1k)	448	85.3	[10]
NTS-Net (part-based)	ResNet-50 (IN-1k)	448	87.5	[9]
TransFG (state of the art class)	ViT-B/16 (IN-21k)	448	91.7	[13]
Ours, ResNet-50 fine-tune	ResNet-50 (IN-1k)	224	**82.4**	
Ours, ConvNeXt-Tiny fine-tune (baseline)	ConvNeXt-T (IN-1k)	224	84.6	
Ours, ConvNeXt-Tiny final	ConvNeXt-T (IN-1k)	384	**87.0** (87.3 TTA)	

Table 6: Comparison with published results on the CUB-200-2011 test split. †Reported by the authors as "validation accuracy". ‡Uses ground-truth bird boxes at test time.

Discussion of the differences.

- **Resolution** is the largest factor. Standard fine-grained baselines use 448×448 inputs; at 224 px our fine-tuned ResNet-50 (82.4%) is about 2–3 points below the 448 px ResNet-50 baselines (84.5–85.3%), consistent with small field marks being lost at lower resolution. At the same 224 px resolution our ResNet-50 is well above the 77.5% reported in [11]; part of this is our training recipe (AdamW, discriminative LRs, label smoothing, augmentation) and the stronger torchvision ImageNet weights (`IMAGENET1K_V2`) we start from.
- **ConvNeXt-Tiny at 224 px matches ResNet-50 at 448 px** (84.6% vs. 84.5%) with about four times fewer input pixels, showing the benefit of a newer architecture.
- **Our final model** (87.0%, full image, 384 px, no annotations) is above the 448 px ResNet-50 baselines (84.5–85.3%) and close to the part-based NTS-Net (87.5%), with a standard architecture and no part-localisation module.
- **From scratch, the cosine loss reproduces the published trend**: Barz & Denzler [14] report 51.9% (cross-entropy) vs. 68.0% (cosine + cross-entropy) for a ResNet-50 trained from

scratch on CUB; our 11M-parameter CNN goes from 52.5% to 66.8% with the cosine loss, bird crops and Mixup/CutMix. Their numbers do not use bounding boxes, ours do, so this row is a trend comparison rather than a like-for-like one.

- **The gap to the state of the art** (TransFG, 91.7%) comes from three things we do not use: a ViT-B/16 pretrained on the 14× larger ImageNet-21k, 448 px input, and explicit part-selection mechanisms designed for fine-grained recognition.
- **From scratch**, our baseline CNN was far below the 300-epoch ResNet-50 of [12] (52.5% vs. 66.7%); with the improvements of Section 10 our final scratch CNN (66.8%) matches it with half the parameters, but with bounding boxes.
- **Limits of the comparison**: we report a single seed, while published baselines differ in epochs, optimisers and augmentation; these numbers should be read as reference points, not as a controlled comparison.

10 Improving the models

After the baseline experiments we tested a series of improvements, **one change at a time** so that the effect of each can be measured. Ideas came from the EDA, from the Grad-CAM analysis, from the literature and from team discussion. As before, **every choice is made on the validation set**; the test set is only reported. All runs in this section use a higher-resolution image cache (shorter side 512 px instead of 256 px). This alone changes results slightly: the standard ResNet-50 recipe re-run on the new cache scored 83.8% instead of 82.4% (sharper crops when RandomResizedCrop zooms in, plus run-to-run noise). We therefore compare *within* each series and always include a re-run baseline.

10.1 Bird-crop preprocessing (bounding boxes)

Motivation. The bird covers only **32% of the image** on median (as little as 5%; 2,739 images are under 20%, Fig. 19), so about two-thirds of every input is background (branches, water, feeders). Grad-CAM had already shown that the scratch CNN used the red feeder rather than the hummingbird — a background shortcut.

Method. The Hugging Face version of CUB has no annotations, so we extracted the official bounding boxes (`bounding_boxes.txt`) from the original CUB-200-2011 release once and matched them to all 11,788 images by file name (`resources/cub_bounding_boxes.csv`). Each image is cropped to a *square* box around the bird with a 15% margin on every side (`crop_to_bird` in `src/data/datasets.py`), so that the later centre crop does not cut off tails or wings, and some context remains. The crop is applied identically to train, validation and test images; all other preprocessing and augmentation then run on the cropped image.



Figure 19: Left: fraction of the image covered by the bird. Right: original images with the official box (top) and our crop (bottom).

Results. Cropping is the single most effective change: **+6.3 points** for the scratch CNN (52.5%→58.7%) and **+1.3 points** for ConvNeXt-Tiny (84.6%→85.9%). It helps the scratch CNN much more because a network that learns from 5,400 images cannot afford to spend capacity on background, while ImageNet features already ignore much of it. Cropping also acts as a *zoom*: the bird occupies the whole 224 × 224 input, so field marks get about 3× more pixels.

Caveat (fairness). Using the ground-truth box *at test time* uses an annotation that a real user would not provide. These results are therefore reported separately as "with ground-truth boxes" and are not compared with annotation-free methods; we also report our best *full-image* model. In a deployed system (and for Milestone 2) a bird detector would supply the box.

10.2 Resolution

At 384 px (instead of 224) on full images, ConvNeXt reached a higher validation accuracy (85.1% vs. 84.3%) but the same test accuracy (84.6%); its best epoch came early (14 of 30) and it costs 2.3× more time per epoch. With the bird crop, 384 px added +0.3 points (85.9%→86.2%). **Conclusion:** at our budget, cropping is a cheaper and more effective "zoom" than raising the resolution of the whole image; the two partly do the same thing.

10.3 Augmentation ablation

Seven augmentation strategies were compared on the same model (ResNet-50 fine-tune, full image, 224 px, 30 epochs):



Figure 20: Augmentation ablation: validation (selection) and test accuracy.

- **Augmentation matters**: with none, test accuracy is 80.9%; every geometric augmentation improves it by about 2–3 points.
- **Light ≈ standard** (83.9% vs. 83.8%, within noise).
- **Too strong hurts**: *strong* (82.7%) sometimes crops the bird out entirely (Fig. 8).
- **RandAugment [17] is the worst augmented setting (82.0%)**. Its policy includes colour-changing operations (Color, Solarize, Posterize, Equalize). This supports our EDA-based decision not to alter colours: colour is a label-relevant feature for birds. TrivialAugment [18], whose operations are sampled with random strength (often weak), stays at the standard level (83.7%).
- **Mixup/CutMix on top of standard is the best** (84.4% test, 85.0% with TTA). Mixup [15] blends two images and their labels; CutMix [16] pastes a patch of one image into another and mixes the labels by area. Both prevent the model from becoming over-confident on 27 images per class. (The low "train accuracy" of mixed runs, ∼67%, is measured on the mixed images and is expected.)

10.4 Loss function: cosine loss vs. cross-entropy

Cross-entropy keeps pushing the true-class logit up, so on a tiny dataset the network can reduce the loss simply by *scaling up* its outputs. The cosine loss of Barz & Denzler [14], proposed for small datasets trained from scratch, L2-normalises the output vector and maximises its cosine similarity with the one-hot vector of the true class, so only the *direction* of the output matters. We implemented their combined form, cosine loss $+\,0.1\times$ cross-entropy on the normalised vector (`src/training/losses.py`); predictions use the (scaled) cosine similarities.



Figure 21: Cosine loss vs. cross-entropy for three models.

Results. As the paper predicts, the cosine loss helps most when training **from scratch** (+1.0 test, +2.3 validation). For the pretrained ConvNeXt it improved validation accuracy by 1.5 points (the best single-change validation score, 85.5%) but test accuracy only by 0.1; for ResNet-50 it was 0.8 points *worse* on test. With pretrained features the over-confidence problem the cosine loss addresses is smaller, so its benefit is inconsistent.

10.5 Scratch CNN: combining the improvements



Figure 22: Cumulative improvements of our from-scratch CNN.

Bird crop (+6.3), cosine loss (+1.0), then Mixup/CutMix with longer training (150 epochs, +6.2) raised the scratch CNN from 52.5% to **66.0%** (66.6% with TTA), a gain of 13.5 points without any pretraining. The overfitting gap also shrank: the original model reached 96% training accuracy against 51% validation; with mixing the model can no longer memorise individual images. Validation accuracy was still rising at epoch 147 of 150, so a longer run is included in the final experiments.

10.6 Test-time augmentation (TTA)

At test time each image is also classified mirrored (horizontal flip) and the two probability vectors are averaged. TTA improved **all 16 runs**, by +0.58 points on average (range +0.22 to +1.07), at the cost of a second forward pass. Being free of training, it is reported for every run from now on.

10.7 Hyper-parameter tuning v2

Tuning v1 had one clear limitation: the 8-epoch proxy runs favoured fast-converging settings, and the tuned configuration did not beat the default at 30 epochs. Tuning v2 fixes the protocol: (i) a 15-epoch proxy, (ii) on the final model family (ConvNeXt-T + bird crop) rather than ResNet-50, and (iii) four hyper-parameters — head LR, **backbone LR multiplier**, weight decay, label smoothing — with random search (8 trials).



Figure 23: Tuning v2: validation accuracy of each trial against each hyper-parameter (red circle = best trial).

The best trial reached 84.5% validation accuracy after only 15 epochs (head LR 1.25×10^{-3}, backbone multiplier 0.25, weight decay 1.3×10^{-5}, label smoothing 0.11). The new parameter was informative: validation accuracy correlates positively with the **backbone LR multiplier** ($r = +0.63$) — trials with a multiplier around 0.05–0.07 were among the worst. Our default of 0.1 adapts the backbone too gently for fine-grained birds; a larger multiplier lets the deeper layers learn bird-specific features. With eight trials these correlations are indicative only. The tuned values are used in the final combined runs.

10.8 Summary of single changes (ConvNeXt-Tiny)



Figure 24: ConvNeXt-Tiny: one change at a time (validation and test accuracy).

ConvNeXt-Tiny run	Val	Test	Test + TTA	Macro-F1
Full image, 224 px (Milestone-1 baseline)	84.3	84.6	—	84.5
Full image, 384 px	85.1	84.6	84.9	84.5
Bird crop, 224 px	83.9	85.9	86.3	85.8
Bird crop, 384 px	84.6	86.2	86.5	86.1
Bird crop, cosine loss	**85.5**	86.1	86.5	86.0
Bird crop, Mixup/CutMix (40 ep.)	84.6	**86.5**	**86.7**	**86.4**

Table 7: ConvNeXt-Tiny improvements (%). Validation differences below ∼1.5 points are within noise (598 images).

10.9 Final combined runs and model selection

Finally we combined everything that helped on its own — 384 px input, Mixup/CutMix (40 epochs) and the tuning-v2 hyper-parameters (head LR 1.25×10^{-3}, backbone multiplier 0.25, weight decay 1.3×10^{-5}, label smoothing 0.1) — in three ConvNeXt-Tiny variants, plus a longer (250-epoch) run of the improved scratch CNN. All four ran in parallel on two Kaggle machines with two T4 GPUs each.

Run	Crop	Loss	**Val**	Test	Test + TTA	Macro-F1 (TTA)
ConvNeXt-T, full image	none	CE	**87.3**	87.0	87.3	87.2
ConvNeXt-T, bird crop	GT box	CE	86.3	87.3	87.5	87.4
ConvNeXt-T, bird crop, cosine	GT box	cosine	86.8	86.9	87.2	87.1
Scratch CNN, all improvements, 250 ep.	GT box	cosine	69.1	66.8	67.5	67.1

Table 8: Final combined runs (%, 384 px for ConvNeXt, 224 px for the scratch CNN). CE = cross-entropy, GT box = ground-truth bounding box.

Selection rule: highest validation accuracy. The winner is the **full-image** ConvNeXt-Tiny (87.3% validation, **87.0% test, 87.3% with TTA**, top-5 97.1%). This is a welcome outcome: the

selected model needs *no bounding box at test time*, so it is directly comparable with annotation-free published methods. Once the model is strong and sees the image at 384 px, the benefit of cropping shrinks to ∼0.3 test points (and reverses on validation) — differences inside the noise level (±0.45 points on test, ±1.4 on validation). We deliberately did *not* pick the crop model because of its slightly higher test score: that would be selecting on the test set. Compared with the Milestone-1 ConvNeXt (84.6%), the final model gains **+2.4 points**; compared with our first from-scratch CNN (52.5%), the final scratch CNN gains **+14.3 points**.

We did not retrain the final model on train+val: the option is implemented (`data.train_on_val`), but without a held-out validation set the result could no longer be checked, and 598 extra images (+11%) would likely change accuracy by less than the noise.



Figure 25: Final ConvNeXt-Tiny: training and validation curves. Training accuracy is measured on mixed (Mixup/CutMix) images and is therefore lower than validation accuracy.

10.10 Grad-CAM of the final models



Figure 26: Images the Milestone-1 ConvNeXt got wrong, with the final ConvNeXt next to it.



Figure 27: The final ConvNeXt's most confident mistakes, compared with the Milestone-1 ConvNeXt and the final scratch CNN.

- **Tighter attention.** The final ConvNeXt's maps are more compact and centred on the head and breast, while the Milestone-1 model's maps spread over the body and background (Fig. 26). This matches the training changes: CutMix forces the model to recognise birds from partial evidence, and the larger backbone learning rate adapts the deep features to birds.
- **Lower confidence on mistakes.** On images the old model misclassified with 0.91–0.94 confidence, the final model makes the same mistakes with lower confidence (e.g. Worm-eating Warbler 0.94→0.64, Red-headed Woodpecker 0.92→0.67): Mixup and label smoothing make the model

less over-confident.

- **Some "mistakes" are probably label errors.** Several of the final model's most confident errors (Fig. 27) look, on visual inspection, like the *predicted* species: e.g. the image labelled *Green Kingfisher* shows the black-and-white plumage of a Pied Kingfisher, which all three models predict. Bird experts estimated that at least 4% of CUB-200-2011 labels are wrong [19], which also caps the accuracy any model can reach on this test set.
- **The scratch CNN still uses the background.** Even after all improvements, its maps for wrong predictions often sit next to the bird (Fig. 27, right column), and its confidences are saturated at 1.00: the cosine head's scaled scores are not calibrated probabilities. Pretraining remains the most important factor for robust features.

11 Final selection

Classifier: ConvNeXt-Tiny, fully fine-tuned on full images at 384 px with Mixup/CutMix and the tuning-v2 hyper-parameters (`configs/improve/final_full_ce.yaml`). It has the best validation accuracy of all runs (87.3% — this is how it was *selected*; the test set was only used for reporting) and reaches **87.0% test accuracy, 87.3% with flip TTA**, 87.2% macro-F1 and 97.1% top-5. It needs no bounding box at inference. Training takes 55 minutes on a T4. **Best from-scratch model:** our residual CNN with bird crops, cosine loss and Mixup/CutMix, 250 epochs: 66.8% (67.5% with TTA).

Encoder for Milestone 2. The final fine-tuned ConvNeXt-Tiny encoder will be the main backbone for colorization and captioning: it provides the best bird-specific features and four feature maps (96–768 channels, strides 4–32) that plug directly into a U-Net decoder. Fine-tuned ResNet-50 is kept as a second backbone for comparison, and the scratch CNN as the from-scratch baseline. All three checkpoints are stored in the shared Google Drive folder.

12 Failures and limitations

- **Scratch CNN overfitting.** The baseline overfit strongly (96% train vs. 51% validation). Bird crops, the cosine loss, Mixup/CutMix and longer training raised it to 66.8%, but Grad-CAM shows it still relies on background context.
- **The CNN without residual connections failed to train well** (44% training accuracy): this was an intended ablation, but it confirms that plain 18-layer CNNs are hard to optimise.
- **Tuning v1 did not transfer to the full schedule**: the 8-epoch optimum gave no improvement at 30 epochs. Tuning v2 (15-epoch proxy, 4 hyper-parameters, final model family) produced the settings used by the final model. Still open: several seeds, Optuna/Hyperband, and tuning augmentation strength.
- **Some ideas did not work**: RandAugment and the *strong* augmentation *lowered* accuracy; 384 px on full images gave no test gain on its own; the cosine loss was worse than cross-entropy for ResNet-50.
- **Ground-truth boxes**: the crop experiments use annotations that are not available for new photos; the final model therefore does not use them. A bird detector would be needed to use cropping in practice.
- **Label noise**: at least 4% of CUB labels are estimated to be wrong [19]; several confident "errors" of our final model look like such cases.
- **Single seed and a small validation set** (598 images): differences below ∼1.5 points are not statistically reliable.
- **Resolution**: baseline runs used 224 px; the final model uses 384 px. 448 px and larger backbones (ConvNeXt-Small/Base, ImageNet-21k weights) were not tried because of the GPU budget.
- **Infrastructure**: the first Kaggle runs silently ran without GPU or internet because the account was not phone-verified; our CLI now refuses to train on a CPU unless explicitly allowed, and the

code, data and weights are packaged so the jobs can run offline.
- **Label noise** (e.g. the nightjar pair) and genuinely ambiguous pairs (crow/raven) cap achievable accuracy.

13 Reproducibility and interface

All final code is pure Python, run through the CLI (`src/cli.py`); notebooks are not used for the final code. Exact commands:

```
python -m src.cli doctor          # checks GPU, CUDA PyTorch, W&B login, data
python -m src.cli prepare         # download, cache, split, deduplicate
python -m src.cli eda
python -m src.cli prepare --out data/processed_hr --short-side 512     # high-resolution cache
python -m src.cli train --task classification --config configs/improve/final_full_ce.yaml
python -m src.cli tune  --config configs/tune_resnet50.yaml --method grid    # or random
python -m src.cli compare-tuning --dirs outputs/tuning/grid_* outputs/tuning/random_*
python -m src.cli evaluate --task classification --checkpoint <run>/best.pt --split test
python -m src.cli predict  --task classification --checkpoint <run>/best.pt --image bird.jpg
python -m src.cli gradcam  --checkpoints <scratch>/best.pt <resnet50>/best.pt --names scratch resnet50
python -m src.cli compare  --runs outputs/runs/*
```

Seeds are fixed, the validation split is stored in `data/processed/metadata.csv`, and every run folder and checkpoint contains the exact configuration it was trained with.

14 Team contributions

Member	Contribution
Abdelrahman Mohamed Zayed	Project structure, data pipeline and EDA, training and tuning pipeline, experiments, report
Ahmed ElSayed	Model module: 23 automated tests of the encoder and classifier contracts (feature-map shapes for every encoder, frozen-encoder behaviour, discriminative learning rates, cosine head, checkpoint save/load), a reproducible encoder size/speed benchmark (`scripts/model_summary.py`) and the model documentation (`docs/models.md`) — PR #2
Saeed Mohamed Negm	Training module: tests for the configuration system, optimizer/scheduler and hyper-parameter search, and the training documentation
Yehya ElAbyad	Data module: 20 automated tests for caption cleaning (including the corrupted-character and punctuation cases found in the EDA), tokenizer, vocabulary, augmentation transforms and dataset, and the data-pipeline documentation (`docs/data.md`) — PR #3
Hassan Hazem	Evaluation module: 11 automated tests for the metrics (hand-computed cases) and Grad-CAM, batch (folder) inference with CSV export in the CLI, and the evaluation and Grad-CAM documentation (`docs/evaluation.md`) — PR #1

References

[1] C. Wah, S. Branson, P. Welinder, P. Perona, S. Belongie. *The Caltech-UCSD Birds-200-2011 Dataset.* Caltech Tech. Report CNS-TR-2011-001, 2011.

[2] S. Reed, Z. Akata, H. Lee, B. Schiele. Learning Deep Representations of Fine-Grained Visual Descriptions. CVPR 2016.

[3] K. He, X. Zhang, S. Ren, J. Sun. Deep Residual Learning for Image Recognition. CVPR 2016.

[4] M. Tan, Q. Le. EfficientNet: Rethinking Model Scaling for Convolutional Neural Networks. ICML 2019.

[5] Z. Liu, H. Mao, C.-Y. Wu, C. Feichtenhofer, T. Darrell, S. Xie. A ConvNet for the 2020s. CVPR 2022.

[6] R. R. Selvaraju et al. Grad-CAM: Visual Explanations from Deep Networks via Gradient-based Localization. ICCV 2017.

[7] J. Bergstra, Y. Bengio. Random Search for Hyper-Parameter Optimization. JMLR 13, 2012.

[8] S. Kornblith, J. Shlens, Q. V. Le. Do Better ImageNet Models Transfer Better? CVPR 2019.

[9] Z. Yang et al. Learning to Navigate for Fine-grained Classification (NTS-Net). ECCV 2018. https://arxiv.org/abs/1809.00287

[10] Cut-Thumbnail: A Novel Data Augmentation for Convolutional Neural Network. ACM MM 2021. https://arxiv.org/abs/2103.05342

[11] T. Leemann et al. When are Post-hoc Conceptual Explanations Identifiable? UAI 2023. https://arxiv.org/abs/2206.13872

[12] Feature Mining: A Novel Training Strategy for Convolutional Neural Network. https://arxiv.org/abs/2107.08421

[13] J. He et al. TransFG: A Transformer Architecture for Fine-grained Recognition. AAAI 2022. https://arxiv.org/abs/2103.07976

[14] B. Barz, J. Denzler. Deep Learning on Small Datasets without Pre-Training using Cosine Loss. WACV 2020. https://arxiv.org/abs/1901.09054

[15] H. Zhang, M. Cisse, Y. N. Dauphin, D. Lopez-Paz. mixup: Beyond Empirical Risk Minimization. ICLR 2018.

[16] S. Yun et al. CutMix: Regularization Strategy to Train Strong Classifiers with Localizable Features. ICCV 2019.

[17] E. D. Cubuk, B. Zoph, J. Shlens, Q. V. Le. RandAugment: Practical Automated Data Augmentation with a Reduced Search Space. CVPR Workshops 2020.

[18] S. G. Müller, F. Hutter. TrivialAugment: Tuning-free Yet State-of-the-Art Data Augmentation. ICCV 2021.

[19] G. Van Horn et al. Building a Bird Recognition App and Large Scale Dataset with Citizen Scientists: The Fine Print in Fine-Grained Dataset Collection. CVPR 2015.

[20] L. Biewald. Experiment Tracking with Weights and Biases, 2020. https://wandb.ai

[21] TorchVision maintainers. TorchVision: PyTorch's Computer Vision library. https://github.com/pytorch/vision