Four New Hybrid Root Bracketing Algorithms: Optimization-Based Approaches for Numerical Root Finding

Abdelrahman Ellithy[1]
Department of Scientific Computing, Faculty of Computers and Artificial Intelligence, Benha University, Benha, Egypt

(Dated: October 13, 2025)

The accurate and efficient determination of roots for nonlinear equations remains a significant challenge in numerical analysis, particularly when dealing with functions that exhibit complex behavior or require robust convergence guarantees. Traditional bracketing methods, such as bisection and false position, offer reliability but often suffer from slow convergence, while optimization-based methods like the secant method provide speed at the cost of stability.This paper presents four novel hybrid root bracketing algorithms that combine the advantages of traditional bracketing methods with optimization techniques. The proposed algorithm Optimized Bisection-False Position (Optimized_BF), Optimized Bisection-False Position with Modified Secant (Optimized_BFMS), Optimized Trisection-False Position (Optimized_TF), and Optimized Trisection-False Position with Modified Secant (Optimized_TFMS)—demonstrate improved convergence rates and computational efficiency compared to their traditional counterparts. Through extensive experimentation on 42 diverse test functions using the SymPy library, our algorithms show consistent performance improvements, with Optimized_BFMS achieving the best overall performance. The hybrid approach leverages the reliability of bracketing methods while incorporating the speed advantages of optimization-based techniques, making these algorithms suitable for a wide range of numerical computing applications.

Keywords: hybrid root-finding algorithms, numerical analysis, optimization, bisection method, false position method, trisection method, modified secant, SymPy, computational mathematics, scientific computing, algorithm benchmarking, convergence analysis, symbolic computation.

I. INTRODUCTION

Root finding is a fundamental problem in numerical analysis with applications spanning engineering, physics, economics, and computer science. Traditional root bracketing methods such as bisection, false position, and trisection provide guaranteed convergence but often suffer from slow convergence rates, especially for functions with complex behavior near the root. The motivation for developing hybrid approaches stems from the need to combine the reliability of bracketing methods with the efficiency of optimization techniques. Recent research has shown that hybrid algorithms can significantly improve convergence rates while maintaining the robustness of traditional methods [1, 3].

Recent advances in root-finding algorithms have improved convergence and robustness by hybridizing classical bracketing methods with optimization techniques. Notable contributions include blended and hybrid algorithms that combine bisection, regula falsi, and secant methods [2, 6], as well as metaheuristic approaches for nonlinear equations[7, 8]. These works have demonstrated that hybridization can yield significant improvements in both speed and reliability, motivating the development of the new algorithms presented in this paper.

The main contributions of this paper are as follows. First, we present four novel hybrid algorithms, each with a solid mathematical foundation, that blend the best aspects of existing root-finding techniques. Second, we provide a comprehensive performance analysis of these algorithms on a diverse set of test functions, demonstrating their effectiveness and generality. Third, we detail the implementation of these methods using the SymPy library for symbolic computation, which allows for high-precision and flexible experimentation. Finally, we offer a comparative analysis with traditional methods, highlighting the advantages and potential of the proposed hybrid approaches in practical numerical computation scenarios.

This paper is organized as follows. Section II (page 2) details the methodology and mathematical foundations of the proposed algorithms. Section III (page 12) describes the experimental setup and test functions. Section IV (page 19) presents the results and analysis. Section V (page 26) discusses the implications and limitations. Section VI (page 28) concludes the paper and outlines future research directions.

II. METHODOLOGY

The methodology adopted in this study is centered on the design and development of four hybrid root bracketing algorithms. Each algorithm is constructed by integrating the strengths of traditional bracketing methods with optimization-based enhancements. For example, the Optimized Bisection-False Position (Optimized_BF) algorithm leverages the interval-halving reliability of bisection and the faster convergence of the false position method. The Optimized_BFMS algorithm incorporates a modified secant step to further accelerate convergence. The trisection-based variants, Optimized_TF and Optimized_TFMS, use a three-way interval split and integrate both false position and secant-based acceleration. All algorithms are implemented using the SymPy library, which provides symbolic computation capabilities and high-precision arithmetic. The mathematical foundations of these methods are rooted in the Intermediate Value Theorem, linear interpolation, and finite-difference approximations for derivative estimation.

The convergence analysis of these hybrid methods follows established theoretical frameworks. For bracketing methods, the convergence is guaranteed by the Intermediate Value Theorem, while the rate of convergence depends on the specific combination of techniques employed. The false position method exhibits superlinear convergence in most cases, while the modified secant step can provide additional acceleration through derivative approximation.

A. Mathematical Foundations

The hybrid algorithms are based on several key mathematical principles. The Intermediate Value Theorem guarantees the existence of a root in the interval $[a, b]$ if $f(a) \times f(b) < 0$, providing the theoretical foundation for bracketing methods [9]. The False Position Method utilizes linear interpolation to estimate the root location, offering a more efficient approach than simple interval halving [10]. The Modified Secant Method accelerates convergence by approximating the derivative using finite differences, which allows for faster root refinement without requiring explicit derivative calculations [11]. Finally, the overall optimization strategy of the hybrid algorithms is to combine these multiple approaches, thereby minimizing the number of function evaluations while maintaining robust convergence properties.

The theoretical convergence analysis follows the framework established by [1] and [3], who demonstrated that hybrid approaches can achieve superlinear convergence rates while maintaining the reliability of bracketing methods. The trisection method, as analyzed by [12], provides a theoretical foundation for the three-way interval splitting approach used in our trisection-based algorithms.

For the false position method, the convergence rate is typically superlinear, with the error reduction following the pattern $|x_{n+1} - \alpha| \leq C \cdot |x_n - \alpha|^p$, where $p > 1$ and C is a constant depending on the function properties. The modified secant method, using finite difference approximation, maintains similar convergence characteristics while avoiding the need for explicit derivative calculations.

B. Algorithm Design, Hybrid Techniques and Pseudocode for Proposed Algorithms

1. Algorithm 1: Optimized Bisection-False Position (Optimized_BF)

The Optimized Bisection-False Position (Optimized_BF) algorithm represents a sophisticated hybrid root-finding approach that strategically combines the guaranteed convergence of the bisection method with the accelerated convergence potential of the false position (regula falsi) method. This algorithm addresses the fundamental trade-off between reliability and speed in numerical root finding by employing a two-phase strategy within each iteration.

The mathematical foundation of this algorithm lies in the sequential application of two complementary techniques. The bisection phase provides a conservative but reliable interval reduction by computing the midpoint $mid = \frac{a+b}{2}$ and evaluating $f(mid)$. This step ensures that the root remains bracketed while providing a baseline estimate. The subsequent false position phase leverages linear interpolation between the interval endpoints to compute a potentially more accurate estimate using the formula:

$$fp = \frac{a \cdot f(b) - b \cdot f(a)}{f(b) - f(a)} \tag{1}$$

This interpolation-based estimate often provides a better approximation to the root than the simple midpoint, especially for functions with significant curvature. The algorithm maintains the bracketing property by ensuring that the root remains contained within the updated interval $[a, b]$ after each iteration.

The key advantage of this hybrid approach is its robustness: even if the false position step produces an estimate outside the current interval (which can occur for certain function behaviors), the bisection step ensures that the interval is always properly reduced. This combination provides faster convergence than pure bisection while maintaining the reliability guarantees that make bracketing methods attractive for critical applications.

The algorithm is defined with the method signature Optimized_BF(f, a, b, tol, max_iter), where f is the function to be evaluated, a and b specify the initial interval $[a, b]$ containing a root (assumed to have opposite signs for $f(a)$ and $f(b)$), tol sets the tolerance for convergence, and max_iter limits the number of iterations. It returns a tuple $(n, x, f_x, a_{final}, b_{final})$, where n indicates the iteration count, x is the root approximation,

f_x is the function value at x, and a_{final} and b_{final} are the final interval bounds.

The implementation uses SymPy for symbolic computation and high-precision arithmetic, with a tolerance of 10^{-14} for convergence testing. The algorithm incorporates robust error handling for potential division by zero in the false position step, ensuring stable operation across diverse function types.

Algorithm 1: Pseudocode for the Optimized Bisection-False Position (Optimized_BF) algorithm. This hybrid method combines the reliability of bisection with the accelerated convergence of the false position method.

Input: Function f, interval $[a, b]$, tolerance tol, max iterations max_iter
Output: Iteration count n, root approximation x, function value $f(x)$, final interval $[a, b]$
$f_a \leftarrow f(a)$, $f_b \leftarrow f(b)$, $\epsilon \leftarrow 10^{-20}$
// Check if either bound is a root
if $|f_a| \leq tol$ **then**
    return $1, a, f_a, a, b$
end if
if $|f_b| \leq tol$ **then**
    return $1, b, f_b, a, b$
end if
if $f_a \times f_b \geq 0$ **then**
    return None, None, None, None, None
end if
for $n \leftarrow 1$ **to** max_iter **do**
    // Bisection Step
    $mid \leftarrow 0.5 \times (a + b)$
    $f_{mid} \leftarrow f(mid)$
    if $|f_{mid}| \leq tol$ **then**
        return n, mid, f_{mid}, a, b
    end if
    if $f_a \times f_{mid} < 0$ **then**
        $b, f_b \leftarrow mid, f_{mid}$
    else
        $a, f_a \leftarrow mid, f_{mid}$
    end if
    // False Position Step with exception handling
    $dx \leftarrow (a \times f_b) - (b \times f_a)$
    try:
        $fp \leftarrow dx/(f_b - f_a)$
    catch (division by zero, overflow, value error):
        $fp \leftarrow dx/((f_b - f_a) + \epsilon)$
    $f_{fp} \leftarrow f(fp)$
    if $|f_{fp}| \leq tol$ **then**
        return n, fp, f_{fp}, a, b
    end if
    if $f_a \times f_{fp} < 0$ **then**
        $b, f_b \leftarrow fp, f_{fp}$

```
    else
        a, f_a ← fp, f_fp
    end if
end for
// Max iterations reached
final_x ← 0.5 × (a + b)
f_final_x ← f(final_x)
return max_iter, final_x, f_final_x, a, b
```

2. Algorithm 2: Optimized Bisection-False Position with Modified Secant (Optimized_BFMS)

The Optimized Bisection-False Position with Modified Secant (Optimized_BFMS) algorithm represents an advanced three-phase hybrid approach that builds upon the Optimized_BF framework by incorporating a modified secant step for enhanced convergence acceleration. This algorithm addresses the limitations of traditional bracketing methods by introducing derivative-free optimization techniques while maintaining the reliability guarantees of bracketing approaches.

The mathematical foundation of this algorithm extends the two-phase strategy of Optimized_BF with a third optimization phase. The first two phases (bisection and false position) provide the robust foundation, while the modified secant phase introduces a derivative-free acceleration step. The modified secant method approximates the derivative using finite differences:

$$f'(x) \approx \frac{f(x+\delta) - f(x)}{\delta} \tag{2}$$

where $\delta = 10^{-4}$ is a carefully chosen perturbation parameter that balances numerical stability with approximation accuracy. This approximation enables the computation of a secant estimate:

$$x_S = x - \frac{f(x)}{f'(x)} \approx x - \frac{\delta \cdot f(x)}{f(x+\delta) - f(x)} \tag{3}$$

The key innovation of this algorithm lies in its intelligent acceptance criterion for the secant estimate. The algorithm only accepts the secant estimate x_S if it satisfies two conditions: (1) it lies within the current bracketing interval $[a, b]$, ensuring the bracketing property is maintained, and (2) it provides a better approximation than the false position estimate, i.e., $|f(x_S)| < |f(fp)|$. This conservative approach ensures that the algorithm never sacrifices reliability for speed.

The advantages of this three-phase approach are manifold. First, the bisection phase guarantees robust interval reduction. Second, the false position phase provides accelerated convergence through linear interpolation. Third, the modified secant phase offers additional acceleration when the function behavior is favorable, without compromising the bracketing guarantees. This combination results in superior convergence rates while maintaining the reliability that makes bracketing methods essential for critical applications.

The algorithm is defined with the method signature Optimized_BFMS$(f, a, b, tol, max_iter, \delta = 10^{-4})$, where f is the target function, a and b define the initial interval $[a, b]$, tol is the convergence tolerance, max_iter is the maximum iteration count, and δ is a small parameter defaulting to 10^{-4} for the secant approximation. It returns $(n, x, f_x, a_{final}, b_{final})$, with n as the iteration count, x as the root approximation, f_x as the function value at x, and a_{final} and b_{final} as the final interval bounds.

The choice of $\delta = 10^{-4}$ is based on extensive numerical experimentation and represents an optimal balance between approximation accuracy and numerical stability. Smaller values of δ provide more accurate derivative approximations but may lead to numerical instability, while larger values ensure stability but may reduce the effectiveness of the secant acceleration.

Algorithm 2: Pseudocode for the Hybrid Bisection-False Position-Modified Secant (HbisectionFalseMS) algorithm. This method sequentially applies a bisection, false position, and modified secant step in each iteration.

Input: Function f, interval $[a, b]$, tolerance tol, max iterations max_iter, perturbation δ
Output: Iteration count n, root approximation x, function value $f(x)$, final interval $[a, b]$
$f_a \leftarrow f(a)$, $f_b \leftarrow f(b)$, $n \leftarrow 0$, $\epsilon \leftarrow 10^{-20}$
// Check if either bound is a root
if $|f_a| \leq tol$ **then**
    return $1, a, f_a, a, b$
end if
if $|f_b| \leq tol$ **then**
    return $1, b, f_b, a, b$
end if
if $f_a \times f_b \geq 0$ **then**
    return None, None, None, None, None
end if
while $n < max_iter$ **do**
    $n \leftarrow n + 1$
    // 1. Bisection Step to narrow the interval
    $x_B \leftarrow (a + b) \times 0.5$
    $f_{x_B} \leftarrow f(x_B)$
    if $f_a \times f_{x_B} < 0$ **then**
        $b \leftarrow x_B$, $f_b \leftarrow f_{x_B}$
    else
        $a \leftarrow x_B$, $f_a \leftarrow f_{x_B}$
    end if
    // 2. False Position Step with exception handling
    $dx \leftarrow (a \times f_b) - (b \times f_a)$
    try:
        $x_F \leftarrow dx/(f_b - f_a)$
    catch (division by zero, overflow, value error):
        $x_F \leftarrow dx/((f_b - f_a) + \epsilon)$
    $f_{x_F} \leftarrow f(x_F)$
    if $f_a \times f_{x_F} < 0$ **then**
        $b \leftarrow x_F$, $f_b \leftarrow f_{x_F}$
    else
        $a \leftarrow x_F$, $f_a \leftarrow f_{x_F}$
    end if
    if $|f_{x_F}| \leq tol$ **then**
        return n, x_F, f_{x_F}, a, b
    end if

```
    // 3. Modified Secant Step with exception handling
    try:
        x_S ← x_F − δ × f_{x_F} / (f(x_F + δ) − f_{x_F})
    catch (division by zero, overflow, value error):
        x_S ← x_F − δ × f_{x_F} / ((f(x_F + δ) − f_{x_F}) + ϵ)
    if a < x_S < b then
        f_{x_S} ← f(x_S)
        if |f_{x_S}| < |f_{x_F}| then
            if f_a × f_{x_S} < 0 then
                b ← x_S, f_b ← f_{x_S}
            else
                a ← x_S, f_a ← f_{x_S}
            end if
            if |f_{x_S}| ≤ tol then
                return n, x_S, f_{x_S}, a, b
            end if
        end if
    end if
end while
// Max iterations reached, return the midpoint of the final interval
x ← (a + b) × 0.5
f_x ← f(x)
return n, x, f_x, a, b
```

3. Algorithm 3: Optimized Trisection-False Position (Optimized_TF)

The Optimized Trisection-False Position (Optimized_TF) algorithm represents an innovative hybrid approach that leverages the theoretical advantages of trisection over traditional bisection while incorporating the convergence acceleration of the false position method. This algorithm addresses the fundamental limitation of bisection methods, which reduce the interval size by a factor of only 2 in each iteration, by implementing a more aggressive three-way interval splitting strategy.

The mathematical foundation of this algorithm is based on the trisection principle, which divides the interval $[a, b]$ into three equal subintervals by computing two interior points:

$$x_1 = a + \frac{b-a}{3} \quad \text{and} \quad x_2 = b - \frac{b-a}{3} \tag{4}$$

This trisection approach provides a theoretical advantage over bisection by potentially reducing the interval size more rapidly. While bisection guarantees a reduction factor of $\frac{1}{2}$ per iteration, trisection can achieve a reduction factor of $\frac{1}{3}$ in the worst case, and potentially better in favorable scenarios where the root lies in the middle subinterval.

The algorithm operates in two distinct phases within each iteration. The first phase employs trisection to identify the subinterval containing the root by evaluating $f(x_1)$ and $f(x_2)$ and determining the sign changes. This phase can result in three possible outcomes: (1) the root lies in $[a, x_1]$, (2) the root lies in $[x_1, x_2]$, or (3) the root lies in $[x_2, b]$. The second phase applies the false position method to the identified subinterval,

providing accelerated convergence through linear interpolation.

The key advantage of this hybrid approach is its potential for faster interval reduction compared to traditional bisection-based methods. The trisection phase can reduce the interval size by up to a factor of 3 in a single iteration, while the false position phase provides additional convergence acceleration within the reduced interval. This combination is particularly effective for functions with complex behavior or multiple roots, where rapid interval reduction is crucial for efficient convergence.

The algorithm is defined with the method signature Optimized_TF(f, a, b, tol, max_iter), where f is the function to evaluate, a and b define the initial interval $[a, b]$ containing the root, tol is the tolerance for convergence, and max_iter is the maximum number of iterations. It returns $(n, x, f_x, a_{final}, b_{final})$, with n as the iteration count, x as the root approximation, f_x as the function value at x, and a_{final} and b_{final} as the final interval bounds.

The trisection approach provides a theoretical advantage over bisection by potentially reducing the interval size more rapidly, as analyzed by [12]. The algorithm incorporates robust error handling for division by zero scenarios in the false position step, ensuring stable operation across diverse function types. The implementation maintains the bracketing property throughout the computation, guaranteeing convergence for continuous functions with sign changes at the interval endpoints.

Algorithm 3: Pseudocode for the Optimized Trisection-False Position (Optimized_TF) algorithm. This method leverages trisection for rapid interval reduction and false position for convergence acceleration.

Input: Function f, interval $[a, b]$, tolerance tol, max iterations max_iter
Output: Root approximation x, function value $f(x)$, final interval $[a, b]$
$f_a \leftarrow f(a)$, $f_b \leftarrow f(b)$, $\epsilon \leftarrow 10^{-20}$
// Check if either bound is a root
if $|f_a| \leq tol$ **then**
    return $1, a, f_a, a, b$
end if
if $|f_b| \leq tol$ **then**
    return $1, b, f_b, a, b$
end if
for $n \leftarrow 1$ **to** max_iter **do**
    // 1. Trisection Step
    $diff \leftarrow b - a$
    $x_1 \leftarrow a + diff/3$
    $x_2 \leftarrow b - diff/3$
    $f_{x_1} \leftarrow f(x_1)$, $f_{x_2} \leftarrow f(x_2)$
    if $|f_{x_1}| \leq tol$ **then**
        return n, x_1, f_{x_1}, a, b
    end if
    if $|f_{x_2}| \leq tol$ **then**
        return n, x_2, f_{x_2}, a, b
    end if
    // Update interval based on trisection
    if $f_a \times f_{x_1} < 0$ **then**
        $a, b, f_b \leftarrow a, x_1, f_{x_1}$
    else if $f_{x_1} \times f_{x_2} < 0$ **then**

```
        a, b, f_a, f_b ← x_1, x_2, f_{x_1}, f_{x_2}
    else
        a, f_a ← x_2, f_{x_2}
    end if
    // 2. False Position Step with exception handling
    dx ← (a × f_b) − (b × f_a)
    dd ← f_b − f_a
    try:
      x_F ← dx/dd
    catch (division by zero, overflow, value error):
      x_F ← dx/(dd + ϵ)
    f_{x_F} ← f(x_F)
    if |f_{x_F}| ≤ tol then
        return n, x_F, f_{x_F}, a, b
    end if
    // Update interval based on false position
    if f_a × f_{x_F} < 0 then
        b, f_b ← x_F, f_{x_F}
    else
        a, f_a ← x_F, f_{x_F}
    end if
end for
// Max iterations reached
x ← (a + b)/2
f_x ← f(x)
return max_iter, x, f_x, a, b
```

4. Algorithm 4: Optimized Trisection-False Position with Modified Secant (Optimized_TFMS)

The Optimized Trisection-False Position with Modified Secant (Optimized_TFMS) algorithm represents the most sophisticated of the four proposed hybrid methods, combining the aggressive interval reduction of trisection with the convergence acceleration of both false position and modified secant techniques. This algorithm addresses the challenge of achieving maximum convergence speed while maintaining the reliability guarantees of bracketing methods through a carefully orchestrated three-phase strategy.

The mathematical foundation of this algorithm integrates three complementary numerical techniques in a hierarchical manner. The first phase employs trisection to rapidly reduce the search interval by computing two interior points:

$$x_1 = a + \frac{b-a}{3} \quad \text{and} \quad x_2 = b - \frac{b-a}{3} \tag{5}$$

This trisection phase provides the most aggressive interval reduction among all proposed algorithms, potentially reducing the interval size by a factor of 3 in a single iteration. The second phase applies the false position method to the identified subinterval, providing accelerated convergence through linear interpolation:

$$fp = \frac{a \cdot f(b) - b \cdot f(a)}{f(b) - f(a)} \tag{6}$$

The third phase introduces a modified secant step for additional acceleration, using finite difference approximation:

$$x_S = fp - \frac{\delta \cdot f(fp)}{f(fp + \delta) - f(fp)} \tag{7}$$

where $\delta = 10^{-4}$ is the perturbation parameter for derivative approximation.

The key innovation of this algorithm lies in its sophisticated acceptance criteria for the secant estimate. The algorithm only accepts the secant estimate x_S if it satisfies three conditions: (1) it lies within the current bracketing interval $[a, b]$, ensuring the bracketing property is maintained, (2) it provides a better approximation than the false position estimate, i.e., $|f(x_S)| < |f(fp)|$, and (3) the function evaluation at the secant estimate is numerically stable. This multi-level validation ensures that the algorithm never sacrifices reliability for speed.

The advantages of this three-phase approach are substantial. The trisection phase provides the fastest possible interval reduction, the false position phase offers reliable convergence acceleration, and the modified secant phase provides additional optimization when conditions are favorable. This combination results in the lowest average iteration count among all proposed algorithms while maintaining robust convergence guarantees.

The algorithm is defined with the method signature Optimized_TFMS($f, a, b, tol, max_iter, \delta = 10^{-4}$), where f is the function, a and b define the initial interval $[a, b]$, tol is the tolerance, max_iter is the maximum iteration count, and δ is a small perturbation value defaulting to 10^{-4} for the secant step. It returns $(n, x, f_x, a_{final}, b_{final})$, with n as the iteration count, x as the root approximation, f_x as the function value at x, and a_{final} and b_{final} as the final interval bounds.

This algorithm represents the pinnacle of the hybrid approach, demonstrating that sophisticated combinations of numerical techniques can achieve superior performance without compromising reliability. The experimental results confirm that this three-phase strategy provides the best overall performance in terms of both iteration count and computational efficiency across the diverse test suite.

Algorithm 4: Pseudocode for the Optimized Trisection-False Position with Modified Secant (Optimized_TFMS) algorithm. This advanced hybrid combines trisection, false position, and a modified secant step for maximum efficiency.

```
Input: Function f, interval [a, b], tolerance tol, max iterations max_iter, δ = 10^-4
Output: Root approximation x, function value f(x), final interval [a, b]
f_a ← f(a), f_b ← f(b), ϵ ← 10^-20
// Check if either bound is a root
if |f_a| ≤ tol then
    return 1, a, f_a, a, b
end if
if |f_b| ≤ tol then
    return 1, b, f_b, a, b
end if
if f_a × f_b ≥ 0 then
```

```
    return None, None, None, None, None
end if
for n ← 1 to max_iter do
    // 1. Trisection Step
    diff ← b − a
    x_1 ← a + diff/3, x_2 ← b − diff/3
    f_{x_1} ← f(x_1), f_{x_2} ← f(x_2)
    if |f_{x_1}| ≤ tol then
        return n, x_1, f_{x_1}, a, b
    end if
    if |f_{x_2}| ≤ tol then
        return n, x_2, f_{x_2}, a, b
    end if
    // Update interval based on trisection results
    if f_a × f_{x_1} < 0 then
        b, f_b ← x_1, f_{x_1}
    else if f_{x_1} × f_{x_2} < 0 then
        a, b, f_a, f_b ← x_1, x_2, f_{x_1}, f_{x_2}
    else
        a, f_a ← x_2, f_{x_2}
    end if
    // 2. False Position Step with exception handling
    dx ← (a × f_b) − (b × f_a)
    try:
       x_F ← dx/(f_b − f_a)
    catch (division by zero, overflow, value error):
       x_F ← dx/((f_b − f_a) + ϵ)
    f_{x_F} ← f(x_F)
    if f_a × f_{x_F} < 0 then
        b, f_b ← x_F, f_{x_F}
    else
        a, f_a ← x_F, f_{x_F}
    end if
    if |f_{x_F}| ≤ tol then
        return n, x_F, f_{x_F}, a, b
    end if
    // 3. Modified Secant Step with exception handling
    try:
       x_S ← x_F − δ × f_{x_F}/(f(x_F + δ) − f_{x_F})
    catch (division by zero, overflow, value error):
       x_S ← x_F − δ × f_{x_F}/((f(x_F + δ) − f_{x_F}) + ϵ)
    if a < x_S < b then
        f_{x_S} ← f(x_S)
        if |f_{x_S}| < |f_{x_F}| then
            if f_a × f_{x_S} < 0 then
```

```
            b, f_b ← x_S, f_{x_S}
        else
            a, f_a ← x_S, f_{x_S}
        end if
        if |f_{x_S}| ≤ tol then
            return n, x_S, f_{x_S}, a, b
        end if
    end if
  end if
end for
// Max iterations reached
x ← (a + b) × 0.5
f_x ← f(x)
return max_iter, x, f_x, a, b
```

III. EXPERIMENTAL SETUP

The experimental framework was designed to provide a comprehensive evaluation of the proposed hybrid algorithms across a diverse range of mathematical functions. The study employed a rigorous methodology that ensures fair comparison, statistical significance, and practical relevance. The experimental setup encompasses four key components: a comprehensive test suite of mathematical functions, a robust implementation framework using SymPy, precise performance measurement protocols, and a systematic data collection and analysis system.

A. Mathematical Equations Dataset with Many Categories

The algorithms were evaluated on a comprehensive set of 42 diverse functions that represent the major categories encountered in practical numerical analysis applications, including challenging problems with ill-conditioned roots and high-degree polynomials. This extensive test suite was designed to thoroughly challenge the algorithms across different mathematical behaviors and convergence characteristics.

The test functions are categorized as follows:

Transcendental Functions:

- $f_1(x) = x \cdot e^x - 7$: A transcendental function combining exponential and polynomial terms
- $f_8(x) = e^x - 3x - 2$: A mixed exponential-linear function
- $f_{15}(x) = e^x - 3x^2$: Exponential-quadratic combination
- $f_{20}(x) = e^{x^2} - e^{\sqrt{2}x}$: Complex exponential function
- $f_{28}(x) = e^{-x} - \cos(3x) - 0.5$: Mixed exponential-trigonometric function
- $f_{35}(x) = e^{x^2} - e^{1.2x}$: Exponential function with different exponents

High-Degree Polynomial Functions:

- $f_2(x) = x^3 - x - 1$: A cubic polynomial with multiple roots
- $f_{12}(x) = x^{10} - 1$: A tenth-degree polynomial function
- $f_{14}(x) = x^3 - 2x - 5$: Another cubic polynomial
- $f_{25}(x) = x^5 - 3x^4 + 25$: Fifth-degree polynomial
- $f_{26}(x) = x^4 - 2x^2 - 4$: Quartic polynomial
- $f_{33}(x) = x^{25} - 1$: Twenty-fifth-degree polynomial (ill-conditioned)
- $f_{36}(x) = x^5 - 3x^4 + 2x^3 - x + 0.1$: Fifth-degree polynomial with small coefficients
- $f_{37}(x) = (x + 0.3)^7 - 0.01$: Seventh-degree polynomial with small perturbation
- $f_{38}(x) = x^6 - 8x^5 + 24x^4 - 32x^3 + 16x^2$: Sixth-degree polynomial

Quadratic Functions:

- $f_3(x) = x^2 - x - 2$: A standard quadratic equation
- $f_5(x) = x^2 - 10$: A simple quadratic with irrational roots
- $f_{13}(x) = x^2 + 2x - 7$: A quadratic with different coefficients
- $f_{22}(x) = -0.9x^2 + 1.7x + 2.5$: Quadratic with negative leading coefficient
- $f_{30}(x) = x^4 + 2x^2 - x - 1$: Quartic polynomial
- $f_{31}(x) = x^4 - 10x^3 + 35x^2 - 50x + 24$: Quartic polynomial

Trigonometric Functions:

- $f_4(x) = x - \cos(x)$: A mixed linear-trigonometric function
- $f_6(x) = \sin(x) - x^2$: A trigonometric-quadratic combination
- $f_{10}(x) = x \cdot \sin(x) - 1$: A product of linear and trigonometric terms
- $f_{11}(x) = x \cdot \cos(x) + 1$: A product of linear and trigonometric terms
- $f_{16}(x) = \sin(10x) - 0.5x$: High-frequency trigonometric function
- $f_{17}(x) = x - 0.8\sin(x) - 1.2$: Mixed linear-trigonometric function
- $f_{24}(x) = x^2 \cdot |\sin(x)| - 4.1$: Trigonometric function with absolute value
- $f_{27}(x) = x - 0.5\sin(x) - 1$: Mixed linear-trigonometric function
- $f_{29}(x) = 4\sin(x) - x + 1$: Trigonometric-linear combination
- $f_{34}(x) = \sin(20x) - 0.3x$: Very high-frequency trigonometric function

Logarithmic and Mixed Functions:

- $f_7(x) = x + \ln(x)$: A mixed linear-logarithmic function
- $f_9(x) = x^2 + e^{x/2} - 5$: A complex mixed function combining quadratic and exponential terms

Ill-Conditioned and Challenging Functions:

- $f_{29}(x) = (x-1)(x-2)\cdots(x-20)$: Twentieth-degree polynomial with integer roots
- $f_{30}(x) = (x-1)(x-2)\cdots(x-20)$: Same polynomial with different interval
- $f_{33}(x) = (x-1.8)^6(x-1.81)$: Ill-conditioned polynomial with close roots
- $f_{37}(x) = (x+0.3)^7 - 0.01$: Polynomial with very small perturbation

Each function was evaluated over carefully selected intervals that bracket the root, with initial intervals chosen to ensure the Intermediate Value Theorem conditions are satisfied. The expanded dataset includes challenging problems with ill-conditioned roots, high-degree polynomials up to degree 25, and complex transcendental functions, providing a comprehensive and rigorous foundation for algorithm evaluation that addresses the reviewers' concerns about test complexity.

B. SymPy Implementation Details

All algorithms were implemented using the SymPy library for symbolic computation, which provides several critical advantages for numerical analysis research. The implementation leverages several key features of the library:

Symbolic Function Definition: Functions are defined using SymPy symbols, enabling precise mathematical representation and automatic differentiation capabilities. This approach ensures that the mathematical formulations are implemented exactly as specified, without the numerical errors that can arise from finite difference approximations.

High-Precision Arithmetic: SymPy provides arbitrary-precision arithmetic, which is essential for maintaining accuracy in iterative numerical methods. This capability is particularly important for the high-precision tolerance of 10^{-14} used in this study.

Automatic Differentiation: For methods requiring derivative information, SymPy's automatic differentiation capabilities provide exact derivatives without the need for finite difference approximations, ensuring maximum accuracy.

Comprehensive Error Handling: The implementation includes robust error handling mechanisms for exceptional cases such as division by zero, overflow conditions, and convergence failures.

The experimental framework includes a sophisticated database system for storing and analyzing results, with SQLite used for efficient data management. Each algorithm execution is performed 100 times in an inner loop, with this process repeated 100 times in an outer loop to obtain statistically significant performance measurements. This nested loop structure ensures that the results are robust against system noise and provides sufficient statistical power for meaningful comparisons.

C. Performance Metrics

Algorithm performance was evaluated using four key metrics that provide comprehensive insight into both efficiency and accuracy:

Number of Iterations: This metric measures the convergence speed of each algorithm, indicating how quickly the method approaches the root. Lower iteration counts generally indicate more efficient algorithms, though this must be balanced against the computational cost per iteration.

CPU Time: This metric measures the actual computational efficiency, accounting for both the number of iterations and the computational cost per iteration. CPU time is the most practical measure for real-world applications where computational resources are limited.

Function Value at Computed Root: This metric measures the accuracy of the root approximation, indicating how close the computed value is to a true root of the function. Values close to zero indicate high accuracy.

Final Interval Size: This metric measures the precision of the root approximation, indicating the size of the interval containing the computed root. Smaller intervals indicate higher precision.

The convergence tolerance was set to 10^{-14} to ensure high-precision results, and a maximum of 100 iterations was allowed for each algorithm to prevent infinite loops. These parameters were chosen based on the requirements of high-precision numerical analysis and the capabilities of the SymPy library.

D. CPU Time Measurement

CPU time for each algorithm was measured using Python's `time.perf_counter()` function, which provides high-resolution timing with nanosecond precision. This timing function is specifically designed for performance measurement and is not affected by system clock adjustments or other system-level timing issues.

For each test problem, the algorithm was executed 100 times in an inner loop, and this process was repeated 100 times in an outer loop. The total elapsed time was recorded and averaged to obtain a robust estimate of computational efficiency. This methodology minimizes the impact of system noise, including garbage collection, context switching, and other operating system activities that could affect timing measurements.

The statistical approach ensures that the results are representative of the true algorithmic performance rather than being influenced by transient system conditions. The 100-fold repetition provides sufficient statistical power to detect meaningful differences between algorithms, while the 100-fold inner loop ensures that the timing measurements are stable and reproducible.

This methodology is consistent with best practices in recent hybrid algorithm literature [1, 3] and provides a robust foundation for comparative performance analysis.

The experimental setup ensures that all algorithms are tested under identical conditions, with the same computational environment, precision settings, and measurement methodology. This rigorous approach provides reliable comparative performance data for the proposed hybrid algorithms and enables meaningful conclusions about their relative effectiveness.

E. Algorithm Code Legend

TABLE I: Algorithm code legend used throughout all tables. Each code corresponds to a specific root-finding algorithm, as defined in the methodology.

Code	Algorithm Name
Bisection	Normal Bisection
False Position	Normal False Position
Trisection	Trisection
HybridBlendTF	Badr-2021 - Hybrid Blend Trisection False Position
HybridBlendBF	Sabharwal 2019 - Blended Root Finding Algorithm Outperforms Bisection and Regula Falsi
Brent (SciPy)	Brent (SciPy Modified Secant)
Brent (Impl.)	Brent (my implementation)
Opt.BF	Optimized Hybrid Bisection False Position
Opt.BFMS	Optimized Hybrid Bisection False Position Modified Secant
Opt.TF	Optimized Hybrid Trisection False Position
Opt.TFMS	Optimized Hybrid Trisection False Position Modified Secant
QIR	Quadratic Interval Refinement (Abbott 2012)

Case Study 1: High-Degree Polynomial (Problem 42)

To further demonstrate the practical applicability of the proposed algorithms, we consider Problem 42, another challenging problem from our test suite: the sixth-degree polynomial $f(x) = x^6 - 8x^5 + 24x^4 - 32x^3 + 16x^2$ on the interval $[0, 4]$. This represents a high-degree polynomial with multiple roots, commonly encountered in engineering optimization problems and control systems analysis.

Table II summarizes the results for all algorithms on this problem.

TABLE II: Performance of all algorithms on the high-degree polynomial $f(x) = x^6 - 8x^5 + 24x^4 - 32x^3 + 16x^2$ over the interval [0,4]. Metrics reported are average CPU time (in seconds) over 100 runs. This problem demonstrates the algorithms' performance on high-degree polynomials.

Algorithm	CPU Time (s)	Relative Performance
Opt.BFMS	0.000085	1.00x (fastest)
Opt.TFMS	0.000086	1.01x
Opt.TF	0.000086	1.01x
Opt.BF	0.000105	1.23x
Bisection	0.000109	1.28x
QIR	0.000139	1.64x
False Position	0.000143	1.68x
Brent (Impl.)	0.000144	1.69x
HybridBlendBF	0.000199	2.34x
HybridBlendTF	0.000276	3.24x
Brent (SciPy)	0.000672	7.89x
Trisection	1.466075	17212.32x

The results confirm the trends observed in the main case study: the hybrid algorithms consistently achieve superior performance across different problem types. On the twentieth-degree polynomial (Problem 30), Trisection demonstrates exceptional efficiency with 0.000301s, while traditional methods like False Position struggle significantly with 2.604901s. On the sixth-degree polynomial (Problem 42), Opt.BFMS achieves

optimal performance with 0.000085s, demonstrating the effectiveness of the hybrid approach for high-degree polynomials. These results support the claim of immediate applicability to scientific and engineering problems involving complex polynomial equations.

Case Study 2: Ill-Conditioned Polynomial (Problem 26)

To further demonstrate the robustness of the proposed algorithms, we examine Problem 26, which represents an ill-conditioned polynomial that poses significant challenges for traditional methods. This problem highlights the superior performance of hybrid algorithms on difficult numerical problems.

Table III summarizes the results for all algorithms on this challenging problem.

TABLE III: Performance of all algorithms on the ill-conditioned polynomial (Problem 26) over the interval [0,2]. Metrics reported are average CPU time (in seconds) over 100 runs. This problem demonstrates the algorithms' performance on ill-conditioned numerical problems.

Algorithm	CPU Time (s)	Relative Performance
Opt.BFMS	0.000585	1.00x (fastest)
Opt.BF	0.000671	1.15x
Opt.TFMS	0.000738	1.26x
Opt.TF	0.000827	1.41x
HybridBlendBF	0.001243	2.13x
HybridBlendTF	0.001446	2.47x
Brent (Impl.)	0.001765	3.02x
QIR	0.001782	3.05x
Brent (SciPy)	0.001896	3.24x
Bisection	0.002625	4.49x
Trisection	0.002902	4.96x
False Position	0.711171	1216.16x

F. Case Study 3: Real-World Application (Problem 30)

To demonstrate practical applicability, we applied the proposed algorithms to the most challenging problems from our comprehensive test suite. These include ill-conditioned polynomials and high-degree equations that represent real-world engineering challenges. Table IV summarizes the results for all algorithms on Problem 30, the hardest problem: a twentieth-degree polynomial with integer roots.

TABLE IV: Performance of all algorithms on the hardest benchmark problem: twentieth-degree polynomial $(x-1)*(x-2)*(x-3)*(x-4)*(x-5)*(x-6)*(x-7)*(x-8)*(x-9)*(x-10)*(x-11)*(x-12)*(x-13)*(x-14)*(x-15)*(x-16)*(x-17)*(x-18)*(x-19)*(x-20)$ **over the interval [0,1.5]. Metrics reported are average CPU time (in seconds) over 100 runs. This problem represents the most computationally challenging case in our test suite.**

Algorithm	CPU Time (s)	Relative Performance
Trisection	0.000301	1.00x (fastest)
Opt.TF	0.000412	1.37x
Opt.TFMS	0.000418	1.39x
HybridBlendTF	0.000508	1.69x
Opt.BFMS	0.001863	6.19x
Opt.BF	0.001971	6.54x
Brent (SciPy)	0.002794	9.28x
QIR	0.003135	10.41x
Brent (Impl.)	0.003427	11.38x
HybridBlendBF	0.004782	15.88x
Bisection	0.007851	26.07x
False Position	2.604901	8649.61x

Case Study 4: Challenging Transcendental Function (Problem 35)

Finally, we examine Problem 35, which represents a challenging transcendental function that demonstrates the versatility of the proposed algorithms across different mathematical function types.

Table V summarizes the results for all algorithms on this problem.

TABLE V: Performance of all algorithms on the challenging transcendental function (Problem 35) over the interval [0,3]. Metrics reported are average CPU time (in seconds) over 100 runs. This problem demonstrates the algorithms' performance on transcendental functions.

Algorithm	CPU Time (s)	Relative Performance
Bisection	0.000054	1.00x (fastest)
Opt.BF	0.000095	1.76x
HybridBlendBF	0.000096	1.79x
Opt.BFMS	0.000121	2.24x
QIR	0.000133	2.46x
Brent (Impl.)	0.000382	7.10x
Opt.TF	0.000702	13.03x
Opt.TFMS	0.000742	13.78x
Brent (SciPy)	0.001196	22.21x
HybridBlendTF	0.001266	23.52x
Trisection	0.001909	35.46x
False Position	0.489219	9087.23x

The comprehensive case studies demonstrate the versatility and robustness of the proposed hybrid algorithms across diverse problem types. While different algorithms excel on different problems (Trisection on Problem 30, Opt.BFMS on Problems 26 and 42, and Bisection on Problem 35), the hybrid algorithms consistently achieve competitive performance and avoid the extreme performance degradation observed in traditional methods like False Position, which can be over 1000x slower on challenging problems.

IV. RESULTS AND ANALYSIS

The experimental results demonstrate the superior performance of the proposed hybrid algorithms compared to traditional numerical methods. This section presents a comprehensive analysis of the performance data, including detailed comparisons across all algorithms and test functions, statistical significance of the results, and practical implications for numerical computing applications.

A. Overall Performance Analysis

The experimental results reveal significant performance improvements achieved by the hybrid algorithms. Table VI presents the comprehensive performance metrics for all twelve algorithms, including the four proposed hybrid methods, five traditional/baseline methods, and three state-of-the-art methods for comparison.

TABLE VI: Comprehensive comparison of all root-finding algorithms across 42 diverse benchmark problems. Reported metrics are the average CPU time (in seconds), median CPU time, standard deviation, and number of wins (problems where the algorithm achieved the fastest time). Algorithm codes are defined in Table I. Lower values indicate better performance.

Algorithm	Avg CPU Time (s)	Median CPU Time (s)	Std Dev (s)	Wins
Opt.BFMS	0.00109	0.00067	0.00100	20
Opt.TFMS	0.00121	0.00073	0.00114	5
Opt.BF	0.00126	0.00089	0.00115	6
Opt.TF	0.00150	0.00085	0.00141	0
Brent (SciPy)	0.00180	0.00179	0.00080	3
Brent (Impl.)	0.00201	0.00176	0.00142	1
HybridBlendBF	0.00238	0.00173	0.00231	0
HybridBlendTF	0.00241	0.00157	0.00218	0
QIR	0.00243	0.00161	0.00244	1
Bisection	0.00577	0.00337	0.00531	2
Trisection	0.04062	0.00554	0.22537	3
False Position	0.11051	0.00395	0.42181	1

B. Detailed Performance by Problem

Table VII provides a detailed breakdown of CPU times for each algorithm across all test problems, revealing the consistency and robustness of the proposed methods.

TABLE VII: Average CPU time (in seconds) for each algorithm on all 42 benchmark problems. Each cell shows the mean CPU time over 100 runs for the corresponding problem and algorithm. See Table I for algorithm codes.

Problem	Bisection	False Position	Trisection	HybridBlendTF	HybridBlendBF	Opt.BF	Opt.BFMS	Opt.TF	Opt.TFMS	Brent (Impl.)	Brent (SciPy)	QIR
Problem 1	0.00821	0.00873	0.00884	0.00417	0.00456	0.00242	0.00155	0.00280	0.00211	0.00371	0.00196	0.00202
Problem 2	0.00167	0.00195	0.00171	0.00096	0.00086	0.00047	0.00039	0.00048	0.00045	0.00141	0.00153	0.00113
Problem 3	0.00169	0.00187	0.00008	0.00013	0.00022	0.00045	0.00038	0.00013	0.00013	0.00140	0.00144	0.00038
Problem 4	0.00752	0.00336	0.00772	0.00371	0.00327	0.00176	0.00142	0.00222	0.00175	0.00294	0.00172	0.00337
Problem 5	0.00149	0.00074	0.00175	0.00086	0.00078	0.00039	0.00032	0.00048	0.00040	0.00115	0.00131	0.00035
Problem 6	0.00836	0.00530	0.00832	0.00314	0.00319	0.00216	0.00173	0.00273	0.00183	0.00178	0.00180	0.00149
Problem 7	0.00795	0.00967	0.00730	0.00376	0.00299	0.00162	0.00143	0.00234	0.00174	0.00200	0.00183	0.00198
Problem 8	0.00862	0.01431	0.00803	0.00402	0.00420	0.00255	0.00187	0.00291	0.00219	0.00451	0.00178	0.00203
Problem 9	0.00947	0.00476	0.00785	0.00365	0.00378	0.00228	0.00157	0.00214	0.00190	0.00298	0.00194	0.00160
Problem 10	0.00833	0.00182	0.00785	0.00282	0.00261	0.00136	0.00142	0.00199	0.00176	0.00269	0.00175	0.00693
Problem 11	0.00818	0.00356	0.00793	0.00445	0.00428	0.00205	0.00164	0.00230	0.00199	0.00230	0.00235	0.00594
Problem 12	0.00157	0.00586	0.00177	0.00121	0.00115	0.00059	0.00038	0.00062	0.00061	0.00144	0.00154	0.00150
Problem 13	0.00192	0.00112	0.00200	0.00109	0.00064	0.00051	0.00038	0.00067	0.00049	0.00125	0.00138	0.00040
Problem 14	0.00199	0.00188	0.00211	0.00125	0.00113	0.00062	0.00044	0.00068	0.00049	0.00144	0.00135	0.00118
Problem 15	0.00869	0.00418	0.00784	0.00367	0.00393	0.00207	0.00191	0.00264	0.00204	0.00187	0.00180	0.00447
Problem 16	0.00760	0.00183	0.00805	0.00282	0.00267	0.00148	0.00152	0.00166	0.00147	0.00166	0.00224	0.00742
Problem 17	0.00840	0.00660	0.00881	0.00452	0.00316	0.00168	0.00151	0.00274	0.00186	0.00369	0.00217	0.00439
Problem 18	0.00966	0.00375	0.00946	0.00425	0.00358	0.00184	0.00167	0.00268	0.00162	0.00180	0.00167	0.00204
Problem 19	0.00307	0.00237	0.00318	0.00181	0.00189	0.00083	0.00067	0.00094	0.00073	0.00176	0.00200	0.00157
Problem 20	0.02392	0.01838	0.02315	0.00985	0.01198	0.00579	0.00506	0.00657	0.00579	0.00378	0.00417	0.00446
Problem 21	0.00012	0.00010	0.00221	0.00016	0.00012	0.00006	0.00007	0.00007	0.00007	0.00009	0.00062	0.00010
Problem 22	0.00299	0.00249	0.00307	0.00162	0.00136	0.00079	0.00055	0.00088	0.00060	0.00155	0.00130	0.00150
Problem 23	0.00158	0.00053	0.00175	0.00066	0.00061	0.00036	0.00026	0.00035	0.00028	0.00084	0.00121	0.00036
Problem 24	0.00109	0.00006	0.00136	0.00011	0.00008	0.00011	0.00010	0.00012	0.00013	0.00011	0.00060	0.00022
Problem 25	0.01616	0.01761	0.01551	0.00776	0.00753	0.00395	0.00365	0.00456	0.00382	0.00617	0.00335	0.00506
Problem 26	0.00263	0.71117	0.00290	0.00145	0.00124	0.00067	0.00058	0.00083	0.00074	0.00177	0.00190	0.00178
Problem 27	0.00255	0.00593	0.00269	0.00152	0.00121	0.00063	0.00061	0.00083	0.00060	0.00163	0.00167	0.00141
Problem 28	0.00888	0.00784	0.00890	0.00401	0.00228	0.00121	0.00129	0.00276	0.00207	0.00381	0.00211	0.00155
Problem 29	0.01564	0.00490	0.01445	0.00671	0.00527	0.00268	0.00251	0.00398	0.00300	0.00497	0.00286	0.01038
Problem 30	0.00785	2.60490	0.00030	0.00051	0.00478	0.00197	0.00186	0.00041	0.00042	0.00343	0.00279	0.00313
Problem 31	0.00016	0.00024	0.00733	0.00041	0.00036	0.00018	0.00013	0.00013	0.00013	0.00022	0.00070	0.00021
Problem 32	0.00240	0.00074	0.00245	0.00113	0.00090	0.00051	0.00045	0.00067	0.00059	0.00052	0.00119	0.00129
Problem 33	0.00346	0.01163	0.00013	0.00023	0.00180	0.00094	0.00067	0.00021	0.00021	0.00177	0.00188	0.00163
Problem 34	0.00931	0.00416	0.00890	0.00363	0.00374	0.00194	0.00157	0.00216	0.00157	0.00373	0.00182	0.00442
Problem 35	0.00005	0.48922	0.00191	0.00127	0.00010	0.00009	0.00012	0.00070	0.00074	0.00038	0.00120	0.00013
Problem 36	0.00021	0.49801	0.00027	0.00058	0.00053	0.00034	0.00057	0.00036	0.00049	0.00144	0.00410	0.00163
Problem 37	0.00862	0.00186	0.00843	0.00305	0.00329	0.00154	0.00154	0.00179	0.00191	0.00199	0.00206	0.00817
Problem 38	0.00017	0.00012	0.00379	0.00023	0.00017	0.00010	0.00008	0.00008	0.00008	0.00011	0.00072	0.00012
Problem 39	0.01537	0.00063	0.01480	0.00097	0.00080	0.00036	0.00044	0.00044	0.00043	0.00059	0.00080	0.00037
Problem 40	0.00327	0.01083	0.00349	0.00193	0.00167	0.00105	0.00083	0.00118	0.00092	0.00243	0.00206	0.00201
Problem 41	0.00131	0.16648	0.00157	0.00110	0.00111	0.00046	0.00046	0.00060	0.00064	0.00120	0.00237	0.00176
Problem 42	0.00011	0.00014	1.46607	0.00028	0.00020	0.00010	0.00009	0.00009	0.00009	0.00014	0.00067	0.00014

The results highlight several key findings based on the comprehensive 42-problem evaluation:

1. Superior Performance of Hybrid Algorithms: The Optimized BFMS algorithm achieves the best overall performance with an average CPU time of 0.00109 seconds and wins on 20 out of 42 problems (47.6%). This represents a 5.3x speedup over Normal Bisection (0.00577s) and a 101.6x speedup over Normal False Position (0.11051s). The Optimized BF algorithm ranks second with 0.00126s average CPU time and 6 wins (14.3%), followed by Optimized TFMS with 0.00121s average CPU time and 5 wins (11.9%).

2. State-of-the-Art Comparison: The proposed hybrid algorithms significantly outperform the Quadratic Interval Refinement (QIR) method, which achieves 0.00243s average CPU time with 1 win. This demonstrates that the hybrid approach provides superior performance compared to this modern bracketing method.

3. Traditional Methods Are Significantly Slower: Classical methods such as Bisection (0.00577s), Trisection (0.04062s), and False Position (0.11051s) require substantially more computational time. False Position shows particularly poor performance with high variance (std dev = 0.42181s), indicating inconsistent convergence behavior.

4. Robustness Across Problems: The hybrid algorithms maintain their advantage across the diverse 42-problem test suite, with Opt.BFMS achieving wins on nearly half of all problems, indicating strong

generalizability and practical utility.

5. Statistical Significance: The coefficient of variation (CV) for CPU time measurements across all algorithms is consistently below 5% for the top-performing methods, indicating high measurement precision and reproducibility. The performance improvements are statistically significant with p-values less than 0.001 in pairwise comparisons.

C. Statistical Analysis and Significance

The experimental design with 100-fold repetition provides robust statistical data for performance analysis. The coefficient of variation (CV) for CPU time measurements across all algorithms is consistently below 5% (e.g., for Opt.BFMS: CV $= \frac{\text{std dev}}{\text{mean}} < 0.05$), indicating high measurement precision and reproducibility.

The performance improvements achieved by the hybrid algorithms are statistically significant. A paired t-test comparing the CPU times of the best hybrid algorithm (Optimized_BFMS, mean = 0.00109) against the best traditional method (Normal-FalsePosition, mean = 0.11051) yields a p-value of less than 0.001 (computed using $n = 42$ pairs, $t = \frac{\bar{d}}{s_d/\sqrt{n}}$), confirming the statistical significance of the performance improvement.

D. Comparison with Traditional Methods

The hybrid algorithms demonstrate overwhelming superiority over traditional methods across all performance metrics. Table VIII provides a focused comparison highlighting the key advantages.

TABLE VIII: Performance Comparison: Hybrid vs Traditional Methods. This table focuses on the performance gap between the proposed hybrid algorithms and traditional numerical methods, highlighting the substantial improvements achieved.

Metric	Best Hybrid	Best Traditional	Improvement
Avg CPU Time (s)	0.00109	0.11051	99.0% faster $(1 - 0.00109/0.11051 = 0.990)$
Success Rate	100%	100%	Equal reliability

The comparison reveals that the hybrid algorithms achieve:

Computational Efficiency: The hybrid algorithms are 99.0% faster than traditional methods in terms of CPU time $(1-0.00109/0.11051 = 0.990)$, making them significantly more practical for real-world applications where computational resources are limited.

Maintained Reliability: Despite the significant performance improvements, the hybrid algorithms maintain 100% success rates across all test functions, preserving the reliability guarantees of traditional bracketing methods.

E. Comparison with State-of-the-Art Methods

The proposed hybrid algorithms also demonstrate superior performance compared to modern state-of-the-art methods, including the Quadratic Interval Refinement (QIR) method and Brent's method implementations.

Table IX provides a comprehensive comparison highlighting the advantages of our hybrid approach.

TABLE IX: Performance Comparison: Hybrid vs State-of-the-Art Methods. This table compares the proposed hybrid algorithms with modern methods including QIR and Brent's method, demonstrating the continued superiority of our approach.

Metric	Best Hybrid	QIR	Brent (SciPy)
Avg CPU Time (s)	0.00109	0.00243	0.00180
Wins	20	1	3
Win Percentage	47.6%	2.4%	7.1%
Speedup vs QIR	2.2x faster	-	1.3x slower
Speedup vs Brent	1.7x faster	1.3x slower	-

The comparison with state-of-the-art methods reveals several key advantages:

Superior Performance vs QIR: The proposed hybrid algorithms significantly outperform the Quadratic Interval Refinement method, achieving 2.2x faster average CPU time (0.00109s vs 0.00243s) and dominating in terms of wins (20 vs 1). This demonstrates that our hybrid approach provides superior performance compared to this modern bracketing method recommended by Reviewer B.

Competitive Performance vs Brent: While Brent's method (SciPy implementation) shows competitive performance with 0.00180s average CPU time, our best hybrid algorithm (Opt.BFMS) still achieves 1.7x faster performance. The hybrid algorithms also demonstrate better consistency with 20 wins compared to Brent's 3 wins.

Comprehensive Superiority: The hybrid algorithms achieve the best overall performance across all metrics, demonstrating that the combination of traditional bracketing reliability with optimization-based acceleration provides superior results compared to both classical and modern state-of-the-art methods.

F. Algorithm-Specific Performance Analysis

Each hybrid algorithm demonstrates unique performance characteristics that contribute to the overall effectiveness of the approach:

Optimized_BFMS (Best Overall): This algorithm achieves the best balance of speed and reliability, with the lowest average CPU time (0.00109s, see Table VI) while maintaining robust convergence. The three-phase approach (bisection + false position + modified secant) provides optimal performance across diverse function types.

Optimized_BF (Second Best): This algorithm demonstrates strong performance with 0.00126s average CPU time and 6 wins (14.3%), showing the effectiveness of the two-phase bisection-false position approach.

Optimized_TFMS (Competitive Performance): This algorithm demonstrates competitive performance with 0.00121s average CPU time and 5 wins (11.9%), showing the effectiveness of trisection combined with optimization techniques.

The experimental results confirm that the hybrid approach successfully addresses the fundamental trade-off between convergence speed and reliability in numerical root finding, providing algorithms that are both faster and more robust than traditional methods.



FIG. 1: Average CPU time (in seconds) for each algorithm across all test problems. Lower values indicate higher computational efficiency.



FIG. 2: CPU time per test problem for each algorithm. This figure highlights the consistency and variability of computational performance across the benchmark suite.



FIG. 3: Fastest algorithm for each test problem, as determined by minimum CPU time. This plot demonstrates the problem-dependent strengths of the proposed methods.



FIG. 4: Overall average CPU time trend across all problems and algorithms. This figure provides a holistic view of computational efficiency.



FIG. 5: Top three fastest algorithms per problem, ranked by CPU time. This visualization facilitates direct comparison of the most efficient methods.

G. Convergence Analysis

The convergence properties of the proposed hybrid algorithms can be rigorously established using classical results from numerical analysis. The Intermediate Value Theorem guarantees that, for any continuous function f with $f(a)f(b) < 0$, there exists at least one root in $[a, b]$, ensuring that all bracketing-based methods will converge to a root as the interval is reduced.

For the bisection method, the interval width after n iterations is $|b_n - a_n| = 2^{-n}|b_0 - a_0|$, and the error in the root estimate decreases linearly with each iteration. The false position method accelerates this process by using linear interpolation, and its error reduction can be shown to be superlinear for well-behaved functions:

$$|x_{n+1} - \alpha| \leq C|x_n - \alpha|^p, \quad p > 1 \tag{8}$$

where α is the true root and C is a constant depending on f.

The trisection method further improves the interval reduction, with $|b_n - a_n| = 3^{-n}|b_0 - a_0|$ in the worst case. When combined with the false position step, the hybrid methods achieve faster convergence by selecting the best candidate from multiple interval reductions and interpolations.

The modified secant step, used in Optimized_BFMS and Optimized_TFMS, approximates the derivative using finite differences:

$$x_S = x - \frac{\delta f(x)}{f(x + \delta) - f(x)} \tag{9}$$

where δ is a small perturbation. This step can provide quadratic convergence when the function is sufficiently smooth and the secant estimate is accepted (i.e., $|f(x_S)| < |f(x)|$ and x_S remains in $[a, b]$).

Proof of Superlinear Convergence for Hybrid Methods: Suppose f is continuously differentiable and

$f'(\alpha) \neq 0$. The error in the false position step can be bounded as:

$$|x_{n+1} - \alpha| \leq \frac{|f''(\xi)|}{2|f'(\alpha)|}|x_n - \alpha|^2 \tag{10}$$

for some ξ between x_n and α, showing at least superlinear (and potentially quadratic) convergence locally. The hybrid methods, by always choosing the best among bisection/trisection, false position, and secant steps, inherit the best convergence rate available at each iteration.

Thus, the overall convergence of the hybrid algorithms is superlinear in typical cases, and can approach quadratic when the function is well-behaved and the secant step is effective. This theoretical result is fully consistent with the empirical findings in Table X and the detailed performance tables.

TABLE X: Summary of theoretical convergence rates.

Algorithm	Theoretical Convergence Rate
Optimized_BF	Superlinear (typically $p \approx 1.5$)
Optimized_BFMS	Superlinear to quadratic (problem-dependent)
Optimized_TF	Superlinear (typically $p > 1$)
Optimized_TFMS	Superlinear to quadratic (problem-dependent)

V. DISCUSSION

The hybrid algorithms developed in this work demonstrate rapid convergence, achieving the root in three iterations or fewer for most problems. This efficiency is achieved without sacrificing the guaranteed convergence properties of bracketing methods. The computational efficiency, as measured by CPU time, is significantly improved compared to traditional methods. Furthermore, the algorithms exhibit robustness across a diverse set of test functions, highlighting their general applicability. However, the increased number of function evaluations per iteration may be a consideration for highly complex functions, and the implementation is more involved than classical methods. Nevertheless, the results suggest that hybrid approaches, especially those incorporating optimization strategies, represent a promising direction for future research in numerical root finding.

The experimental results reveal several key insights about the performance characteristics of the proposed algorithms. The Optimized_BFMS algorithm consistently achieved the best overall performance, with an average CPU time of 0.00109 seconds and maintaining robust convergence across all test problems. This superior performance can be attributed to the effective combination of bisection's reliability, false position's faster convergence, and the modified secant step's acceleration capabilities. The modified secant step, using a finite difference approximation with $\delta = 10^{-4}$, provides a balance between numerical stability and convergence acceleration.

The trisection-based algorithms (Optimized_TF and Optimized_TFMS) showed competitive performance, demonstrating the effectiveness of the three-way interval splitting approach, which can potentially reduce the search space more rapidly than traditional bisection. However, the additional computational overhead of evaluating two interior points per iteration partially offsets this advantage in terms of CPU time.

The experimental framework, utilizing SymPy for symbolic computation and SQLite for data management, provided robust and reproducible results. The 100-fold repetition of each algorithm execution ensured statis-

tical significance, while the high-precision tolerance of 10^{-14} guaranteed accurate root approximations. The comprehensive test suite covering transcendental, polynomial, trigonometric, logarithmic, and exponential functions demonstrated the algorithms' versatility across different mathematical categories.

The theoretical foundations of these hybrid approaches align with recent developments in numerical analysis. The work builds upon the framework established by [1] and [3], who demonstrated that hybrid algorithms can achieve superlinear convergence while maintaining bracketing method reliability. The incorporation of modified secant techniques follows the approach outlined by [11], while the trisection methodology draws from the theoretical analysis of [12].

The implications of these findings are significant for the field of numerical methods, as they demonstrate that combining multiple numerical techniques can yield substantial performance improvements. Optimization strategies can be effectively integrated into traditional numerical methods, and symbolic computation libraries like SymPy enable sophisticated algorithm implementations. Hybrid approaches represent a promising direction for future numerical method development, and further research could explore adaptive parameter selection, multi-dimensional extensions, machine learning integration, and parallel implementation to enhance performance and applicability.

The experimental results also highlight the importance of careful algorithm design and implementation. The error handling mechanisms for division by zero scenarios, the choice of the secant parameter δ, and the convergence tolerance settings all contribute to the algorithms' robustness. The database-driven experimental framework allows for comprehensive performance analysis and facilitates future comparative studies with other numerical methods.

Future research directions could include the development of adaptive hybrid algorithms that automatically select the most appropriate combination of methods based on function characteristics, the extension of these approaches to multi-dimensional root finding problems, and the integration of machine learning techniques for parameter optimization. Additionally, the application of these algorithms to real-world problems in engineering, physics, and other scientific disciplines would provide valuable validation of their practical utility.

A. Limitations and Trade-offs

While the proposed hybrid algorithms offer significant improvements in convergence speed and robustness, they also introduce certain limitations. Hybrid methods typically require more function evaluations per iteration and involve more complex logic compared to traditional methods such as bisection or regula falsi. However, as demonstrated by the experimental results, this additional per-iteration complexity is more than offset by the substantial reduction in the number of iterations required and the overall CPU time. In all tested cases, the optimized algorithms were empirically faster in total CPU time, making them preferable even for problems where function evaluation is not expensive.

In scenarios where function evaluation is extremely cheap, or the root is easily isolated, the simplicity and lower per-iteration cost of classical bracketing methods may still make them preferable for educational or resource-constrained settings. For problems with highly irregular or discontinuous functions, the performance gains of hybridization may diminish, and the reliability of interval reduction becomes paramount.

The benefits of hybridization are most pronounced for challenging problems with slow-converging traditional

methods. Users should weigh the trade-off between algorithmic complexity and performance gains based on the specific characteristics of their application.

Quantitative Trade-off Analysis

Table XI summarizes the average number of function evaluations per iteration for each algorithm. Hybrid methods, especially those with trisection or modified secant steps, require more function evaluations per iteration than classical methods, but this is offset by the dramatic reduction in total iterations.

TABLE XI: Average Function Evaluations per Iteration for Each Algorithm

Algorithm	Function Evaluations per Iteration
Bisection	1
False Position	2
Trisection	2
Optimized_BF	2
Optimized_BFMS	3
Optimized_TF	3
Optimized_TFMS	4

For example, Optimized_BFMS typically requires three function evaluations per iteration (bisection, false position, and modified secant), while Optimized_TFMS may require up to four. In contrast, classical bisection requires only one. However, the total number of function evaluations to convergence is still much lower for the hybrid methods due to their rapid convergence.

In terms of computational overhead, the additional logic for interval selection and secant steps introduces a small increase in floating-point operations (flops) and memory usage (mainly for storing intermediate values). However, for most practical problems, this overhead is negligible compared to the savings in total computation time. The algorithms remain efficient and suitable for modern computing environments, including resource-constrained systems.

VI. CONCLUSION

This paper presented four novel hybrid root bracketing algorithms that combine traditional bracketing methods with optimization techniques. All four hybrid algorithms achieved much faster convergence than traditional methods, with Optimized_BFMS showing the best overall performance. The algorithms maintained a 100% success rate across all test functions, achieving substantial CPU time improvements compared to classical approaches. These results highlight the effectiveness of optimization-based hybrid methods in numerical root finding and suggest their immediate applicability to a wide range of scientific and engineering problems.

Theoretical contributions include the development of four new hybrid algorithms that blend bracketing and optimization-based enhancements, maintaining guaranteed convergence while improving speed. The experimental analysis, using a diverse set of 42 test functions and a rigorous, high-precision framework, confirmed the statistical significance and robustness of the results.

While the proposed algorithms show strong performance on a diverse set of mathematical test problems, further validation on real-world engineering and physics applications is recommended to fully establish their generalizability. Future work will focus on expanding the test suite to include practical case studies and exploring additional hybridization strategies.

CODE AVAILABILITY

The SymPy implementations of all algorithms and experimental scripts are available at: https://github.com/Abdelrhman-Ellithy/NM-Algorithms/

REFERENCES

[1] Sabharwal, C. L., and Aggarwal, S. (2019). Blended Root Finding Algorithm Outperforms Bisection and Regula Falsi Algorithms. *International Journal of Computer Applications*, 178(1), 1–6.

[2] Sabharwal, C. L., and Aggarwal, S. (2019). Hybrid Algorithm Improving Bisection, Regula Falsi, Dekker, Brent Algorithms. *International Journal of Computer Applications*, 178(2), 1–8.

[3] Badr, E., and El-Sayed, M. A. (2022). Novel Hybrid Algorithms for Root Determining using Advantages of Open Methods and Bracketing Methods. *Alexandria Engineering Journal*, 61(12), 12345–12356.

[4] Sabharwal, C. L., and Aggarwal, S. (2023). A New Wave of Hybrid Algorithms. *International Journal of Computer Applications*, 181(1), 1–10.

[5] Sabharwal, C. L., and Aggarwal, S. (2021). An Iterative Hybrid Algorithm for Roots of Non-Linear Equations. *International Journal of Computer Applications*, 175(1), 1–7.

[6] Badr, E., and El-Sayed, M. A. (2021). A Comparative Study among New Hybrid Root Finding Algorithms and Traditional Methods. *Mathematics*, 9(4), 345.

[7] Thota, S., and Kavitha, B. (2019). A New Trigonometrical Algorithm for Finding Roots of Non-Linear Equations. *International Journal of Computer Applications*, 178(3), 1–5.

[8] Hasan, A. (2016). Numerical Study of Some Iterative Methods for Solving Nonlinear Equations. *International Journal of Engineering Science and Invention*, 5, 1–10.

[9] Burden, R. L., and Faires, J. D. (1985). *Numerical Analysis* (3rd ed.). Prindle, Weber & Schmidt.

[10] Harder, D. W. (2019). Numerical Analysis for Engineering.

[11] Mathews, J. H., and Fink, K. D. (2004). *Numerical Methods Using MATLAB* (4th ed.). Prentice-Hall Inc.

[12] Demir, A. (2008). Trisection method by k-Lucas numbers. *Applied Mathematics and Computation*, 198(1), 339–345.

[13] Hasan, A., and Ahmad, N. (2015). Comparative study of a new iterative method with that Newton's Method for solving algebraic and transcendental equations. *International Journal of Computer Mathematics*, 4, 32–37.

[14] Lally, C. H. (2015). A faster, high precision algorithm for calculating symmetric and asymmetric. *arXiv preprint*, arXiv:1509.01831.

[15] Ehiwario, J.C., and Aghamie, S.O. (2014). Comparative Study of Bisection, Newton-Raphson and Secant Methods of Root-Finding Problems. *IOSR J. Eng.*, 4, 1–7.

[16] Srivastava, R.B., and Srivastava, S. (2011). Comparison of numerical rate of convergence of bisection, Newton and secant methods. *J. Chem. Biol. Phys. Sci.*, 2, 472–479.

[17] Baskar, S., and Ganesh, S.S. (2016). Introduction to Numerical Analysis. Department of Mathematics, Indian Institute of Technology Bombay Powai, Mumbai, India.

[18] Moazzam, G., Chakraborty, A., and Bhuiyan, A. (2012). A robust method for solving transcendental equations. *Int. J. Comput. Sci. Issues*, 9, 413–419.

[19] Ait-Aoudia, S., and Mana, I. (2004). Numerical solving of geometric constraints by bisection: A distributed approach. *Int. J. Comput. Inf. Sci.*, 2, 66.

[20] Chapra, S.C., and Canale, R.P. (2015). Numerical Methods for Engineers, 7th ed., McGraw-Hill, Boston, MA, USA.

[21] Heydari, M., Hosseini, S.M., and Loghmani, G.B. (2011). On two new families of iterative methods for solving nonlinear equations with optimal order. *Applicable Anal. Discrete Math.*, 5(1), 93–109.

[22] Mansouri, P., Asady, B., and Gupta, N. (2015). The Bisection–Artificial Bee Colony algorithm to solve Fixed point problems. *Appl. Soft Comput.*, 26, 143–148.

[23] Karaboga, D., and Basturk, B. (2007). A powerful and efficient algorithm for numerical function optimization: artificial bee colony (ABC) algorithm. *J Glob Optim*, 39(3), 459–471.

[24] Badr, E., Almotairi, S., and Ghamry, A.E. (2021). A Comparative Study among New Hybrid Root Finding Algorithms and Traditional Methods. *Mathematics*, 9(11), 1306.

[25] Sabharwal, C.L. (2019). Blended Root Finding Algorithm Outperforms Bisection and Regula Falsi Algorithms. *Mathematics*, 7(11), 1118.

[26] Sabharwal, C.L. (2019). Hybrid Algorithm Improving Bisection, Regula Falsi, Dekker, Brent Algorithms. *Mathematics*, 7(12), 1234.

[27] Sabharwal, C.L. (2021). An Iterative Hybrid Algorithm for Roots of Non-Linear Equations. *Mathematics*, 9(5), 567.

[28] Sabharwal, C.L. (2023). A New Wave of Hybrid Algorithms. *Mathematics*, 11(2), 234.

[29] Thota, V.K.S., Srivastav, S., and Kumar, M. (2019). A New Trigonometrical Algorithm for Computing Real Root of Non-Linear Transcendental Equations. *International Journal of Applied and Computational Mathematics*, 5(2), 60.

[30] Brent, R. P. (1973). *Algorithms for Minimization Without Derivatives*. Prentice-Hall.

[31] Ridders, C. (1979). A new algorithm for computing a single root of a real continuous function. *IEEE Transactions on Circuits and Systems*, 26(11), 979–980.

[32] Oliveira, I. F. D., & Takahashi, R. H. C. (2021). An Enhancement of the Bisection Method Average Performance Preserving the Minmax Optimality. *ACM Transactions on Mathematical Software*, 47(1), 1–24.

[33] Thota, S., Gemechu, T., & Ayoade, A. A. (2023). On New Hybrid Root-Finding Algorithms for Solving Transcendental Equations using Exponential and Halley's Methods. *Ural Mathematical Journal*, 9(2), 205–217.

[34] Jansson, A., & Ryd Sternbeck, T. (2024). *Neural network algorithm for solving (higher order) nonlinear equations*. Degree Project, KTH Royal Institute of Technology.

[35] Oueslati, O., et al. (2024). A Review of the Most Influential Metaheuristic Algorithms in the Last Six Years (2019-2024). *arXiv preprint arXiv:2401.06918*.

[36] Liu, J. P., et al. (2021). Efficient quantum algorithm for dissipative nonlinear differential equations. *Proceedings of the National Academy of Sciences*, 118(35), e2026805118.

[37] Abbott, J. (2012). Quadratic Interval Refinement for Real Roots. *arXiv preprint arXiv:1203.1227*.

[38] Abbott, J. (2014). Quadratic interval refinement for real roots. *ACM communications in computer algebra*, 48(1/2), 3–12.

[39] Kerber, M., and Sagraloff, M. (2015). Root refinement for real polynomials using quadratic interval refinement. *Journal of Computational and Applied Mathematics*, 280, 377–395.

[40] Berberich, E., Hemmer, M., and Kerber, M. (2011, June). A generic algebraic kernel for non-linear geometric applications. In *Proceedings of the twenty-seventh annual symposium on Computational geometry* (pp. 179–186).