ADVANCED METHODS OF AI · WORKSHEET 3

Asking, Defining, Constraining, Deriving, Generating


Worksheet 3 · querying a knowledge base with the Entity Query Language

> **Now:** in pairs, open `03-pizza_queries.ipynb` (link on Stud.IP) and run its **setup cell**. It installs EQL while we talk.

WHERE WE ARE

Last week: represent. Today: use.

- Worksheet 2: the pizza world in first-order logic, in OWL, and as Python classes.
- Today a service robot in a pizzeria *uses* that knowledge. Everything it does starts with one kind of expression: a **description**.



LOGIC

A query is a formula with free variables

$$\text{Pizza}(x) \land \exists t\, (\text{hasTopping}(x, t) \land \text{CheeseTopping}(t))$$

- The picture of the pizzeria is an **interpretation**: a domain of objects and the extension of every predicate.
- The **answers** are the values of the free variable x that make the formula true in it.
- That is *checking* one model, not proving that something holds in *every* model. The difference will matter: does the robot know everything?

EQL: the same formula, over Python objects

```
cheesy = a(Pizza)(toppings=a(CheeseTopping)).from_(pizzas)
```

EQL	first-order logic
`a(Pizza)`	a variable x with Pizza(x)
`toppings=a(CheeseTopping)`	$\exists t$ (hasTopping(x, t) $\wedge$ CheeseTopping(t)): *some* element of the list
`.from_(pizzas)`	the objects x ranges over; left out: the registry, every object the robot created
`cheesy.tolist()`	all values of x that satisfy the formula

Read it aloud: *“a pizza with a cheese topping, from the pizzas”*. Writing a query computes nothing; `.tolist()` evaluates it.

EQL

Every and no, and naming variables

```
a(Pizza)(toppings=every_is(VegetableTopping)).from_(pizzas)
pizza   = a(Pizza).from_(pizzas)
topping = a(PizzaTopping).from_(pizza.toppings)
pizza.where(for_all(topping, HasType(topping, VegetableTopping)))
```

$$\text{Pizza}(x) \land \forall t\,(\text{hasTopping}(x, t) \rightarrow \text{VegetableTopping}(t))$$

- In a pattern, `a(…)` says *some*; `every_is(…)`, `none_is(…)` say *every*, *no*. Both queries are one formula.
- Other conditions: name the topping, then quantify over it with `exists` or `for_all`.
- A path, `pizza.toppings.spiciness == MILD`, filters on *a* topping.
- Every `a(…)` is a variable of its own; `set_of(x, y)` returns several at once.

LOGIC

A class declaration is already a set of axioms

```
class MozzarellaTopping(CheeseTopping): ...
class Pizza:
    toppings: list[PizzaTopping]
class VegetarianPizza(Role[Pizza]): ...
```

KRROOD reads	first-order logic
a subclass	$\forall x\,(\text{MozzarellaTopping}(x) \rightarrow \text{CheeseTopping}(x))$
a typed attribute	$\forall x\,\forall t\,(\text{Pizza}(x) \wedge \text{hasTopping}(x, t) \rightarrow \text{PizzaTopping}(t))$
a role of a pizza	$\forall v\,(\text{VegetarianPizza}(v) \rightarrow \text{Pizza}(\text{roleTaker}(v)))$

All are *necessary* conditions: what follows from being a C. A **definition** adds the *sufficient* one, $\text{C}(x) \leftrightarrow \varphi(x)$, and only that lets the robot decide what is a C. (Act 2)

TODAY

One description, five uses

Act	Story	The description is …	Logic
1 Asking	“Which pizzas have cheese?” “*The* one with olives.”	a question	∃, ∀, ¬ in one interpretation
2 Defining	“Which pizzas may carry the green V?”	a definition	↔: check, classify, conclude
3 Constraining	“Ben must never get milk.”	a constraint	¬∀ ≡ ∃¬
4 Deriving	the kitchen writes allergen warnings	the body of a rule	∃ in the head: new objects
5 Generating	Dana orders a pizza that does not exist	a specification	constructing a model

The expression stays the same. Asking and constraining *read* what the robot knows; defining, deriving and generating *write* to it. A rule's new objects are forced, a generator's are chosen.

TODAY

Two questions to keep in mind

- **Does the robot know everything?** The query treats what it knows as complete; last week's OWL reasoner did not. Who is right about `unclosed_1`? (Act 1)
- **What happens when the world changes?** A cook makes a mistake at 19:50. Which of the robot's conclusions still hold? (Act 4)

TODAY

How we work today

- In pairs, one laptop. The evening happens in the **notebook**; every cell runs as it is, and a `TODO` you cannot solve does not stop you.
- **Guess, then run.** Type your guess before a prediction cell runs: the robot tells you what surprised you, and why. A wrong guess is where you learn the most.
- **Three pen breaks.** Laptops aside, the logic by hand on the sheet; then the board and your questions.

Slides 8′, then:

Ask	Pen	Define	Constrain	Pen	Derive	Generate	Pen
22′	7′	12′	8′	7′	9′	6′	11′