

Copy 13

```
#include <stdio.h>
int main()
{
    int n, x, A, S, present = 0, absent = 0, session;
    printf("entre number of students");
    scanf("%d", &n);
    printf("enter minimum attendance :");
    scanf("%d", &A);
    printf("entre absence thershold");
    scanf("%d", &S);
    for (int i = 1; i <= n; i++)
    {
        printf("entre number of attendance for the student number %d : %d ", i, x);
        if (x < A)
        {
            printf("the student numbe is absent");
            absent = absent + 1;
        }

        else
        {
            printf("the student is present");
            present = present + 1;
        }

        if (absent > S)
        {
            printf("max absence reched");
            return 1;
        }

    }

    if (present > absent)
    {
        session = 1;
    }

    else
    {
        session = 0;
    }

    printf("the number of present students : %d ", present);
    printf("the number of absent students : %d ", absent);
    if (session)
    {
        printf("session valid");
    }
}
```

```
else
{
    printf("session cancelled");
}

return 0;
}
```

Copy 14

```
#include <stdio.h>
int main()
{
    int N, A, S;
    int i, x, ab = 0, p = 0;
    printf("Enter the total number of registerd students \n");
    scanf("%d", &N);
    printf("Enter the minimum attendance requiveed \n");
    scanf("%d", &A);
    printf("Enter the absence threshold \n");
    scanf("%d", &S);
    for (i = 1; i <= N; i++)
    {
        printf("Enter the number of attended session for student : %d \n", i);
        scanf("%d", &x);
        if (x < A)
        {
            printf("the student is absent");
            ab = ab + 1;
        }

        else
        {
            printf("the student is present");
            p = p + 1;
        }

        printf("the number of present student is : %d \n", p);
        printf("the number of absent students is : %d \n", ab);
    }

    if (i == N || ab < S)
    {
        printf("the total number of present student is : %d \n", p);
        printf("the total number of absent students is : %d \n", ab);
        if (ab > p)
        {
            printf("session cancelled");
        }

        else
        {
            printf("session valid");
        }
    }

    else
    {

```

```
        printf("Simulation was stoped");  
    }  
  
    return 0;  
}
```

```
#include <stdio.h>
int main()
{
    int S, A, N;
    int x;
    int absent = 0, present = 0;
    printf("Enter number of students N");
    scanf("%d", &N);
    printf("Enter minimum attendance A");
    scanf("%d", &A);
    printf("Enter absence threshold S");
    scanf("%d", &S);
    while (N <= S && S > absent)
    {
        printf("Student number %d enter attended sessions", i);
        scanf("%d", &x);
        if (x < A)
        {
            absent++;
        }

        else
        {
            present++;
        }

        i++;
        printf("Processing %d : Present %d / Absent %d \n", i, present, absent);
        if (S <= absent)
        {
            printf("Final Status: Exam Cancelled");
        }

        else
        {
            printf("Final Status: Exam Valid");
        }

    }

    return 0;
}
```

Copy 16

```
#include <stdio.h>
int main()
{
    int N, A, S, X, i;
    printf("enter total number of registered students, N :");
    scanf("%d", &N);
    printf("enter absence threshold, S :");
    scanf("%d", &S);
    for (i = 1; i <= N; i++)
    {
        for (i = 0; i <= S; i++)
        {
            printf("enter The number of attended sessions, X");
            scanf("%d", &X);
            printf("enter a minimum attendance required, A");
            scanf("%d", &A);
            if (X < A)
            {
                printf("the students is absent");
            }

            else
            {
                printf("the students is present");
            }

        }

    }

    printf("total processed students");
    if (present > absent)
    {
        printf("Session valid");
    }

    else
    {
        printf("session cancelled");
    }

    return 0;
}
```