

```
root@ilbar:/etc/bind# service bind9 restart
root@ilbar:/etc/bind# nslookup 10.42.31.60
60.31.42.10.in-addr.arpa      name = www.unesa.ac.id.
60.31.42.10.in-addr.arpa      name = mail.unesa.ac.id.
60.31.42.10.in-addr.arpa      name = unesa.ac.id.
```

```
root@ilbar:/etc/bind# service bind9 restart
```

GNU nano 7.2

/etc/resolv.conf *

nameserver 10.42.31.60

nameserver 8.8.8.8_

```
root@ilbar:/etc/bind# nano /etc/resolv.conf
```

```
options {
    directory "/var/cache/bind";

    // If there is a firewall between you and nameservers you want
    // to talk to, you may need to fix the firewall to allow multiple
    // ports to talk.  See http://www.kb.cert.org/vuls/id/800113

    // If your ISP provided one or more IP addresses for stable
    // nameservers, you probably want to use them as forwarders.
    // Uncomment the following block, and insert the addresses replacing
    // the all-0's placeholder.

    forwarders {
        8.8.8.8;
        8.8.4.4;_
    };

    //=====
    // If BIND logs error messages about the root key being expired,
    // you will need to update your keys.  See https://www.isc.org/bind-keys
    //=====
    dnssec-validation auto;

    listen-on-v6 { any; };
};
```

```
root@ilbar:/etc/bind# nano named.conf.options
```

```
;
; BIND reverse data file for local loopback interface
;
$TTL      604800
@         IN      SOA      unesa.ac.id. root.unesa.ac.id. (
                        1          ; Serial
                        604800     ; Refresh
                        86400      ; Retry
                        2419200    ; Expire
                        604800 )   ; Negative Cache TTL
;
@         IN      NS       unesa.ac.id.
60        IN      PTR      unesa.ac.id.
60        IN      PTR      www.unesa.ac.id.
60        IN      PTR      mail.unesa.ac.id._
```

```
;
; BIND reverse data file for local loopback interface
;
$TTL      604800
@         IN      SOA      unesa.ac.id. root.unesa.ac.id. (
                        1          ; Serial
                        604800     ; Refresh
                        86400      ; Retry
                        2419200    ; Expire
                        604800 )   ; Negative Cache TTL
;
@         IN      NS       unesa.ac.id.
1.0.0     IN      PTR      unesa.ac.id.
```



```
root@ilbar:/etc/bind# nano db.ip
```

```
;  
; BIND data file for local loopback interface  
;  
$TTL      604800  
@          IN      SOA      unesa.ac.id. root.unesa.ac.id. (  
                        2      ; Serial  
                        604800  ; Refresh  
                        86400   ; Retry  
                        2419200  ; Expire  
                        604800 ) ; Negative Cache TTL  
;  
@          IN      NS       unesa.ac.id.  
@          IN      A        10.42.31.60  
www        IN      A        10.42.31.60  
mail       IN      A        10.42.31.60  
_
```

```
;  
; BIND data file for local loopback interface  
;  
$TTL      604800  
@         IN      SOA      unesa.ac.id. root.unesa.ac.id. (  
                        2      ; Serial  
                        604800  ; Refresh  
                        86400   ; Retry  
                        2419200 ; Expire  
                        604800 ) ; Negative Cache TTL  
;  
@         IN      NS       unesa.ac.id.  
@         IN      A        127.0.0.1  
@         IN      AAAA     ::1
```

```
;
; BIND data file for local loopback interface
;
$TTL      604800
@         IN      SOA      localhost. root.localhost. (
                        2      ; Serial
                        604800  ; Refresh
                        86400   ; Retry
                        2419200  ; Expire
                        604800 ) ; Negative Cache TTL
;
@         IN      NS       localhost.
@         IN      A        127.0.0.1
@         IN      AAAA     ::1
```

Replace this instance?

Y Yes A All
N No ^C Cancel

Replace with: unesa.ac.id

^G Help

^C Cancel

^P Older

^N Newer

Search (to replace): localhost

^G Help	M-C Case Sens	M-B Backwards	^P Older
^C Cancel	M-R Reg.exp.	^R No Replace	^N Newer

Search:

☐ G Help	☐ -C Case Sens	☐ -B Backwards	☐ P Older	☐ T Go To Line
☐ C Cancel	☐ -R Reg.exp.	☐ R Replace	☐ N Newer	

```
;  
; BIND data file for local loopback interface  
;  
$TTL      604800  
@         IN      SOA      localhost. root.localhost. (  
                2          ; Serial  
                604800     ; Refresh  
                86400      ; Retry  
                2419200    ; Expire  
                604800 )   ; Negative Cache TTL  
;  
@         IN      NS       localhost.  
@         IN      A        127.0.0.1  
@         IN      AAAA     ::1
```

[Read 14 lines]

^G Help	^O Write Out	^W Where Is	^K Cut	^T Execute	^C Location	M-U Undo	M-A Set Mark	M-] To Bracket	M-O Previous
^X Exit	^R Read File	^N Replace	^U Paste	^J Justify	^- Go To Line	M-E Redo	M-6 Copy	^Q Where Was	M-W Next


```
root@ilbar:/etc/bind# nano db.ilbar
```

```
root@ilbar:/etc/bind# cp db.local db.ilbar
root@ilbar:/etc/bind# cp db.127 db.ip
```

```
// prime the server with knowledge of the root servers
zone "." {
    type hint;
    file "/usr/share/dns/root.hints";
};

// be authoritative for the localhost forward and reverse zones, and for
// broadcast zones as per RFC 1912

zone "localhost" {
    type master;
    file "/etc/bind/db.local";
};

zone "127.in-addr.arpa" {
    type master;
    file "/etc/bind/db.127";
};

zone "0.in-addr.arpa" {
    type master;
    file "/etc/bind/db.0";
};

zone "255.in-addr.arpa" {
    type master;
    file "/etc/bind/db.255";
};

zone "ilbar.unesa.ac.id" {
    type master;
    file "/etc/bind/db.ilbar";
};

zone "31.42.10.in-addr.arpa" {
    type master;
    file "/etc/bind/db.ip";
};
```

```
// prime the server with knowledge of the root servers
```

```
zone "." {  
    type hint;  
    file "/usr/share/dns/root.hints";  
};
```

```
// be authoritative for the localhost forward and reverse zones, and for  
// broadcast zones as per RFC 1912
```

```
zone "localhost" {  
    type master;  
    file "/etc/bind/db.local";  
};
```

```
zone "127.in-addr.arpa" {  
    type master;  
    file "/etc/bind/db.127";  
};
```

```
zone "0.in-addr.arpa" {  
    type master;  
    file "/etc/bind/db.0";  
};
```

```
zone "255.in-addr.arpa" {  
    type master;  
    file "/etc/bind/db.255";  
};
```

```
zone "localhost" {  
    type master;  
    file "/etc/bind/db.local";  
};
```

```
zone "127.in-addr.arpa" {  
    type master;  
    file "/etc/bind/db.127";  
};
```

```
// prime the server with knowledge of the root servers
```

```
zone "." {  
    type hint;  
    file "/usr/share/dns/root.hints";  
};
```

```
// be authoritative for the localhost forward and reverse zones, and for  
// broadcast zones as per RFC 1912
```

```
zone "0.in-addr.arpa" {  
    type master;  
    file "/etc/bind/db.0";  
};
```

```
zone "255.in-addr.arpa" {  
    type master;  
    file "/etc/bind/db.255";  
};
```

```
// prime the server with knowledge of the root servers
```

```
zone "." {  
    type hint;  
    file "/usr/share/dns/root.hints";  
};
```

```
// be authoritative for the localhost forward and reverse zones, and for  
// broadcast zones as per RFC 1912
```

```
zone "localhost" {  
    type master;  
    file "/etc/bind/db.local";  
};
```

```
zone "127.in-addr.arpa" {  
    type master;  
    file "/etc/bind/db.127";  
};
```

```
zone "0.in-addr.arpa" {  
    type master;  
    file "/etc/bind/db.0";  
};
```

```
zone "255.in-addr.arpa" {  
    type master;  
    file "/etc/bind/db.255";  
};
```

```
root@ilbar:/etc/bind# nano named.conf.default-zones
```

```
root@ilbar:/etc/bind# ip a
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue state UNKNOWN group default qlen 1000
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
    inet 127.0.0.1/8 scope host lo
        valid_lft forever preferred_lft forever
    inet6 ::1/128 scope host noprefixroute
        valid_lft forever preferred_lft forever
2: enp0s3: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc fq_codel state UP group default qlen 1000
    link/ether 08:00:27:95:bc:bc brd ff:ff:ff:ff:ff:ff
    inet 10.42.31.60/24 brd 10.42.31.255 scope global dynamic enp0s3
        valid_lft 3262sec preferred_lft 3262sec
    inet6 2404:c0:3468:215b:a00:27ff:fe95:bcbc/64 scope global dynamic mngtmpaddr
        valid_lft 6986sec preferred_lft 6986sec
    inet6 fe80::a00:27ff:fe95:bcbc/64 scope link
        valid_lft forever preferred_lft forever
root@ilbar:/etc/bind# _
```



```
root@ilbar:~# cd /etc/bind
root@ilbar:/etc/bind# ls
bind.keys  db.0  db.127  db.255  db.empty  db.local  named.conf  named.conf.default-zones  named.conf.local  named.conf.options  rndc.key  zones.rfc1918
root@ilbar:/etc/bind# _
```

```
root@ilbar:~# apt update && apt upgrade -y
Hit:1 http://security.debian.org/debian-security bookworm-security InRelease
Hit:2 http://kartolo.sby.datautama.net.id/debian bookworm InRelease
Hit:3 http://kartolo.sby.datautama.net.id/debian bookworm-updates InRelease
Reading package lists... Done
Building dependency tree... Done
Reading state information... Done
All packages are up to date.
Reading package lists... Done
Building dependency tree... Done
Reading state information... Done
Calculating upgrade... Done
0 upgraded, 0 newly installed, 0 to remove and 0 not upgraded.
root@ilbar:~#
```

```
root@ilbar:~# apt install bind9 dnsutils
Reading package lists... Done
Building dependency tree... Done
Reading state information... Done
The following additional packages will be installed:
  bind9-utils dns-root-data
Suggested packages:
  bind-doc resolvconf ufw
The following NEW packages will be installed:
  bind9 bind9-utils dns-root-data dnsutils
0 upgraded, 4 newly installed, 0 to remove and 0 not upgraded.
Need to get 428 kB of archives.
After this operation, 1,614 kB of additional disk space will be used.
Do you want to continue? [Y/n] y
```