

Lab Report

Lab Report

Time Spent: 03:37

Score: 4/4 (100%)

Pass

Passing Score: 4/4 (100%)

TASK SUMMARY

Required Actions & Questions

Capture and filter DHCP traffic

Disable and enable the enp2s0 network interface

Q1 What is the IP address of the rogue DHCP server?

Your answer: 20.10.10.239

Correct answer: 20.10.10.239

Q2 What is the IP address of the legitimate DHCP server?

Your answer: 192.168.0.14

Correct answer: 192.168.0.14

EXPLANATION

Complete this lab as follows:

1. Use Wireshark to capture and filter DHCP traffic.
 - a. From the Favorites bar, select **Wireshark**.
 - b. Under Capture, select **enp2s0**.
 - c. Select the **blue fin** to start a Wireshark capture.
 - d. In the *Apply a display filter* field, type **bootp** and press **Enter**.
2. Disable and enable the enp2s0 network interface.
 - a. From the Favorites bar, select **Terminal**.
 - b. At the prompt, type **ip addr show** and press **Enter** to view the current IP configuration.
 - c. Type **ip link set enp2s0 down** and press **Enter**.
 - d. Type **ip link set enp2s0 up** and press **Enter** to enable the interface and request an IP address from the DHCP server.
3. Locate the rogue and legitimate DHCP servers.
 - a. Maximize the Wireshark window for better viewing.
 - b. In Wireshark, under the *Source* column, find the IP addresses of the rogue and legitimate DHCP servers that sent the DHCP Offer packets.
 - c. In the top right, select **Answer Questions**.
 - d. Answer the questions.
 - e. Select **Score Lab**.