

Lab Report

Your Performance

Your Score: 4 of 4 (100%)

Elapsed Time: 22 minutes

Pass Status: Pass

Required Score: 100%

Task Summary

Required Actions

- ✓ Change the password for the admin account to P@ssw0rd.
- ✓ Set a 15 minute session timeout for pfSense.
- ✓ Create and configure a new pfSense userShow Details
- ✓ Enable anti-lockout for HTTP

Explanation

Complete this lab as follows:

1. Access the pfSense management console.
 - a. From the taskbar, select **Google Chrome**.
 - b. Maximize the window for better viewing.
 - c. In the Google Chrome address bar, enter **198.28.56.18** and then press **Enter**.
 - d. Enter the pfSense sign-in information as follows:
 - Username: **admin**
 - Password: **pfsense**
 - e. Select **SIGN IN**.
2. Change the password for the default (admin) account.
 - a. From the pfSense menu bar, select **System > User Manager**.
 - b. For the admin account, under Actions, select the **Edit user** icon (pencil).
 - c. For the Password field, change to **P@ssw0rd** (use a zero).
 - d. For the Confirm Password field, enter **P@ssw0rd**.
 - e. Scroll to the bottom and select **Save**.
3. Create and configure a new pfSense user.
 - a. Select **Add**.
 - b. For Username, enter **zolsen**.
 - c. For the Password field, enter **St@yout!**.
 - d. For the Confirm Password field, enter **St@yout!**.
 - e. For Full Name, enter **Zoey Olsen**.
 - f. For Group Membership, select **admins** and then select **Move to Member of list**.
 - g. Scroll to the bottom and select **Save**.
4. Set a session timeout for pfSense.
 - a. Under the *System* breadcrumb, select **Settings**.

- b. For Session timeout, enter **15**.
 - c. Select **Save**.
- 5. Disable the webConfigurator anti-lockout rule for HTTP.
 - a. From the pfSense menu bar, select **System > Advanced**.
 - b. Under webConfigurator, for Protocol, select **HTTP**.
 - c. Select **Anti-lockout** to disable the webConfigurator anti-lockout rule.
 - d. Scroll to the bottom and select **Save**.