Demo Client · DEMO-0012
11 November 2026 · v1.0

Runbook

> Demonstration: built from synthetic data.

1. Every morning (two minutes)

1. Open the latest log in `logs/` (or the email, if a notification is set up). The first line says how the night went: **ok**, **warnings** or **failed**.
2. On **warnings**, read the lines below it: each names a batch, what happened to it and why.
3. On **failed**, nothing was published that night; the tables from the night before are still there. Read the error and call the platform's owner.

The run starts at 02:30 every night. Exit codes: **0** ok · **2** loaded, with warnings or batches set aside · **1** failed.

2. The sources

Source	Reached by	Load mode	Contract
pos	file_drop	new_files	yes
menu	file_drop	snapshot	yes
branches	file_drop	snapshot	yes
ledger	file_drop	snapshot	yes
ads	file_drop	snapshot	no
hr	database	snapshot	no

3. When something goes wrong

What you see	What it means	What to do
A batch **quarantined**	The file broke its contract (a required column missing, too many unreadable values) and was set aside whole	Open `quarantine/<night>/<source>/*.reason.txt`; ask the source's owner for a corrected file and drop it in the same folder: it loads the next night
New column(s)	The system changed its export	Nothing breaks: the column is kept in the raw layer. Agree the new format with the provider, then add the column to the mapping if it is needed
Column(s) no longer sent	The system stopped sending a column	If it was required, the batch is quarantined; otherwise ask the provider whether it is a mistake
Skipped: same content	The same file was sent again under a new name	Nothing to do
	A source has not sent its latest data, or its file was set aside	Ask the source's owner; check the quarantine folder

What you see	What it means	What to do
Data older than N days or **a site behind**		
A table test **failed**	A published table broke a rule (a duplicate key, a total that does not agree)	Nothing was published; call the platform's owner

4. Changes

- **A new source:** add it under `data_sources`, map it under `intake`, give it a load mode and a contract under `platform.loads`, then run once by hand.
- **A changed column name:** change the mapping, not the data.
- **Moving to the company's database:** run `deploy/postgres/create_tables.sql` (or the BigQuery script) once, set `platform.warehouse` to `{type: sqlalchemy, url: "${WAREHOUSE_URL}"}` and put the address in `.env`.

5. Back-up and restore

The whole platform is one folder. Back up `warehouse/` and `platform.yaml` every night with the rest of the company's files. To restore, put them back and run once: what is new since the back-up loads again.

6. Access and secrets

Passwords and keys live only in `.env` on the machine that runs the platform. Give each source a read-only user. When someone leaves, change the keys they knew.